Elsewhere in ICE Proceedings

S. K. Fullalove, *Editor*

The following are summaries of papers published in other parts of ICE *Proceedings* during 2003 that readers of *Bridge Engineering* may find of interest. You can get copies of individual papers emailed or posted to you for £5 or faxed to you for £2 per page from the ICE library (telephone +44 (0) 20 7665 2251; fax +44 (0) 20 7976 7610; e-mail library@ice.org.uk). In all cases you need to complete a copy request form which can be downloaded from the ICE website at www.ice.org.uk/library/icepdqrq.html. Summaries of all papers in ICE journals are also freely available and fully searchable at the 'journals on-line' section of the ICE website at www.ice.org.uk/jol.

Shear strengthening of existing concrete bridges

P. Valerio and T. I. Ibell

Proceedings of the Institution of Civil Engineers—Structures and Buildings, 156, February, 75–84

The shear capacity of existing concrete bridge beams is often inadequate and unable to meet current code requirements. This is often due to increased traffic loads, inadequate shear-resistance provision in the original design or deterioration of materials due to aggressive environments. This paper deals with a new type of shear strengthening for existing concrete bridges. It is proposed that vertical steel or fibre-reinforced plastic bars be inserted into pre-drilled holes and fastened in place using epoxy resin. This method has the advantage that only the soffit of the concrete bridge beam (or slab) is required for access, allowing the top surface to remain undamaged during strengthening. This could allow the bridge to be used during strengthening works, with traffic relatively unhindered by work being carried out below. Further, no threaded bars and plates are required in this scheme, solving the notorious installation and maintenance problems associated with present shear-strengthening schemes. Ten laboratory tests are presented here to demonstrate the system, and comparisons are made against current code predictions for the strength of such concrete beams with and without transverse reinforcement. An upper-bound plasticity-based solution is also provided as a means to explain enhancement in shear capacity in specimens with very few embedded vertical bars. The results of this work show that the proposed strengthening scheme is effective and provides significant improvement in the shear-carrying load capacity. Additionally, code predictions for capacity of the strengthened beams are rather accurate, so that this strengthening method may be adopted with confidence.

Strengthening of London's Lambeth Bridge

A. Kumar

Proceedings of the Institution of Civil Engineers—Structures and Buildings, 156, May, 151–164

This paper summarises the findings of the principal inspection and load assessment of Lambeth Bridge, which had identified a structural deficiency in the original construction of the arched steel ribs of the bridge. The design for the strengthening of the bridge involved rectification of this deficiency as well as consideration of other repairs and repainting of the bridge. The paper briefly describes the various site operations involved in the works contracts resulting in the strengthening of this landmark bridge in London.

Bridges: when is single mode seismic analysis adequate?

T. Isakovic, M. Fischinger and P. Kante

Proceedings of the Institution of Civil Engineers—Structures and Buildings, 156, May, 165–173

Single-degree-of-freedom (SDOF) models are frequently used in the seismic analysis of bridges, in particular in recent years when inelastic, SDOF-based push-over analysis has become increasingly popular. However, the scope of applicability of these models has not yet been clearly defined (e.g. in the Eurocode 8/2). Using SDOF models, displacements and forces could be significantly underestimated, especially in 'irregular structures'. The authors have therefore proposed a more adequate criterion for the applicability of SDOF models, and a clearer definition of regularity. The seismic response of some typical European viaducts has been studied. Several different seismic analysis methods, both elastic and inelastic, were used, incorporating different levels of structural model simplification. Differences in the response obtained by using SDOF and multi-degree-of-freedom (MDOF) models were analysed. If these differences were significant, the response was considered to be irregular and the SDOF model unsuitable. For the quantitative estimation of the regularity and applicability of SDOF models a 'regularity index' has been introduced. The index is based on a comparison between the different displacement shapes obtained within two iterations of the single mode static analysis. Using this index the main parameters influencing the irregular response of the viaducts were identified and analysed.

Thermal actions on a steel box girder bridge

J.-M. Lucas, A. Berred and C. Louis

Proceedings of the Institution of Civil Engineers—Structures and Buildings, 156, May, 175–182

Most studies of thermal actions on bridges have been devoted to concrete structures. In this paper, we focus our analysis on steel box girder bridges. The statistical analysis is based on data collected over a three-year period by temperature gauges placed in appropriate places on the Normandy Bridge, France. Temperature–time series are generally known to contain a deterministic and a random part. The deterministic component is due to the natural seasonal fluctuation over a whole year. The same phenomenon has been observed in the case of the Normandy Bridge. At design stage, engineers need to know the extreme fluctuations of thermal actions (average temperature and thermal gradient) to ensure the durability and safety of a structure. Design codes prescribe extreme values called characteristic values defined on a return period of 50 years. The statistical analysis allows the calculation of these characteristic values as well as frequent and quasi-permanent values.

Wind-induced vibration analysis of the Hong Kong Ting Kau Bridge

C. Su, D. J. Han, Q. S. Yan, F. T. K. Au, L. G. Tham, P. K. K. Lee, K. M. Lam and K. Y. Wong

Proceedings of the Institution of Civil Engineers—Structures and Buildings, 156, August, 263–272

Because of their high flexibility and relatively low structural damping, long-span bridges are prone to wind-induced vibration. An efficient wind field simulation technique for wind-induced vibration analysis of long-span bridges is first introduced in this paper. The time-domain expressions for the buffeting and self-excited forces acting on long-span bridges can then be found from the wind velocities. Based on the above theory and the aerodynamic parameters obtained by wind tunnel tests, a study of the wind fluctuations and aerodynamic forces is carried out on the Hong Kong Ting Kau Bridge, which is a cable-stayed bridge comprising two main spans and two side spans. The buffeting response of the bridge is analysed in the time domain by using step-by-step numerical integration techniques. The aerodynamic behaviour of the bridge can therefore be obtained, and the safety performance of the bridge against strong wind can further be evaluated. Numerical results basically agree with the experimental data, indicating that the theory presented in this paper is applicable to engineering practice.

Environmental impact of brick arch bridge management

K. Steele, G. Cole, G. Parke, B. Clarke and J. Harding

Proceedings of the Institution of Civil Engineers—Structures and Buildings, 156, August, 273–281

Historically the management of infrastructure assets has been governed by social, economic and technical constraints. However, in the latter part of the twentieth century, with the advent and growth of the sustainability agenda, it became increasingly apparent that a fourth issue, environment, must also be included in decision-making. Surrey County Council (SCC), as the principal owner of highway assets within its boundaries, is

directly responsible for over 1000 road bridges. To meet the authority's own environmental and sustainability objectives, it is clear that there is a need for knowledge on ways in which the organisation can reduce the environmental impact of its activities. The addressing of this need has called for an entirely new approach to assessing structure management activities. With the adoption of life-cycle thinking, a methodology has been developed to enable environmental comparison of alternative structure management strategies. In the context of brick arch highway bridges, the scope of this paper is to present this method and the findings it can produce. The development of the approach is important for SCC objectives, but also provides insight for the wider civil engineering industry, and gives perspectives on how it may tackle the issue of environment.

Protection of bridge piers using a sacrificial sill

Y. Chiew and S. Lim

Proceedings of the Institution of Civil Engineers—Water and Maritime Engineering, 156, March, 53–62

This experimental study explores the effectiveness of using a sacrificial sill as a pier scour countermeasure. Experiments were conducted under both clear-water and live-bed conditions. Many interdependent parameters affecting the sill performance were systematically examined. The results show that the sill is efficient in reducing the equilibrium clear-water scour depth, reaching a maximum percentage reduction of pier scour depth, %RDP, of approximately 50% under the most favourable condition. The optimum state occurs under the following conditions: (a) the sill is vertical; (b) the sill height is larger than 0.3 times the depth of flow; (c) the clear distance between the pier and sill is 4.4 times the pier width; and (d) the angle of attack is zero. A large angle of attack or flow skewness is detrimental to the performance of the sill. However, this shortcoming may be overcome by installing a sill with a wedge angle of 270° . The efficiency of the sill decreases under live-bed conditions, with the %RDP reducing to approximately 20% at a velocity ratio, U/U_c .

Gateshead Millennium Bridge—an eye-opener for engineering

John Johnson and Peter Curran

Proceedings of the Institution of Civil Engineers—Civil Engineering, 156, February, 16–24

The Gateshead Millennium Bridge over the River Tyne in north-east England is an unique tilting bridge for pedestrians and cyclists. Opened by the Queen in May 2002, the inspirational 105 m span structure subsequently became the first bridge to win the Royal Institute of British Architect's 2002 Stirling Prize for 'Building of the Year'. This paper provides an overview of what has become known as the 'blinking eye' bridge and of the processes adopted to achieve and deliver it—not least the spectacular superstructure installation.

Hungerford Bridge millennium project—London

John Parker, Gareth Hardwick, Martin Carroll, Nigel Nicholls and Daniel Sandercock

Proceedings of the Institution of Civil Engineers—Civil Engineering, 156, May, 70–77

The £50 million Hungerford Bridge millennium project in

London provides two stunning new cable-stayed footbridges across the Thames, one on each side of Charing Cross railway bridge. Effectively it recreates Brunel's 1846 suspension footbridge to Hungerford market, the piers of which remain in the railway bridge structure. Heightened fears over unexploded bombs in the river bed led to a major redesign just after work started but a switch to the NEC contract helped ensure a smooth completion.

Electrification of US opening rail bridges

Roger Wilson

Proceedings of the Institution of Civil Engineers—Civil Engineering, 156, May 83–92

Electrification of the final stretch of the busiest passenger railway in the USA required substantial modification to five existing opening bridges—some nearly 100 years old—to accommodate 25 kV overhead power lines. This paper reports on the development and installation of an innovative, moving catenary system, believed to be the first of its kind in the world, which has breathed new life into an ageing infrastructure.

Crowd-related failure of bridges

Bill Wolmuth and John Surtees

Proceedings of the Institution of Civil Engineers—Civil Engineering, 156, 116–123

Over the past 180 years there has been a significant number of crowd-related bridge collapses around the world. Barring natural disasters or human conflict, they have involved greater

loss of life than any other form of structural failure. This paper reviews crowd-related bridge collapses over the years, providing details of geographic and chronological distribution, form of structure, primary materials, imposed loading, crowd behaviour and the extent of injuries. It concludes that those responsible for bridge design and maintenance must ensure that design details are robust, structures are properly maintained, and crowds are effectively managed.

Highway bridges and environment—sustainable perspectives

Kristian Steele, Graham Cole, Gerard Parke, Brian Clarke and John Harding

Proceedings of the Institution of Civil Engineers—Civil Engineering, 156, 176–182

Civil engineering infrastructure is generally maintained in accordance with safety, economic and technical issues. But what of the environmental impact of such activities? Regular maintenance can have a significant environmental impact—particularly in the case of bridges, where closure can result in traffic jams and lengthy detours. Higher cost but lower maintenance components and transfer of structures to lower-grade sites are possible answers which until now have been difficult to assess. This paper reports on a life-cycle assessment method developed to factor environmental impact into bridge maintenance strategy. Though developed for bridges, it has potential application throughout the facilities management sector.