Ackhurst, Marisa

ISBN 978-0-7277-6361-7

<http://dx.doi.org/10.1680/dvgsqw.63617.175>

ICE Publishing: All rights reserved

Index

- Absi, E 63
- accidental design situation 42, 95–7
- actions/combinations of actions 45, 47, 51–2, 54, 55, 58, 60, 66, 69, 71, 74, 82, 84, 87–9
- actions/combinations of actions 45–6
- accidental design situation 42, 45, 47, 51–2, 54, 55, 58, 60, 66, 69, 71, 74, 82, 84, 87–9
- actions caused by ships 136–40
- actions on the apron 68–71, 85
- backfilling 47, 50, 54, 55–64, 66–9, 71, 77, 81, 82
- berthing 46, 55, 71–4, 83
- block walls 51, 57–8, 62, 64–6, 71, 73, 75–6, 77
- British Standards 45–7, 51, 54–5, 58–60, 62–3, 66, 69, 71–4, 77–9, 81–3, 85–7
- caisson walls 48, 51, 57–8, 64, 65–6, 76
- combinations of actions 84–9
- destabilising actions 45, 47, 52, 93, 102, 107–9, 110–11
- earth pressure *see* earth pressure
- Eurocodes 45, 54, 62, 69, 77–9, 84, 85
- geometry 45, 46, 50–2, 54, 58, 60, 61–2, 68–9, 71, 73
- hydrostatic pressure *see* hydrostatic pressure
- L-walls 51, 55, 57, 58–9, 62
- mooring action 74–7, 89
- partial factors 45, 54, 59, 62, 67, 71–2, 84–9
- persistent design situation 46, 47, 51, 53, 54–6, 57–8, 60, 66, 69, 71, 74, 76, 82, 88, 89
- scour protection 46, 51, 84
- seismic action *see* seismic action
- seismic design situation 47, 51, 54, 55–6, 58, 60, 62, 63, 66, 69, 71, 74, 89
- snow and ice 82–3
- soil pressure 46, 55, 58, 60, 62, 64, 66
- stabilising actions 45, 47, 52, 66, 68, 71, 93, 102, 107–9, 110–11
- structure types 45, 47, 51–2, 54–5, 57–8, 60, 65–6, 69, 73, 76, 82, 83
- thermal actions 46, 83–4, 86, 87
- tidal lag *see* tidal lag
- transient design situation 46, 47, 51, 54, 55, 58, 60, 66, 69, 74, 82, 84, 88, 89
- types of actions 45–6
- ultimate limit states 45, 46, 47, 54, 60, 69, 71, 74, 77, 82, 83, 84, 85–6, 8
- variable action *see* variable action
- wave action *see* wave action
- wave pressures 47–51, 52
- active pressure 60, 62–3, 64, 67, 81, 153
- admixtures 150, 151–2
- aggregates 114, 119, 126, 149–50, 161
- Allsop, NWH 48, 50
- alternative construction materials 1, 138, 161
- architectural features 4, 11, 14
- architectural requirements 15, 34
- armour layer 135–6, 139, 140, 141, 147–8
- backfilling 15
- actions/combinations of actions 47, 50, 54, 55–64, 66–9, 71, 77, 81, 82
- choice of structure 3, 4, 6, 7, 9–10
- design 100, 106, 107, 112, 113, 115, 117, 123, 126, 132, 140, 141–3
- technical specifications and construction aspects 148, 152–3, 154
- base blocks 5, 6, 58, 64–5, 66, 96, 102–3, 105, 108, 155
- bathymetry 15, 152, 154
- bearing capacity 12, 15, 16, 21, 80, 95, 100–102, 103, 105, 107, 147
- bearing pressure 5, 8, 35, 45, 93, 100–103, 106, 132, 140, 154
- bearing/foundation failure 94, 100–105
- bending 122, 123–5, 151
- berth depth requirements 32–3
- berthing action 46, 55, 71–4, 83
- Bishop's routine method 98
- block walls
- actions/combinations of actions 51, 57–8, 62, 64–6, 71, 73, 75–6, 77
- block-on-block sliding/toppling 5, 108–9
- choice of structure 4–7, 12, 13
- design 93, 96, 102–3, 105, 107, 113–14, 126–8, 132, 141–2, 143
- geometry 28, 35–6
- technical specifications and construction aspects 151, 153–5
- bollards 7, 9, 10, 33
- actions/combinations of actions 74–7
- design 102, 109, 110, 122
- technical specifications and construction aspects 157–9, 160
- Bond, A 101
- bonded blockwork 4–6, 51, 75–6, 141–2
- boreholes 16
- breaking waves 7, 13
- actions/combinations of actions 47, 48–52
- broken waves 27–9, 47, 48, 49
- design 129–31, 134–5
- geometry 26–9

- British Standards (BS codes) 1, 39–40, 42
 - actions/combinations of actions 45–7, 51, 54–5, 58–60, 62–3, 66, 69, 71–4, 77–9, 81–3, 85–7
 - design 93, 96, 97, 105–6, 112–13, 114–20, 124, 126, 140, 143
 - geometry 15, 16, 27, 31, 32, 34, 35
 - technical specifications and construction aspects 148, 149, 150
- bulk diffusion 149
- caisson walls 157, 161
 - actions/combinations of actions 48, 51, 57–8, 64, 65–6, 76
 - choice of structure 7–9, 10, 12, 13
 - design 93, 94, 96, 101 102, 106, 111, 113, 122, 128, 142–3
 - geometry 34–6
 - technical specifications and construction aspects 148, 149, 154, 155
- Calabrese, M 48, 52
- capstans 157, 159
- cellular walls 7, 11
- chloride ingress 113, 114, 150, 151
- choice of structure
 - backfilling 3, 4, 6, 7, 9–10
 - block walls 4–7, 12, 13
 - caisson walls 7–9, 10, 12, 13
 - cellular walls 7, 11
 - counterfort walls 9–11, 12
 - L-walls 3, 8, 9–11
 - multi-criteria assessment 11–14
 - structure types 3–14
- circular caisson walls 8
- Classification of Soils and Rocks for the Maritime Dredging Process* 152
- climate change 15, 31
- cloverleaf caisson walls 8
- Coastal Engineering Manual* 48, 83, 93, 134, 135, 140, 147
- codes of practice/guidelines 39–42
 - see also* British Standards/Eurocodes
- cohesive/cohesionless soils 21, 60, 62, 64, 80, 89, 97, 101, 141
- column blockwork 4, 6
- concrete/concrete construction 147, 148–52
 - concrete materials 150
 - concrete reinforcement 147, 152
 - concrete specifications and testing 148–50
- constructability 8, 9, 12, 13
- construction costs 1, 11, 13, 133, 144, 154
- construction joints 127–8, 147
- construction time 12, 13
- cope level 15, 16, 26–8, 31, 32–4, 49, 131, 133
- coping beams 73, 74, 153, 154, 159
 - choice of structure 4, 6, 7, 9–10
 - design 123, 128, 131, 132
 - geometry 15, 16, 31, 33, 34
- Coulomb's approach 62–5, 66, 80
- counterfort walls 36, 154, 155
 - actions/combinations of actions 57–9, 65–6
 - choice of structure 9–11, 12
 - design 122–3, 128, 143
- cover spacers 150
- CPT (cone penetration test) 17, 19–21, 77, 152
- crack widths 9, 114, 119–20, 122–5, 161
- crane rails 7, 9, 10, 45–6, 60, 68–9, 71, 147, 158, 160–1
- creep 97, 127, 132
- Cuomo, G 48, 50
- curing (of concrete) 112, 114, 150, 151
- damping constant 18, 22
- deep slip 40, 41, 94, 97–100
- DEF (delayed ettringite formation) 113–14
- degree of utilisation 93, 95, 97–8, 100, 103, 105–11, 122, 125, 131, 133
- design 93–6
 - backfilling 100, 106, 107, 112, 113, 115, 117, 123, 126, 132, 140, 141–3
 - bearing/foundation failure 94, 100–105
 - block walls 93, 96, 102–3, 105, 107, 113–14, 126–8, 132, 141–2, 143
 - British Standards 93, 96, 97, 105–6, 112–13, 114–20, 124, 126, 140, 143
 - caisson walls 93, 94, 96, 101 102, 106, 111, 113, 122, 128, 142–3
 - deep slip 40, 41, 94, 97–100
 - degree of utilisation 93, 95, 97–8, 100, 103, 105–11, 122, 125, 131, 133
 - design situations *see under* accidental; persistent; seismic; transient
 - filter design 140–1
 - geometrical allowances and partial factors 93, 96–7
 - geometry 95, 96, 112, 113, 119, 123, 128, 131, 134, 136, 137, 140
 - hydraulic failure 111–12
 - L-walls 93, 120, 123, 124, 125, 143
 - loss of static equilibrium 110–11
 - overturning/toppling 94, 95, 97–8, 104, 107–10
 - partial factors 93, 95–8, 102–4, 106, 107, 109–12, 128
 - physical modelling 28, 34, 40–1, 47, 48, 74, 134–5, 136, 144
 - scour protection 93, 128, 133–4, 136–7, 139–41, 144
 - serviceability requirements 113, 128–33
 - soil pressure 100, 101, 102, 104, 106, 107, 109–11, 140
 - sliding *see* sliding
 - stone beds 102, 105, 109, 112, 133, 140
 - structural design *see* structural design
 - tidal drains 112, 133, 141–3
 - ultimate limit states 93–7, 110–11
 - uplift due to buoyancy and/or wave action 94, 111, 112
 - wall joints 112, 141–3
 - wave action 93, 97, 111, 114, 128, 130, 131, 134–6, 140, 142, 144
- design life 42, 93, 115–18, 126, 128, 139, 151
 - actions/combinations of actions 46, 47, 51, 54, 58, 60, 66, 69, 76, 82
 - choice of structure 3, 11, 12, 14
 - geometry 16, 26, 31, 34–5
- design process 1–2, 15, 26, 72, 93, 137, 147

- design thrust 67, 68
 design vessels 15, 32–4, 74, 76, 139,
 designer and contractor experience (multi-criteria
 assessment) 13
 destabilising actions 45, 47, 52, 93, 102, 107–9, 110–11
 destabilising moment 107, 108, 110
 downfall pressures 31, 46, 47, 50–1
 drainage design 161
 dredging and excavation 4, 6, 13, 15–16, 33, 96, 97, 147–8,
 152–3
 dry docks 2, 8, 11, 12, 34, 154
 durability 15, 17, 34, 126, 149, 152
 choice of structure 7, 12, 14
 structural design 112, 113–20, 121
 DWT (dead-weight tonnage) 73, 137, 139
- earth pressure 3, 6, 40, 41, 59, 80–2, 95, 123
 background 60
 classification 59–60
 combinations of actions 84, 86, 88
 formulae 60–5
 geometry 60, 61–2
 structure types 60, 65–6
 worked example 66–8
 edge protection 158, 159
 effective stress analyses 97
 environmental concerns 1, 13, 78
 environmental loads 47, 51, 54, 58, 68, 87
 Eurocodes 1, 39, 42
 actions/combinations of actions 45, 54, 62, 69, 77–9, 84,
 85
 design 93, 95–8, 100, 114, 123–4, 126, 132
 EurOtop 31–2, 41, 129, 130, 131
 excavation *see* dredging and excavation
 expansion joints 9, 40–1, 74, 76, 127–8, 160, 161
 exposure (multi-criteria assessment) 13
- failure mechanisms 93, 94
 fenders 7, 9, 10, 33
 actions/combinations of actions 71–4, 76, 83
 design 122, 136, 137
 technical specifications and construction aspects 147,
 157–9
 filter design 140–1
 FLOODsite 72–3, 129
 formwork 112, 114, 119, 121, 126, 147, 150–2, 153, 155
 foundation beds 9, 15, 28, 29, 55, 58, 105–6, 112, 133–4,
 147–8
 freeze–thaw cycles 113, 114
 function (multi-criteria assessment) 12
 future extensions 13
- geometrical allowances 93, 96–7
 geometry 1, 154
 actions/combinations of actions 45, 46, 50–2, 54, 58, 60,
 61–2, 68–9, 71, 73
 architectural requirements 15, 34
 British Standards 15, 16, 27, 31, 32, 34, 35
 caisson walls 34–6
 choice of structure 5, 10, 13
 construction and design aspects 34–6
 design 95, 96, 112, 113, 119, 123, 128, 131, 134, 136,
 137, 140
 geotechnical investigations 15–16, 17–22
 metocean data 15, 16, 23–31
 operational requirements 15, 31–4
 overtopping 15, 25, 26, 27–8, 29, 31–2, 34
 scour protection 15, 16, 26, 32–3
 site considerations 15–31
 wave action 25, 26–9, 30, 31, 46, 50–2
 geotechnical investigations 15–16, 17–22
 geotextiles 112, 140–3, 148, 154–5
 Goda, Y 27, 29, 47–50, 51–2
 GPS (global positioning system) 153
 granular fill 3, 60, 106
 grout socks 5, 6, 142, 143, 154
- Harris, A 101
 highest astronomical tide (HAT) 27, 55–6, 58
 hollow blocks 5
 horizontal action 3, 72, 100, 101, 103, 106
 horizontal load 82, 101, 142
 horizontal thrust 57, 59, 67–8
 hydraulic failure 111–12
 hydraulic heave 45, 111
 hydrostatic pressure 9, 10, 40, 41, 46, 54, 77, 85, 153
 background 55
 choice of structure 9, 10
 classification 54
 design 100, 101, 119, 142
 formulae 55, 57
 structure types 54–5, 57–8
 worked example 58–60
- ICE Manual of Geotechnical Engineering* 61–2
 impacting waves 13, 22, 26, 28–9, 47–8, 49–51
 impulsive waves 25, 26, 28, 29, 47, 49, 51, 53, 130
 index tests 17, 149
 interface friction 60, 62, 66, 67, 102, 105, 107, 108,
 internal erosion 45, 111–12
 internal friction angle 6, 19, 106
 I-shaped blocks 5, 151
- Jarvis, RJ 135
 Joint exceedance curves 30
 joint probability 29–31, 55, 129, 135
- kerbs 158, 159
 Kerisel, J 63
- ladders 157, 159
 land use requirements 15, 34
 lateral earth pressure 5, 60, 62, 64, 66, 69
 lever arms 49, 50, 52, 54, 57–9, 67–8, 102, 107, 109–10,
 123
 lifebuoys 159
 life cycle costs 13
 line loads 60, 65, 68, 71

- ul style="list-style-type: none;">
- liquefaction risk 77, 80
- loading case 48, 52
- lowest astronomical tide (LAT) 9, 32, 55–6, 58, 142, 159
- L-walls 36, 154, 155
 - actions/combinations of actions 51, 55, 57, 58–9, 62
 - choice of structure 3, 8, 9–11
 - design 93, 120, 123, 124, 125, 143
- magnitude of applied actions 12
- maintainability (multi-criteria assessment) 12, 13
- maintenance 15, 33, 34, 157, 160
 - choice of structure 10, 12, 13
 - design 95, 128, 134, 142
- Marth, R 51
- materials (multi-criteria assessment) 13
- Maynard, ST 135–6
- MBL (minimum breaking load) 75
- McConnell, KJ 28, 29, 47–8, 49, 50, 52
- mean high water springs (MHWS) 27, 56, 58, 114
- mean higher high water (MHHW) 27
- metocean data 15, 16, 23–31
- middle-third rule 106, 107, 108, 110
- mineral additions 150
- mooring action 74–7, 89
- mooring rings 74, 157, 158, 159
- morphology 15
- Muller, G 135
- multi-criteria assessment 11–14
- National Annex 79, 95, 96–7, 123–4
- operational aspects (multi-criteria assessment) 14
- operational requirements 15, 31–4, 159
- outfalls 1, 135, 137, 157, 158
- overtopping
 - actions/combinations of actions 47, 49, 50–1, 55
 - choice of structure 3, 7, 9, 10, 13
 - codes of practice 40, 41
 - design 94, 128–31, 134, 135, 144
 - geometry 15, 25, 26, 27–8, 29, 31–2, 34
- overturning/toppling 35, 40–1
 - actions/combinations of actions 45, 54, 69, 77, 80
 - design 94, 95, 97–8, 104, 107–10
- partial factors 42
 - actions/combinations of actions 45, 54, 59, 62, 67, 71–2, 84–9
 - design 93, 95–8, 102–4, 106, 107, 109–12, 128
- passive pressure 60, 67, 105
- patch loads 68–9
- performance-based methods 114, 149
- permanent action 45, 54–5, 57, 59, 67–9, 71, 82, 85, 101, 111, 132
- permeability 3
 - actions/combinations of actions 54–5, 56–8, 80
 - design 96, 112, 141–2
 - geometry 16, 17, 18, 21, 28
 - technical specifications and construction aspects 148, 149, 150–2, 155
- persistent design situation 42, 95, 96, 97, 101, 102, 104, 107, 108, 111, 125, 132
 - actions/combinations of actions 46, 47, 51, 53, 54–6, 57–8, 60, 66, 69, 71, 74, 76, 82, 88, 89
- physical modelling 28, 34, 40–1, 47, 48, 74, 134–5, 136, 144
- pipings 45, 111, 112, 141
- point loads 21, 51, 69, 75–6, 148, 159
- Portland cement 119, 150
- precast blocks 6, 7, 64, 113, 126, 143, 153, 157
- preloading 4, 7, 9, 10, 132, 140, 148, 154
- prescriptive methods 149
- PROVERBS research project 16, 28, 48
- pulsating waves 25, 28, 29, 46, 47, 48–50, 52, 53
- quick-release hooks 15, 74, 75
- Rankine 58, 62–3, 65–6
- RCPT (rapid chloride permeability test) 149
- reaction forces 72–4
- rectangular caisson walls 8
- reference peak ground accelerations 78–9
- reflecting waves 29, 46
- regulatory compliance 12, 13
- removability (multi-criteria assessment) 13–14
- replacement (multi-criteria assessment) 14
- risk of vandalism and theft (multi-criteria assessment) 14
- rock/rock construction 147–8
 - rock fill 5, 6, 60–1, 77, 97, 100, 102, 140, 143, 147–8
 - rock grading 135, 147
- safety 12, 14, 31, 34, 39, 159, 160
- Sainflou formula 28, 29, 47–8, 49–50, 51–3
- scour protection
 - actions/combinations of actions 46, 51, 84
 - choice of structure 4, 7, 9, 10
 - design 93, 128, 133–4, 136–7, 139–41, 144
 - geometry 15, 16, 26, 32–3
 - technical specifications and construction aspects 147–8, 155
 - see also* toe protection
- seismic action 8, 46, 47, 77, 88, 89
 - background 77
 - classification 77
 - codes of practice 40, 41
 - design approach 80–2
 - formulae 77–82
 - reference peak ground accelerations 78–9
 - seismic performance 77–8
 - structural categorisation 77, 78
- seismic design situation 26, 42, 95
 - actions/combinations of actions 47, 51, 54, 55–6, 58, 60, 62, 63, 66, 69, 71, 74, 89
- seismic zones/seismicity 7, 12, 15, 16, 26
- semi-probabilistic methods 28, 42
- service tunnels 7, 9, 10, 12, 157, 158, 159–60
- serviceability requirements 45, 113, 128–33
- serviceability verification 93, 94
- settlement 15, 16, 40, 41, 161

- actions/combinations of actions 60, 77, 78
- choice of structure 4, 7, 9, 10, 11
- design 93, 94, 122, 128, 130, 131–3, 140, 142, 144
- technical specifications and construction aspects 148, 151, 153–4
- shear modulus 18, 22
- shear reinforcement 124–5
- shear resistance 9, 124
- shear wave velocity 18, 77
- shearing resistance 17, 19, 60, 62, 66, 67, 81, 89, 97, 102–4
- ships, actions caused by 136–40
- single-source principle 54, 101, 107, 110
- site considerations 15–31
- sliding 94, 95, 97, 104, 105–6, 153
 - actions/combinations of actions 57, 66, 69, 76–7, 80, 84
 - block-on-block 5, 108, 109
 - codes of practice 40, 41
 - sliding resistance 97, 105–6, 108
 - worked example 106–7
- slip circle analysis 98–9
- snow and ice 40, 41, 46, 82–3
- soil conditions 12, 64, 77, 80, 153
- soil investigations 12, 16, 101
- soil parameters 16, 17–22, 60–1, 66–7, 80, 104, 111
- soil pressure
 - actions/combinations of actions 46, 55, 58, 60, 62, 64, 66
 - geometry 15, 35
 - design 100, 101, 102, 104, 106, 107, 109–11, 140
- soil stresses 66, 67
- Specification for Ground Treatment* 153
- SPT (standard penetration test) 17, 19–21, 77, 152
- stabilising actions 45, 47, 52, 66, 68, 71, 93, 102, 107–9, 110–11
- stability verification 93, 94, 110
- static equilibrium, loss of 110–11
- stone beds 6, 9, 10, 52
 - design 102, 105, 109, 112, 133, 140
 - technical specifications and construction aspects 147–8, 153–5
- strength classes (concrete) 115–18, 121, 124, 126
- strength verification 93, 94, 97
- structural design 112–13
 - durability 112, 113–20, 121
 - structural member failure 122–7
 - worked examples 120, 122, 125
- structural member failure 122–7
- structure types 1–2, 16, 147, 155
 - actions/combinations of actions 45, 47, 51–2, 54–5, 57–8, 60, 65–6, 69, 73, 76, 82, 83
 - choice of structure 3–14
- surcharge loading 12, 63, 64, 67–8, 69–70, 71, 80, 83, 100–101
- sustainability (multi-criteria assessment) 14
- SWL (safe working load) 74, 75
- SWL (still water level) 27, 29, 46, 47, 50, 51, 55, 57, 63, 66, 68, 88
- technical specifications and construction aspects 147
 - backfilling 148, 152–3, 154
 - block walls 151, 153–5
 - British Standards 148, 149, 150
 - caisson walls 148, 149, 154, 155
 - concrete reinforcement 147, 152
 - concrete/concrete construction 147, 148–52
 - dredging/marine excavation 147, 152
 - earthworks and fill 147, 152–3
 - rock/rock construction 147–8
 - sea or quay wall construction 147, 153–6
 - scour protection 147–8, 155
 - stone beds 147–8, 153–5
 - wave action 148, 151, 155
- The International Levee Handbook* 98
- The Rock Manual* 26, 134, 135, 141, 147
- thermal actions 40, 41, 46, 83–4, 86, 87
- Thoreson, CA 32, 74–5, 83, 159
- tidal drains 7, 10, 54, 58, 112, 133, 141–3
- tidal lag 3, 40, 41, 45–6, 54, 112
 - background 55, 56
 - classification 54
 - combinations of actions 85, 87, 88, 89
 - structure types 54–5, 57–8
 - worked example 58–60
- tilt 66, 68, 77, 78, 94, 128, 132–3, 148
- toe protection 24, 26, 29, 33, 40–1, 105, 112, 133–4, 140–1
 - see also* scour protection
- topography 15, 80
- toppling *see* overturning/toppling
- total stress analyses 97
- total ultimate resistance 101, 105
- transient design situation 26, 42, 95, 96, 97, 111–12, 125
 - actions/combinations of actions 46, 47, 51, 54, 55, 58, 60, 66, 69, 74, 82, 84, 88, 89
- triangular pressure distribution 48, 51, 55
- Tsinker, GP 126
- ultimate limit states 39, 42
 - actions/combinations of actions 45, 46, 47, 54, 60, 69, 71, 74, 77, 82, 83, 84, 85–6, 8
 - design 93–7, 110–11
- underwater work 13, 17, 33, 122
- undrained shear strength 17, 20
- uniform surcharges 65, 68, 70
- uplift due to buoyancy and/or wave action 45, 47–9, 52, 54, 94, 111, 112
- variable action 45–6, 54, 55, 57, 59, 66, 68–9, 71
 - combinations of actions 84–9
 - design 98, 106, 107, 111
- vertical action 100, 107, 111
- vertical load 6, 10, 35, 69, 159
- vertical thrust 57, 59
- vertical vessel motion allowances 33–4
- Vicinanza, D 48, 50
- virtual back 58, 62–3, 66–7
- virtual plane 62–5
- visibility 13, 148, 151
- wall joints 9, 10, 13, 51, 57–8, 112, 141–3, 147, 154

- water flow 6, 55, 140
- water levels 159–60
 - actions/combinations of actions 49, 51–2, 54–5, 57–8, 59, 62, 66
 - design 96, 112, 113, 129, 131, 135, 136, 138, 142
 - geometry 15, 16, 17, 24–5, 26–7, 29–34
 - technical specifications and construction aspects 148, 153, 154
- water pressure 6, 17, 20, 153
 - actions/combinations of actions 45, 54, 57, 58, 59, 64, 66, 77, 80
 - design 97, 101, 132, 140, 144
- wave action 46–7, 55, 57, 85, 157
 - background 47
 - choice of structure 3, 7, 11, 12–13
 - classification of 47
 - design 93, 97, 111, 114, 128, 130, 131, 134–6, 140, 142, 144
 - downfall pressures 47, 50–1
 - geometry 25, 26–9, 30, 31, 46, 50–2
 - structure types 47, 51–2
 - technical specifications and construction aspects 148, 151, 155
 - wave condition 47, 48–50, 51–3
 - worked example 51–4
- wave chambers 1, 12, 157, 158
- wave condition 3, 130, 134, 157
 - geometry 16, 23, 25, 26–31
 - wave action 47, 48–50, 51–3
- wave defence structures 34, 35
- wave pressures 6–7, 47–51, 52
- wind data 23, 25, 26
- Young's modulus 18, 21