Editorial

Nuggehalli M. Ravindra PhD

Professor, New Jersey Institute of Technology, Newark, NJ, USA

As *Emerging Materials Research* completes two exciting and successful years since its inception, I thank the contributors, readers and members of the Editorial Board. I welcome you to the first issue of the journal for 2014.

The gross expenditure on Research and Development, globally in 2013, was about US\$1559 billion. It is anticipated that this spending will increase to about US\$1618 billion in 2014. With China's aggressive commitment to Research and Development, Southeast Asia has become the world's largest region for research investment. Collaborations with research firms in USA and Europe has been on a rise.^{1,2}

During the last three decades, the growth in materials research has been highlighted by the increasing number of articles published. There were about 60 000 articles and reviews published in 2011. Materials research has focused on interdisciplinary areas mainly in nanoscience, which serves as a bridge between physics and chemistry, with a link to biology. Other major areas of research include enhanced visible-light photocatalytic hydrogen production, aggregation-induced emission characteristics and compounds, dye-sensitized and organic solar cells, fuel cells and polymerization. Nanopore DNA sequencing and silicon nanowires for lithium-ion battery anodes are other upcoming areas. Research in electronic properties of single-layer carbon film, that is, graphene, have been areas of continuous research with about 9524 citations from 2006 to 2010. Research in metal-organic frameworks (MOFs) is another upcoming field in materials arena. MOFs have been recently described by Nobel laureate Sir Harry Kroto as, 'molecule-by-molecule assembly of more complex systems with advanced functions at the nanoscale dimensions and as simply 21st century advanced chemistry'.³ 'Electrospun nanofibrous scaffolds for tissue engineering' ranked tenth by citations in materials science from 2004 to 2011, with about 1899 identified articles from 2000 through May 2011. Materials being investigated recently include ductile bulk metallic glasses, negative index materials and bone-like materials for tissue engineering.

At the time of preparation of this editorial, Princeton University celebrated the 90th birthday of Philip W. Anderson by hosting a workshop⁴ marking his scientific accomplishments. It is indeed appropriate that the first article in this issue of the journal focus on superconductors. In the absence of strong pinning, high- T_c superconductors suffer from thermal instability, especially at higher temperatures. According to the Anderson-Kim model, based on thermally activated flux jumps, the net jump rate of individual

fluxoids over pinning barriers is the difference of two jump rates, one with the driving force and the other against the driving force.

The first of the articles⁵ in this issue of *Emerging Materials Research* presents a study on the 'Distribution of Activation Energies in Superconducting BSCCO Tapes' by C. S. Pande, R. L. Holtz and D. J. Gillespie of Materials Science and Technology Division, Naval Research Laboratory, Washington, DC, USA. Earlier studies have shown that collective pinning behavior in high- T_c superconducting oxides can be reconciled to a model of distribution of activation energies, in their thermally activated flux motion. In this article, the authors provide experimental evidence for such a distribution and show that this distribution is lognormal as predicted.

Alkaline texture etching is a standard procedure for manufacturing solar cells with (100) oriented single crystalline silicon wafers as substrates. This is done to reduce reflectance from the wafer surface. Alkaline etching, being anisotropic in nature, results in unique texture on the surface of each crystallographic orientation of silicon. Hence, the reflectance of each grain of a multicrystalline silicon (mc-Si) substrate can be treated as a signature of its crystal orientation. This provides an opportunity to ascertain the orientation of each grain in a mc-Si wafer by the shape of the textures formed on its surface and henceforth, its corresponding reflectance.

The second article⁶ in this issue focuses on 'Reflectance Calculations of Textured Multicrystalline Silicon by Ray Tracing – A New Approach'. This article by D. Guhabiswas, B. Sopori and N. M. Ravindra is a collaborative effort between the National Renewable Energy Laboratory and New Jersey Institute of Technology. In this article, a model that can predict and create surface textures for any arbitrary crystal orientation of silicon upon anisotropic alkaline etching has been developed. The model has been implemented in a computer program written in C++ to perform rigorous ray tracing computations to calculate reflectance curves for textured silicon of any crystal orientation, wafer thickness and texture height. A database of reflectance curves for multiple crystal orientations has been built. This has led to a new and ultrafast method for grain orientation characterization using reflectance of each grain.

In recent years, tungsten has been preferentially chosen and used for a variety of structural applications that necessitate the need for both an exposure and use at elevated temperatures. This is primarily due to its excellent combination of properties that include high melting point, high density, good elastic modulus, adequate resistance to

thermal shock, low coefficient of thermal expansion and good to moderate strength at elevated temperatures.

‘Synthesis and Characterization of Ultrafine Tungsten Samples Produced by Plasma Activated Sintering’, by Kannan Manigandan and Tirumalai S. Srivatsan of the Department of Mechanical Engineering, Division of Materials Science and Engineering, The University of Akron, OH, USA, and T. S. Sudarshan of Materials Modification Inc., Fairfax, VA, USA, is the next article⁷ in this issue. The authors have used plasma-activated sintering (PAS) to densify micron-size tungsten powders to obtain bulk samples. This sintering technique offers the capability of producing bulk samples having a very high density. Using a combination of pressure and temperature, during sintering, several samples were prepared. The extrinsic influence of processing parameters used during sintering, namely, pressure and temperature, on the microstructural development to include the presence, size and distribution of porosity, density, microhardness, nanohardness and stiffness is presented and discussed.

Waste generation inclusive of organic dyes and other coloring material is an inevitable by-product of the rapid and enhanced industrialization and urbanization. These wastes cause serious and irreparable damage to the environment and are not amenable to conventional method of waste treatment. Water used in the industries creates waste water that has the potential hazard for the environment because of introducing various contaminants such as synthetic dyes into the soil and water resources. Organic dyes are harmful to the environment and are too difficult to degrade by conventional chemical methods. Over the past few decades, a significant progress has been achieved in heterogeneous photocatalysis for photodegradation of undesirable organics in aqueous phase. Semiconductors, such as titanium oxide, are the most widely used catalysts in the field of photocatalytic applications.

In this article,⁸ Rahangdale K. Pralhad of Bhawabhuti College, Amgaon, India, discusses the results of ‘Newly Developed TiO₂-2-HABT Advanced Functional Material for Water Treatment’. In this investigation, 2-hydroxyacetophenone-biuret-trioxane (2-HABT) terpolymer was successfully synthesized, purified and characterized. Then, titanium oxide photocatalyst was anchored on 2-HABT terpolymer using molecular adsorption–deposition method. The titanium oxide particles, deposited on the 2-HABT terpolymeric molecules, formed a coating of about 100 nm in thickness. This newly modified functional photocatalytic material was characterized by various methods. An anatase-type titanium oxide was uniquely developed. This new TiO₂-2-HABT photocatalyst exhibited an excellent photocatalytic activity in the photodegradation of concentrated dyes.

The underlying principle of self-compacting concrete (SCC) is that it compacts under its own weight and needs no mechanical

vibration. The fundamental study on the flowability of self-compacting concrete was explored in Japan in the late 1980s. In the 1990s, use of SCC technology spread to Europe and USA. In India, investigation on SCC began in the late 1990s. The specific material properties of SCC can be achieved by the coordination of high deformability and segregation resistance.

Debashis Das and Abhijit Chatterjee of Material and Structural Evaluation Group, CSIR-CMERI, India, present their studies⁹ of ‘Taguchi and Anova Approach for Optimization of Flow Characteristics of Self-compacting Concrete’. Sand-rich self-compacting concrete (SCC) with high volume of fly ash requires specific experimental design for optimized response in freshened state. The analysis of the results of an experimental investigation by Taguchi method for optimization of the effect of size of coarse aggregate and fine aggregate content on the quality characteristics of SCC are presented in this study.

Due to their excellent oil- and fuel-resistant characteristics, nitrile rubber composites find important applications in several industries related to manufacturing of hose, belts, O-ring, cable, gasket, oil seal, printer roller, healthcare products, plastics and so on. However, incorporation of reinforcing fillers into rubber matrix is necessary to achieve optimum mechanical and related properties. Although carbon black is the most widely used filler for rubber, silica is also an important reinforcing filler. The use of silica has several advantages, as it is capable of providing better tear strength, abrasion resistance, ageing resistance and lower rolling resistance to rubber composites.

In this article¹⁰ in *Emerging Materials Research* – ‘Filler–Filler and Rubber–Filler Interactions in Nitrile Rubber/Silica Composites’, Bharat P. Kapgate and Chayan Das of Visvesvaraya National Institute of Technology, Nagpur, India, describe their studies of the effects of surface modification on the filler–filler and rubber–filler interactions in silica-filled nitrile rubber composites. Nitrile rubber composites are prepared with untreated stöber silica, organosilane-treated stöber silica and externally added precipitated silica along with organosilane. Morphological studies show better filler dispersion in composites containing silane-treated stöber silica-filled composites. The studies of the mechanical properties and dynamic mechanical analysis reveal the strong filler–filler interaction in untreated stöber silica filled and externally added precipitated silica-filled composites.

Fibers when used as reinforcement materials in concrete rely on the bond, which is derived as a function of the material strength and the type of frictional grip provided by the fibers. Fibers have various bond strengths; however, all fiber materials such as steel, glass and polymers of varying modulus suffer from a cross-sectional area reduction when under load and this in turn breaks the bond between the fiber and the surrounding concrete, reducing the ability of the fiber to transfer a sustained load.

The last article¹¹ in this issue, by Alan Richardson and Kathryn Anne Coventry of Northumbria University, Newcastle, UK, in collaboration with Riyadh Boussoffara, Ecole d'ingenieurs, Nanterre, France, discusses the 'Performance of Dove Tailed Synthetic Fibers in Concrete'. Synthetic fibers tend to be made from low-modulus materials when compared with steel crack control products, and they suffer a greater diameter reduction and increase in length when compared with steel, for an equal load. Diameter reduction of fibers in concrete causes debonding and eventual failure. Dovetailed fibers are designed to offer additional bond when a diameter reduction occurs under load. This research investigates the bond strength and toughness of a range of widely used commercially available synthetic structural fibers and compares these against novel prototype dovetailed synthetic structural fibers. The findings, by these authors, show large degrees of toughness when using dovetailed fiber technology.

REFERENCES

1. King, C.; Pendlebury, D. A. *Research Fronts 2013*. New York:Thomson Reuters, 2013.
2. Grueber, M.; Studt, T. *2014 Global R&D Funding Forecast. R&D Magazine 2013*.
3. Adams, J.; Pendlebury, D. A. Global Research Report. In *Materials Science & Technology*. New York:Thomson Reuters, 2011.
4. See <http://physics.princeton.edu/indico/internalPage.py?pageId=9&confId=129> for further details. Accessed 14/12/2013.
5. Pande, C. S.; Holtz, R. L.; Gillespie, D. J. Distribution of activation energies in superconducting BSCCO tapes. *Emerging Materials Research* **2014**, 3, 4–9.
6. Guhabiswas, D.; Sopori, B.; Ravindra, N. M. Reflectance calculations of textured multicrystalline silicon by ray tracing. *Emerging Materials Research* **2014**, 3, 10–18.
7. Manigandan, K.; Srivatsan, T. S.; Sudarshan, T. S. Synthesis and characterization of ultrafine tungsten samples produced by plasma activated sintering. *Emerging Materials Research* **2014**, 3, 19–30.
8. Pralhad, R. K. Newly developed TiO₂-2-HABT advanced functional material for water treatment. *Emerging Materials Research* **2014**, 3, 31–36.
9. Das, D.; Chatterjee, A. Taguchi and Anova approach for optimization of flow characteristics of self-compacting concrete. *Emerging Materials Research* **2014**, 3, 37–45.
10. Kapgate, B. P.; Das, C. Filler-filler and rubber-filler interactions in nitrile rubber/silica composites. *Emerging Materials Research* **2014**, 3, 46–51.
11. Richardson, A.; Coventry, K. A.; Boussoffara, R. Performance of dove tailed synthetic fibers in concrete. *Emerging Materials Research* **2014**, 3, 52–66.