A general formula for uniform flow in self-formed alluvial channels

G. LACEY & W. PEMBERTON

Mr A. R. Thomas, Consultant, Binnie & Partners

Nearly half a century after their introduction, through an Institution paper which gave rise to lengthy discussion, during which time there have been considerable advances in the same field, the Lacey formulae are still widely used, especially in the design of irrigation canals. This is a measure of their value to the profession and, by the same token, any revision of the formulae is a matter of importance and should be subjected to close examination before acceptance.

31. The revisions proposed in the Note consist, first, of a modification of the slope relationship and, second, of the introduction of gravity, density and viscosity to render the equations dimensionally homogeneous. The two are distinct and can be considered separately.

32. In their original form, the Lacey formulae could be summarized by three equations: one relating mean velocity and depth of flow, another relating width and discharge and the third relating mean velocity, depth and longitudinal slope. The first two were derived from observations on canals; the third was derived by the use of Manning's formula to introduce slope, but was later^{10,11} verified by plots of $V/R^{1/2}$ against $R^{1/2}S$ and V against R^2S covering a wide range of bed material and channel size, including some rivers, apparently confirming the validity of equation (13) over the whole range.

33. The Lacey formulae are essentially empirical in derivation and if equation (13) is to be replaced by the revised relationships for classes A to D it is necessary to consider them in the context of all the relevant data. The plots in Figs 3–5 are convincing in relation to the data used, but what of the data previously plotted by Lacey^{10,11} which apparently confirmed equation (13)?

34. Turning to the physical interpretation, the comparison between the geometry of the curves of Figs 1 and 2 is ingenious and interesting. Some years ago I suggested,¹¹ in the context of sediment bearing channels of various particle sizes, that a transition in the physical law should be expected at a change in the fluid drag function, which in the case of quartz particles took place in the range 0.1–3 mm dia., as may be seen from Fig. 2. That this transition might be reflected in the formulae is therefore not unexpected, although it might have been more readily understood if it had occurred in the relationship between f and sediment particle size. As suggested by White¹² and Rouse¹³ it seems reasonable that movement of sediment in the process of pick-up and deposit should be governed by its fall velocity rather than by its particle size. Therefore f should be a function of V_s rather than of diameter. A preliminary plot of limited data shows that $f = 0.45 V_s^{1/2}$, where V_s is fall velocity in cm/s, may give a fair practical indication of f for a given bed material under conditions of applicability of the Lacey formulae. One such condition is a significant but small rate of sediment transport. At higher rates of transport, f increases and all the Lacey equations must be affected.

35. Returning to Figs 1 and 2, since $V/R^{1/2} \propto f^{1/2}$ and assuming that $f \propto V_s^{1/2}$ a connexion can be seen between Figs 1 and 2 which helps to clarify the Author's analogue, although $V/R^{1/2}$ corresponds to $V_s^{1/4}$ rather than to $V_s^{1/2}$. Again although $R^{1/2}S$

DISCUSSION

increases with grain size, it is not clear why it should be proportional, as implied here and as Lacey has stated to be the case.¹⁴ As far as I am aware, no supporting data plot have been published. It is evident that R , S , the height of bed forms and the size of bed material are related, but the relationship is known to be complex and sensitive. The random variation of bed forms may be a cause of the wide scatter in some data plots.

36. It is unfortunate that the Authors attempted to provide dimensionally complete equations in the absence of supporting data or physical argument. No data in which g or V have been systematically varied have been presented or presumably used in the derivations. Application of dimensional theory to complete the equations is dangerous without a physical basis. However, in the case of sediment transport in straight uniform channels at low Froude number there is one simple physical rule which can be applied, as I outlined in discussion on Lacey's 1958 paper.¹⁵ There is on the average no unbalanced acceleration of the fluid, and so gravity can enter the equations only when coupled with slope or with the apparent density of submerged sediment, and then only in the form of gS or $g(\rho_s - \rho_f)$ respectively, where S is the energy gradient and ρ_s and ρ_f are the densities of sediment and fluid respectively. None of the equations (5)–(7), (9), (11), (12), (14) and (16) satisfies this check. In practical applications no one will welcome the extra labour of calculating $\nu_* g$, nor should this be necessary. If the practical purpose of the introduction of g and ν_* into the equations were only to facilitate conversion to metric units, the Authors would be on safer ground if they used a single coefficient in each equation and stated its dimensions.

37. In § 13 the Authors use another analogue in their suggestion that the Blasius formula for pipes should apply to channels in fine alluvium. The purpose of this is not clear as the boundary conditions are different in the two cases.

38. A curious omission in the Note is any mention of sediment load as a factor in the equations. The early Lacey formulae contained no parameter for sediment load, but as they were derived from data of canals with moderately active beds coupled with a small sediment load, this was the condition in which they were intended to apply. It is presumed that the formulae presented in this Note are similar in this respect. Are all the data used consistent with this condition?

39. Since the appearance of Lacey's first paper,¹ I have valued and used the regime formulae, believing that they came very close to true representation of the conditions of stability in alluvial channels with low sediment loads. I see no reason now to change this view in the context of the parameters tested by data. If the revised slope formulae are shown to be supported by the data, they will represent an advance to be used in design. The doubts over the dimensionally complete equations need not detract from the practical value of the formulae, and it is hoped that the Authors will in due course provide a complete set of revised equations with simple coefficients in both Imperial and SI units.

Mr G. R. Hoffman, Sir M. MacDonald & Partners

The number of variables involved in the definition of uniform flow in self-formed alluvial channels, or regime theory, and the fact that most of the available data omit observations of one or more of them has made the derivation of general relationships between them extremely difficult. Problems also arise in connexion with such factors as cohesion of bed and/or bank material, assumptions in respect of 'regime' or 'dominant' discharge (at which the proposed relationships between the variables apply), the definition of 'effective' sediment diameter, and the sediment charge and associated bed formations (ripples or dunes). The effects of these factors are reflected in a confusing scatter of observed points, to such a degree that the uninitiated dismissed past attempts to rationalize the data as mere juggling with empirical relationships.

41. For any advance in the understanding of the subject it was clearly necessary

to derive some basic framework for the interdependence of the variables which could be generally accepted as applicable in the ideal case. Departures from the ideal in actual practice could then be interpreted correctly and research could go forward on well defined lines.

42. It appears to me that the Authors have now provided this framework and that it represents the most significant advance in this field since Lacey's first paper on the subject in 1930¹ or his paper in 1958,¹⁶ for which he was awarded a Telford Gold Medal. The analogue presented applies over such a wide range of conditions, both in natural rivers and in canals, that its validity is difficult to question. The formulae presented in equations (5)–(7), once generally accepted, will provide the starting point for further advances in the understanding of this important subject.

43. It would be interesting to have the Authors' views on how other apparently conflicting theories fit into the now neatly defined general picture; further discussion of the approach of Blench⁷ and of the implications in the derivation of the Manning equation from the regime equation (§ 14) would be valuable; also, in § 19, the implications of the suggestion that the sediment size criterion C_s may be constant throughout the complete sediment size range could be elaborated; further discussion of the conditions under which the shape factor E (§ 21) is involved would be of interest. It may be that the new approach proposed would be more readily accepted by those not familiar with the subject if more detailed information on the sources of the data used, as well as some of the more important data, could be given.

44. The Authors have reduced the general formula of equation (2) to particular equations, which form chords to the curve in Fig. 1, and which can be used in the practical application of the theory. They can be summarized as shown in Table 1.

45. The particular equations apply to different ranges of sediment diameter and for classes A, B and D figures have been presented showing how the available data fit the proposed equation. In the case of class C it is stated that no similar figure is included, yet no reason is given for this. For the sake of completeness could the Authors present this figure?

46. Particular lines for future research are apparent from a preliminary study of the Note. Among them may be mentioned

- (a) the relationship between m as determined from the sediment size equation and the particle size distribution of the sediment in which the channel is formed

Table 1

(a) General formula $V = K \frac{S^{(n+1)/2}}{(v_*g)^{n/3}} R^{(n+1)/2} S^n$

(b) Particular equations

Class	Sediment range, mm	Value of n	Equation
A	$m < 0.2$	1	$V = K_1 R S$
B	$0.2 < m < 0.6$	$\frac{1}{2}$	$V = K_2 R^{3/4} S^{1/2}$
C	$0.6 < m < 2.0$	$\frac{1}{3}$	$V = K_3 R^{2/3} S^{1/3}$
D	$2.0 < m$	$\frac{1}{4}$	$V = K_4 R^{5/8} S^{1/4}$

(c) Sediment size equation

$$m = \frac{S^{1/2} (v_*g)^{1/3}}{g C_s} R^{1/2} S$$

DISCUSSION

- (b) the effect of particle shape on application of the formula
- (c) dependent on the results of (a) and (b), the development of a relationship between n and m to produce a general equation
- (d) the effect of cohesion on application of the formula
- (e) the effect of sediment charge on application of the formula.

47. The exhaustive analysis made on past, incomplete, records has probably now been carried as far as is possible. It is suggested that further advance in this field is unlikely to be possible except by collection and analysis of new, comprehensive data.

48. It would be interesting to have the Authors' views on priorities for future research and the essential observations which should be made in collecting data for further analysis.

Mr F. G. Charlton, Hydraulics Research Station

Of particular interest is the extension of the family of flow formulae to include rivers with gravel beds. This is an area of the subject about which there is little information; many of the recorded observations are unreliable and nearly all are deficient in some respect, making appraisal difficult. With these limitations in mind, a purification board in Scotland and several river authorities in England and Wales are co-operating with the Hydraulics Research Station in a programme to gather data from selected rivers with gravel beds.

50. In publications on regime theory it is often stated that channel cross-sections may be uniquely determined for a given discharge, sediment diameter density and concentration, provided the sediment is loose and incoherent. This is probably true for most artificial canals, but with natural rivers caution is necessary as the history of the channel may have an effect on the final hydraulic geometry. This has been shown by the Hydraulics Research Station. After a study of alluvial channels in fine sand, which developed from a straight channel initially too narrow,^{17, 18} the resulting section and pattern formed from a channel initially wider than previously required was observed. The channel section was less deep and wider, and the pattern tended towards the braided type but had a serious thalweg of the same wave length as the narrower channel carrying the same discharge. The channel pattern also affects the cross-section;¹⁷ at bank full flow meandering channels are wider than straight channels at the same discharge. It is thus important to remember that deviations from the basic regime geometry due to history and channel alignment are possible and natural.

51. The Authors have stated that at low stages the largest sediment particles are overlain by those of smaller size. While this is generally true, in rivers with gravel beds coarse material may overlies finer material, as I have observed in some rivers in Nepal, and frequently large isolated shoals of sand may be observed. Kellerhals¹⁹ has also described an experiment in which he observed sand moving along with stones in the vicinity of the bed and in which stones rolled over sand deposits. It appears, therefore, that in gravel rivers the movement of the various sizes of bed material is complex, and more data on this subject are necessary.

52. A recent examination by the Hydraulics Research Station of the parameter V^3/W_s , deduced initially for channels with hydraulically smooth banks,²⁰ using data from gravel rivers indicated that there was no acceptable correlation. Kellerhals¹⁹ reached the same conclusion. Other approaches are therefore necessary if equations describing the geometry of gravel rivers are to be deduced; hence the Authors' family of formulae which include rivers with gravel beds is of great interest. Their equations in Fig. 6 have been compared with the following, deduced from equations developed by Kellerhals¹⁹

$$V = 10.8d_*^{0.15}R^{0.29}S^{0.19} \quad . \quad . \quad . \quad . \quad . \quad . \quad (19)$$

Fig. 7

where $d_* = A/W_n$. If $d_* = R$ this may be reduced to

$$V = 10.8(R^{2.33}S)^{0.19} \quad (20)$$

which is applicable to dominant discharge conditions. Bhowmik²¹ reduced a similar equation which, if depth may be taken as equal to hydraulic mean depth, may be expressed as

$$V = 10(R^{2.5}S)^{0.167} \quad (21)$$

The equations proposed by the Authors are

$$V = 13.1(R^{2.5}S)^{0.25} \quad (22)$$

$$V = 9.34(R^{2.5}S)^{0.25} \quad (23)$$

53. However, in spite of this similarity equation (4) may require slight modification. Plots of $V/R^{0.5}$ against $R^{0.5}S_*$ show that data from rivers with gravel beds (class D) may occur in the areas designated class C and even class B. This suggests examining the relation between $R^{1/2}S_2$ and m . The Authors' views on the choice of a typical representative particle size for m would be appreciated, as recent studies at the

Fig. 8

Hydraulics Research Station suggest that there appears to be no obvious choice of any one particle size.

54. A plot of $R^{1/2} S_*$ against the particle size such that 90% of the material is finer (Fig. 7) suggests that for field data

$$R^{0.5} S_* = 0.026 m_{90} \quad (24)$$

or

$$R^{0.5} S_* = 8 D_{90} \quad (25)$$

Using the median size to represent the bed material (Fig. 8)

$$R^{1/2} S_* = 0.049 m_{50} \quad (26)$$

or

$$R^{1/2} S_* = 15 D_{50} \quad (27)$$

where m_{90} and D_{90} are the particle sizes such that 90% of the material is finer than this size in millimetres or feet respectively. The symbols m_{50} and D_{50} may be similarly defined.

55. It is interesting that in Figs 7 and 8 the points which appear nearest to equation (4) are those from laboratory data usually with low values of the ratio of depth to particle size. The data of Leopold and Wolman²⁴ which lie between lines I and II are from rivers mainly with low values of depth to particle size (usually less than about 4).

56. In rivers with sandy beds the ratio of depth to particle size is normally large but this is not the case in many gravel rivers. Current studies show that below a ratio of about 6 scatter of plotted available data makes simple correlation unsound. The Authors' views on the magnitude of the ratio of depths to particle size above which their equations for class D materials are valid would therefore be appreciated.

57. Recent studies at the Hydraulics Research Station using the limited data available suggest that the equation of Kellerhals¹⁹

$$\frac{v}{\sqrt{(gRS)}} = 6.5 \left(\frac{d_*}{D_{90}} \right)^{0.25} \quad \dots \dots \dots (28)$$

provides an acceptable equation for practical use, accepting some scatter of the data. Equation (22) may be transformed using either equation (4) or equation (24). These produce equations

$$\frac{v}{\sqrt{(gRS)}} = 3.11 \left(\frac{R}{D_{90}} \right)^{0.25} \quad \dots \dots \dots (29)$$

$$\frac{v}{\sqrt{(gRS)}} = 7.75 \left(\frac{R}{D_{90}} \right)^{0.25} \quad \dots \dots \dots (30)$$

respectively which support the view that equation (4) should be re-examined.

Mr M. J. Snell, Lahmeyer International, Frankfurt

The title of this Note with Mr Lacey as one Author could lead one to expect a paper to "liberate" the regime theory from the colossal burden of misleading... "information", as Prus-Chacinski pleaded in 1970,²⁷ or a pragmatic guide to the design of stable unlined earth channels. In fact the Note's aim is neither of these, but it is of great interest and helps to clarify the matter of friction formulae.

59. It deals mainly with friction formulae connecting V , S and R . The relationships are all of the form

$$V = KR^a S^b$$

with the values of a and b given in Table 2. The wide range of indices, even when related to ranges of soil grain size, is somewhat bewildering to the uninitiated. The plot of $V/R^{1/2}$ against $R^{1/2}S$ in Fig. 1 seems to offer some unity. This entirely empirical figure follows the traditional method of grouping variables in some inspired way and plotting them. However, the Authors then go further by splitting the figure into

Table 2

Equation	a	b	Agreement with Lacey's $a=(b+1)/2$
Phillips (Authors, class A)	1	1	Yes
Blasius	5/7 (0.714)	4/7 (0.571)	No
Authors, class B	3/4 (0.750)	1/2 (0.500)	Yes
Manning	2/3 (0.667)	1/2 (0.500)	No
Authors, class C	2/3 (0.667)	1/3 (0.333)	Yes
Authors, class D	5/8 (0.625)	1/4 (0.250)	Yes

DISCUSSION

four ranges and fitting four straight lines. For class A, fine sand, the data shown in Fig. 3 fit Phillips' $V = KRS$ well, but for class B the two straight lines with arbitrary shift in Fig. 4 seem to fit the data less well than the curved line of Fig. 1. Since the whole process is empirical would it not be better to use the curved line, rather than to strain the correlation by seeking not only constant but exact fraction indices? The use of such fractional indices in empirical correlations (dating probably from Lacey's replacement of Kennedy's $V = KD^{0.64}$ by $V = KD^{1/2}$) has perhaps been partly responsible for the subsequent attempts to develop a theoretical derivation for regime relationships.

60. The practising engineer often finds himself having to design a channel, perhaps in a preliminary manner for a feasibility study, without the benefit of extensive measurements on nearby similar channels. The regional regime approach is then of little help. He needs three criteria to choose slope, width and depth. Either Lacey's or Blench's version of the regime theory gives three equations which imply respectively a friction formula $V = F(R, S)$, a width or side stability criterion, and a depth or bed stability criterion. However, the published guidelines on choice of coefficients for a particular soil are so imprecise and mutually inconsistent that one can only deduce a range of values for each variable. This applies particularly to the slope for a given flow, for which the extremes of the range may show a ratio of 4 or more. The fact that authors on the regime concept have used at least five different friction formulae, sometimes three at once, contributes to the uncertainty. Many engineers prefer Manning's formula because there is plenty of detailed published guidance on the choice of the coefficient.

61. In practice the range of slope values produced by the regime theory often corresponds to the reality of the design situation; the designer wishes to choose within a range according to whether head loss or excavation or land take is to be minimized. Although the regime theory postulates a unique solution for each flow/sediment/canal material combination, the range of suggested coefficients yields instead a limited range of solutions (as does the tractive force approach) within which the designer must choose on other grounds.

62. It is hoped that someone who has the time and energy required will distil from the 40 years' regime theory research and discussion a simple practical method of designing unlined channels, in situations without extensive regional data. It may be impossible, but if it can be done it will earn the gratitude of many for whom similitude and minimum entropy are fascinating but useless.

Mr P. Ackers, Consultant, Binnie & Partners

Largely as a result of studies by Lacey over many years, it has long been recognized that the geometry of stable channels, whether they are man-made canals in alluvium, rivers, estuaries or tidal inlets, could be related to the flow they carry through regime equations. Experimental and field studies over the past forty years have provided many such equations, usually applicable to a limited range of conditions, although in some cases their authors had not appreciated their limitations. The present Note is therefore a considerable advance in that it seeks to bring coherence and generality to the system of equations.

64. The Authors put forward a new hypothesis or analogy based on the similarity of plots of $V/R^{1/2}$ against $R^{1/2}S_*$ for regime channels and of $V_s^{1/2}$ against m , the diameter of the sediment which comprises their boundaries. An impressive quantity of field data is used to demonstrate the reasonableness of the conclusion that, breaking the sediment into four size zones, the slope of the fall velocity graph provides also the exponent n in their general formula equation (1). I have also sought physical explanations of channel regime, and in 1964 reported on experiments carried out at the Hydraulics Research Station.²⁸ The hypothesis I put forward then was recently restated as follows:²⁹

'A straight channel which adjusts its width, depth and slope to achieve stability for a given supply of fluid and sediment is defined by these three geometric factors. To predict these values, three independent equations are needed, and in this context independence implies formulae describing three relevant but different physical phenomena. The appropriate phenomena appear to be:

- (i) Hydraulic friction
- (ii) Sediment transport
- (iii) Stability of the banks.

'If we had a complete understanding of channel friction, sediment transport, and the problem of bank stability (soil-mechanics stability no less than direct erosion by the flow of water), then the three "formulae" for these processes could be used to define completely the regime geometry of an alluvial channel. They could, alternatively, be combined algebraically to yield equations expressing width, depth, and slope in terms of discharge. These would include coefficients—perhaps complex ones—representing the influence of the many variables, i.e. bed form, sediment size, grading and specific gravity, fluid properties, and relevant soil properties for the bank material.'

65. The Hydraulics Research Station experiments undoubtedly confirmed that the equations relating geometry (width, depth and slope) to discharge could indeed be derived from relationships which were more fundamental, in the sense that they described identified physical processes. Partly because of this link, recent research on sediment transport at the Hydraulics Research Station has aimed at developing a simple, yet accurate, equation describing sediment transport. Some of the Author's comments might equally apply to that study, yet other aspects of the Note are at variance with its conclusions.

66. The similarity is in the statement in § 19 that 'when the sediment is fine it is all suspended, and alternatively when it is very coarse there is a close approach to rigid boundary conditions'. My new approach to sediment transport, developed with White,³⁰ starts from the twin premises that

- (a) a fine sediment is transported primarily in suspension, and hence the governing variables are the overall turbulent energy of the stream and the work rate implicit in keeping the transported sediment in suspension against the action of its fall velocity
- (b) a coarse sediment is transported primarily as a bed process, and hence the governing variables are the net shear applied by the flow to the granular surface (evaluated as if the boundary were rigid) and the work rate implicit in sliding, rolling or saltating the sediment at the bed.

67. These principles lead to two different dimensionless groupings of the variables, and it was then hypothesized that there would be a transitional range of sediment sizes which could be represented by taking the product of the alternative fine and coarse sediment parameters, raised to the powers n and $1-n$ respectively (not the Authors' variable n , although there is some analogy). The hypothesis was tested by a non-subjective, computer-based optimization that evaluated n and several other coefficients, using previously published data from flume studies. Indeed the optimum value of n varied as predicted and the fine sediment hypothesis was found to apply to sand of 0.04 mm or less and the coarse sediment hypothesis to sand of 2.5 mm or more. The Authors' classes A, B and C would thus be transitional, and according to reference 30 the full suspension mode of transport would be restricted to those silts and clays commonly regarded as providing the wash load.

68. The parameter that was developed³¹ to describe sediment size—a dimensionless sediment diameter—is

$$D_{gr} = D_{50} \left\{ \frac{g(s-1)}{v^2} \right\}^{1/3} \quad . \quad . \quad . \quad . \quad . \quad . \quad (31)$$

DISCUSSION

where s is the specific density of the solid relative to that of the fluid. ($D_{50} = m \times 10^{-3}$ in the Authors' notation, for SI units elsewhere.) This dimensionless sediment diameter can be derived from the parameters for settling velocity, or from the Shields parameters for bed movement, or from similarity considerations if viscous forces are related to the immersed weight of an individual grain.

69. Here there is a difference from the Authors' incorporation of viscosity and gravity into their equations. Unless there is a free-surface effect (and this is possible only in steep streams carrying coarse sediment at shallow depth), gravitational acceleration may only appear multiplied by $s-1$ as in equation (31) or multiplied by the gradient S . The former association arises from the relevance to sediment movement of the immersed weight of a particle, and the latter from the stream's energy degradation rate which provides the motive power. The Authors' use of $v_*g = vg/(s-1)$ and gR appears not to have any physical foundation, in the absence of confirmation from data for materials other than sand. The parameter D_{gr} has been fully confirmed by data for lightweight sediments.³¹

70. It is not clear what the physical significance of the analogy suggested in the Note might be. The stream velocity V , the shear stress at the bed gRS or the stream power $gRSV$ might be expected to be related to sediment size in a regime channel. In fact, the implication of the research described in reference 31 is that V is relevant for coarse sediment, gRS for fine sediment and a combination of them for transitional sizes, passing through $gRSV$ for 0.15 mm sand. Have the Authors any suggestions regarding the meaning of $R^{1/2}S_*$ and $V/R^{1/2}$?

71. Did the Authors test the possibility of finding other, perhaps similar, analogies by plotting other combinations of R , S and V than were used in Fig. 1? It is interesting, for example, that multiplying both variables by $R^{1/2}$ would give a plot of V against RS , a test of the Chezy equation. If on this basis a similar analogy existed, it would imply that the ratio of channel velocity to fall velocity was the same as the ratio of shear stress to the weight of a layer of grains, which would be physically plausible.

72. Can the Authors comment on the relationship of the equations given to channel resistance and sediment transport formulae? It is interesting that the class B equation has the form of a resistance equation, appropriate to large relative roughness values such as occur in duned channels or small rippled bed channels. A similar equation was deduced for experimental channels in reference 28.

Dr T. M. Prus-Chacinski, Partner, C. H. Dobbie and Partners

The Authors have once again presented river engineers with a useful amplification of Lacey's regime theory as applied to natural rivers. The formulae represented in Figs 3-6 describe the regime velocity as

$$V = KR^n S^m \text{ ft/s}$$

where K , m and n vary according to the size of alluvial sand or silt of the bed of the river. I believe this is a most valuable addition to the regime expressions because it provides a direct powerful check on the value of the silt factor f which is almost always troublesome. In most cases I tend to apply the regime expressions in their simplest form. The results are usually satisfactory and sometimes even spectacular.³²

74. I believe that many additions to Lacey's original regime expressions which have been published by several authors during the past fifty years, tend to cloud the simplicity of Lacey's theory rather than improve on it. The Authors' addition does not belong to this category and therefore it should be welcomed by all practical engineers.

75. In § 28 the Authors seem to offer an apology for the past mistakes. I should like to digress a little in the hopes of helping young engineers who cannot sort through all the papers which have been written on Lacey's theory over the past fifty years.

76. Until the end of the Second World War Lacey's theory was applied only in

the countries of the then British Empire. In India and New Zealand it was applied in Lacey's original form. In Egypt and the Sudan it was applied with local variations. The Americans were rather sceptical and the theory was virtually unknown in Europe and it certainly was not applied there.

77. In the 1930s the Russians started large irrigation works in Russian Turkestan. The disastrous failures of many of their irrigation channels forced Russian engineers to devise their own form of the regime theory which differs in some important aspects from Lacey's theory but is similar to it in many other aspects. The references (all in Russian) are too numerous to be quoted. A 'borrowing' from Lacey is probable but this is not important. The Russian variations of the regime theory seem to work reasonably well.

78. After the end of the Second World War, the dispersal of British irrigation engineers, mostly from India, resulted in a better appreciation of Lacey's theory in all English speaking countries (perhaps with the exception of Australia). As a result there was, and still is, a sustained effort in research both in the laboratory and in the field in the USA, Canada and in the UK, particularly at the Hydraulics Research Station.³³⁻³⁵ Ackers²⁹ indicates that the future fortunes of the regime theory are in good hands in the UK and one hopes that the research carried out at the Hydraulics Research Station will be sustained.

79. Meanwhile the value of Lacey's theory has been discovered and appreciated by geographers and geophysicists for their own work. This results in a flood of papers which may be of value if by chance they are read by a skilful engineer.

80. All the research and many papers have added little to the original theory and later modifications by Lacey himself. An exception is the concept of the bankful discharge of natural rivers which has proved very useful.

81. The information about the regime theory has spread all over the world. I have recently noticed two papers which indicate the interest in Poland.^{36,37} These may have been influenced by reference 38 but they are certainly strongly influenced by recent Russian papers (e.g. reference 39) which are numerous and well informed about Lacey's theory.

82. At present it may be said with confidence that as worldwide information on the behaviour of natural rivers gradually becomes collected and available the regime theory will become, within the next decade, a general purpose tool for all river and irrigation engineers. Indeed, it is likely that the regime theory is the only tool which is generally useful. Admittedly this tool must be used with discretion and skill, but this is common throughout engineering fields. Also, although laboratory studies are helpful, in my opinion the only place to study rivers is at a river.

83. The progress of civil engineering theoretical hydraulics, as opposed to fluid mechanics, since the times of Prandtl has not been spectacular, to say the least. How can one deal with a hydraulic theory with a mobile bed of a river if one cannot calculate from first principles the resistance to turbulent flow in a straight, smooth, circular pipe?

84. A quotation from a recent paper⁴⁰ is sobering: 'What is the true significance of the free surface? Can a liquid propagate a shear wave if the frequency is high enough? The whole field of liquid dynamics is imperfectly understood. Perhaps most important of all at the moment: do any of the theories describe liquids at all? Despite apparent successes they sometimes, like the Borne-Green equation, seem mere mathematical expediency. There is still doubt.' Indeed there is doubt, but anybody who dares to write the Reynolds number as the ratio of velocities will know without doubt that liquids propagate a shear wave. However, this knowledge will not be useful because at present one still cannot calculate from first principles virtually anything in turbulent flow of water (not to mention the mobile bed of a river). This should not worry engineers unduly.

85. American astronauts have landed on the moon several times and, although they went there in a spaceship propelled by a stream of high energy particles, nobody

knows what energy is. Indeed nobody knows whether it is possible to discover such knowledge.

86. The beauty of the regime theory is that it cuts across the physical and scientific difficulties of mobile bed hydraulics and that, in so doing, it provides the river engineer with a powerful tool. This is due mostly to Lacey's work.

87. I think it is time the regime theory was included in the graduate curriculum of civil engineering departments in British universities. One may also hope that a British book on regime may appear soon.

88. In view of the comments in §§ 75–86 the Authors' apologies in § 28 are not necessary. The mistakes, if any, made by Lacey in the past were more than compensated by the accurate statements made by him in his papers. The Authors should have the gratitude and congratulations of all practical river engineers on the present Note.

Professor S. Sugio, Department of Construction Engineering, Tokushima University, Japan

The Authors offer two attractive statements: the mean velocity is well expressed by a single continuous curve with the $V/R^{1/2} - R^{1/2}S_*$ relation over the entire range of sediment size of bed materials, and the magnitude of $R^{1/2}S_*$ is nearly equal to the sediment size as shown in equation (4). Classifying mean velocity formulae into four typical groups depending on the sediment size, they add a successful contribution to Lacey's general formula (8). At what stage should R be selected when the stage of a river with gravel and sand bed varies considerably, S_* remaining almost constant?

90. In § 11 what does 'considerable element of discontinuity between classes A and B' mean? I think the existence of such discontinuity seems reasonable because in meandering rivers bend effects tend to give additional resistance to flow and accurate measurements, especially of water surface slope in low water, are hard to obtain.

91. The Authors referred two rivers in Japan. However, the Liao Ho River is not in Japan but in Manchuria, now the People's Republic of China.

92. According to Fig. 5, the Liao Ho River (at Wafumo Gauging Station) belongs to class D, for which the proper sediment size must be larger than 2 mm from Fig. 2. However, the mean sediment size reported by Nagai² is as large as 0.673 mm and $d_g = 0.554$ mm. This yields an unfavourable result compared with the Authors' statement.

93. It is interesting that equation (4) is applicable to many existing rivers, but is the sediment size the only major factor governing the mean velocity? For example, consider a river with bed slope S_* almost constant with mixed sediment of various sizes. In low water the sediment of much smaller size than the mean grain size can be moved by the tractive force exerted by the flow. As the flow discharge increases the sediment size of bed material which can be moved tends to become larger causing the increase in sediment transport rate. According to my analysis, when the flow discharge becomes so large as to cause 90% of all bed material to move the bed form will change, for instance, from dunes to ripples for group 2 rivers, resulting in the appreciable change in the resistance to flow. Therefore, it seems reasonable to consider that the property of sediment distribution curve and the maximum sediment size which can be moved by the tractive force would play the major role in determining the mean velocity formula.⁴¹

94. The Authors' conclusion that it is fruitless to seek one simple exponential general equation of the Manning type applicable to the entire range or class of sediment in alluvial streams is correct. Their proposal is to recommend the mean velocity formula, equation (1) classified into four classes depending on the sediment size, whereas my method is to use four parallel formulae, $V = KR^{0.54}S^{0.27}$, in which the magnitude of K is classified into four groups depending on the various bed forms.

95. The Authors deal only with the data in which changes of bed forms did not occur as the flow discharge changed, but it should be noted that in some rivers, such as the Watari River and the Kuma River in Japan, changes occur during flood—

from dunes to ripples. In the Rio Grande and the Shira River another sort of change occurs—from ripples to transitions. These phenomena are analysed by the investigation of the relation between the tractive force of the flow and the sediment distribution curve of bed materials as shown in reference 41.

Dr T. Blench, Emeritus Professor of Civil Engineering, University of Alberta

My comments depend on the following personal views. The original Lacey regime theory was based on coverage of all data available at the time, analysis of channel groups within each of which the time-average water sediment complex could be assumed fairly uniform, fairly well known formative discharges and a policy of representing data plots by equations that, within the limits of statistical significance, had simple indices, and so might express physical laws for the simple circumstances behind the actual rather complex ones. The evaluation of data was helped by Lacey's 20 years of irrigation canal experience. The canals were characterized by duned sand beds, a small range of bed material sizes, unmeasured but small bed load charges and enough turbidity during the three river flood months to alter rating curves appreciably.

97. The equations that evolved—three basic ones corresponding to self-adjustment of breadth, depth and slope—make physically suggestive statements that I would word on the following lines³⁵

'For duned sand-bed canals with small bed-load charge, turbid water and cohesive erodible-depositable sides:-

1. Channels with the same water-sediment complex tend to acquire that same Froude Number in terms of some measure of depth, d .
2. Channels with the same water-sediment complex and the same measure of resistance to erosive attack on their sides tend to acquire the same dissipation of energy per unit mass per unit time, gVS .'

98. My measure of erosive attack on sides, V^3/b , may be viewed as the result of comparing the basic original Lacey relation $P=2.67Q^{1/2}$ with the identity $b=(F_b Q/F_s)^{1/2}$ in which F_b stands for V^2/d , F_s stands for V^3/b and bd is the cross-sectional area of flow. The constant 2.67 was found later to vary between systems, but the index $1/2$ remained fixed. No dynamically justified definition exists for b and d , but most practical definitions within the field range of variables will give about the same functional forms for plots or formulae, within the limits of statistical significance, except for coefficients. Accordingly, I use b , d to indicate that their joint definition is open, so embraces P , RF_b , F_s are to suit them and embrace V^2/R , V^3/P .

99. In the original regime investigations no firm relationship between V^2/d and D (used instead of m in this contribution) was proposed. Sufficient reasons are that the extreme range of D was from about 0.15 mm to about 0.40 mm and V^2/d is affected by the unmeasurable small bed load charge C and the suspended load charge and constitution. In the Note, certain parameters that have served well are used for D from about 0.15 to 5.0 mm to find how their interrelations are affected by D . Detailed discussion is difficult because the raw data are not recorded, the data are scanty considering possible influences from bed and suspended loads, bed forms are not considered as indicators of possible functional changes and river data have been used extensively without explanation of the principles behind the selection of the river stages at which to make observations. In particular the White Nile appears to have been observed at one place, Malakal, over a discharge range in which the velocity almost doubles. I feel these matters require attention, if only because workers in flume transport continue to obtain self-consistent plots (Figs 7(a-z) in reference 42 and Fig. 4 in reference 27) that disagree grossly with each other for reasons that I believe include neglected factors. Accordingly the following comments are aimed mainly at possible physical meanings behind the results.

100. First, consider

$$gVS \propto (V^2/d)^p \quad \dots \dots \dots (32)$$

Fig. 9. Contours from Fig. 1, plus canal and gravel river data for small C (references 47 and 51)

which might combine statements 1 and 2 in § 97. The original Lacey value for p was 2. Relations of the type of equation (1) can be written as

$$V^x \propto R^y S \quad \dots \dots \dots (33)$$

and will be identical to the form of equation (33) if $p = y = 0.5(x + 1)$. The equations of the Note for classes A, B, C, D all satisfy this condition and give $p = 1, 1.5, 2, 2.5$, so a major advance from original findings is that p is not constant, but is a function of at least D . Maddock⁴³ has correlated flume data of $VSC^{-3/4}$ (where C is bed load charge) directly with D from 0.0002 to 8.0 mm. The relevance of his result to the preceding values of p and to Figs 1 and 2 (which are for canal and river data) can be assessed by plotting total data, with $\sqrt[3]{(vg)} D/\nu$ values noted against the points, on Fig. 9 and its S counterpart, and remembering that the bed form zone boundaries on those figures are rather rough and are for some medium sand grade only. The statements 1 and 2 in § 97 are unaffected by the behaviour of p .

101. Second, consider the equivalent form for equation (33)

$$V \propto F_b^{-q} d^{3/4} S^{1/2} \quad \dots \dots \dots (33a)$$

which is a standard flow formula of the original Lacey type (and probably universal according to §§ 14.4–14.7 of reference 35) in which F_b^q appears in the role of a conventional roughness factor and therefore a power of a roughness height. (The original Lacey value for q was 1/4.) Algebraically, if $p = 0.5(x + 1)$ then

$$q = (2p - 3)/4 \quad \dots \dots \dots (34)$$

so the values of q for classes A, B, C and D are $-1/4, 0, +1/4$ and $+1/2$.

102. The position of the roughness factor in the numerator of equation (33a) when q is negative, instead of in the denominator as in rigid boundary hydraulics, corresponds to the long-known phenomenon that, in some duned bed conditions, an increase in sand size results in dunes flattening and roughness decreasing. A relevant histori-

cal item about this peculiarity is that the original regime theory's various dependent regime formulae, each derived algebraically from the basic three, gave different but functionally related values of V^2/R when the same field data in the category B range were inserted in them (§§ 2.33–2.35 of reference 44). Most of this anomaly was removed by the King formula

$$V^2/gdS \propto (Vd/\nu)^{1/4}(b/d)^{1/4} \quad (35)$$

in which b/d takes cognizance of the difference between bed and side roughnesses. This, combined with $F_b = V^2/b$, yielded

$$gVS \propto (\nu F_b)^{1/4} F_b \quad (36)$$

or

$$V^2/gdS \propto (d/x)^{1/4} \quad (37)$$

where

$$x = (\nu F_b)^{1/2} / F_b \quad (37a)$$

which was tantamount to $q = -1/4$ in equation (33a) because F_b follows V^2/R reasonably. I use equation (37) in practice for sand beds.

103. Therefore the alternative statement of the advance is that V^2/d does not serve alone in the role of a roughness height in a flow formula but has to be combined in some way with, at least, D . This is not surprising considering that V^2/R was regarded in the original theory as a 'turbulence criterion' and various authorities accept that turbulence is responsible for effective uplift on bed particles and, therefore, for reduction of resistance to entrainment. So effective roughness height in mobile boundaries should contain both V^2/d and D in general. This agrees with the general concept of bed roughness being due to each of bed form, entrainment and ordinary particle roughness in various proportions.

104. The second advance is the idea of comparing a plot of $V/R^{1/2}$ against $R^{1/2}S_*$ with a plot of the square root of settlement velocity against D (see Figs 1 and 2). However, the points of Fig. 1 do not seem to be those of Figs 3–6 which have no class C but contain two class D lines which could not both fit Fig. 1. A means of transferring the information in Figs 3–6 to Fig. 1 is shown from Fig. 6 as follows. Write its equation as $V = 13.1 \times 10^{-3/4} (R^{1/2}S_*)^{1/4} = 2.34(R^{1/2}S_*)^{1/4}$. Then on Fig. 1 draw a line of slope 1/4 through ordinate 2.34 and abscissa 1.0. This should be a tangent to, or short chord of, the curve if Fig. 6 agrees with Fig. 1. My findings are that the lower class D tangent fits the curve but the upper is well above it, there is no class C tangent, the class B tangent fits well and the class A tangent slopes to suit the actual points within its class but is a little high in them and is appreciably steeper than the part of the fitting curve in the range of points—in fact it is parallel to the tangent to the fitting curve shown extended to the bottom of the class range. Considering this, that different sets of data in any one class must be influenced appreciably by their collectors' guesses at the 'dominant discharges' at which to observe, that the range of anomalous settlement velocity has been barely exceeded and that dunes were probably still in existence at the large D values, I feel that the total evidence in the Note does not establish the curve of Fig. 1. In fact, the limited imperfect data seem as consistent with Inglis' $V^2/R \propto V_s^{1/2}$ (p. 137 of reference 45) as with the linear relation indicated by the congruence of Figs 1 and 2 as drawn. However, the slope of the class D section of the curve is exactly that for unduned gravel if the line marked Eq. 5–22 in Fig. 9 is correct. So it seems that, if all the Authors' data were incorporated in Fig. 9 and all their up-dated data were used in a new figure with dimensionless $R^{1/2}S$ replacing d/D , some doubts might be removed and attention directed to improved data collection, which Fig. 9 shows to be a universal need.

105. Further comments concern the emerging picture within which Lacey regime theory is a major and relatively basic and practically useful part. During the past two decades work in all phases of behaviour has been extensive, but comprehensive plots have crystallized only recently.^{44, 46, 47} Principal advantages are starting to

Fig. 10. Approximate flume data surface for medium sand (after Cooper⁵²)

accrue from the 'statement of prototype case'.^{27, 35, 48} This statement, reduced to symbols, shows that the general functional forms for V^2/gd , S and the bed wave mean lengths and amplitudes λ and α cannot be simpler, for practical purposes, than V^2/gd , S , λ/d , $\alpha/d = \text{fn } s[\sqrt[3]{(vg)D}/v, C, d/D, b, d, s, \text{ other sediment properties}]$ (38)–(41) where fn means 'some function of' and s is the specific gravity of solids relative to fluid. The many algebraic equivalents of these equations can be found easily by algebraic manipulations.⁴⁹

106. A simple manipulation of equations (38) and (39) to apply to the Note is the replacement of d/D in equation (38) by

$$(d/D)^{1/2} S [\sqrt[3]{(vg)D}/v]^{1/2}$$

to give

$$V^2/gd = \text{fn} [\sqrt[3]{(vg)D}/v, d^{1/2} S (\sqrt[3]{(vg)/v})^{1/2}, C, b/d, \dots] \quad (42)$$

This shows that, unless Nature happens to decree that certain terms in the equation are relatively unimportant, the introduction of D separately into a correlation between V^2/d and $d^{1/2}S$ is mandatory and there is no justification for defining and using a measure of depth without taking separate cognizance of channel shape b/d and relative properties of sides and bed. (Actually there is now strong evidence, from flumes, that the use of full depth (instead of R) permits values of b/d greater than 2 to be ignored in equation (38). However, I think that the simultaneous use of hydraulic radius for d in certain slope formulae may permit b/d to be ignored over a fair range. In practice the use of both full depth and hydraulic radius in equations might produce more confusion than is merited by the crudity or impossibility of measuring the properties of the complex; in research it deserves test.)

107. A major advance in co-ordinating information on phases of transport in terms of the preceding statement of case is due to the initiative of Cooper and Peterson.⁵⁰ Analysis, results and opinions are given in references 42 and 51. Fig. 10 shows the single three-dimensional surface which world flume data are competent to define for V^2/gd . It is approximately for one value of D (rigorously, Vig number $\sqrt[3]{(vg)D}/v$), but as the data showed strong negative association between d/D and Vig number (Fig. 11) it must drop at the right-hand end by an indefinite but probably small amount. On the surface approximate zones of major bed forms are marked.

Fig. 11. Poverty and accidental association of flume data⁴²

108. From information outside the range of Fig. 10 and to some extent from rigid boundary hydraulics, it seems that adequate information within the d/D range of Fig. 10 would produce a set of Vig number surfaces merging at the left and running out to the horizontal at the right, and each would have its own set of bed form curves. Also the members of the set might have some irregularities not apparent in Fig. 9 and might have differences in shape. Obviously the data for such a range of surfaces will not be produced with the present restricted facilities and support of university and government research laboratories and organizations.

109. Figure 9 shows the surface of Fig. 11 by means of contours of C values. In addition, two firm horizontals to the right indicate the approximate range of regime theory observations. The dotted horizontal is my guess at the line for 50 mm gravel at small C , if there are duned conditions and if they justify V^2/d varying as the square root of settlement velocity; it gives passable results in practical problems. The regime theory lines are for small unknown values of C and for water with enough suspension, during about half the running time, to affect rating tables obviously. Therefore, even if their C values were known, they could not be used to move the dropping C lines (for decreasing values of D) near them to proper positions for fixed D , although they do indicate that those lines should have little or no drop at their end. The firm line marked Eq. 5-22 to the left is an estimate for gravel rivers without duned beds and for very small C . It is placed centrally in the band enclosing the Kellerhals and Lane data.¹⁹ Its slope is chosen to suit the form of the Lacey flow formula (equation (33a)) and the Meyer-Peter (or Shields) relation $gds \propto D$. The alternative dotted line is for comparison and is obtained by substituting the Manning form of equation for equation (33a). In view of ignorance of the facts I have dotted a couple of fanciful transitions to represent imagined experiments in which, with one D , d/D was varied at very small charge over the whole breadth of Fig. 9. In part this exercise is to illustrate that there are some factual grounds for the hypothesis that there is a universal flow formula in which the friction factor varies as the fourth root of a relative roughness and the roughness height is expressed in terms of all the properties of the complex when there are dunes, and is proportional to D , without involvement of viscosity, when the bed is free from dunes. The S counterpart of Fig. 9 is in its references.

110. Direct applications to the Note are to outline what the limited factual information shows about beliefs such as

DISCUSSION

- (a) formulae change as bed forms change
- (b) formulae obtained from flume experiments require four dimensions so cannot be extrapolated to canals whose formulae require only three, and vice versa
- (c) there may be a universal flow formula

$$V \propto (d/x)^{1/4} (gdS)^{1/2} \quad (43)$$

for a value of d that takes cognizance of the different influences of bed and sides; for the mobile bed x is a function of at least the nature of the water sediment complex and contains parts related to bed form, entrainment and conventional grain roughness—it is simplest when one of these factors predominates; for clear water in circular pipes x measures conventional roughness height and texture or a proportional to a so-called laminar film thickness $(\nu d/V)^{1/2}$ according to rough or smooth conditions

- (d) there will be no major advance in the factual knowledge essential to engineering practice until scientifically designed and controlled flume-type observations are obtained at field scale, e.g. in large bypass or escape channels of irrigation systems.

Mr Lacey and Mr Pemberton

The Lacey equation⁹

$$V = \frac{1.3458}{N_a} R^{3/4} S^{1/2} \quad (44)$$

is one which has served to stimulate research and set up a chain reaction. This equation, applicable to canals in Northern India is immediately identifiable with class B. The boundary moves and the equation should not be confused with a similar one applicable to channels with rigid boundaries.

112. It appears then that the silt factor f in terms of V^2/R might well be a function of N_a the rugosity coefficient. Assuming that N_a might vary as $f^{1/4}$ it is found algebraically that

$$V = KR^{2/3} S^{1/3}$$

which is recognized as the equation for class C, namely equation (13). The matter rests there and for years this equation was regarded as a general equation applicable to the entire range of sediment size from very fine to very coarse.

113. Where does the error lie? The error arises in failing to recognize that the general expression is $N_a \propto f^n$, in which n is a variable. Thus assuming that $N_a \propto f^{1/2}$ gives

$$V = KR^{5/8} S^{1/4}$$

which, as might be anticipated, represents class D and is equation (15). **Dr Blench**, adopting an entirely independent approach, suggests that in the case of equation (44) $N_a \propto f^0$ and finally a solution which is both elegant and unexpected suggests that N_a might also vary as $f^{-1/4}$ in which case

$$V = KRS$$

which is the Phillips equation for smooth turbulence, equation (8). This disquisition may serve to clarify concepts which were previously obscure and we hope removes some of **Mr Thomas's** doubts.

114. **Mr Thomas**, having regard to the proved value of the regime equations as a tool in the design of irrigation channels, contends that it is all the more necessary to subject the new equations to the closest scrutiny before they are adopted. We fully agree with this contention. He also argues that if equation (13), hitherto regarded as a general equation, were to be replaced by classes A–D, it is necessary to consider them in the light of all the relevant data. This is agreed but it must be borne in mind

that the relevant data now available are much more numerous than when it was thought that equation (13) was applicable to the entire spectrum of sediment size. It was this misconception which disorientated research for 40 years.

115. It is self-evident that many of the new observations are embodied in classes A-D. Mr Thomas does not state whether he accepts the Phillips equation for class A, or the new equation, class D, for the coarsest sediment. We have urged that whenever fresh observations of V , R and S are made available the logs of $V/R^{1/2}$ should be plotted against those of $R^{1/2}S$ and note taken of the extent to which they deviate from those plotted in Fig. 1. All the indications are that equation (13) is not a general equation but is as valid as the other three equations for classes A, B and D and so it has been put in class C.

116. With the intention of establishing our empirical equations on a physical basis, we ventured to clothe them with dimensions, taking care to include the more important variables. Having achieved this end the equations would ultimately be stripped of dimensions and presented in a form assimilable by the practical engineer. Mr Thomas takes exception to our dimensioned equations, mainly because, in his view, we failed to observe the dimensional proprieties which he sets forth, and second because eight of our equations fail to satisfy a very simple physical rule which he has devised as a test or check of the validity of a dimensioned equation. The point at issue is whether our equations are valid or not. If they are not valid, it would have been invaluable if Mr Thomas had given his own dimensioned version of equation (13).

117. In § 1 we should have stated that ideally the sediment should be 'incoherent'. The operative words in the title of the Note are 'uniform flow' and this full stage discharge, with minor fluctuations, should persist long enough for it to be considered the dominating factor in determining the width and depth of the channel. This factor on great rivers such as the Mississippi and Ganges is defined broadly as the 'bankfull discharge'.

118. These considerations indicate that an appreciable number of observations used by early research workers in the field of regime should have been discarded. Mr Hoffman refers to the problems arising in respect of the cohesion of the bed and/or bank material. This suggests channels excavated by the engineer in earth. If they are intended to form part of an irrigation system transporting a moderate sediment load, the solution is to make them wide enough and deep enough for an envelope of sand to be formed on the bed and at the sides.

119. It has been asked what happened to the observations on which equation (13) was based, and why we did not present a figure for class C. The answer is that all the observations are in reference 9 and values of V against R^2S are plotted in Fig. 4 of that paper and show a fair correlation. When this equation was first derived classes A and D were unknown; we are now satisfied that the equation is none other than that for class C.

120. The use of the words 'basic framework' by Mr Hoffman was very apt. We hope that our Note will become a framework on which data can be hung. There is a great need for more observations. This is fully realized insofar as making new observations is concerned, but there is a greater need for an authority charged with the collation and publication of observations recorded in different countries.

121. We are pleased that Mr Hoffman raises no objections to the form in which we presented our equations after they were rendered dimensionally homogeneous. However, we should explain the origin of the new parameter (v_*g) and its value when the problem of assigning dimensions to empirical equations arises. It is clear that engineers other than Mr Thomas might well have difficulty in recognizing its function or utility and this is due in part to the fact that the angle of approach to the dimensional problem is unusual.

122. Mr Thomas has devised a test, or physical rule, based on the manner in which acceleration g should be associated with other variables. His contention is correct

DISCUSSION

but to almost every rule there is usually an exception; in this instance it is the parameter v_*g which is merely a useful means to an end as finally it can be eliminated. The general formula for the settling velocity of sediment in a viscous fluid can be written as

$$V_s = K(gm)^n/(v_*g)^{(2n-1)/3} \quad (45)$$

When the sediment is fine and Stokes' law is applied, $n=2$ and the resultant equation is

$$V_s = K(gm)^2/(v_*g) = Kgm^2/v_* \quad (46)$$

123. It is evident that no harm is done by using the parameter v_*g . The first alternative makes it easier to check any equation. Thus $(gm)^2$ has obviously the dimensions of V^4 and (v_*g) has the dimensions of V^3 .

124. In § 43 Mr Hoffman asks for the Authors' views on how conflicting theories fit into the general picture we have defined. We feel we have completed the task we undertook and it is for those who have held different views and theories in the past to undertake their task of cogitation and re-appraisal. We agree with many of the points raised by Mr Hoffman. There is one important limitation to which we would draw attention.

125. There is no question in our minds of the fact of smooth turbulence in certain rivers and canals. The implications of that fact are, however, a different matter. If the Blench criterion of smooth turbulence to the boundary is accepted, and the Phillips equation is recognized as valid it immediately follows that there is a Manning equation applicable to smooth turbulence and this is different from the Manning equation applicable to rough turbulence in channels with rigid as opposed to moving boundaries.

126. Recent plotting of logs of $R^{1/2}S$ against those of the observed median diameter, class B, medium sand, show that $R^{1/2}S/m$ is constant. This does not hold good for coarse sediment. For a sandy bed the median diameter is m_{50} whereas for the coarsest sediment m_{90} is now found to be appropriate. This may differ little from the maximum size of the sediment. The argument previously was that the equation for class D was $V = KR^{5/8}S^{1/4}$ and if this were multiplied by $(R^{1/2}S/m)^{1/4}$ the resultant equation was

$$V = K(R/m)^{1/4}(gRS)^{1/2} \quad (47)$$

Thus at the limit the moving bed and rigid or at least quiescent bed equations were reconciled. The Rubey Chart so far as the very coarse sediment is concerned cannot have been based on the settling velocity of large quartz particles; for this purpose smaller particles of much greater density were used.

127. Mr Hoffman suggests that further discussion of the conditions under which the shape factor E is involved would be interesting. The factor is an important variable in most observations on irrigation channels and natural streams. Most observations are in terms of V , R and S . There is no valid reason why values of W_s should not be recorded as well as those of the wetted perimeter P , without which it would not have been possible to compute the value of R , the hydraulic mean depth. In practice if the values of W_s , E and Q are quoted, nothing more is needed.

128. The values of W_s and Q are of use because they may provide supporting data in confirmation of the well-known equation correlating the water surface width with the square root of the discharge. This applies only to channels in alluvial plains and not to sub-montane torrents and rivers in gravel and shingle. The value of W_s is also of value in computing the value of D_m unless the values of R and E are known. It is unfortunate that in most recorded observations values of R are on record but not those of D_m . This has a bearing on Fig. 1. It would have been preferable and more rational to plot values of $V/D_m^{1/2}$ instead of $V/R^{1/2}$.

129. No observations of the sediment load are on record or were made on most of the data plotted in Fig. 1. It seems that it would be premature to attempt the labour of incorporating the sediment load until the analogue is supported by new observations. Also it seems that as yet there is no agreed uniform method approved

137. In channels transporting fine sediment the ratio of depth to particle size is great, but in gravel rivers very small. Thus Mr Charlton reports that current studies show that below a ratio of about 6 scatter of plotted available data makes simple correlation unsound. The data of Leopold and Wolman²⁴ are reported to be consistent with ratios of depth to particle size as low as 4. The expedient of using a value of m_{90} instead of m_{50} reduces the ratio of depth to particle size. Much depends on the sediment size distribution. If for example $m_{90}/m_{50}=1.5$ the same result might be achieved by reducing the depth, in theory but not in practice, by one-third. We are happy to leave the solution of this problem to Mr Charlton.

138. A simple equation which we have derived fits classes A–D and in some respects is illuminating

$$V = KR^{1-x}S^{1-2x} \quad , \quad , \quad , \quad , \quad , \quad , \quad (48)$$

It suffices to give three examples of its use. When the value of x is zero the equation is that of Phillips, $V = KRS$; when the value of x is $\frac{2}{3}$ the equation is that for class D, $V = KR^{5/8}S^{1/4}$, and when $x = 0.50$ is assumed the equation becomes $V = KR^{1/2}$ —that for the critical velocity. The hiatus between class D and the stage where the critical velocity is established deserves study.

139. **Mr Snell** seems to be concerned with the design of stable unlined earth channels. His hope that the Note would serve as a pragmatic guide is misplaced. His dilemma is that of the practical engineer who might be called on to design a channel—as part of a feasibility study—without the benefit of extensive measurements on nearby similar channels. In such a case it is best to accept that time spent in reconnaissance is seldom wasted.

140. Mr Snell states that the designer wishes to be in a position to choose, within a given range of slope, a design dependent on whether head loss, excavation or land take has to be minimized. He is on sound ground in this instance of selecting *faute de mieux* the Manning equation when making such studies. It is true that there was published guidance in respect of selecting an appropriate value of Manning's coefficient, N . However, he will find that differing values are given for channels in perfect, good, indifferent or bad condition depending on the standard of maintenance. Mr Snell expresses the hope that someone could distil from 40 years of regime research 'a simple practical method of designing unlined channels, in situations without extensive regional data'. We hope Mr Snell will dedicate himself to that task.

141. In § 69 **Mr Ackers** draws attention to a difference of opinion in respect of the manner in which we incorporated gravity and viscosity in our equations. He does not think that the equation $v_*g = vg/(s-1)$ has any physical foundation; Mr Thomas is more emphatic.

142. Our use of the symbol v_* has obvious merits to commend it. The objection is the use of the parameter v_{*g} . In §§ 122 and 123 it is shown that its use reduces some of the labour in assigning dimensions to empirical equations when the more important variables are known. Further, when the operation is complete the suspect v_{*g} , having served its purpose, can be neatly eliminated. Equation (45) is a general formula.

143. Mr Ackers asks the meaning of $V/R^{1/2}$ and $R^{1/2}S_*$. Briefly, $V/R^{1/2}$ took care of the saltated and suspended sediment, and $R^{1/2}S_*$ was associated with the material on the bed. $V/R^{1/2}$ was a criterion of turbulence and $R^{1/2}S_*$ of the moving bed drag. There was discussion on the correlation of the silt factor with the settling velocity of the particle. In terms of the analogue, if one accepts it merely as a hypothesis, the silt factor V^2/R varies as V_s the settling velocity throughout the entire sediment size spectrum. In class D f varies as $m^{1/2}$ and the term which includes viscosity vanishes.

144. It is to be hoped that when sufficient observations are available to confirm the validity of the analogue further research on sediment transport will make it possible to incorporate it in the equations in the Note. Mr Ackers's final comment on the equation for class B is of great interest. It is true that the equation at first sight

appears almost identical with that for a rough channel with a rigid boundary. In this instance the roughness height k as it appeared in the term $(R/k)^{1/4}$ would be a length and proportional to $v_*^{2/3}/g^{1/3}$ or, alternatively and equally valid, $(v_*g)^{2/3}/g$.

145. It is clear that **Dr Prus-Chacinski** fully understood the purpose of the Note and we share his view that the next decade, if the ways and means are made available, should result in great advances in regime theory. Dr Prus-Chacinski states that the new equations, each applicable to a given range of sediment size, are a valuable addition to existing regime expressions because they provide a direct powerful check on the value of the silt factor f which is apt to give trouble. He thinks additions of this character should be welcomed by practical engineers.

146. The regime theory must be used with discretion and skill, but this Dr Prus-Chacinski considers is common throughout the engineering field. It is included in the curriculum of more than one university in the UK. In this matter it is difficult to lay down guide lines.

147. **Professor Sugio's** comments will be of great interest to all who have studied the behaviour of rivers and torrents transporting gravel and shingle. His difficulties in assessing the size of sediment which is dominant as opposed to the median diameter m_{50} are discussed by Mr Charlton in §§ 56 and 57. The answer to the question at the end of § 89 depends on the purpose for which the value of R is selected.

148. We are inclined to regard equations for the velocity V as being most important when there is risk of damage due to a high flood. Presumably maximum floods will be recorded every year and the gauge and high flood level recorded. It is doubtful whether the same velocity equation will be applicable at intermediate stages. Nevertheless it is desirable to take discharges for a number of different values of R and attempt to obtain a stage discharge table for that particular site and gauge station. Perhaps attempts have been made in the past.

149. The discontinuity between classes A and B is a feature not only of the correlation of the settling velocity of the sediment particle V_s with its diameter m but also of $V/R^{1/2}$ with $R^{1/2}S_*$. When the Stokes equation is applied V_s varies as m^2 . The flow around the sediment is smooth laminar, but at a critical value of V_s when the value of m is about 0.17 the sediment particle begins to shed eddies until the stage when a complete train of eddies is established, and there is a radical change V_s thereafter varying as the diameter m instead of m^2 . When $V/R^{1/2}$ is correlated with $R^{1/2}S_*$ the same effect is produced as when the Phillips smooth turbulence equation in which V varies as RS_* undergoes a radical change and thereafter varies as $R^{3/4}S_*^{1/2}$. There are other examples of discontinuity but in all cases it appears that they derive from random fluctuation in eddy formation and eddy dissipation.

150. We regret that we ascribed the observations on the Liao Ho River to Japan instead of the People's Republic of China. It is important to record whether all the observations are made at one site and are taken throughout the year or at approximately maximum discharge of a number of different channels on the same system, or at least on channels operating under the same conditions. Thus Lane and Carlson's²³ observations on channels with gravel paved beds were very different from those made at one site on the Liao Ho River.

151. Within classes A and B the parameter $R^{1/2}S_*$ varies directly as the sediment size m , but with increase in the size of the sediment it is necessary to state $R^{1/2}S_*$ as a function of the sediment size. The need to substitute for the criterion m_{50} that of m_{90} is recognized. This is because at the limit a near approach to rigid boundary hydraulics is established. It follows that at present no quantitative relationship has been devised between $R^{1/2}S_*$ and m , although qualitatively much has been learnt.

152. Our method in deriving the velocity equations for the four classes of sediment was first to plot values of $V/R^{1/2}$ against those of $R^{1/2}S_*$ and having thus obtained the index n in the general formula $V/R^{1/2} = K(R^{1/2}S_*)^n$ (equation (1)) to use equation (2).

DISCUSSION

It is essential to use these two steps. The parameter $V/R^{1/2}$ is a turbulence criterion and the parameter $R^{1/2}S_*$ is a measure of moving bed drag and a function of the sediment size.

153. If this procedure is followed one has the advantage of knowing what one is doing. If, for example, in Fig. 1 there were a shift to the right of some of the observations plotted it might be inferred that this was due in part to a change from ripples on the bed to dunes. At one time it was thought that equation (13) was of the same kind as that of Manning; the Manning equation had a variable rugosity coefficient N , whereas in equation (13) the K remained constant. Equation (13) was never verified by plotting $V/R^{1/2}$ against $R^{1/2}S$.

154. We agree with Professor Sugio that the nature of the sediment distribution curve and the maximum size of sediment which can be moved by tractive force play a major role in determining the mean velocity formula. However, this problem seems to arise only with coarse sediment and particularly the coarsest type as exemplified by class D. Sediment of the coarsest kind found in a channel is by common consent defined as m_{90} . It is only when the depth is relatively small that the size of the largest sediment particles produces what might be termed an abnormal relative roughness factor.

155. In Professor Sugio's method (§ 94) the index of 0.27 differs little from 0.25 in our class D, but the index 0.54 is much less than 0.625 which we adopted. The equation $V = K(R^2S)^{1/3}$, at one time thought in error to be a general formula, is well known. Professor Sugio correlates V with R^2S and instead of an indent of 1/3 obtains 0.27. If Professor Sugio were to plot log values of V against those of $(R^{2.5}S)$ we believe he would obtain an improved relationship $V = K(R^{2.5}S)^{0.25}$.

156. It is remarkable that Dr Blench, adopting an entirely different angle of approach, obtains indices identical with those we assigned to our equations for classes A–D.

157. In §§ 96 and 97 Dr Blench omits mention of the basic Lindley theorem: that, for a given discharge Q and water sediment complex, the width, depth and slope of a channel in incoherent alluvium are uniquely determined. One result of this relationship is that when the water surface width W_s varies as $Q^{1/2}$, the mean depth D_m as $Q^{1/3}$, the velocity V as $Q^{1/6}$ and the slope as $Q^{-1/6}$, the product SV is a constant and the Blench–King side factor V^3/W_s is also a constant.

158. The original Blench theory postulates that the parameter V^3/W_s is indicative of smooth turbulence at the sides of the channel. It seems inconsistent to re-define this factor as one of erodibility, because that would immediately conjure up the erodibility of different earth, friable or rendered tenacious by clay. The early Blench–King channels were trapezoidal and, following the Kennedy tradition given side slopes of one horizontal to two vertical, it was suggested that if the side slopes were gentle as they should be when the channels were large the principle of smooth turbulence at the sides would be vitiated. The early correlation of W_s with Q was made from observations near bridge sites; it took the form $W_s = 2.67 Q^{1/2}$, W_s being defined as an empirical equation for 'determining the minimum stable waterway of rivers in sandy beds'.¹ (In such circumstances the banks might well consist of sandy soil also.)

159. A remarkable feature of what might be termed the 'Blench theory' is that neither the water surface width W_s nor the mean depth D_m enter Blench's equations as variables. The cross-sectional area A has in the past been obtained by means of the product PR or alternatively by $W_s D_m$. For several years the sediment factor f had been defined as $0.75 V^2/D_m$, or in SI units $2.46 V^2/D_m$. In Fig. 1 it was necessary to use $V/R^{1/2}$ because most tables of observations recorded V , R and S but omitted W_s and Q which would have enabled D_m and P to be computed.

160. The concept Dr Blench expresses in § 98 is in our opinion rather nebulous unless it is associated with our shape factor E in equation (18). The variables b and d require explanation. The first step is to plot a cross-section regarded as typical of

References

9. LACEY G. Uniform flow in alluvial rivers and canals. *Proc. Instn Civ. Engrs*, Part 1, 1934, **237**, 421–453.
10. LACEY G. *Regime flow in incoherent alluvium*. Publication 20. Central Board of Irrigation, India, 1939, Figs 3 and 4.
11. THOMAS A. R. Factors in the movement of bed-load in channels and in its relation to suspended load. *Annual report, Technical*, Central Board of Irrigation, India, 1944, 56–64.
12. WHITE C. M. The equilibrium of grains on the bed of a flowing stream. *Proc. R. Soc.*, series A, **174**, 1940, 322.
13. ROUSE H. Criteria for similarity in the transportation of sediment. *Proceedings of Hydraulics Conference, Iowa*, 1939, 33.
14. LACEY G. Discussion on stable channels with gravel-paved beds. *J. WatWays Harb. Div. Am. Soc. Civ. Engrs*, 1967, **93**, WW4, 249.
15. THOMAS A. R. Discussion on flow in alluvial channels with sandy mobile beds. *Proc. Instn Civ. Engrs*, 1958, **11**, Oct., 237–240.
16. LACEY G. Flow in alluvial channels with sandy mobile beds. *Proc. Instn Civ. Engrs*, 1958, **9**, Feb., 145–164.
17. ACKERS P. and CHARLTON F. G. The geometry of small meandering streams. *Proc. Instn Civ. Engrs*, 1970, **suppl.**, 289–317.
18. ACKERS P. and CHARLTON F. G. The slope and resistance of small meandering channels. *Proc. Instn Civ. Engrs*, 1970, **suppl.**, 349–370.
19. KELLERHALS R. Stable channels with gravel paved beds. *J. WatWays Harb. Div. Am. Soc. Civ. Engrs*, 1967, **93**, WW1, Feb., 63.
20. BLENCH T. and KING C. Effect of dynamic shape on Lacey relations. *Annual Report, Technical*, Central Board of Irrigation, India, 1941, 75.
21. BHOWMIK N. G. *The mechanics of flow and stability of alluvial channels formed in coarse materials*. PhD thesis, Colorado State University, 1968.
22. *Untersuchungen in der Natur über Bettbildung, Geschiebe und Schwebestoffführung*. Mitteilung No. 33, Amtes für Wasserwirtschaft Bern, Switzerland, 1939.
23. LANE E. W. and CARLSON E. J. Some factors affecting the stability of canals constructed in coarse granular materials. *Proceedings of the Minnesota International Hydraulics Convention, Minneapolis*, 1953, 37.
24. LEOPOLD L. B. and WOLMAN M. G. *River channel patterns, braided, meandering and straight*. US Geological Survey Professional Paper 282-B. US Government Printing Office, Washington, 1957.
25. SIMONS D. B. and ALBERTSON M. L. Uniform water conveyance channels in alluvial material. *J. Hydraul. Div. Am. Soc. Civ. Engrs*, 1960, **86**, HY2, May, 33–71.
26. HARIRI D. *Relation between the bed pavement and the hydraulic characteristics of high gradient channels in non-cohesive sediments*. DPhil dissertation, Utah State University, 1964.
27. Discussion on a similitude framework of regime theory. *Proc. Instn Civ. Engrs*, 1970, **45**, Feb., 299.
28. ACKERS P. Experiments on small streams in alluvium. *J. Hydraul. Div. Am. Soc. Civ. Engrs*, 1964, **90**, HY4, July, 1–37.
29. ACKERS P. River regime: research and application. *J. Instn Wat. Engrs*, 1972, **26**, July, 257–281.
30. ACKERS P. and WHITE W. R. *Sediment transport by currents; a new approach and analysis*. Unpublished report.
31. ACKERS P. *Sediment transport in channels: an alternative approach*. Report INT 102. Hydraulics Research Station, Wallingford, 1972.
32. PRUS-CHACINSKI T. M. Cutting a new mouth for the River Spey. *Dock Harb. Auth.*, 1963, **44**, June, 41–47.

33. LEOPOLD L. B. *et al.* *Fluvial processes in geomorphology*. W. H. Freeman, San Francisco and London, 1964.
34. Discussion on a study of bank-full discharges of rivers in England and Wales. *Proc. Instn Civ. Engrs*, 1959, **14**, Dec., 395-425.
34. BLENCH T. *Mobile-bed fluviology*, 2nd edition. University of Alberta, Edmonton, 1969.
36. MORDZINSKI S. Description of the river meanders (in Polish). *Water Control*, 1971, No. 6.
37. RATOMSKI J. An attempt of the description of the geometry of river meanders (in Polish). *Water Control*, 1971, No. 7.
38. PRUS-CHACINSKI T. M. Theory of the stability of river channels (in Polish). *Technology and Science*, 1968, No. 28.
39. ANTROPOWSKIY W. J. *Introduction to hydromorphology and further discussion* (in Russian). Gidrometeoizdat, Leningrad, 1969.
40. WOODHEAD-GALLOWAY J. Towards the structure of liquids. *New Scientist*, 1972, 16 November.
41. SUGIO S. Variations in bed-form and mean velocity in alluvial channels and streams. *Bull. Fac. Engng, Tokushima Univ.*, 1972, **9**, No. 1.
42. COOPER R. H. *et al.* A critical review of sediment transport experiments. *J. Hydraul. Div. Am. Soc. Civ. Engrs*, 1972, **99**, HY5, May, 827-843.
43. MADDOCK T. (JR). Hydraulic relations for sand-bedded streams. *Sedimentation*. Hsieh Wen Shen, Department of Civil Engineering, Colorado State University, Fort Collins, 1972, Ch. 15.
44. MERCER A. G. Analysis of alluvial bed forms. *River mechanics*. Hsieh Wen Shen, Department of Civil Engineering, Colorado State University, Fort Collins, 1971, Ch. I-10.
45. INGLIS C. C. *The behaviour and control of rivers and canals*. Research Publication 13. Central Board of Irrigation, India, 1949.
46. SIMONS D. B. and RICHARDSON E. V. Flow in alluvial channels. *River mechanics*. Hsieh Wen Shen, Department of Civil Engineering, Colorado State University, Fort Collins, 1971, Ch. I-9.
47. BLENCH T. Regime problems of rivers formed in sediment. *River mechanics*. Hsieh Wen Shen, Department of Civil Engineering, Colorado State University, Fort Collins, 1973, Ch. III-5.
48. BLENCH T. Mobile bed hydraulics. *J. Hydraul. Res.*, 1970, **8**, No. 2.
49. BLENCH T. *Dimensional analysis and dynamical similarity*. University of Alberta Bookstore, Edmonton, 1969.
50. COOPER R. H. and PETERSON A. W. *A review of data from sediment transport experiments*. Report HY-1969-ST2. Department of Civil Engineering, University of Alberta and US Department of Commerce, 1970.
51. BLENCH T. *et al.* Comprehensive graphs of regime data. *In International symposium on river mechanics, Bangkok*. International Association for Hydraulics Research, 1973.
52. COOPER R. H. *A study of bed material transport based on the analysis of flume experiments*. PhD thesis, University of Alberta, 1970.
53. GANGUILLET E. and KUTTER W. R. *A general formula for the uniform flow of water in rivers and other channels*. Translated by R. Hering and J. C. Trautwine. Wiley, New York, 1907.