A simple explicit formula for the estimation of pipe friction factor

J. J. J. Chen

Professor D. I. H. Barr, *University of Strathclyde*

The Author has surveyed the development of approximations to the Colebrook–White function² which are explicit for solution for piezometric gradient. In so doing he has uncovered some new instances of the many attempts to establish such approximations. But if this task is worth doing, it is worth doing as correctly as is reasonably feasible. The Author appears to have erred in this respect. Firstly, there is the dubiety concerning the origin of the logarithmic approximation to the logarithmic smooth turbulent law. It is the latter law which gives the component of the complete function which results in solution for piezometric gradient being implicit. The smooth turbulent logarithmic approximation in its earliest evaluation is

$$1/\sqrt{\lambda} = 1.8 \log(R/7) \quad (24)$$

where λ is the Darcy–Weisbach friction factor and R is Reynolds number.

19. Although, as the Author has stated, the writer¹⁴ has ascribed this approximation to Colebrook, he, the writer,¹⁵ had previously stated it to have been originated by Nikuradse. Perhaps this was because of a reading of Finnicome's¹ work, as referenced by the Author. The Finnicome article appears to have been the first of a series published at considerable intervals. Certainly it was reprinted, without resetting of the type, as the first substantive chapter of Finnicome's book,¹⁶ which was published in 1954 with the same title as his 1950 article. In the book there is a final list of references. However, Finnicome appears to have misinterpreted the position in stating that equation (24) was given by Nikuradse¹⁷ in his 1932 paper on resistance in smooth pipes. Careful examination of the original paper has failed to clarify the reason for this contention. Nikuradse dealt with the assessment of the then available data, including his own new data, in terms of the now standard form logarithmic smooth turbulent law, which he then evaluated for the whole range as

$$1/\sqrt{\lambda} = 2 \log(R\sqrt{\lambda}) - 0.8 \quad (25)$$

20. Later, Colebrook used this evaluation in the form given by the Author as his equation (3)

$$1/\sqrt{\lambda} = 2 \log(R\sqrt{\lambda}/2.51) \quad (26)$$

Nikuradse also showed the degree of fit achieved by a higher Reynolds number evaluation of the logarithmic smooth turbulent law

$$1/\sqrt{\lambda} = 1.95 \log(R\sqrt{\lambda}) - 0.55 \quad (27)$$

as is included in Prandtl's text.¹⁸ But the explicit formula which Nikuradse stressed, as also giving close agreement with his new data was

$$\lambda = 0.0032 + 0.211/R^{0.237} \quad (28)$$

Therefore, there does not appear to be any basis for Finnicome's contention, taken up by the Author, that usage of equation (24) formed an important part of Nikuradse's 1932 paper. Thus there still remains the problem of the origin of equation (24).

21. Secondly, there is the matter of the first use of an explicit transition approximation with the form

$$\frac{1}{\sqrt{\lambda}} = -2 \log \left(\frac{A}{R^n} + \frac{k}{3.7d} \right) \quad (29)$$

where A and n are constant and exponent respectively, and k and d are equivalent sand roughness and diameter respectively. The writer cannot but be gratified that the Author's extensive search has not uncovered an example prior to that of Churchill⁶ in 1973, with A and n deriving directly from equation (24) as 5.7622 and 0.9 respectively. This is because there is no dubiety regarding the earlier date of the instance missed by the Author. This is in the Proceedings in 1972, when the writer¹⁹ proposed values for A and n of 5.15 and 0.892 respectively. These values were obtained on the basis of achieving agreement with equation (25) at λ values of 0.030 and 0.014. At that time, eight figure logarithmic tables had been used to obtain the solutions to the curve fitting. Later, the writer²⁰ recalculated on the same basis and then suggested 5.1286 and 0.89 for A and n . The Reynolds numbers corresponding to the points of agreement were 11.17×10^3 and 357×10^3 , whereas the corresponding values for approximations based on A and n values of 5.7622 and 0.9 are 15.8×10^3 and 2.26×10^6 . By and large, the writer believes that the first of these combinations corresponds to a better compromise in the direct use of equation (29) than does the second, albeit that the exponent of 0.89 has to be used rather than 0.9. This also applies even if 0.892 were adopted, as having been part of the earliest instance of the use of an approximation of the form of equation (29).

22. The Author makes the statement that approximations of the form of equation (29) are the simplest capable of accurate prediction. This is so true that it is not clear what net advantage there would be in adopting his pair of wholly exponential equations (22) and (23). Neither is significantly simpler to use than is an evaluation of equation (29), assuming that the calculator to hand deals as readily with logarithms as with exponents. To have to use alternatives, depending on the circumstances, makes the Author's overall proposal somewhat untenable, because a more accurate, and almost as simple, single approximation has been available for more than a decade.

23. The first practical use of equation (29) was by the writer,¹⁹ to sketch in detail for a resistance diagram. This is now recognized as having been less than justified, but it does make the point about the relatively high accuracy of the simple approximation, especially if evaluated with thought given to its usage. However, the writer contends that there is only one way forward from that position so as to obtain approximations which are, in fact, sufficiently accurate as so to

be used for diagram plotting. This is to improve the smooth turbulent approximation and also to introduce an alignment correction, as already detailed by the writer.^{14,21}

Mr A. B. Swann, Nanyang Technological Institute, Singapore

The equations presented by the Author are explicitly soluble to give values of pipe friction factor f approximately equal to those given by the Colebrook–White equation. They provide a direct means of estimating the value of f for use in solving pipe flow problems in which discharge Q is known. In such circumstances the Colebrook–White equation cannot be solved directly. However, for pipe flow problems in which available head is known and discharge is to be calculated, the Colebrook–White equation can be used to calculate pipe friction flow directly. This can be effected by first calculating the value of the subsidiary dimensionless parameter quoted by Dally and Harleman²² and used in the preparation of their modified Moody diagram.

25. The derivation of this subsidiary dimensionless parameter is as follows. The Darcy–Weisbach equation

$$h_f = 4fLV^2/2gD$$

is rearranged to give

$$V^2 f = \frac{gDh}{2L}$$

or, taking square roots of both sides

$$V\sqrt{f} = \frac{gDh}{2L} \quad (30)$$

26. Also, from the definition of Reynolds Number

$$Re = VD/\nu$$

Velocity

$$V = \nu Re/D$$

Substituting for V in (30) gives

$$Re\sqrt{f} = \frac{D}{\nu} \left(\frac{gDh}{2L} \right)^{1/2}$$

Provided that the head available to overcome friction h_f is known, the subsidiary dimensionless parameter

$$\frac{D}{\nu} \left(\frac{gDH}{2L} \right)^{1/2}$$

can be evaluated and the value substituted for the term $Re\sqrt{f}$ in the Colebrook–White equation (pipe friction factor f is here defined by the equation $f = T_0/\frac{1}{2}\rho V^2$)

$$\frac{1}{\sqrt{f}} = -4.0 \log_{10} \left(\frac{1.26}{Re\sqrt{f}} + \frac{k}{3.7D} \right)$$

DISCUSSION

By this means the value of $1/\sqrt{f}$ and hence of f is obtained directly.

27. A sample BASIC program for evaluating pipe friction factor f is given in Fig. 1.

Dr D. J. Zigrang, *Mechanical Engineering Department, and*
Dr N. D. Sylvester, *Chemical Engineering Department, University of Tulsa*

In his Paper, *Mr Chen* proposes an explicit friction factor equation which he notes to be simpler than any of those he has reviewed but not as accurate as the more accurate equations he has considered. *Mr Chen* presents his equation in two versions. His equations (22) and (23) are

$$f = 0.3164 \left[\frac{1}{Re^{0.83}} + 0.11 \left(\frac{\varepsilon}{D} \right) \right]^{0.3} \quad (22)$$

$$f = 0.184 \left[\frac{1}{Re^{0.67}} + 0.7 \left(\frac{\varepsilon}{D} \right) \right]^{0.3} \quad (23)$$

He shows that these equations have an accuracy relative to the Colebrook equation²

$$\frac{1}{\sqrt{f}} = -2.0 \log \left[\frac{\varepsilon/D}{3.7} + \frac{2.51}{Re\sqrt{f}} \right] \quad (31)$$

of about $\pm 10\%$ for the ranges $4000 \leq Re \leq 10^7$ and $10^{-4} \leq \varepsilon/D \leq 0.05$.

```

10 REM ***** Routine for evaluating the pipe friction factor 'f' *****
20 REM ***** and hence pipe discharge Q using the Colebrook-White *****
30 REM ***** equation. *****
40 REM
50 REM *** Input required data. ***
60 DISP " Pipe data : Length L (m) , Diameter D (m) , Roughness size k (mm)"
70 INPUT L,D,K
80 DISP " "
90 DISP " Friction Head hf (m). "
100 INPUT HF
110 DISP " "
120 DISP " Fluid kinematic viscosity (m2/s). "
130 INPUT NU
140 REM *** Calculate the value of the subsidiary parameter. ***
150 G=9.81 @ K=K/1000
160 P=D/NU*SQR (G*D*HF/(2*L))
170 REM *** Calculate the value of 1/(f^.5) using Colebrook-White ***
180 X=- (4*LGT (K/(3.71*D))+1.26/P))
190 REM *** Calculate the value of the pipe friction factor 'f' ***
200 F=1/(X*X)
210 REM *** Calculate Relative Roughness. ***
220 RR=K/D
230 REM *** Calculate Pipe Conveyance. ***
240 C=F*L/(3.05*D^5)
250 REM *** Calculate Pipe Discharge Q (m3/s). ***
260 Q=SQR (HF/C)
270 REM *** Display Results. ***
280 DISP " Subsidiary Parameter = ";P
290 DISP " Relative Roughness = ";RR
300 DISP " Pipe Friction factor = ";F
310 DISP " Pipe Discharge Q = ";Q;" m3/s."
320 STOP

```

Fig. 1. A sample BASIC program for evaluating pipe friction factor f

29. In view of the widespread use of hand-held programmable calculators, we question the need for an explicit friction factor equation as simple as the Author's. However, if one were needed, an even simpler and considerably more accurate one was given by Zigrang and Sylvester²³

$$\frac{1}{\sqrt{f}} = -2.0 \log \left[\frac{\varepsilon/D}{3.7} + \frac{13}{Re} \right] \quad (32)$$

Equation (32) can be rearranged to give

$$f = \frac{1}{4 \left[\log \left(\frac{\varepsilon/D}{3.7} + \frac{13}{Re} \right) \right]^2} \quad (33)$$

30. Equation (33) can be solved with 25 strokes on a calculator (ELSIMATE EL-5806) while equation (22) requires 31 strokes. For $Re = 10^5$ and $\varepsilon/D = 0.001$, the Colebrook equation yields 0.022173; equation (22) yields 0.023845 (+7.5%); and equation (33) yields 0.021656 (−2.4%). More importantly, for the matrix of values resulting from combining Reynolds numbers of 4000, 10^4 , 10^5 , 10^6 and 10^7 with values for ε/D of 0.0001, 0.001, 0.01 and 0.05, equation (22) has an average absolute error relative to the Colebrook equation of 6.0%. The average error for equation (23) is 6.9%. The average error for equation (33) is only 1.5%.

31. Thus, if a very simple explicit friction factor equation is required for preliminary engineering calculations, the use of equation (33) is recommended.

Mr E. S. Webber, National Water Supply and Sewerage Board, Boroko, Papua New Guinea

It is the writer's opinion that since the publication of the *Tables for the Hydraulic Design of Storm Drains, Sewers and Pipelines*,²⁴ by the Hydraulics Research Station, Wallingford, based on the Colebrook–White equation, there has been no reasonable excuse for using any less accurate formulation for pipe friction in the turbulent flow regime.

33. This has been reinforced in recent years by the ready availability of programmable calculators with which rapidly to iterate evaluation of implicit formulae.

34. The scale of errors indicated by Table 1 is such that it is doubtful whether the Author's formulation has anything to offer in comparison with an exponential formula such as Hazen–Williams with a constant friction factor, while yet being more cumbersome in application.

Mr Chen (now at the University of Auckland, New Zealand)

I would like to point out that the main reason for proposing equations (22) and (23) was to provide a reasonably accurate, yet simple and easily memorized explicit expression for the prediction of pipe friction factor from known flowrate. It is believed that those who deal with fluid flow and/or convective heat transfer are familiar with the Blasius equation given as equation (1). Thus, to obtain equation (22) from equation (1), the only extra terms that need to be memorized are simply the term $0.11(\varepsilon/D)$ and the exponential index of 0.3. Moreover, under certain situations where algebraic manipulation is necessary, the logarithmic form is often not as convenient as the exponential form, as will be shown in §§ 40–46.

36. I am grateful to *Professor Barr* for pointing out the misinterpretation of Finnicome¹ on which I based the claim that equation (20) or (24) was attributable to Nikuradse. I also apologize for having missed equation (29) in my literature review. The third point raised by *Professor Barr* has been covered in § 35.

37. I would like to thank *Mr Swann* for pointing out the well-known fact that given the available head loss, the Colebrook–White equation is the more convenient one to use. This fact has been stated in at least one of the articles⁹ to which reference is made in my Paper, and has also been discussed and presented in a standard work²⁵ and text books.^{26,27}

38. My apology to *Dean Sylvester* and *Professor Zigrang* for having missed their equation (32) in my literature review. This equation is, however, also of the logarithmic form and resembles somewhat equation (18) originated by Round.¹²

39. I would like to thank *Mr Webber* for his discussion and offer § 35 as my reply to the points raised.

40. It is perhaps necessary to give a few examples of where the equation I proposed may have some advantages over the Colebrook–White equation. In open-channel flow, the Manning–Strickler formula is commonly used;^{28,29} this equation becomes numerically almost equal to the Colebrook–White equation if the Reynolds number in the latter equation becomes large, implying that the Manning–Strickler equation is only valid for fully turbulent flow. This comparison is presented in graphical form in Henderson’s book.²⁸ However, if equation (22) were used for substitution into the expression for the Chezy C factor

$$C = \sqrt{8g/f} \quad (34)$$

where g is the acceleration resulting from gravity, equation (34) becomes

$$C = \left[\frac{8g}{0.184[Re^{-0.67} + 0.7(\epsilon/D)]^{0.3}} \right]^{1/2} \quad (35)$$

41. At large values of Re , equation (35) becomes

$$C = 6.96 \sqrt{(g)(D/\epsilon)^{0.15}} \quad (36)$$

As $D = 2R$, where R = radius, substituting into Manning’s equation

$$n = (R/C)^{1/6} \quad (37)$$

results in

$$n = \frac{(D/2)^{1/6}}{6.96 \sqrt{(g)(D/\epsilon)^{0.15}}} \quad (38)$$

If the units are in feet and seconds

$$n = 0.023D^{0.017}\epsilon^{0.15} \quad (39)$$

For most practical purposes, equation (39) is very close to the Strickler formula as given in Henderson²⁸

$$n = 0.034\epsilon^{1/6} \quad (40)$$

42. In fact, Williamson³⁰ showed that, after corrections, Nikuradse’s results in the fully rough region fall closely along a straight line given by

$$f = 0.180(\epsilon/D)^{1/3} \quad (41)$$

which is very close to equations (22) or (23) when the effects of the Reynolds number are negligible.

43. Thus, the Manning–Strickler equation may be viewed as a special case of equation (35) when the flow is completely turbulent. The Manning–Strickler form of equation may therefore be extended to the transitional region, as indicated by equation (35).

44. In convective mass transfer inside pipes, the commonly used correlation equation is that due originally to Levich³¹

$$Sh = 0.0523Sc^{1/2}Re(f/4)^{1/2} \quad (42)$$

where Sh is the Sherwood number and Sc the Schmidt number. For heat transfer, provided that the eddy thermal diffusivity is equal to the mass eddy diffusivity, equation (41) is also applicable with the substitution of Nu for Sh and Pr for Sc , where Nu and Pr are the Nusselt and Prandtl numbers respectively.

45. For the fully rough region, Davies³¹ used

$$(f/4)^{1/2} = 0.197(\varepsilon/D)^{0.15} \quad (43)$$

for substitution into equation (42); and for the case of a smooth tube, the commonly used equation is

$$Sh = 0.015Sc^{1/3}Re^{0.88} \quad (44)$$

46. It has been suggested³² that equation (22) may be used with slight modifications to unify the equations for the fully rough region and for smooth tubes, as well as providing a correlation for the transitional regions.

References

15. BARR D. I. H. Discussion of accurate explicit equation for friction factor by A. K. Jain. *J. Hydraul. Div. Am. Soc. Civ. Engrs*, 1977, **103**, Mar., No. HY3, 334–337.
16. FINNICOME J. R. *The friction coefficient for circular pipes at turbulent flow*. Emmott and Co, Manchester, 1954.
17. NIKURADSE J. Gesetzmäßigkeiten der turbulenten Strömung in glatten Röhren. *ForschArb. Geb. IngWes.*, 1932, No. 356.
18. PRANDTL L. *Essentials of fluid dynamics*. Blackie, London, 1952.
19. BARR D. I. H. New forms of equations for the correlation of pipe resistance data. *Proc. Instn Civ. Engrs*, 1972, **53**, Sept., 383–390.
20. BARR D. I. H. Two additional methods of direct solution of the Colebrook–White function. *Proc. Instn Civ. Engrs*, 1975, **59**, Dec., 827–835; and 1976, **61**, June, 489–497.
21. BARR D. I. H. The transition from laminar to turbulent flow. *Proc. Instn Civ. Engrs*, Part 2, 1980, **69**, June, 555–562.
22. DAILY J. W. and HARLEMAN D. R. F. *Fluid Dynamics*. Addison-Wesley, 1966.
23. ZIGRANG D. J. and SYLVESTER N. D. Explicit approximations to the solution of Colebrook's friction factor equation. *Am. Inst. Ch. Engrs J.*, 1982, **28**, No. 3.
24. HYDRAULICS RESEARCH, WALLINGFORD. *Tables for the hydraulic design of pipes and sewers*. Thomas Telford Ltd, London, 1983, (4th edn with new title).
25. ROUSE H. Evaluation of boundary roughness. *Proc. 2nd Hydraulic Conf.*, University of Iowa Studies in Engineering, 1943, Bulletin No. 27; or *Selected writings of Hunter Rouse*. Dover, New York, 1971.
26. ROUSE H. *Elementary mechanics of fluids*. John Wiley & Son, New York, 1946.
27. MCCABE W. L. and SMITH J. C. *Unit operations of chemical engineering*. McGraw-Hill, New York, 1967, 2nd edn.
28. HENDERSON F. M. *Open-channel flow*. Macmillan, London, 1966.
29. CHOW V. T. *Open-channel hydraulics*. McGraw-Hill, New York, 1959.

DISCUSSION

30. WILLIAMSON J. The laws of flow in rough pipes. *La Houille Blanche*, 1951, Sept.–Oct., 738–748.
31. DAVIES J. T. *Turbulence phenomena*. Academic Press, New York, 1972.
32. CHEN J. J. J. *A single correlation for mass (heat) transfer in turbulent smooth and rough tube flow*. Int. Comm. Heat Mass Transfer. (To be published).

Conversion factor

<i>Imperial</i>	<i>SI</i>
1 ft	0.305 m