Mr. JAMES KENNEDY, (Liverpool,) through the SECRETARY, said that there were two, or three points, touching the history of the locomotive, which, in his opinion, had been inaccurately stated in the Paper. It was stated,¹ that, "The form of engine primitively adopted in the 'Planet,' by Stephenson, was with four wheels and inside cylinders. * * * Expansions of this normal arrangement were, the inside-cylinder engines of Sharp, Wilson, Kitson, Bury, Stephenson, Hawthorn, and Gooch." This, Mr. Kennedy submitted, was not correct. Having taken an active part in planning the engines for the Stockton and Darlington Railway in 1824, under the late Mr. George Stephenson, and having from that time until recently been practically engaged in the construction of locomotive engines, he was cognizant of all the improvements which had been successively introduced. The plan of constructing locomotives with cranked axles and horizontal cylinders, was contrived and introduced by Mr. Kennedy, and was first applied in the locomotive 'Liverpool,' which was started on the 22nd of July, 1830, by Mr. Edward Bury, then of Liverpool, and was employed in aiding in the construction of the Liverpool and Manchester Railway. The 'Planet,' the first engine constructed by Messrs. Stephenson on this plan, was not started until four and a half months afterwards; and a little later Mr. Hackworth set the 'Globe' engine to work on the Stockton and Darlington line. The late Mr. George Stephenson had told both Mr. Bury and Mr. Kennedy, after having seen the 'Liverpool' engine on the Liverpool and Manchester Railway, that his son, the present Mr. Robert Stephenson, had taken a fancy to the plan of the 'Liverpool' engine, and intended to make, immediately, a small engine on the same principle. Further, the late Mr. Robert Stephenson, brother to the late Mr. George Stephenson, had, as soon as he saw the 'Liverpool,' declared it was the best type for locomotives, and that all would have to come to it by-and-by. In fact, in the engineering world, the 'Liverpool' was considered a great stride in the right direction. That engine was as efficient a machine as had ever been made of that weight. It had been stated, that Mr. Brunel was the first to make wheels of more than 5 feet in diameter; now the driving wheels of the 'Liverpool' were 6 feet in diameter, and that engine often ran at the rate of 58 miles per hour, on a level part of the line, and with a load of twelve waggons. It had also been asserted, that the idea of the dome for a steam chamber on the boiler, in the case of the engines for the London and Birmingham Railway, was copied from Mr. Church's engine; but the latter was not made until seven years after the 'Liverpool,' and it could be proved, incontestably, from an old bill-head of the time,

¹ *Vide ante*, page 16.

that the dome on the 'Liverpool' was exactly similar to those on the succeeding engines made at the Clarence Foundry, Liverpool, by Messrs. Bury, Curtis, and Kennedy.

Mr. R. STEPHENSON, M.P.,—President,—remarked, that the working drawings of the 'Planet,' which was admitted to have been the type of the engines employed on the Liverpool and Manchester line, had been made, and the engine constructed under his direction, without any reference to, or knowledge of the 'Liverpool.' These facts could be fully confirmed by those who were confidentially employed upon the engine at the time. Neither was there any analogy between the two machines, for the 'Planet' had a multitubular boiler, the fire being urged by a blast-pipe, and the cylinders, which were as nearly horizontal as their position would permit, were fixed inside, or between the frames, because it was only by such an arrangement that they could be placed within the smoke-box, where it was considered desirable to fix them, in order to prevent the condensation of the steam in the cylinders, and the consequent loss of power. This had been resolved upon, from information given to Mr. R. Stephenson by the late Mr. Trevithick, who, in the course of some experiments, had built a brick flue round the cylinder, and had applied the heat of a fire directly to the metal, with very beneficial results, as regarded the economical use of steam. With the cylinders in the smoke-box, a cranked axle was indispensable, and there was not anything new in its use in locomotives, for the 'Novelty,' by Braithwaite and Ericsson, had one in 1829. Horizontal cylinders and cranked axles had also been commonly employed long previously, in Trevithick's, Gurney's, and almost all the other locomotives for turn-pike roads. The statements alleged to have been made by the late Mr. George Stephenson, as to the priority of the peculiar arrangement of the 'Liverpool,' in this respect, or those asserted to have proceeded from the late Mr. Robert Stephenson, as to its being the best type for locomotives, could not therefore be admitted to be correct.

Mr. EDWARD WOODS said, he had always understood that the 'Planet' was the first of the class of engines with inside cylinders, outside bearings, and cranked axles; and up to the present time, no claim had, to his knowledge, been put in, on behalf of the 'Liverpool,' that it suggested the kind of engines which had long been designated of the 'Planet' class. In a letter he had recently received from Mr. Booth—well known from his long connection with the Liverpool and Manchester Railway—that gentleman stated, that "the 'Planet' engine was always regarded as the first of her type of engine—namely, inside cylinders and outside framing. Mr. Bury's engines, as far as my recollection will carry me back, (twenty-six years), had inside cylinders, but without out-

side framing. As to dates, I find by an old minute-book, that the arrival of the 'Planet' was reported to the Directors, at their meeting on the 4th of October 1830—and three weeks afterwards, at their meeting on the 25th October, it was reported that Mr. Bury's engine, the 'Liverpool,' was ready for trial. Substantially, these two engines appeared to be contemporaneous."

Mr. Woods added, that the 'Planet' took the first load of merchandize from Liverpool to Manchester on the 4th December 1830. He thought it probable that the 'Liverpool' might have arrived on the line at the end of July 1830, and that it was employed, in the first instance, in ballasting; but no trial of the engine took place until some weeks after the arrival of the 'Planet.' It was, therefore, evident that the designs of the two engines were totally independent of each other, and that the 'Liverpool' did not lead to any suggestions, as regarded the construction of the 'Planet,' from which it differed materially. The 'Liverpool' was a four-wheeled coupled engine, with cranked axles and cylinders under the smoke-box. The hand-gearing was placed in front of the smoke-box, where the driver stood, the stoker being in the usual position, at the other extremity of the engine, or fire-box end. The outer fire-box was domed, and contained a very small internal fire-box. The boiler was not multitubular, like that of the 'Rocket,' 'Planet,' and all subsequent locomotive engines, and which contributed essentially to the excellence of their performance, but contained a number of convoluted flues, dissimilar to the series of flues in the ordinary locomotive of the present day. The furnace was urged by a blast from a pair of bellows working under the tender, and not by the aid of the blast-pipe. This engine, after having been tried for some time, was not purchased by the Liverpool and Manchester Railway Company, probably from their not being satisfied with its performance, or construction. It was then transferred to the branch colliery line from Kenyon to Bolton, where it met with an accident, through the breaking of a wheel, and received much damage, the driver being killed. It was in consequence returned to Messrs. Bury's works, where it underwent repair, and the multitubular boilers of the 'Rocket' and 'Planet' having been found so successful, that form of construction was adapted to this engine. In this state it was again employed, and for many years remained in the service of Mr. John Hargreaves, the lessee of the Bolton and Kenyon line of Railway. In this second stage of its existence, it might be accounted as the type of the excellent class of engines for which Messrs. Bury's firm became so deservedly celebrated. In its first stage it did not represent any form of engine now in use, much less that of the 'Planet,' which had the multitubular boiler, with cranked axles, cylinders in the smoke-box, outside frames, and outside bearings.

It could not, therefore, be said to have suggested, in any way, the form of the 'Planet.'

Mr. PHIPPS said, it appeared from the delivery Journal kept at Messrs. Stephenson's manufactory at Newcastle, that the 'Planet' was charged to the Liverpool and Manchester Railway Company on the 3rd September 1830. Therefore, assuming Mr. Kennedy's statement to be correct, that the 'Liverpool' arrived in July, there would not have been sufficient time to have constructed another engine. He might state that at the time referred to, he was engaged with Mr. Robert Stephenson, at Newcastle, and could speak confidently as to every bolt and nut that was introduced into the engine. It was a subject of frequent consultation between Mr. R. Stephenson and himself, and he was sure that he should have recollected hearing of so important a fact, as that of a cranked axle having been used in any other engine. He did not recollect to have even heard of the name of the 'Liverpool' engine until this discussion arose, and it was fair to assume, that nothing was known of it at Newcastle at that time. With regard to the position of the cylinders, repeated conversations were held between Mr. Stephenson, the late Mr. Hutchinson, and himself, with respect to the saving of fuel that would be effected by placing the cylinders within the smoke-box; they also had a great desire to fix the cylinders in a horizontal position, as it was found necessary when an engine travelled at a quick speed, that the vertical motion of the springs should be eliminated from the cylinders, and this naturally led to the horizontal arrangement.

Mr. KENNEDY explained, through the SECRETARY, that the 'Liverpool,' as previously stated, was first set to work on the Liverpool and Manchester Railway, on the 22nd July, 1830. After being at work some time, the cranked axle was broken, when she was taken off the road to have it welded. The 25th of October, the date given by Mr. Booth, was that of Mr. Bury's second application to the Directors of the Liverpool and Manchester Railway, to allow his engine to be again put on the line, after her cranked axle had been repaired, and not that of the first application, which was made and granted some months before. The letter-book of the firm, for the year 1830, contained the whole correspondence on the subject, between the Directors and Mr. E. Bury.

Mr. D. K. CLARK said, that this was entirely a question of dates. But with regard to the cranked axle, he might remark, that the question of precedence was not, in his judgment, important, inasmuch as he believed the cranked axle essentially an objectionable feature in locomotives, and one which would ultimately be superseded in railway practice by the straight axle.

Since the Paper was written, he had collected a few more par-

ticulars of the working of engines, bearing upon the points of economy treated of in the Paper.

1st. As to the economy of fuel, by the correct equilibration of the engine. The 'Canute' passenger-engine, and the 'Norman' goods-engine, on the South-Western line, having been equilibrated with good results, the other engines of the same classes were likewise equilibrated. He was not in possession of results for the passenger-engines in the form proper for comparison; but, for the goods-engines, he obtained from the Company's works, the following results of working, before and after they were correctly equilibrated, up to a recent date:—

Name of Engine.	Before Equilibration.			After Equilibration.		
	Miles Run.	Average Load in Waggon.	Coke and Coal per Mile.	Miles Run.	Average Load in Waggon.	Coke and Coal per Mile.
	Miles.	Waggon.	lbs.	Miles.	Waggon.	lbs.
Norman . . .	26,888	31·2	26·1	21,319	27·5	23·4
Saxon . . .	36,418	28·0	28·3	12,279	25·9	23·6
Albion . . .	19,042	26·4	28·4	13,662	27·3	20·9
Samson . . .	26,143	26·4	24·1	12,434	27·7	23·9
Total . . .	108,491	..	..	59,694	..	..
Average . .	..	28·0	26·7	..	27·1	22·95

The averages of these four goods-engines, showed that before equilibration, the consumption of fuel was nearly 27 lbs. per mile, with an average train of 28 waggon; and after equilibration, 23 lbs. per mile, with an average train of 27 waggon. Allowing, say 1 lb. of fuel extra for the same number of waggon, there remained a saving of 3 lbs. per mile, or 11 per cent. This result confirmed the estimate of presumable saving already made in the Paper.

Two passenger-engines on the Cork and Bandon Railway had been equilibrated, according to the rule given in the Paper, with similar satisfactory results. On the same class of trains, the consumption of fuel before and after equilibration, was stated to be at the rates of 26 lbs. and 22 lbs. per mile, and there were 8 and 10 carriages in the train, respectively; showing a saving of at least 15 per cent. of fuel.

Respecting the economy by heating the feed-water, he had found, on referring to the records of American practice, that at least 25 per cent. of fuel was saved by the use of heated feed-water; confirming his deductions of the advantage resulting from the system.

He further remarked, that Messrs. Randolph, Elder, and Co., of Glasgow, had become, by experience, so convinced of the saving to

be effected by the use of hot feed-water and dry steam, in marine engines, that they had constructed for the 'Valparaiso,' Royal mail packet, a pair of double cylinder expansive engines, of 320 HP., in which the feed-water was heated, and the steam was kept dry.

On the question of the relative cost of coke and coal as fuel for locomotives, he had obtained from twenty-two locomotive Superintendents, in different parts of the country, returns of the cost of fuel used by them; and he found that the average cost of coke was, in June 1856, 18*s.* 2*d.* per ton, and of coal, 8*s.* 7*d.* per ton: showing that coal cost less than half the price of coke, whilst in estimating the saving to be effected by substituting coal for coke universally, he had only assumed a reduction of one-third in the cost of fuel.

Mr. E. WOODS said, that the experiments referred to by the Author, as having been made on the London and North-Western Railway, to ascertain the comparative mechanical values of coal and coke, were made with a particular kind of fuel,—the Hawksbury Main coal, from a colliery near to Coventry. On analysis it was found, that this coal contained 67 per cent. of carbon, and 5 per cent. of hydrogen, equal to 72 per cent. of combustible matter, whilst the coke contained from 94 to 96 per cent. of carbon. In all cases where coal was brought into comparison with coke, it was important that the chemical analyses should be known, in order that the heating powers of each might be noted. He believed the statement was correct that, in these trials, 1 lb. of coke evaporated 8.65 lbs. of water, whilst 1 lb. of coal only evaporated 5.83 lbs. of water. If worked out, the evaporative powers would be found to be nearly in proportion to the amount of carbon which each contained.

The experiments on the South-Western Railway were, he believed, conducted with a superior quality of semi-bituminous Welsh coal. The fact of 1 lb. of that coal evaporating 9 lbs. of water, showed that it must have been of a very superior quality. He had travelled upon some of the improved engines on the South-Western Railway, and though he had not, in all cases, had an opportunity of weighing the fuel used, yet he was impressed with the opinion that they worked with economy of fuel and water, and the smoke was effectually consumed. He was not at present prepared to agree fully with all the claims to economy which Mr. Clark had advanced; but still he was of opinion that there was room for greater economy in the consumption of fuel and in the cost of repairs.

Mr. FREDERICK BRAITHWAITE said, judging from the title of the Paper, he was not prepared for the turn which the discussion had taken, inasmuch as it did not apply so much to the improvement of the locomotive, as to the reduction of the working ex-

penses of the locomotive department of a railway. He had heard, with satisfaction, that there was a probability of coke being superseded by the use of coal in locomotives. He believed it would be generally found, that it required 5 tons of coal on the average to produce 3 tons of coke. The great peculiarity of Mr. Beattie's engine was, that the coal coked itself in the process of combustion in the fire-box, so that the great loss of heat occasioned in the manufacture of coke was saved—a waste equal to from 1 to 2 tons of coal, on the calculation that it required 5 tons of coal to produce 3 tons of coke; and if such were the facts, a great economy would be effected, tending to reduce the locomotive expenses, especially if it was true that 1 lb. of coal would, in practice, evaporate 9 lbs. of water. When, however, they were told of other savings of 30 per cent. in one direction, and 20 per cent. in another, he confessed that he was taken by surprise.

MR. BEATTIE said, that he had extracted from the books of the locomotive department of the London and South-Western Railway, the data from which the following statement was drawn up, showing the consumption of fuel and average loads of five engines burning coke, and five burning coal, to and fro on the main line between London and Southampton:—

COKE-BURNING ENGINES.			COAL-BURNING ENGINES.		
Name of Engine.	Lbs. of Coke per Mile.	Average No. of Vehicles per Train.	Name of Engine.	Lbs. of Coal per Mile.	Average No. of Vehicles per Train.
Hecla	19·7	9·7	Ironsides . . .	21·2	14·9
Stour	20·6	10·6	Canute	17·7	12·6
Vulcan	20·8	10·2	Harold	17·6	10·4
Trent	21·4	10·7	Conqueror . . .	19·0	11·0
Frome	20·9	10·7	Crescent	19·1	12·2
Average . . .	20·68	10·38	Average . . .	18·92	12·22

From this it appeared, that the consumption of coal per mile had been $8\frac{1}{2}$ per cent. less than coke, whilst the number of vehicles per train was $14\frac{3}{4}$ per cent. greater. At the same time, the piloting of the coke-burning engines averaged 220 miles per half-year, whilst that of the coal-burning engines had averaged only 60 miles. The average cost of the coke had been 27s. 6d. per ton, and this calculated on 20·68 lbs. gave 3·04d. per mile. The coal (Welsh inland) had cost 18s. 6d. per ton, giving 1·87d. as the cost per mile of 18·92 lbs., or a saving in favour of coal-burning engines of 1·17d. per mile, equal to 38 per cent., with trains $14\frac{3}{4}$ per cent. heavier than those drawn by the coke-burning engines. If the loads had been equal, that is, if the coke-burning engines had

drawn trains of the same weight as the coal-burning engines, the consumption of fuel would have been at the rate of nearly 24 lbs. per mile instead of 20·7 lbs., and the cost per mile would have been 3·5*d.*, showing a saving of 46½ per cent. in favour of the coal-burning engines, without taking into account the extra assistance rendered by piloting to the coke-burning engines. Of this economy, as it took 1½ ton of the best coal to produce 1 ton of coke, he thought about 33 per cent. was due to the use of coal in place of coke, and about 13½ per cent. must be attributed to the application of the hot feed-water.

He might here remark, that he thought great economy resulted from the use of the fire-tiles; and that without them the engines would not consume their own smoke. In consequence of the fire-tiles becoming greatly heated, the smoke evolved from the coals was consumed; in point of fact the engine was making its own coke during its transit, and at the same time getting the benefit of the combustion of the gases evolved, which were for the most part wasted in the manufacture of coke. The advantage in this respect was much felt in the performance of an engine towards the end of a journey; as under those circumstances it would run home with very little fuel in the fire-box,—the heat from the fire-tiles being alone almost sufficient to keep up the pressure of steam. Recently a coal-burning engine, using only small coal, or slack, had brought a train, consisting of twenty-four carriages, from Woking to London, a distance of 25 miles, in 37 minutes, being at the rate of above 40 miles per hour, and when it reached the Waterloo Station, there was only a small quantity of fire in the box; still the steam was at a pressure of 110 lbs., and it had not been at less than an average of 120 lbs. during the whole journey. He ventured to say, that no coke-burning engine would have brought in that train, at the same velocity, with so little fuel in the fire-box. He should be happy to repeat those experiments, with any one who desired to test the working of coal-burning engines. He had not tried coke in the same engines, because he was quite satisfied with the results of the coal-burning.

A few months back the Belgian Government sent over to this country M. Belpaire, one of their engineers, for the purpose of examining into the merits of the coal-burning engines. In his Report to the Minister of Public Works, at Brussels, that gentleman had stated that the flame in the fire-box was white, and the combustion was perfect. There was no smoke, even whilst firing and stoking. If, during the stoppages after firing, the gases from the chimney were faintly tinged with colour, a slight jet of steam discharged up the chimney rendered them colourless again. The steam-generating power of the boiler was also admitted to be undoubted. In a trial with the 'Canute,' coal-burning passenger-

engine, M. Belpaire found, that from London to Southampton an average speed of 0·635 of a mile per minute was maintained, when exerting a tractive force equal to drawing 760 carriages a mile. On the return journey from Southampton to London, the average speed was 0·492 of a mile per minute, and the tractive force was equal to drawing 1,146 carriages a mile. The consumption of fuel was 19·15 lbs. per mile, including the quantity used in lighting the fire.

Mr. CRAMPTON said, that for the last two years they had been burning coal, pressed together with a little tar, on the Great Northern of France Railway. Twenty of his express engines were running daily, burning only coal: and altogether there were two hundred coal-burning engines on that line, and at least four hundred in France. The result had been a saving of one-third in the cost of fuel. On the Great Northern of France line the coal used was very good, and there was very little smoke from it. The only means adopted for the consumption of the smoke was a step-grate, which was merely a horizontal arrangement of the fire-bars, placing them transversely, and in steps across the fire-box, so as to have wide air-spaces, without the risk of losing the fuel through the spaces. By care in firing, they got such a mass of flame, that with a copious admission of air, the smoke was perfectly consumed. When, however, very bituminous coal was tried, the experiment was a failure.

In the consideration of this subject the quality of the fuel formed an important element, in determining the quantity of water which a pound of coke, and the same quantity of coal, would respectively evaporate. He did not think that the comparative evaporative efficiency of coal and coke could be fairly arrived at, by contrasting the results of Mr. Beattie's coal-burning engines with coke burnt in other engines; because Mr. Beattie had an ingenious method of heating the feed-water by means of the waste steam, which, there was little doubt, induced an economy of 15 per cent. It would have been more conclusive to have tried coal and coke in the same engine alternately. He mentioned this, in order that they might not be led away by false ideas of saving.

Mr. D. K. CLARK said, that he had burned coal and coke, alternately, in the same engine, the 'Canute.' In one of his experiments the consumption of coal was 915 lbs. per hour—the area of the fire grate being 16 square feet. In this case $9\frac{1}{3}$ lbs. of water were evaporated by each 1 lb. of coal, whilst in the same engine only $7\frac{1}{3}$ lbs. of water were evaporated by each 1 lb. of coke.

Mr. BEATTIE, in reply to questions from different Members, said, he had recently got up steam with 4 cwt. of Griff, which was a hard coal, and had afterwards used on the journey to Southampton and back, 21 cwt. of coking coal, which was highly

bituminous, and both were consumed with the same satisfactory results. The first cost of the boilers of the South Western coal-burning engines would be little more than that of ordinary boilers, and there did not, at present, after very heavy running, appear to be any evidence of more rapid destruction of tubes, or of fire-boxes, than when burning coke. Indeed there was reason to apprehend, that the particles of coal in combustion would do less mechanical injury to the tubes, than the bits of hard coke rapidly travelling through. Thin and careful firing was recommended by engineers who had tried to consume coal in locomotives, but in the arrangement of boiler he had described, this was not necessary, the firing being less frequent to maintain high-pressure steam, than with the engines burning coke. There could not be a doubt but that the locomotive boiler could be made to consume coal, with as good a result as the stationary boiler, under which coke was never considered necessary. He could not give any precise information as to the expense of repairs, as so few had as yet been required. The fire-bricks lasted as long as in coke ovens. Some of the engines had run from 28,000 to 30,000 miles during the present year.

Mr. CRAMPTON remarked, that the capability of burning both coking and hard coal equally well was an important fact. He had not seen any apparatus that would thoroughly consume the gases, and at the same time get up steam. In his own case, if he ran an express train with strong coal, there was much smoke; but with the Belgian coal, which was a dry coal, very similar to the Welsh, this was not the case. He had no desire to disparage the system advocated by Mr. Beattie, who, he thought, was entitled to great credit for what he had done. Still, as a practical man, he must confess that he doubted whether that gentleman's particular form of engine would be the one generally adopted for burning coal in locomotives. It appeared to him that the boiler was too complicated, and that, in practice, there would be some difficulty in properly arranging and adjusting the fire-tiles. Under Mr. Beattie's own eye the system might perhaps be made to answer, but when consigned to the care of ordinary workmen, he doubted whether the results would be so satisfactory.

Mr. H. ROBERTSON was convinced, that the use of coal, in place of coke, on railways, would result in a large saving in the expenses of the locomotive department. The chief difficulty to be overcome was to get rid of the nuisance of smoke. From experience he could say, that this had been successfully accomplished in the South Western coal-burning engines, and also on the Shrewsbury and Hereford Railway, where coal only had been used during the last six months. Mr. Brassey, who was the lessee of the latter line,

had encouraged Mr. Jeffrey, the locomotive superintendent, to persevere in overcoming this difficulty, and he had done so completely. The plan adopted by Mr. Jeffrey was to fit each engine with a moveable frame for the fire-bars, which were thin and flat, had a space of $1\frac{1}{4}$ inch between them, and were placed longitudinally in the fire-box. There was thus plenty of room for the admission of air, and little liability to clinker. By the use of the rocking frame, the level of the bars could be varied at pleasure, according to the condition of the fire and the work to be performed. At the end of a trip, the fire could be dropped out without disturbing the bars, saving not only the fuel, but the bars, and the labour attendant on the old mode of dropping the fire; and by lifting one side of the frame any clinker could be removed. By this contrivance, an engine having run from Shrewsbury to Hereford, could be taken over the pit, drop her fire, have the whole of the clinker removed, and be ready to start with a clean fire in about a quarter of an hour. There was no difficulty in getting up the steam.

Mr. Jeffrey had furnished him with the following results of burning all coal in the six passenger- and eight goods-engines on the Shrewsbury and Hereford Railway. The average price of coke was taken at 20s. per ton, and of coal at 11s. per ton at the terminal stations.

PASSENGER-ENGINES.

	Miles Run.	Coke.		Coal.		Coke per Mile.		Coal per Mile.		Total Fuel per Mile.	
		Tons.	Cwt.	Tons.	Cwt.	Lbs.	Value	Lbs.	Value	Lbs.	Value
Burning Coke and Coal. . .	360,632	1660	10	1757	12	10·31	1·10	10·92	0·64	21·23	1·74
Burning Coal only	81,969	..	..	693	3½	..	..	18·94	1·12	18·94	1·12
Saving per Mile										2·29	0·62

The above statement showed a saving of 0·62 of a penny per mile on the cost of fuel by burning all coal, compared with burning half coal and half coke. These engines, when burning only coke, could never be got below $18\frac{1}{2}$ lbs. per mile, whereas they now only burned 18·94 lbs. of coal, taking the same average load of six carriages, and running at the same speed in all cases. This gave a saving of about 50 per cent. in value in favour of all coal as compared with all coke.

FOUR-WHEELED GOODS-ENGINES.

	Miles Run.	Coke.		Coal.		Coke per Mile.		Coal per Mile.		Total Fuel per Mile.	
		Tons.	Cwt.	Tons.	Cwt.	Lbs.	Value	Lbs.	Value	Lbs.	Value
Burning Coal and Coke	189,593	2782	2	1422	9	32·87	3·51	16·81	0·99	49·68	4·50
Burning Coal only	39,193	..	..	719	19	..	..	41·14	2·42	41·14	2·42
Saving per Mile										8·54	2·08

The foregoing statement showed a saving of 2·08 pence per mile on the cost of fuel by burning all coal, compared with burning one-third coal and two-thirds coke. The average load was 168 tons, including waggons, in both cases.

SIX-WHEELED GOODS-ENGINE.

	Miles Run.	Coke.		Coal.		Coke per Mile.		Coal per Mile.		Total Fuel per Mile.	
		Tons.	Cwt.	Tons.	Cwt.	Lbs.	Value	Lbs.	Value	Lbs.	Value
Burning Coke and Coal	72,473	1232	8	613	4	38·09	4·07	18·95	1·12	57·04	5·19
Burning Coal only .	47,550	..	..	917	4	..	..	43·20	2·54	43·20	2·54
Saving per Mile										13·84	2·65

This statement showed a saving of 2·65 pence per mile on the cost of fuel by burning all coal, compared with burning one-third coal and two-thirds coke. The average load was 188 tons, including waggons, in both cases.

These facts were valuable, as being commercial results from the regular working of the whole traffic of the Company, with the same engines, doing the same work, on the same line of railway; the conditions being all alike, except that, in one case, all coal was used instead of a mixture of coke and coal. These returns gave the whole quantity of coal used in the department, including the workshops, and the coal used for lighting the fires. He did not think a more successful result could be expected from engines constructed for burning coke, and he looked forward to improved results from engines specially constructed for burning coal, like the 'Canute' of Mr. Beattie. The great difficulty was in avoiding

[1856-57. N.S.]

D

the emission of smoke ; but, by having a jet of steam in the funnel, to produce a draught when the engine was waiting at stations, and getting the men into a proper system of firing, there was no fear of complaint on that score. He had seen coal-burning engines come into the Shrewsbury general station emitting less vapour than was sometimes the case with the coke-burning engines. With respect to the question of the repairs of the tubes, he would add, that Mr. Jeffrey had found the cost less, when burning coal than with coke, as the tubes were comparatively free from the fine particles of coke, which were carried through by the sharp draught, and which "furred" up and cut the tubes. This "furring" up of the tubes required a frequent use of the cleaning rod, which was not the case with the coal-burning engines.

Mr. A. SLATE remarked, that the use of coal, instead of coke, in engines, resolved itself into the question of the combustion of the carbon evolved from the fuel in the first instance. When more carbon was mechanically disengaged from the mass, than was chemically combined with the gases, visible smoke was formed. He had no doubt that the same thing occurred, to some extent, in the combustion of coke, although the gaseous vapour might not be visible. Heat was an important element in the proper combustion of the gases. The reason why carbon escaped, in the shape of smoke, in an engine burning coal, was that there was not a due supply of oxygen ; whereas in Mr. Beattie's engine, the element of heat was, to some extent, supplied, by the heated fire-bricks. On an average these bricks would be raised to a higher temperature than the gases, and they would give out the heat necessary for combustion. It appeared to him that, in all locomotive engines, there was an inadequate supply of oxygen. If a due amount of air, at a high temperature, could be injected into and be mingled with the gases evolved, they might obtain an amount of heat similar to that produced by the blowpipe.

Mr. EXALL thought the object was not so much to get rid of the nuisance of smoke, as to obtain the greatest quantity of heat from the coal, as the nuisance was generally least when the economy was greatest. When the fire was even and thin upon the bars, smoke was avoided ; but if the mass of fuel was thick, smoke was evolved, as the passage of the air through the mass was prevented, and consequently there was imperfect combustion. His experience with portable engines had been chiefly confined to those of a small class, generally having about 4 to 6 square feet of fire-grate, and a light blast. In these he had found that the best fire was about 3 inches thick on the bars, or 2 inches if the coal was very fine, and sometimes even as little as 1 inch. The finer the coal, the thinner should be the fuel upon the bars. He preferred thin bars, only sufficiently thick to prevent warping, and getting out of shape.

Care must be taken to keep the bars always properly covered. The great thing, however, was the proper admission of air through the coal; as much mischief might be done by letting in air which was not necessary for combustion, as by keeping it out. He believed that, with proper care, almost any kind of coal might be burnt with advantage.

Mr. T. WEBSTER could bear his testimony to the freedom from smoke of the engines on the South-Western Railway, under Mr. Beattie's system. An alarm was at one time felt, with regard to the distance the sparks would fly, at a heat dangerous to contiguous property, but he thought that question was now set at rest. Referring back to the Minutes of the Institution, he found that in 1839,¹ Mr. C. W. Williams read a Paper "On the Properties and Composition of Peat and Resin Fuel," in which various instances were quoted of the great additional amount of heat obtained from coke, as compared with a like quantity of coal; and tested in that manner, no doubt such a result would follow. The coke, however, was produced in the most perfect state for use, at an expenditure of heat in another place. In the course of that discussion, it was stated by Mr. Lowe² that, "to say that the 15 cwt. of coke, produced from a ton of coal, was equal in heating powers to the original ton, was to say that there were no heating powers to be derived from the 9,000 or 10,000 cubic feet of gas produced, or the 10 gallons of tar." As regarded Mr. Beattie's engine, the practical point was, whether he had not discovered the means by which he could so combine the gases as to utilize them in the combustion of the coal? It might be matter for consideration, whether it would be more economical to drive off a certain amount of hydrogen, ordinarily found in coals, and other gases which either produced water, or were incombustible; but if no advantage was to be derived from that, then the great desideratum must be, so to construct the furnace, either of the locomotive, or of fixed engines, as to be able to utilize all the gases evolved. Another discussion on the same subject took place in 1840, on a Paper by Mr. Charles Hood, "On the Properties and Chemical Constitution of Coal,"³ when Mr. Parkes gave the results of some recent experiments by Mr. A. M. Perkins, as to the destruction, on the same grate, of equal weights of coal and coke, when it was found that coke effected a greater evaporation than coal, at similarly rapid and slow rates of combustion. That was what might have been expected, when there was no economical application of the gases evolved from the coal.

¹ *Vide Minutes of Proceedings Inst. C.E., vol. i. (1839), p. 38.*

² *Ibid., p. 41.*

³ *Vide Minutes of Proceedings Inst. C.E., vol. i. (1840), p. 62.*

Mr. G. P. BIDDER, V.P., said, they were much indebted to Mr. Clark for having brought this subject before the Institution, because a saving, however small, in any department of the working of a railway, taking into account the enormous extent of the system, was a matter of great importance. Although the question had been treated with great ability by Mr. Clark, and the documentary evidence brought forward during the discussion was very conclusive, there were needed many more facts of an accurate description, to enable a sound conclusion to be arrived at. The discrepancy in the evaporative powers of coal and coke must be explained, as otherwise no useful result whatever could be obtained. The relative prices of coal, and its character in different localities, must also be known, and in the case of export to places where no coal was found, the relative condition in which coal and coke would arrive at their destination, must be taken into consideration. At this moment, in India, it would be important to burn only coal, as indeed had been done on the East Indian Railway for some time, and therefore, it was desirable to ascertain, as clearly as possible, which were the best methods for effecting this object.

He travelled constantly upon the South-Western Railway, and could bear testimony to the remarks which had been made, as to the general absence of smoke. He had no doubt that the use of coal, in certain situations, would result in considerable saving; and he believed that Mr. Beattie's system deserved great attention, and that it might be applied in many instances with advantage.

With regard to the equilibration of engines, which had been too little touched upon in the discussion, that was a subject which had for a long time occupied the attention of locomotive superintendents, particularly of Mr. J. V. Gooch, on the Eastern Counties Railway. The express trains on that line ran from London to Norwich and Yarmouth, at a speed of about 38 miles an hour, including stoppages. These trains were heavy, and yet the consumption of fuel, including getting up the steam, was only 18 lbs. of coke per train per mile. This result Mr. Gooch attributed, in a great measure, to the balancing of the engines, which not only induced economy in the consumption of fuel, but what was of more importance, reduced the wear and tear of the carriages, and increased the safety of the running of the trains.

He hoped that on a future occasion the subject would be again discussed, when the experiments would be more precise than anything that had been laid before that meeting; because the condition of the engines—the amount of care in working them—and even the state of the wind—would occasion discrepancies, which, if not noticed, would lead to very erroneous conclusions.

Mr. CRAMPTON, through the SECRETARY, stated, that he coincided with Mr. Clark's views respecting the unsteadiness of ordinary

locomotives, and attached importance to balancing the working parts. But as it appeared to be considered, that Mr. Crampton's locomotives obtained superior steadiness, only at the expense of increased wear and tear of the tyres of the leading wheels, he hoped that a few remarks would not be thought inappropriate.

Some time before the gauge controversy, and whilst engaged on the Great Western Railway, Mr. Crampton's attention was first drawn to the necessity of giving increased steadiness to the engine; and he addressed a letter to the Editor of the 'Railway Times,' in 1843,¹ in which he expressed the opinion, that one of the causes of unsteadiness, was owing to the piston, piston rod, and connecting rod, being unbalanced, and that this unsteadiness did not result from the action of the steam, as had been supposed. This he believed to be the first published statement upon the subject. In the first engine which he constructed, all the reciprocating parts were weighed, and two-thirds of their weight were applied to balancing. In this particular case it was not necessary to use the whole weight for that purpose, inasmuch as there was only a trifling weight upon the centre wheels. Mr. Bodmer's plan was the only one that he knew of, which effected a perfect balance, but that was too complicated. Monsieur Nollau, in 1848, and Monsieur Le Chatelier, in 1849, investigated the subject theoretically, and it might be said, that it had been practised on the Continent as a principle, before English Engineers as a body admitted its value.

It did not appear that the conclusions to which Mr. Crampton had arrived respecting the requirements of locomotives were fully appreciated by Mr. Clark. These were, never to use a cranked axle, as straight axles were simpler, and engines having them could easily be made to run steadily; to place every portion of the machinery, including the eccentrics, regulators, &c., completely on the outside; to lower the centre of gravity; and to have the greatest weight upon the extreme wheels. All these points had been carried out, and appeared to have been generally appreciated, since fourteen out of the twenty-two locomotive engines exhibited at the French Exhibition embodied, in one form or another, parts of this system; and there were at present upwards of six hundred engines at work constructed upon this principle.

With regard to the weights on the wheels, he might state, that in fifty engines of one class, the total weight being 27 tons, 11 tons were placed on the driving wheels, 7 tons on the centre wheels, and 9 tons on the front wheels. In his opinion, 11 tons was the maximum load which should be put upon the driving wheels. The

¹ Vide 'Railway Times,' vol. vi. (1843), p. 135.

weight on the leading wheels was about the same as was usually placed upon those of ordinary engines of a total weight of 27 tons. It was not necessary that, for the same power, there should be a greater distance between the extreme wheels, inasmuch as the total length of the engine could be reduced, if required, by adopting a larger boiler with shorter tubes. All practical men knew, that his system did not involve any additional weight for a given power, under similar circumstances. No correct results could be arrived at, by comparing one of Mr. Bury's engines of $20\frac{1}{2}$ tons weight, with one of his engines of 27 tons weight. It was no doubt possible to find a few engines of very early construction on his principle, which might contain several objectionable points; this was incidental to all novelties; but when a system was criticised, it was illusory to select, as examples, the results of first efforts, but rather its later developments.

With regard to the asserted increased wear and tear of his engine, he had been furnished with a statement by the Engineer of the Northern Railway of France, which showed that the cost of repairs of all the engines on his plan, from 1849 to the end of November 1856 (nearly eight years), was sixteen and a half per cent. less than that of other engines on that line, during the same time. The total distance run had been 4,010,607 miles; and the average distance run yearly by each engine, during the whole of that period, was 25,428 miles. This was the more remarkable, when it was considered, that the distance between the extreme wheels was 2 feet 6 inches more, the distance run by each engine one-third more, and the speed attained one-third greater, than was the case with the other engines. The Engineer attributed these results to the facility with which every part could be inspected and kept in repair, and also to the increased steadiness of the engine. Although these results were more favourable than Mr. Crampton could have anticipated, yet he felt convinced, that in all cases in which engines were equally well constructed, those offering the greatest facilities for inspection and repairs, and which ran the steadiest, must show an advantage, both as regarded cost of maintenance, as well as in the number of miles run in a given time.

Mr. D. K. CLARK observed, in reply to Mr. Crampton's remarks, communicated through the SECRETARY, that the first public assertion of the principle of complete equilibration of locomotives in this country, was made by Mr. Bodmer, in 1841, when he patented his mode of making a perfect balance. If Mr. Crampton balanced two-thirds of the reciprocating weight, in the first engine he constructed, it was remarkable, that he ceased to do so, in the engines he subsequently made, on his principle. Mr. Crampton's conclusions as to the requirements of locomotives,

were not, as a system, appreciated in this country; after various trials, that system had been abandoned, and only in France had it been extensively adopted. Practical men did not all agree, that that system involved no additional weight for a given power. This assertion was only true of the system, with respect to the particular element of boiler-power; whereas, boiler-power was of no particular advantage, and was a real disadvantage, in so far as it involved superfluous dead weight, unless the two other elements, cylinder-power, and adhesion-power, were proportioned to it. The adhesion-power was, in reality, the practical limit; now, Mr. Crampton had acknowledged that 11 tons was the maximum driving load that should be placed on a pair of driving-wheels, and the experience of engineers would confirm the assertion that there were steady-running engines, weighing 21 tons, like Mr. Bury's, with single wheels, containing ample power of boiler and cylinders, for 11 tons driving weight. It followed, that the gross weight of Mr. Crampton's 27 tons engine, with the same driving weight, 11 tons, was 6 tons more than the weight which was usefully available, for purposes of adhesion, or was necessary for stability. Mr. D. K. Clark, so far from selecting, for comparison, the results of the first efforts of Mr. Crampton, had selected the class of engine made by MM. Dérosne and Cail, Paris, for the Chemin de Fer du Nord (No. 122), and which Mr. Crampton had said, embodied a fair representation of his system. If a reference might be permitted to the 'Liverpool,' on that system, made for the London and North Western Railway, and which weighed 35 tons gross, it might be mentioned that, with 12 tons on the driving wheels, there were 17 tons on the leading wheels, or nearly one-half more,—showing the comparative scarcity of weight, on this system, where most was required. The statement of the performance of these engines in France was of no value in this discussion, without an accompanying detail of the various classes of engines alluded to. The expedient suggested for reducing the length of the wheel-vase, to that of the ordinary system, by enlarging the boiler and shortening the tubes, was of very limited practical use; it had been worked out to an injurious excess, on one of the principal lines in this country, as had been demonstrated by the results of practice; and, further, the same expedient was applicable to all systems.

Mr. W. BRIDGES ADAMS, through the SECRETARY, said, that as the process of coking diminished the total weight of the coal 25, or more, per cent., while the cost per ton was nearly doubled as compared with coal, it was natural that locomotive superintendents should desire to substitute, if possible, coal for coke. But both coal and coke were of varying qualities. Coal was commonly divisible into coking, or bituminous, and anthracite, or non-bitu-

minous. There were objections to both kinds. The bituminous coal melted into a mass, and the anthracite decrepitated under heat, so that in both cases the free passage of atmospheric air amongst the particles of the burning fuel, which was essential to combustion, was impeded. Coke, by its peculiar chemical and mechanical structure, required less air than bituminous coal, and provided freer passage between the lumps. To burn coal, therefore, required a large grate area, with reduced depth of fuel; whilst to burn coke, a small grate area, with a considerable depth of fuel, would suffice. In burning bituminous coal in a locomotive fire-box, a distillation of the coal into gases took place, which gases could not be burnt without a large supply of air and heat in direct contact. As heat was abstracted by water-lined surfaces, it was essential to resort to some substance serving as a heat accumulator. This had been accomplished by Mr. Beattie, with the perforated brick diaphragm, in which the principle of the heated bridge of stationary smoke-consuming furnaces was judiciously applied. With regard to burning coal in existing locomotives, there was an experiment worth trying. Some years back, there was an article used in ordinary domestic fires, called a fire-ball. It was a sphere of fire-clay, about 4 inches in diameter, and pierced through in several directions, intersecting the centre, by holes $\frac{1}{2}$ an inch to $\frac{3}{4}$ of an inch in diameter. Several of these balls were placed in the bottom of the grate, on the ordinary bars. They got red hot, and kept up a supply of heated air to the burning fuel mixed with them. He thought it would be worth while to place a layer, or two, of these balls, on the bars of a locomotive, to try the experiment of burning coal, with their aid. Wood-burning engines required constant feeding, and were exceedingly wasteful. He had been informed that locomotives burning anthracite, were now used in the United States, and that the fire-boxes were much larger than those of the wood burners.

It must not be forgotten, that one considerable advantage in the use of coke was, getting rid, more or less, of the sulphur, which was very mischievous in its consumption to iron, copper, and brass. Therefore, if raw coal were used, it would be important to select the quality containing the least amount of sulphur. The experiment might be made, of lining the whole of the fire-box and the fronts of the tubes and roof with fire-bricks, and covering the bars with fire-balls, in order to ascertain if very sulphurous coal could be burnt without injury to the metal. It would also be desirable to try, if artificial fuel could be prepared, of a denser body than coke. It was obvious, that every time the door was opened to feed the fire, the temperature was lowered, by the rush of cold air through the tubes; and if, by condensing the fuel to as high a point as possible, the fire-box could be charged for a whole trip,

this disadvantage might be avoided. Possibly, anthracite coal, crushed, to destroy its crystalline texture and friability, and then recombined, might answer well. He suggested whether economy might not result from the use of distilled water in the boilers, so as to avoid incrustation, and the necessity for blowing off. It would be better to consume a certain amount of fuel in providing pure water, than to consume fire-box and tubes and extra fuel in producing steam from foul water, and at the same time lowering the power of the locomotive. It would be a great advantage, not to cool the boiler surfaces suddenly, and thus avoid leakage, the tendency to rust after evaporation, and saving time in the morning in getting up the steam.

Mr. BEATTIE remarked, through the SECRETARY, that as so much interest had been manifested in the particular form of coal-burning engine which he had brought out, he should have great pleasure in presenting to the Institution an engraving of the 'Canute,' referred to by Mr. D. K. Clark, for publication in the Minutes of Proceedings (Plate 1). The most precise description of this engine was that given in the specification of his patent, from which the following portion was extracted :—

" Fig. 1 is a side elevation of the engine and part of the tender, showing the condenser **K** in front of the chimney, with the overflow pipe, **11**, which carries the hot water back to the tender, through the pipes **S** and **T**.

" Fig. 2 is a longitudinal section, showing the boiler **I**, combustion chamber **F**, and furnaces **A** and **C**; also the internal arrangements of the heating apparatus, on the inside and the outside of the smoke-box, together with the disposition of the pumps.

" Fig. 3 is a transverse section of the combustion chamber, through the centre of the manhole **G**, showing the arrangement of the fire-tiles.

" Fig. 4 is a transverse section through the smoke-box and heating apparatus, showing the connection of the steam-cylinders and exhaust-pipes, and the heating and condensing apparatus.

" Figs. 2 and 3 show the construction of the furnaces and boiler, wherein the crude coal and the gases generated therefrom are consumed. **A** and **C** are two furnaces separated from each other by the inclined water-space partition **B**, which is perforated by rows of tubes. A transverse hanging bridge **D** is attached to the roof of the fire-box.

" The apertures **A'** and **C'**, for supplying the coal to the furnaces, are formed by hollow water-space rings, which are riveted to the outer and inner fire-boxes. The combustion chamber **F** is complete and independent in itself, and is permanently fixed in the boiler, by means of the manhole **G**, and the stays which pass through the water-space division; and the ring is supported by

the transverse hanging bridge **F**. The connection between the furnaces and the combustion chamber is formed by the hollow water-space ring **E**, which is riveted to the fire-box and bolted to the combustion chamber; by which means, when the fire-box is worn out, or requires repair, it can be taken out, without the necessity of disturbing the combustion chamber, or the tubes **11**, in the boiler.

"The first set of fire-tiles, **1, 1**, are placed across the narrowed outlet, or throat of the furnace, **A**, and leave intervening spaces between, for the passage of the flames and gases generated in the furnace. The second set of fire-tiles, **2, 2**, are octagonal and tubular, and are placed in the combustion chamber, thereby allowing the flame and gases to pass through and around them. The coals being ignited in the furnace **A**, the gases generated therefrom are raised to a high temperature, whilst passing between the heated fire-tiles, and are prepared for flaming; they are then deflected downwards, by the hanging bridge **D**, over the fire in the furnace **C**, being mixed with the flames and gases emanating therefrom, and all pass through the fire-tiles situated in the combustion chamber. The furnaces **A** and **C** are furnished with separate and distinct ash-pans and dampers, so that the combustion of the gases can be adjusted most accurately, by the admission of air to either furnace.

"The apparatus for heating the feed-water consists of an outer condenser, formed of two upright pipes, **J, K** (Fig. 4), placed in front of the chimney, and of an inner tubular chamber, **L L** (Figs. 2 and 4), placed inside the smoke-box. The pipe **J** communicates at the bottom with the exhaust steam in the lower chamber **L L**, and is provided with a throttle-valve **6**, to regulate the admission of steam. The other pipe **K**, or condenser proper, communicates with and receives its steam from the pipe **J**, by means of the cap **7** at the top; it is further furnished with an injection-pipe **8**, which is perforated near the top, and is connected to the cold-water pump at the bottom, by means of the pipe **10**. The tubular chamber **L L** is constantly filled with steam from the exhaust pipes **P P**, whereby the tubes **33** are highly heated. The chamber **L L** is surmounted at each end by hollow caps, **M N**, for the ingress and egress of the water, which is delivered into the apparatus from the hot-water pump **O** (Fig. 2), through the pipe **4** (Fig. 4), and then passes out by the pipe **5** into the boiler. The overflow-pipe **11** conveys the hot water from the condenser, which, passing through the outer coupling-pipe **S**, and inner inclined tube **T**, is delivered into the tender. The overflow-pipe **11** is furnished with a branch pipe **12** (Fig. 1), and a cock with handle **13**, which communicates with the feed-pipe **14**, and the hot-water pump.

"The action of the combined heating apparatus is as follows :—

BEATTIE'S LOCOMOTIVE ENGINE
FOR THE COMBUSTION OF COAL AND HEATING THE FEED WATER.

PLATE 1 VOL. XVI.

Scale 1/4 an inch to the Foot.

JOSEPH BEATTIE DEL.

Plate presented by J. Beattie.

Minutes of Proceedings, Institution of Civil Engineers, Vol. XVI. Session 1856-7.

The cold water from the tender is constantly being forced, by the cold-water pump, through the injection-pipe **8**, into the steam contained in the condenser **K**; the heated water generated by such process falls to the bottom of the condenser, and is carried off by the overflow-pipe **11**, to the tender **R**; but when a supply of water is required for the boiler, the engineman opens the hot-water feed-cock **13**, which allows a certain portion of the hot water from the overflow-pipe to pass into the hot-water pump, from which it is sent through the tubes **3 3**, contained in the lower heating chamber **L L**. These tubes being surmounted, at the same time, with the exhaust steam, direct from the blast-pipe, the feed-water acquires a proportional further heating, and is then passed to the boiler by the pipe **5**. Both pumps are provided with suitable cocks and clack-boxes, so that, should a failure occur in either heating apparatus, the water may pass from the pumps direct to the boiler, and work as an ordinary engine."

November 18, 1856.

GEORGE P. BIDDER, Vice-President,
in the Chair.

The discussion upon the Paper No. 949, "On the Improvement of Railway Locomotive Stock, &c.," by Mr. D. K. Clark, was continued throughout the Meeting, to the exclusion of any other subject.

SELF-ACTING PENSTOCK, OR FLUSHING MACHINE.

After the Meeting, Mr. ROGER SALTER explained two models of his Self-acting Penstocks, or Flushing Machines, for cleansing house drains and sewers. These machines were of two kinds, the one having a valve hung horizontally, the other a valve, or gate, hung vertically. In house drains a tank, or cesspool, was formed, for the collection and retention, during one day, of all the waste water running from the house, and this water, which would otherwise possibly help to create the necessity for flushing, was used as the flushing medium. If the rain water also was allowed to run into and collect in this tank, then the number of flushings would be increased. Although it was not contended, that the construction of flushing-tanks was a new idea, yet it was believed that the mechanical arrangements for making them self-acting were novel and important. The mode of accomplishing this was very simple:—A cast-iron pipe was fixed to the bottom of the tank, and on a level, or nearly so, with the bottom of