Mr. D. K. CLARK wished to direct special attention to certain important points in the working of coal-burning locomotives. In the first place, the steam should always be kept up, while the engine was running. In most of the systems in use, a considerable quantity of cold air was drawn through the flue tubes, the strength of the draught towards the flue tubes not allowing it to approach sufficiently near the surface of the fire, to mix with the smoke. In Mr. Connor's system, although the inclined plate, or deflector, at the doorway, gave the air a downward direction, yet, when it was under the action of a strong blast, the current undulated over the arch. In Mr. Douglas's and Mr. Frodsham's systems, the diverting action was still more injurious, because there was no assistance from a brick arch in bringing together the smoke and the air; the air did not strike upon the fire, but went at once towards the tubes. On that account, he thought the brick arch a very useful adjunct, in connection with the inclined entrance of the air into the box. In the plan of Mr. Ramsbottom, the air was introduced in too large a body, through only two places, and, therefore, a great quantity of it must pass through unmixed. He had come to the conclusion, that the air, where it entered the box, should be introduced at the proper level for immediate mixture with the smoke.

But if it was necessary to keep up the steam when the engine was working, it was also important to keep down the steam whilst the engine was standing at the stations, or running without steam on. The chimney blower was required, in order to create a sufficient current of air in the fire box to consume the smoke. Where tubes were placed in the front and back of the box, and induction jets were used, instead of a jet in the chimney, as the nozzles operated above the level of the fuel, the tendency was to prevent the draught through the grate, and thus to suspend the generation of smoke, as well as the consumption of fuel. This was the reason that the steam was not so liable, in this system, to rise to a dangerous pressure.

Another important point was the question of management. It was desirable, that any system employed should be capable of being easily managed; and as the difficulty principally occurred at high speeds with express trains, he considered that which required the least fuel, and the least labour from the stoker, was the best.

He thought, that with deflectors, there was a large quantity of cold air introduced into the fire box. He had taken the sectional areas of the air entrances in some of the systems he had alluded to. In Mr. Connor's plan, for example, the sectional area of the entrance was $67\frac{1}{2}$ square inches, or 5 square inches per square foot of grate. In Mr. Ramsbottom's system, it was 7 square inches per square foot of grate. In Mr. Sinclair's arrangement of Mr. Frodsham's system, upon the Eastern Counties Railway, the area of entrance

MC CONNELL'S SYSTEM, LONDON & NORTH WESTERN RAILWAY.

CUDWORTH'S SYSTEM, SOUTH EASTERN RAILWAY.

D.K. CLARK DEL.

YARROW'S SYSTEM,
SCOTTISH NORTH EASTERN RAILWAY.

JENKINS' SYSTEM, LANCASHIRE & YORKSHIRE RAILWAY.

BEATTIE'S SYSTEM LONDON & SOUTH WESTERN RAILWAY.

CLARK'S SYSTEM, SOUTH EASTERN RAILWAY.

Minutes of Proceedings, Institution of Civil Engineers, Vol. XIX. Session 1859-60.

WILSON'S SYSTEM, OXFORD, WORCESTER & WOLVERHAMPTON RAILWAY.

RAMSBOTTOM'S SYSTEM, LONDON & NORTH WESTERN RAILWAY.

LEE'S SYSTEM, EAST LANCASHIRE RAILWAY.

DOUGLAS' SYSTEM, BIRKENHEAD RAILWAY.

FRODSHAM'S SYSTEM, EASTERN COUNTIES RAILWAY.

CLARK'S FEED-WATER HEATER.

WILL BROS LITHO CASTLE ST HOLBORN

was $5\frac{1}{2}$ inches per square foot of grate. In his own apparatus, the area had been as low as 3 inches; and the maximum allowed was 4 inches per square foot of grate. A plan had been applied to one, or two engines on the Caledonian Railway, for supplying the air direct upon the top of the fire, through a wide spout from the doorway; and that plan was more effective than any other upon the deflecting principle, and was worked with a small sectional area of air entrance. The exit of the air was about 3 inches above the usual level of the fuel, and the air was discharged upon the middle of the fire. A similar plan was employed upon the North London Railway, but it was even simpler; it consisted in using a long shovel instead of a short one, reaching to the middle of the fire box, with an arch. The brick arch appeared to be considered an essential adjunct, in the present practice of coal-burning on railways.

The feedwater-heating apparatus was simply applied to locomotive engines, in the form of a pipe on one side, and a return pipe to the other side. It did not alter the arrangements of any existing engines.

Mr. HAWKSHAW, V.P., had noticed, that in the comparisons made by the Author between his own system and those of others, he had only alluded succinctly to that of Mr. Jenkins. Mr. Hawkshaw had long been acquainted with that system, and it was now extensively applied, at a very small cost, on the Lancashire and Yorkshire Railway. He thought it one of the best, because it was the simplest. One great advantage it possessed, was that it did not interfere with the future use of coke, in the locomotives to which it was applied. It was also free from most of the objections urged against many of the systems of smoke-burning. It mainly consisted in making a certain number of the stays hollow, instead of solid, with as many rows of apertures in the fire box as might be desired. Atmospheric air introduced in this manner, mixed with the products of combustion, and effectually destroyed the smoke. Moveable slides were fixed outside the fire box, by means of which the apertures could be opened and closed, at the pleasure of the engineman. When the apertures were closed, the locomotives were fitted for burning coke as before. He had sent to India, several engines fitted with this apparatus, on account of the equal facility which it afforded for burning either coke, or coal, as circumstances might render necessary. As far as he understood the Author's system, it seemed to be nearly the same as that of Mr. Jenkins, except that the former introduced jets of steam through the apertures. As the latter system had been some time in use upon the Lancashire and Yorkshire Railway, and had effected, as he believed, a large saving in

fuel, he thought it was entitled to more notice than had been bestowed upon it in the Paper. The Author had referred to the difference in the consumption of coal by Mr. Jenkins's system, when applied on the Lancashire and Yorkshire Railways and on the Brighton Railway; but was the same description of coal used in both cases?

Mr. WRIGHT observed, that the experiments on the railway were entirely conducted by his Brother, and he was not in a position to state the results. He only knew, generally, that a considerable saving was considered to have been effected, by the adoption of the system.

Mr. FLETCHER inquired, when the jets were most in use; whether with the engine running, or standing still.

Mr. D. K. CLARK replied, that the steam jet was used, occasionally, whilst running, but it was mostly used when the engine was standing still. *Staveley* coal was employed in the comparative trials on the Brighton Railway, but he took no part, personally, in the experiments.

Mr. G. BERKLEY remarked, that the plan with hollow stays, which had been described, was tried, about nineteen years ago, on the Midland Railway, and was the invention of Mr. Hall, (of Basford). He had also made experiments himself, and with results similar to those at present given. The evaporation of water was from 5 to 15 per cent. less per lb. of coal, than per lb. of coke. An objection was made at the time, that the tubes for the admission of air were liable to be burnt, and he had yet to learn, that such was not still the case. Economy, however, was the order of the day, and where coal could be obtained at much less cost than coke, a want of simplicity, or slight additional repairs would be overlooked. He found, generally speaking, that in the north, coal was not used for the engines; on the North Eastern Railway, it had not been introduced, or only to a slight extent. This was owing, probably, to coke being almost as cheap as coal, in the north of England; so also it was at Bombay. In coal districts, or where there was a large charge for freight to be added to the first cost of the fuel, there was little, or no advantage in using coal. Practically, there was only a saving where the price of coal was considerably lower than coke, but it was obtained at a sacrifice of cleanliness, and, to a certain extent, of simplicity. Mr. Hall's plan and that in use on the Great Western Railway, which was the same as Mr. Hall's, had not been mentioned in the Paper; this was a serious omission. If the complexity was not found objectionable, the introduction by the Author, of the nozzles for blowing steam through the hollow stays, to mix the air with the incandescent gases, commended itself to notice.

Mr. W. H. BARLOW remarked, that upon the Midland Railway there was in operation, a very simple, but efficacious, contrivance, which cost only a few shillings. It consisted of a broad, inclined shovel, placed on the top of the fire-box door; there were no hollow stays and no brick arches. It was assisted by a small jet of steam in the chimney, during the stoppages at the stations; but when the engine was running, the jet was not used. This simple and cheap arrangement was employed, with complete success, upon all classes of engines.

Mr. LONGRIDGE said, that the plan introduced upon the Midland Railway, had particularly come under his notice. He regarded the Author's plan as essentially the same as that introduced, many years ago, by Mr. Hall; a system of hollow stays, introduced into the fire box, by which the air was brought in, to mix with the hydro-carbons. The chief fault found with the system, at the time it was brought forward by Mr. Hall, was, that when an engine was standing at a station, it emitted black smoke. Mr. Hall remedied this, by a small steam jet in the chimney, to create a draught, whilst the engine was standing still, and thus the smoke was effectually prevented. Objections were then raised to the whistling sound of the steam jet, and eventually, the plan was abandoned. He thought, if more willingness had been exhibited by the officers of the company to assist in bringing the plan into working operation, Mr. Hall might have carried it out quite as well as others who had followed him.

Addressing himself to the general question, he said that, after a great many experiments upon the consumption of smoke, he had arrived at this conclusion, which he was satisfied was correct, that deflecting plates and brick arches were of little importance. All that was wanted, was sufficient air to mix with the hydro-carbons, and if it was moderately diffused over the surface of the fuel, there would be little, or no smoke. He had burnt at the rate of 66 lbs. per square foot of fire grate per hour, of bituminous coal, without emitting smoke from the chimney. With the apparatus proposed, many years ago, by Mr. Williams, he was able to introduce a sufficient amount of air, without deflecting plates, or brick arches. With respect to the jets of steam, it was curious, that in 1856, at the time he was much engaged upon this subject, among the plans which came under his notice, was one from Mr. Robert Longridge, of Manchester, who proposed to use hollow stays, with small jets of steam to promote the passage of a sufficient quantity of air. The reason of proposing jets of steam in that case, was, that in the boilers of marine engines, great difficulty was experienced in getting the requisite quantity of air, through the limited number of tubes which could be conveniently

used; but by employing jets of steam, the quantity of air passing through these hollow stays, might be greatly increased. With a jet of steam, as much air passed through a tube 2 inches in diameter, as through one 6 inches, or 8 inches in diameter, without the jet. In a locomotive engine with all the sides open, he did not see any difficulty in putting in a sufficient number of hollow stays, to admit the proper quantity of air for consuming the hydrocarbons. In the furnaces of marine engines for burning north country steam coal, there should be an air entrance of about 4 square inches per square foot of grate. With that amount of area, any gas coal could be burnt without smoke; with less, a sufficient quantity of air would not enter, unless aided by an artificial draught.

The only other point to which he would allude, was the comparative heating powers of coal and coke. This subject was discussed in a Paper, "On the Evaporation of Water from Steam Boilers," which was read at the Institution many years ago.¹ The theory then propounded was, that the same evaporative effect was obtained from coke, as from the quantity of coal from which it had been made. Having had considerable experience with coke ovens, he could not avoid the conclusion, that the flame which issued from them during the process of the manufacture, would boil water, and, therefore, he entirely dissented from that theory.

In a series of experiments with Garesfield coal and coke, which he made in conjunction with Sir William Armstrong and Dr. Richardson, at Elswick, in 1857-58, it was determined to settle this question. The best mode of treating coal, in order to produce the greatest amount of evaporative power, was first ascertained, and then the coke made from the same coal was similarly treated. The final result was, that the evaporative power of the coal comparatively to that of the coke was, weight for weight, as 100 to 89; the actual numerical quantities being:—

Water evaporated from 32° by 1 lb. of coal . .	lbs. 12·54
Do. by 1 lb. of coke made from the same coal . .	lbs. 11·16

But this was scarcely the correct way of stating the question. To produce that coke, the coal would be reduced at least one-third in amount, 100 tons of coals producing less than 66 tons of coke; consequently, taking the above figures, it would be found, that whilst 1 lb. of coal would evaporate 12·54 lbs. of water, the same coal converted into coke, would only evaporate $11·16 \times 0·66 = 7·41$ lbs. of water; so that the true proportion was as 100 to 58. He

¹ Vide Transactions Inst. C.E., vol. ii., p. 16, *et seq.* and Minutes of Proceedings Inst. C.E., vol. i., (1838), p. 17, *et seq.*

could vouch for the accuracy of those results, and he thought they set at rest the theory to which he had alluded.

Mr. HAWKSLEY said, that having been engaged, incidentally, upon this subject, he was gratified at the account of the experiments made twenty years ago, upon the Midland Railway. Mr. Samuel Hall, (of Basford,) the pioneer of surface condensation, was also the originator, almost in its present form, of the system now in use for burning coal in locomotive engines. He was personally acquainted with Mr. Hall, and had taken some share in the experiments from which Mr. Hall obtained his economical results. The apparatus used was extremely simple, and it did not materially differ from some of the diagrams exhibited by the Author of the Paper. It consisted of small tubes, not originally intended for hollow stays, but afterwards frequently adopted for them, which were inserted in the sides, and sometimes, also in the front of the fire box of the engine. By this plan the smoke was almost, but not entirely consumed. The railway companies being then more particular with regard to the consumption of smoke, than they appeared to be at present, refused to adopt the plan which was, therefore, supposed to have failed; but so far as he knew, its success was fully equal to that now obtained with other apparatus. The smoke was not perfectly consumed under all circumstances, nor was it now, for the amount of dust and smoke, issuing from the coal-burning engines of the fast trains of the present day, was so considerable, that the windows of the carriages could not be opened, without covering the passengers, and filling their eyes with small particles of dirt and cinder.

Mr. Hawksley had also occasion, at that time, to make some elaborate experiments upon the relative values of coal and coke. As the Engineer of the Nottingham Gas Company, and of the Nottingham Waterworks Company, he had an opportunity of exactly determining the quantity of coke which could be manufactured, in closed vessels, from a given weight of coal. He had also the opportunity of trying the evaporative power of the coke, as contrasted with that of the coal from which it was made, under the furnace of a pumping engine, raising a known quantity of water to a known height. He found, upon the average of a year's working, that from 20 cwt. of coal of the midland counties, which was very different from the north country coal, $11\frac{1}{2}$ cwt. of coke were obtained, besides other products. He then ascertained, that 6 cwt. of coke would evaporate exactly the same quantity of water as 7 cwt. of coal. It followed, therefore, that it required almost precisely 3 tons of coal reduced to coke, to produce the effect of 2 tons of the same coal, and consequently, there was a loss in converting the coal into coke for the purpose of producing steam; but considered only in reference to weight, coke had an advantage over

coal, in the proportion of 7 to 6. Such would be the result with most of the midland coals. The Derbyshire coal contained in every ton, no less than 300 lbs., or 350 lbs. of oxygen and hydrogen in such proportions as to combine, during distillation, and to form water: this quantity was, of course, entirely lost. Tar was another product of distillation, which was burnt in the ordinary process of forming coke, but which, in the process used for manufacturing gas, was caught in tanks; that amounted to another 100 lbs. per ton. So that, in every ton of this Derbyshire coal, there were from 400 lbs. to 450 lbs. of matter which could not be utilised in the shape of coke, in addition to more than 350 lbs. of inflammable gases which passed off in the conversion, besides carbonic acid and other non-inflammable gases, amounting altogether to more than 900 lbs. in every ton of coal; the residue alone was coke.

Reference has been made to the possibility of consuming smoke economically. He believed it to be physically impossible to consume smoke once formed, without loss, and the reasons were sufficiently obvious. If all the carbonaceous matter of the smoke was consumed, additional heat was, certainly, obtained, but by means which entailed more than a corresponding loss. This was proved both by experiment and by calculation; because if a certain quantity of oxygen was introduced into a furnace, a much greater quantity of nitrogen was introduced at the same time; 7 lbs. of nitrogen, in fact, for every 2 lbs. of oxygen. The nitrogen did not contribute to the combustion, but required to be itself heated, and therefore, it carried up the chimney a large quantity of the heat evolved from the combustion of the particles of smoke. But independently of that, there were no means of getting every particle of smoke which escaped unconsumed from the fire, to meet with the necessary particles of oxygen, unless a much larger quantity of air was introduced above the fire, than was theoretically necessary for the purpose. But in so doing, a correspondingly larger quantity of nitrogen was also introduced at the same moment, and thus the loss occasioned by heating the excess of oxygen and nitrogen, was much greater than the gain from utilising the heat of the carbonaceous particles of which the smoke consisted.

In making his experiments on the combustion of smoke, he had used a very perfect, self-acting apparatus applied to the boilers of a pumping engine, with the following results:—1st. When the engine was well fired, without the admission of air above the fire, the consumption of fuel was 100; but in this case, smoke was evolved in considerable quantity. 2nd. When the air was admitted in sufficient quantity to consume the smoke, without being shut off during any portion of the interval between the firings, the consumption of fuel became 120. 3rd. When the self-acting apparatus was brought into operation, to exclude the air so soon as smoke had

ceased to be emitted, then the consumption of fuel was reduced to 110.

The smallest additional consumption consequent on the consumption of the smoke, was about 10 per cent. The trial was frequently continued for several days together, without putting the air holes into operation, and then the consumption uniformly went down; when they were again called into action, the consumption as uniformly increased. He believed it was impossible to conduct experiments with greater care, or in a better manner, for determining the point in dispute between those who alleged, that the combustion of smoke was not, in a pecuniary sense, economical, and those who asserted the contrary. He thought the Paper had sufficiently shown, by the average of all the experiments related, that weight for weight, the consumption of coal in locomotives was greater than that of coke; and this result was confirmed by calculation, which proved, that such must, necessarily, be the case. It might, nevertheless, happen, that when the coke was consumed in an ill-adapted furnace and the coal was consumed in a well-adapted furnace, the contrary would result, and the experimenter would be led to an erroneous inference. Unless, however, 6 cwt. of coke could be delivered into a tender as cheaply as 7 cwt. of coal, when the smoke was not consumed, and about 8 cwt. when the smoke was consumed, the mere pecuniary economy must be on the side of the coal.

Mr. YARROW,—through the Secretary,—observed, that it would appear from the Paper, that the system used upon the Great North of Scotland Railway was superior to the others, as regarded the amount of fuel consumed per mile, relatively to the gross load carried. To enable a proper comparison to be made, the Paper should give, in addition to the average speed per mile for the whole distance run, and the number of pounds of water evaporated by 1 lb. of coal, the greatest altitude surmounted in each case,—the average gradient,—and also its length. The experiments should be made on the same line of rails, with a train running at the same speed, and with the same stoppages. On the Scottish North Eastern Railway, for example, the speed of the passenger trains was about 35 miles per hour, whilst on the Great North of Scotland Railway, it did not exceed 25 miles per hour. The two cases did not, therefore, admit of comparison, as there was a greater amount of resistance, and consequently, more power was expended, on one of the lines, than on the other. Again, the speed of the goods trains, upon the Great North of Scotland Railway, was about 13 miles per hour, whereas upon the Caledonian Railway, it was about 20 miles per hour. On the Scottish North Eastern Railway, there was a rise of $340\frac{1}{2}$ feet above the level of the terminal station, of which $234\frac{1}{4}$ feet had to be surmounted within a distance of

7 miles, the heaviest gradient on that part of the line being 1 in 91. There were various other steep gradients on the line; for instance, on another portion, $171\frac{1}{2}$ feet had to be surmounted within a distance of $3\frac{1}{2}$ miles.

Mr. ZERAH COLBURN,—through the Secretary,—presented the following observations on coal-burning locomotives in the United States:—

The circumstances affecting the substitution of coal for other fuel, were dissimilar in England and in the United States. So far as the question concerned English railway companies, it appeared to have already received a satisfactory solution; but it was still the subject of much discussion in America.

The cost of fuel on the lines in the Northern and Eastern States, averaged as much as 9*d.* per train mile. This fuel consisted, generally, of wood, which was sold by the 'cord' of 128 cubic feet, weighing about $1\frac{1}{2}$ ton. One cord and a half, or rather more than 2 tons of good wood, would evaporate as much water as 1 ton of coal; and this quantity of wood sometimes cost as much as £2. 3*s.* The Directors of the Baltimore and Ohio Railroad Company, although their line intersected rich beds of semi-bituminous coal, stipulated, so long ago as 1831, that the engines to be constructed for their line should burn anthracite, so as not to emit any smoke. In 1837, the Beaver Meadow Railroad Company adopted the use of anthracite coal in their engines, which were of ordinary construction, and they still continued to employ it. In attempting, however, the general introduction of the same coal for long and heavy traffic, it was found, that although there was not any smoke, the steam was kept up with difficulty, and that the fire box and fire bars were quickly burnt out. Notwithstanding these objections to its use, anthracite was, in some cases, a cheaper fuel than wood. The Reading Railroad, the principal channel of the anthracite coal trade, was worked with this fuel, which was burned, however, with considerable waste. The fire box was very large, and was sometimes placed entirely behind the wheels of the engine, so as to obtain sufficient room for a grate, 5 feet in width. For the heavy goods engines, the grates were, generally, 7 feet in length and 3 feet 6 inches in width. The fire box was made, in most cases, of iron plates, $\frac{5}{16}$ ths of an inch thick, but copper was sometimes used about the bottom. The tubes were of iron, $2\frac{1}{4}$ inches in diameter and 14 feet in length. The top of the fire box sloped off at an angle, and the fire was partially fed through a door in the roof. The hinder end of the fire box had no water space, being covered with a cast-iron plate, having two doors across its entire width, for feeding the fire, and two others below them, for raking out the fire bars. A few large openings were made in these doors, for the admission of air. The fire bars were always of cast iron, and were,

in the engines under notice, very heavy; the width between the bars was as much as $1\frac{1}{2}$ inch. They were cast in pairs, and each pair of bars had a shank, or stem, projecting behind the fire box: through a round hole in this shank, a bar was, occasionally, inserted, to shake the grate and to break up and dislodge the accumulated clinker. The ash pan was made with a water-tight bottom, and water was, occasionally, turned into it from the tender, to quench the hot coals and cinders dropping through, which would, otherwise, burn out the fire bars. A variable blast pipe was always applied, with a nozzle capable of being contracted from 18 to 6 square inches. With these arrangements, the reports of the company showed, that anthracite coal was burned at the average rate of 117 lbs. per mile, in engines weighing 28 tons, and drawing a gross load of 750 tons, at a speed of from 10 miles to 12 miles per hour, on a level. The evaporation of water was from $5\frac{1}{2}$ lbs. to 6 lbs. only, per lb. of coal. Mr. Colburn had conducted trials over the line in winter, when the consumption was 13,500 lbs. of coal, for 95 miles, or 142 lbs. per mile. The engines on this line had eight coupled wheels, 3 feet 7 inches in diameter; the diameter of the cylinders was 19 inches, and the stroke was 22 inches.

When the question of a general substitution of coal for wood was agitated, ten, or twelve years ago, among railway authorities in the United States, it was assumed, that only anthracite coal could be adopted, as smoke was thought to be inseparable from the use of bituminous coal. The locomotive superintendents of the various lines took out no patents, however, and the question was left open to inventors generally, most of whom appeared disposed to make the greatest possible changes in the ordinary form of boiler. Their plans were carried out by builders of locomotives, as well as by the different railway companies, and were worked with more, or less success. As some of these plans had, in this way, acquired considerable prominence in America, it might be desirable to give a brief description of them.

Phleger's boiler, as constructed in the engines made by Messrs. Richard Norris and Son, of Philadelphia, had a combustion chamber, formed by a deflecting water bridge in front of the tubes which, with the barrel of the boiler, were placed rather lower than usual. At first, the fire boxes of these boilers had close water bottoms, the air for combustion being forced in by a blower. The water bottom was still retained, although the air was allowed to enter in the usual way. A variable blast pipe, and a steam jet, or blower in the chimney, were provided, as in all American coal-burning locomotives.

In Dimpfel's boiler, the water was contained in the tubes, and also in a long annular water space, answering to the ordinary

[1859-60. N.S.]

2 Q

cylindrical barrel of the boiler. The tubes were of iron, and of small diameter. They descended from the roof of the fire box, bending and extending thence to a water space at the forward end of the boiler. This plan had been extensively introduced by the Taunton Locomotive Manufacturing Company.

Boardman's boiler, as constructed in the engines made by Messrs. William Mason and Co., of Taunton, had upright tubes, through which the heat descended from a long combustion chamber, or flue, in the upper part of the boiler. This flue extended to and opened into the smoke box, but a plate was interposed, a few feet from the smoke box, the heat descending through the tubes next the fire box, and traversing an ash pan, before ascending the front tube.

Phleger's, Dimpfel's, and Boardman's boilers had been used, more, or less, for the last ten, or twelve years; but experimentally rather than practically. They had been made to burn bituminous as well as anthracite coal, and they were used on passenger as well as on goods trains. Each of these plans furnished considerable space for combustion, and in each, air was admitted in numerous fine streams over the fire. Each had obvious disadvantages, and neither was applicable to the existing stock. All were heavy and complicated, Boardman's boiler especially, and much of its weight was thrown upon the front wheels of the engine, where it was least desirable. The boiler occupied the whole space between the framing of the engine. This was not, however, an important objection, as, since 1854, all American locomotives had been made with outside cylinders, not only for the gauge of 4 feet 8½ inches, but also for those of 4 feet 10 inches, of 5 feet, of 5 feet 6 inches, and of 6 feet; the latter being the widest railway gauge in the United States. The staying of the flat sides of the Boardman boiler required great care, and with the stays fastened, as they had been, on the inside of the boiler, it was very difficult to replace them.

Within the last three, or four years, renewed attempts had been made, to adapt the existing stock of engines to the use of bituminous coal. The difficulties to be encountered, consisted in the large quantity of coal required to be burned in a given time, under an intense draught, and in the character of the coal itself, which produced a great quantity of clinker. American railways, generally, required more power to work them than was necessary on English lines. This arose from the steeper gradients and the sharper curves in the former, and from the inferior condition of the permanent way. The trains, although less frequent, and although running at a speed slower by one-third to one-fourth than the trains on English lines, were from one-third to one-fourth heavier. The engines, on the other hand, were not heavier, on

the average, than in England, nor had they more heating surface. They burned more fuel, however, and evaporated fully one-third more water, in a given time ; a result depending on the strength of the draught. The average evaporation in American locomotives, might be taken at 120 cubic feet of water per hour. The 8 cwt., or 9 cwt. of coal necessary for this evaporation, had to be burned on a grate of which the area, generally, was not more than 14 square feet, giving a combustion of from 60 lbs. to 70 lbs. per square foot of grate per hour. The coal, besides being smoky and often sulphurous, was of that kind which quickly crusted over the top of the fire, and it, generally, made a large quantity of clinker : this was sometimes carried, by the strength of the draught, against the ends of the tubes, which thus became, in some cases, completely closed within half an hour after starting.

In December, 1856, Mr. George S. Griggs, of the Boston and Providence Railroad, introduced a fire-brick arch below the tubes, in the fire boxes of some of the engines of that line. With a few holes for the admission of air above the fire, this arch was found to improve the working of the fire box, when burning coal. A good deal of fine coal was carried through the tubes, and the ordinary spark-arrester of the wood-burning engines was, therefore, retained. By carefully selecting the best coal in the market, Mr. Griggs was enabled to use the ordinary fire bars ; but on other lines, with coal producing more clinker, bars had been adopted which could be moved while the engine was running. In some cases, the whole fire grate had been formed of stout chains, suspended across the fire box ; the flexibility of this arrangement had an important influence in keeping the fire clear of clinker. It had been also found, that with coal producing much clinker, the air opening of the grate required to be materially diminished, so as to localise the draught over a comparatively small area, and thus, by intensifying the combustion, to thoroughly fuse the clinker, which then ran off like glass. On the Iowa Central Railroad, the grates of the coal-burning engines were, at one time, covered with fire brick, so as to leave exposed only about 2 square feet of the original surface of the bars, and of this area less than 1 square foot was used as an air opening. This arrangement was found to work well, with coal producing much clinker ; and, notwithstanding the diminution in the area of the air opening, as much coal was burned, and as much steam was made as before. In other coal-burning locomotives, it was now usual to close up from 12 inches to 30 inches of the front ends of the fire bars, and in many cases, the 'dead plate,' as it was called, extended along the sides of the fire box, reducing the area of the grated portion of the fire box bottom to 4, or 5 square feet, of which less than one-half was air opening. Upon the dead plate, the coal

became partially coked before entering into active combustion. The fire was fed, generally, with small quantities of coal, frequently and equally applied. More recently, perforated door plates and air distributors, the latter set up within the fire box, had been extensively adopted. It was only rarely, that the spark arrester of the wood-burning engines was dispensed with, in burning coal. This apparatus intercepted considerable quantities of fine coal, which, under a strong draught, would otherwise have been thrown out at the top of the chimney.

The circumstances affecting American railway traffic were so different from those which existed in England, that it would hardly convey an accurate idea of the success of these plans, to give the consumption of coal per train mile. It might be said, however, that they worked with tolerable freedom from smoke, that they generally afforded a good command of steam, and that they gave an evaporation of from $6\frac{3}{4}$ lbs. to $8\frac{1}{2}$ lbs. of water per lb. of coal.

Mr. LONGRIDGE said, he had already given the results of some carefully-conducted experiments, showing a decided advantage in the evaporative powers of Garesfield coal, over the coke made from that coal. He should not have again referred to those results, had it not been contended, that theoretically, as well as practically, coke was superior in heating power to the coal from which it was made. It was not possible to determine, theoretically, the precise temperature arising from the combustion of fuel, owing to ignorance of the specific heats of the products of combustion at high temperatures, and also of the latent heat of some of the generated gases which were, probably, emitted in a solid form in a body, like coal. So far, however, as theory would go, calculation¹ showed, and his experience confirmed the fact, that the

¹ HEAT GENERATED BY 1 lb. OF COAL.

	lbs.	Units of Heat.
Carbon	0.8152	$\times 14,500 = 11,820$
Hydrogen	0.0522	
Less the amount to combine with the oxygen in the coal	0.0077	$= 0.0445 \times 62,032 = 2,760$
Sulphur	0.0115	$\times 4,152 = 48$
Total heat generated		<u>14,628</u>

PRODUCTS OF COMBUSTION, MULTIPLIED BY THE SPECIFIC HEAT.

	lbs.	Specific heat.
Carbonic acid	2.989	$\times .217 = 0.6486$
Sulphurous acid gas	0.023	$\times .240 = 0.0055$
Nitrogen	8.912	$\times .245 = 2.1834$
Steam	0.470	$\times .475 = 0.2223$
Ash	0.046	$\times .200 = 0.0092 = 2.860$

Consequently, the resulting temperature = $\frac{14,628}{2.860} = 5,098^{\circ}$.

[Proceeding

temperature resulting from the combustion of 1 lb. of Hartley coal, was greater than that resulting from 1 lb. of the coke made therefrom, in the proportion of $5,098^{\circ}$ to $4,695^{\circ}$, or of 100 to 92; and the proportion would be still higher in a coal like the Garesfield, containing more hydrogen.

It had been urged, against the economical use of bituminous coal, that to prevent the smoke arising from its use, it was necessary to introduce into the furnace, an extra quantity of air, which carried off a large amount of heat. Now the extra quantity of air required for perfect combustion, was not nearly so large as was generally thought. He had made direct experiments to ascertain the fact, with an apparatus so arranged, that the quantity of air actually passing through the furnace could be accurately measured, separating, moreover, what passed through the bars from what was admitted above the fire surface. The result was, that to burn 1 lb. of Hartley coal perfectly, it required 149.4 cubic feet of air at 60° and 30 inches of mercury.¹ Now it was found, that

Proceeding in the same manner with the coke, consisting of:—

Carbon	. . .	94 per cent.
Ash	. . .	6 „

HEAT GENERATED BY 1 lb. OF COKE.

Carbon	. . .	$0.94 \times 14,500 = 13,630$
--------	-------	-------------------------------

PRODUCTS OF COMBUSTION, MULTIPLIED BY THE SPECIFIC HEAT.

	lbs.	Specific heat.	
Carbonic acid	. . .	$3.415 \times .217 =$	0.7411
Nitrogen	. . .	$8.774 \times .245 =$	2.1496
Ash	. . .	$0.060 \times .200 =$	0.0120 = 2.9027
Consequently, the resulting temperature =		13,630	
		2.9027	= $4,695^{\circ}$.

This, in the case of coal, was found = $5,098^{\circ}$;

Therefore, 1 lb. of coal : 1 lb. of coke :: $5,098^{\circ}$: $4,695^{\circ}$
 :: 100 : 92 nearly.

¹ QUANTITY OF AIR REQUIRED FOR THE PERFECT COMBUSTION OF 1 lb. OF HARTLEY COAL.

Composition of 1 lb. of Coal.

Oxygen	. . .	0.0615
Hydrogen	. . .	0.0522
Nitrogen	. . .	0.0150
Sulphur	. . .	0.0115
Carbon	. . .	0.8152
Ash	. . .	0.0446

Oxygen required for the Perfect Combustion of the above.

Carbon	. . .	$0.8152 \times \frac{16}{8} =$	2.1738 lbs.
Hydrogen	. . .	$0.0522 \times \frac{8}{1} =$	0.4178
Sulphur	. . .	$0.0115 \times \frac{16}{8} =$	0.0115

		2.6031
Deduct oxygen in coal	. . .	0.0615

Oxygen required from the air . . . 2.5416 lbs.

Hence, the weight of air will be $2.5416 \times \frac{28}{8} = 11.4372$ lbs.; from which the volume of 60° and 30 inches of mercury is found = 149.4 cubic feet.

with the ordinary system of stoking and making a dense smoke, the quantity of air which passed through the furnace, was only 100 cubic feet per lb. of coal burnt, showing conclusively, that a great deal of carbonic oxide was passing off with the products of combustion. When smoke was entirely prevented, by air admitted above the fire, the quantity was found to be 158 cubic feet, being only 9 cubic feet above what was necessary for the perfect combustion of the coal. The temperature of the up-take was also ascertained under the two circumstances, with and without the additional quantity of air. When 100 cubic feet of air per lb. of coal passed through, the temperature was 448° ; with 158 cubic feet of air passing through, the temperature was 480° .¹ To the boiler in which these experiments were tried, there were adapted means of regulating the quantity of air admitted above the grate. In another case, with no air except that which passed through the bars, and with much smoke, the temperature in the chimney was 600° . With one aperture open, the temperature was 625° ; with two apertures, it was 633° ; with three, it was 638° ; and with five, it fell to 620° ; showing again, that up to a certain point, the admission of air did not decrease, but rather increased, the temperature. He thought these results were conclusive proofs; first, that it was not necessary to introduce an excessive quantity of air, above what was chemically required for combustion; and secondly that the result of the admission of air, in such quantity as was required to prevent smoke, was to increase the temperature of the chimney, and to decrease the consumption of fuel.

This had, however, been fully confirmed by experiments made by order of the Admiralty, in March and April, 1859, on board the 'Bustler,' to ascertain the advantages, or otherwise, of the use of ventilating doors for the prevention of smoke. Those made in March, showed an advantage of $16\frac{1}{2}$ per cent., and in April,

¹ RESULTS OF TEN EXPERIMENTS ON HARTLEY COAL, made at ELSWICK, in July, 1857, by J. A. LONGRIDGE, SIR WILLIAM ARMSTRONG, and DR. RICHARDSON.

Weight of Coal burnt, per Square Foot of Fire grate per Hour, in lbs.	Water Evaporated from 212° by each lb. of Coal, in lbs.	Total quantity of Water Evaporated, per Hour, in Cubic Feet.	Quantity of Air used per lb. of Coal burnt, in Cubic Feet.	Temperature of Smoke Box.	Remarks.
17.34	12.27	56.71	158*	480°	No Smoke.
21.00	10.06	56.01	100	448	Much Smoke.

* Of this, about 88 cubic feet were admitted through the doors, and 70 cubic feet through the fire bars.

The quantity of air required for the perfect combustion of 1 lb. of this coal, is 149.4 cubic feet, at 60° Fahrenheit, and 30 inches of mercury, as shown in the preceding note; (pages 576-7).

of not less than 21 per cent. of coal per indicated H.P., in favour of the use of the ventilating doors; thus fully bearing out the results arrived at by Mr. Longridge, Sir William Armstrong, and Dr. Richardson, in the Elswick experiments. The following Table was extracted from a return to the House of Commons, "of the Results of Experiments which have been made by the Admiralty on board any of Her Majesty's ships, with a view to the consumption of smoke, combined with the economy of fuel, within the last eighteen months," and which was ordered by the House to be printed on the 18th of April, 1860:—

Date of Trial.	Draught of Water.		No. of Experiments.	No. of Runs in each.	Duration of Experiment.	Total Coal burnt.	Mean Indicated H.P.	Coal per H.P. per Hour.	Mean Revolutions.	Mean Pressure.	Mean Speed.
	Forward.	Aft.									
1859.	Ft.	in.	Ft.	In.	Hours.	lbs.		lbs.	Per Min.	lbs. sq. in.	Knots per Hour.
10 Mar.	7	1	6	8	4	6,326	244·9	6·45	23·10	16·92	8·879
18 Mar.	6	11	6	9	4	7,410	241·4	7·67	23·20	16·60	8·964
15 Apr.	6	11	7	2	4	5,600	245·4	5·70	22·34	17·53	8·467
19 Apr.	6	11	7	2	4	7,100	246·6	7·20	22·80	17·26	8·793

The experiments on the 10th of March and on the 15th of April, were made with the ventilating doors open, and firing at the sides of each furnace alternately; on the 18th of March and the 19th of April, these doors were closed. Bituminous, north country coal was used in the first pair of experiments. On the 10th of March, smoke was only visible when the fires were urged and stirred; it was then of a light brown colour, and in moderate quantity. On the 18th of March, the smoke was dense and black during the trial. In the second pair of experiments, the coal was of good quality, and in a fair condition as to size. On the 15th of April, only a light brown smoke issued from the chimney, and for a considerable portion of the time, there was no smoke. The mercury in the barometer, on this occasion, stood at 29·1 inches, and there was a strong gale of wind on the beam, so that it was with difficulty the vessel was kept in a straight course, consequently showing a reduced speed. On the 19th of April, the weather was calm, the mercury in the barometer stood at 29·6 inches, and much black smoke was emitted.

Mr. HAWKSLEY did not doubt, that the experiments made at Elswick, had been as carefully carried out, as experiments of that nature could be, and he concurred in the results, but he could satisfactorily explain them. If there was an insufficient quantity of air below the fuel, carbonic acid was generated, and as it progressed, it decomposed into carbonic oxide, an unflammable gas, which required fresh air to be introduced, in order to re-convert it

into carbonic acid gas. That action always took place when the fire was deep. It was evident, that in the cases mentioned, carbonic oxide was formed, because, when the air was admitted over the fire, the temperature was increased. Those experiments, therefore, although perfectly well made, were not experiments which settled the matter in dispute. The furnace was not in that particular condition which was necessary for burning the particular fuel placed upon it, and his observations had reference to coal and coke, burnt in furnaces constructed for the purpose. In his own experiments, perfect combustion was obtained in both cases, and as he had already stated, the result was, without entering into the commercial part of the question, that, weight for weight, coke was superior to the coal from which it was made. He believed the reason of it to be, that the coal contained moisture and other matters which did not contribute, during its combustion, to the production of heat.

Mr. E. A. COWPER,—through the Secretary,—remarked, that when burning coke, carbonic oxide was always formed in greater, or less quantities, even with a moderately thin fire, and it was interesting to know the area of opening for air which was considered sufficient, per square foot of grate, to properly consume it. The coke, as well as the coal, ought to be burnt in the best manner, in order to institute a fair comparison. He was much gratified, that the decisive experiments upon the quantity of air actually used for the consumption of fuel, had proved it to be nearly the amount theoretically required, as it confirmed him in a conviction he had long entertained, that Count Rumford and others were wrong in stating, that twice the theoretical quantity of air had always to be passed through the fire, to effect proper combustion. Now it was quite certain, that with any ordinary boiler fire, some air must be passed over the fuel, in order to prevent smoke; for it was, practically, impossible to keep a fire sufficiently thin to pass enough air through it, for burning all the gases and carbon, as then the grate would frequently be partially uncovered. There was a decided economy in burning the carbonic oxide and hydrogen, by the introduction of air in proper quantities, so as to prevent smoke, though the advantage was not very great. In numerous experiments which he had made with different sorts of coal and coke, he had found, that good oven coke was more valuable, weight for weight, than good coal, when each was burnt in the best manner, and that good gas coke was, generally, equal to coal. He believed, that the steam coals for the navy ranked, to a great extent, in proportion to the per-centage of carbon in them.

With regard to the water heater, he mentioned, that about the year 1848, he had seen a similar contrivance at Renfrew, in Scotland, and that it answered very well, giving the feedwater a tem-

perature of nearly 212° . It consisted of a box, into one side of which the steam entered, passing out at the top, whilst the water to be heated came in at the top, and fell through the steam, being entirely encompassed and in direct contact with it; he believed the same system had been employed at Mr. Hague's, and at many other places.

The plan of admitting air through hollow stays into the fire boxes of locomotives, as proposed by Mr. Hall, of Basford, had been revived by Mr. M'Connell, with the addition of jets of steam supplied from the boiler, to drive in the air. The advantage of being able to forcibly drive powerful jets of air into the gases was, no doubt, very great, as the jets would penetrate the gases in a similar manner to the blast in a blast furnace; and the opportunity it gave of preventing all vacuum, or draught in the fire box, when standing at a station, was also of great utility. He did not think, that it was clearly stated in the Paper, that all the plans had the means of regulating the quantity of air admitted, so that in none of them was there, necessarily, a large quantity of air entering at all times. In the most recent plan, that of the long spout, or shovel, there were on many lines, proper sliding doors in front, so that the driver could easily regulate the quantity of air, by touching the doors with his foot, or hand. It was an exceedingly simple and excellent contrivance, but did not, like the tubular stays and steam jets, give the power of introducing air when the engine was standing.

Mr. C. GREAVES,—through the Secretary,—thinking it desirable, that the progress in the economy of fuel, so far as those occupied in the locomotive branch of engineering had succeeded in carrying it, should be made known, would bring forward some results derived from the experience of stationary engines, to assist the discussion, so far as there might be any analogy between the different circumstances.

The philosophy of the production of smoke appeared to have been succinctly stated in the Paper. The hydrogenous compounds in coal were those most readily extracted by heat. The hydrogen did not leave the coal without bringing with it a portion of carbon, but notwithstanding their union, the hydrogen was still the more easily inflammable of the two. Neither of them would burn without the presence of atmospheric air; if, therefore, there was only a limited quantity of air, the hydrogen was burnt without the carbon and it formed smoke. It was, however, practically found, that it required less heat to consume the hydrogen, than to burn away the solid carbonaceous portions of the coal. There were, consequently, two methods of preventing the occurrence of smoke; either to force, or to admit to the inflaming hydrogen, a sufficient quantity of air to render the combustion of

both it and its gasified carbon complete, and to continue this only so long as it was necessary ; or to delay the explosion of the hydrogen and gaseous carbon, so that the ordinary flow of air, admitted through the bar, for the combustion of the solid carbon, should suffice for the combustion of the hydrogenous compounds. Now the latter process could not be easily effected in locomotive fires, but in land and stationary boilers, it was not difficult, with the cheapest small coal, so to damp the coal and to lay it on the fire quickly in a thick heap, that the charge of coal should ignite only from the face in contact with the previous fire. The combustion of the gaseous part was slackened to the rate of the admission of the air from the fire grate, and a smokeless process was maintained. This was not a theory, for he had now, for some years, practised the plan, at the rate of 4,000 tons per annum, with perfect success as to smoke, and with excellent results as to efficiency, as the following Table would show :—

TABLE showing the amount of fuel employed in four sets of boilers, the comparative proportion of small coal contained in it, (the rest being gas coke,) and the evaporative power obtained per lb., at an average temperature of 80° ; during the first half of the year 1859 :—

	Fuel, in Cwt.	Per Centage of Small Coal.	Water Evapo- rated, in lbs.
No. 1 . .	16,259	92·97	7·91
„ 2 . .	14,248	89·71	8·32
„ 3 . .	4,265	90·00	8·16
„ 4 . .	4,578	82·98	8·61
„ 5 . .	5,701	88·68	7·59

The following were the results during the second half of the year 1859 :—

No. 1 . .	17,814	91·63	7·81
„ 2 . .	12,186	84·03	8·00
„ 3 . .	7,435	86·75	8·13
„ 4 . .	8,083	88·35	7·82
„ 5 . .	1,367	85·73	8·18

The average rate of combustion of the whole, was about 6 $\frac{1}{4}$ lbs. per square foot of grate per hour.

The relative calorific power of coal and coke had been, similarly, the subject of patient investigation, and reliable results had been obtained from trials extending over a long period. Taking the small of the best coal as a standard of comparison, the use of gas coke gave a result superior to it, of 14 per cent. The combustion of those coals usually called steam coals, as Holywell Main, West Hartley, South Peareth, &c., only produced an effi-

ciency from 5 to 10 per cent. more than that of small coal, which, on an average, cost about 11s. 6d. per ton. The steam coal was burnt without any attempt to avoid smoke.

He regretted, that it should ever have been stated, that coke would do more work than the coal from which it was made. His experience had, unequivocally, proved, that under boilers commonly called Cornish, worked at high pressure, at a moderate rate of thorough combustion and with every advantage, one ton of coke would perform more work than one ton of such coal as that from which coal gas was made. Indeed it would, he thought, be generally admitted, that the calorific power of that part of the coal, which produced the hydro-carbons, or the gaseous matter, was lower than the calorific power of the carbon, which burned by direct combustion with oxygen. Both coal and coke, as ordinarily burnt, contained about 7 per cent. of waste; and coal, burnt as coal, appeared to afford 65 per cent. of solid combustible matter, and 28 per cent. of combustible gas. Now picked and clean coke would evaporate ten and a half times its weight of water, at a temperature of 80°; therefore 0.65 lb. of the pure carbon in 1 lb. of coal would evaporate 7.34 lbs. of water. But 1 lb. of coal afforded 4.46 feet of gas, and 100 feet of gas only evaporated 28.3 lbs. of water, at which rate, 4.46 feet would evaporate 1.26 lb.; and admitting, that a larger proportion of carbon was burnt in a gaseous form with an open fire, than with retorts, the result was 7.34 lbs. and 1.26 lb., which with an addition of, say 0.65 lb., made the total efficiency of good coal 9.25 lbs., as compared with 10.5 lbs., the efficiency of good coke, at a temperature of 80° Fahrenheit. The relative values of 9.25 lbs. for coal and 10.5 lbs. for coke, on special trials, with care and exactness, were about equivalent to 8 lbs. for coal, and 9 lbs. for coke, in ordinary practice and with long trials; and from his own experience, he adopted the latter quantities as their relative value by weight. Generally speaking, all trials of relative value, by the cost of the fuels, were much more favourable to coal. There were, unfortunately, no good Reports of the calorific power of gas, used in a practical way; a good series of experiments would be extremely valuable.

He had the highest opinion of the plan advocated by the Author, the control of the acting force, being, under the peculiar and varying conditions in which locomotives were placed, the point to be aimed at; increasing the admission of air up to the irregular requirements of the coal gases, rather than delaying the explosion of gases to the minimum rate of admission of air, through the ordinary fire grate.

MR. D. K. CLARK said, the result of his experience was, that so far as locomotive engines were concerned, a saving of coal to

the extent of 18 per cent. had been effected, by properly consuming the smoke. If coal was burnt in a locomotive, without any provision for the admission of air above the fuel, certain unconsumed gases were sent through the chimney. In 1856, he had made a comparison of the cost of coke and coal, and he found, that coke cost, upon an average, 18s. 2d. per ton, and coal 8s. 7d. per ton; the recent introduction of coal-burning in locomotives had slightly reduced the price of the coke. The prices at Crewe, were 14s. 11d. for coke, and 7s. 10d. for coal. On the Oxford, Worcester, and Wolverhampton Line it was 21s. for coke and 10s. 6d. for coal, and on the Midland Railway 20s. for coke and 9s. for coal. On the North Eastern Railway the price of coking coal was not more than 6s. per ton, its conversion into coke would raise it to 9s., and allowing 1s. per ton for labour and the maintenance of furnaces, the total cost would be 10s. per ton. The difference in price as compared with coal, was thus only about 4s. per ton, scarcely sufficient to induce the company to use the latter.

In reply to remarks by Mr. G. Berkley,—that the coke was made from the refuse of the coal, and by Mr. T. E. Harrison, that a large quantity of coke was supplied to the North Eastern Railway Company, at 9s. per ton,—Mr. Clark said, that the information he received was, that the coking coal was sold at 6s. per ton. He had not been able to give in detail, the particulars of Mr. Jenkins's apparatus, as employed upon the Lancashire and Yorkshire Railway, but he had understood, that the air was admitted to the furnace, through rows of tubes, at different levels, varying from each other as much as 12 inches, in their height above the grate; if the lower rows were covered by the fuel, the air so introduced below the level of the fuel did not contribute towards the prevention of smoke. As regarded the comparative performances of Mr. Jenkins's apparatus and that of the Author, on the Brighton Railway, the two systems were applied in the same passenger engine No. 89, and by the Official Report of Mr. Craven, the locomotive superintendent, the respective results were as he had stated them in the Paper. The number of miles run by the engine under Mr. Jenkins's system was 1,949, with a consumption of coal of 33·6 lbs. per mile; and under his own system, on the same duty, 878 miles, with a consumption of 29·3 lbs. of coal per mile. It should be observed, that the longer mileage run in the first case, was a favourable circumstance in the trial of Mr. Jenkins's system, as the excessive consumption of fuel incidental to the trial of new systems, during the first few days, was arranged over a greater number of miles in his case, than in Mr. Clark's.

He might state, that the greater part of the information demanded by Mr. Yarrow, for the purpose of enabling a proper com-

parison to be made, was given in the Tables ; that it was of no use to give the altitudes simply, unless the particulars of the inclines, and the length of the trips were also given ; that the average speed of the goods trains on the Caledonian Railway, deduced from the service time tables, was 12 miles per hour, not 20 miles per hour, and on the Great North of Scotland Railway, it was, by the time tables, $14\frac{1}{4}$ miles per hour, not 13 miles ; further, that the average distance run between stopping stations was, on the Caledonian, $6\frac{3}{4}$ miles, and on the Great North of Scotland, 4 miles.