MR. AIRY remarked that the Paper was simply an accurate investigation in one single instance of a very difficult problem, and was not framed to exhibit a complete theory on the subject; but the principle on which the strains had been investigated, and which had been, in the present instance, successfully applied, was, he believed, novel, elegant, safe, and applicable to a great number of complicated structures, such as lattice-girders, station-roofs, and trussed arches. It was no unusual thing for an engineer, with an important or extraordinary work on his hands, to have a model made of the intended structure for the purposes of experiment, if it was thought that thereby results might be arrived at affecting the security and expense of the work. This, then, was what had been done in the present instance; he had shown how such a model could be constructed, so as to obtain important results, which could scarcely be obtained except by direct experiment. The reasons which led to the selection of the instance in question were these:—He was engaged on the calculation of the strains on the different parts of a bowstring girder; and after easily determining the strains on the bow and on the string, had found himself totally at a loss for a correct or reliable method of determining the strain on the ties, and, by reason of the difficulty of the theoretical investigation, had found himself driven to adopt the experimental method described in the Paper.

MR. W. H. BARLOW said, the process described was at once novel and interesting, but the experiment only applied to a particular construction—a steel top with a wooden tie-bar. As in practice steel bowstring bridges with wooden ties were not used, he did not know to what extent the tensions that might arise on the different parts would be affected. No doubt the principle would be applicable for ascertaining the strains upon girders made of the same metal throughout; but he was not sure whether the tensions exhibited on the diagrams would be correct, if they were intended to be applied to any other than the identical structure alluded to in the Paper.

MR. AIRY replied that the principle was applicable to any complicated structure. He could not say that the experiments would be at all affected by employing a steel or iron string; it would simply make the difference of a little stiffness, and he did not believe it would affect the operation in any degree.

Captain H. W. TYLER remarked, that in the diagram (Plate 18, Fig. 14), which represented a beam loaded with 52 lb. weights distributed along it, the strain in tension on the middle upright was marked 19, and the strains on the uprights on each side of it were marked 21; while the strains in tension then went down again, in succeeding uprights on either side, to 19, and afterwards increased towards the ends to 26, 29, and 30. He should be glad

to learn how it was that these strains did not decrease regularly towards the middle of the girder. Similar irregularities were observable in the strains marked on the diagonal braces.

Mr. AIRY could only say that the strains put down in the diagram, although they ran very curiously, were nevertheless correct. They were not only the results he had obtained from compounding all the separate weights at different points; but they were also the results he had got directly from three sets of weights. He had hung one set of weights and taken the tensions of every string; he then hung another set and took the tensions, and again with the third set; and the increments for the last two sets were equal. Provided all the wires were in tension at the time of introducing the additional load, the precise amount of the tension on each was not essential to the problem; this, he thought, would be more clearly seen if he described the entire process: The wires were each separately secured to the string by a small screw-bolt and nut; and before any weight whatever was hung upon the girder, every wire was just drawn straight by its nut, and, as nearly as could be judged by touch, they were all drawn equally. It would be readily seen that in this condition they would be all quite slack, there being no weight for them to pull against; then a uniformly distributed weight was applied on the girder, and all the wires would at once go into tension, as he had observed. This was merely an artifice to throw everything, by a natural process, into a measurable state of tension, and it was neither assumed, nor likely, that the wires would each have the exact strain which it would have had if the wires had been all in precisely the same condition of strain, or rather of freedom from strain, before any weight was applied. After the aforesaid uniformly distributed load had been applied, and all the wires had gone into tension, the tension of each was taken as stated in the Paper; and then a travelling weight was introduced in addition, and hung at some one point, and the tension of every wire was again taken, and the differences $+$ or $-$, as the case might be, were quoted as the tensions or thrusts due to the additional weight. The actual and correct strains, due to a uniformly distributed load, as given on the diagrams, were found precisely in this manner, by using a uniformly distributed load as the additional weight, and taking the tensions on every string before and after its application; and the difference of the tensions for each string was taken as the tension due to the additional distributed load.

Mr. J. T. HARRISON remarked, through the Secretary, that when the load was evenly distributed, the strains were considered anomalous and different to the strains as ordinarily provided for in designing similar girders. The Author truly described the strains on the suspension-ties as resulting from "an iron arch
[1867-68. N.S.]

distorted by a weight;" and in the word "distorted" was the clue to an explanation of the apparent anomalies. Were the bow uniformly compressed, and not distorted by the load, the strains upon the suspension-ties would give very different and more uniform results.

It might seem probable that the string of the girder acted in this case (Plate 18, Fig. 14) simply as a tie-rod, and that it supported very little if any of the weight applied: this did not, however, appear to be the case, as on resolving the strains on the diagonals, and adding the vertical resultants to that on the vertical tie-rod, the following results ensued, which showed that 34 parts of the weight (572) attached were borne by the string of the girder. Of these, 33 parts were thrown upon it immediately adjoining the springing of the bow. Throughout the remaining length of the girder, the string was strained transversely, in some cases relieving the tie-rods, in others adding to the strain upon them by extraordinary distortion transmitted through them from the bow.

This would be further considered (Plate 19, Fig. 4):—

Points of Application.	Weight applied.	Vertical Strain on Tie-rods.	Difference.	
			+	—
<i>a</i>	52	35½	..	16½
<i>b</i>	52	49½	..	2½
<i>c</i>	52	54½	2½	
<i>d</i>	52	50	..	2
<i>e</i>	52	53	1	
<i>f</i>	52	53	1	
<i>g</i>	52	53	1	
<i>h</i>	52	50	..	2
<i>i</i>	52	54½	2½	
<i>k</i>	52	49½	..	2½
<i>l</i>	52	35½	..	16½
	572	538	8	42

Difference borne by bowstring = 34.

Showing 8 as the extra strain put upon the ties in places;
and 42 as the strain at other points taken off the ties;

leaving 34 borne by bowstring.

The action of the string was generally so insignificant, as affecting the strains on the ties, that for the present it might be disregarded, and the case might be considered simply as an arch springing from abutments O and R, subjected to a load evenly distributed, and applied by means of vertical and diagonal rods attached to the bow at equal distances.

Suppose the rods to be of uniform strength, and the points from which they were suspended to be immovable, the strain thrown upon each of them would depend upon the degree to which they

were respectively stretched in proportion to their length, the strain upon each rod varying inversely as its length and diminishing upon the diagonals as the angle of inclination from the vertical line increased. Thus if a weight were attached at A (Plate 19, Fig. 1), the junction of three tie-rods, suspended at B, C, and D to an inflexible beam, and the effect was to stretch the rods to E, the vertical tie would be the most extended, both in reality and in proportion to its length, and would therefore be strained most. The strain upon B E would be the next greatest in both these respects, and that upon D E would be the least. Should the beam, however, be either displaced or distorted, the conditions would be entirely altered, and with them the strains also.

If the beam were deflected from B D to B E (Plate 19, Fig. 2) a greater strain would be thrown upon the ties B F and C F, and the strain on E F would be diminished. If the beam were bent upwards, as B E D (Plate 19, Fig. 3), the chief strain would be thrown upon the vertical tie, and the strains upon the diagonals would be diminished; on the contrary, if the beam were deflected in the centre at C, the suspended weight would receive greater support from the diagonal ties, and the vertical would be relieved. All these varying conditions were exhibited in the bowstring girder upon which the experiments had been made by the Author.

The bow was an arc of a circle to which, in the first place, an evenly distributed stationary load was applied. Now it was well known that a segmental arch thus loaded would inevitably become distorted when the centres were struck, that it would sink at the crown and rise at the haunches. The Author seemed to admit that an iron arch was so distorted, and the experiments appeared to prove it. Had the bow formed a catenary curve, it would have been in equilibrium under a load which was uniform as the length of the bow: but whereas a catenary when under extension was in stable equilibrium, under compression its equilibrium was very unstable, and the least departure from the true catenary curve tended to general distortion. The bow experimented upon nearly coincided with a catenary of the same length.

Assuming distortion in the bow, in consequence of the application of the weights, viz., sinking at the crown and rising at the haunches, there would be two points about P and Q (Plate 19, Fig. 4) which would retain their relative positions to the fixed points O and R, from which the bow sprang. Then the curvature of the bow between P and Q would be diminished, and consequently the point f' , as regarded e' and g' , would be depressed, and the points d' , e' , f' , g' , h' , would all be depressed in relation to the stationary points P and Q. At the haunches, the curvature of the bow between the points O and P, and Q and R, respectively, would be increased, the points b' and k' being elevated

to the greatest extent relatively to a' , c' , i' , l , as well as to O, P and Q, R. Had the points e' , f' , g' , sunk uniformly, the greatest strain would have been upon the vertical rod $f'f$, instead of which the strain on all three ties was similar, viz., 19. It did not appear easy to account for this on any other supposition than the relative depression of f' with respect to e' and g' . Again, the points e' and f' being depressed more than d' , which was near the fixed point P, the strain was relieved from the diagonal attached to the bow at f' , and thrown upon the ties ee' and ed' . The weight suspended at d was thrown chiefly upon the diagonal dc' , in consequence of the elevation of the bow at the point c' , and the diagonal de' was relieved as the point e' was depressed. Again, the strain caused by the weight at c was thrown equally upon the rods cb' and ce' , as the points b' and c' were raised whilst the rod cd' was relieved by d' being somewhat depressed. The weight at b was thrown chiefly on the vertical tie-rod bb' , as the point b' was raised to a greater degree relatively than the points a' and c' . There was only one diagonal at a , and the string of the girder evidently supported a large proportion of the weight suspended at that point. This seemed to explain generally the relative strains on the several tie-rods. It would, however, be a difficult problem to demonstrate the actual strain upon each tie. The first point to determine would be the distortion of the bow of given dimensions and material under a given load uniformly distributed. To determine the influence on the strains when the altered position of the points of suspension was determined was comparatively easy. It seemed probable that, as the distortion would increase with the weight applied, so the relative strains thrown on the ties would be increased or diminished proportionally with the distortion; but this was not borne out by the Author's experiments, from which it might be gathered that the strains on the ties were found to increase throughout uniformly in proportion to the weight applied.

The string of the girder evidently influenced the amount of strain on the tie-rods; in some cases it increased, in others it diminished these strains. It would be liable to distortion similar to that of the bow. Below the points P and Q its curvature would be reversed round some points near S and T. To this distortion the string would offer resistance in proportion to its transverse strength, which was greatly increased by the points of rest S and T virtually becoming points of support. But it by no means followed, that the curvature of the string would follow the contortions of the bow without offering resistance varying at different points. The difference in the resultant vertical strains on each side of the vertical points S and T was very striking—at c and i being $54\frac{1}{2}$, whilst at d and h they were only 50. This seemed to arise from the string at c being raised, by the rising of the haunches of the bow at b' and

Fig: 1.

Fig: 2.

Fig: 3.

Fig: 4.

c' , more in proportion than it was lowered at d ; the ties attached at c receiving an increased strain, whilst those attached to the point d were relieved by the girder-string bearing a portion of the strain. The increased vertical pressure at the three central points of suspension e , f , and g , was apparently accounted for by the string at those points being strained downwards more than the bow of the girder—a result very probable, as the points c and i , which were so near the neutral points S and T , would be considerably raised. The curvature which the string would assume at b and k seemed to be greater than that of the bow at b' and k' , as the rods attached to b and k were relieved of a portion of the weight attached to them. A considerable portion of the weight suspended at a and l was evidently borne by the bowstring.

From these considerations it would result, that the bow of such girders as the Author had experimented upon should possess considerable transverse stiffness to prevent distortion; and that its curvature should be adapted to the load it was intended to support.

In pursuance of the notice on the card of the Meetings, it was proposed, and resolved unanimously :—

“That in order to insure a fuller attendance of Members than could be obtained on Easter Tuesday, the Meeting be adjourned until Tuesday evening, the 21st of April.”