Discussion.

The discussion upon Mr. Blandy's Paper on "Dock Gates,"¹ which was read at the concluding meeting of the last session, was then taken.

Mr. Phipps.

Mr. G. H. PHIPPS observed that, without going at length into all the details of the Paper, he would express a general concurrence with the methods given for calculating the strains at various points of Dock Gates. They were the same as he had adopted and explained in the discussion of Mr. Hayter's Paper on the Charing Cross Bridge in 1863.² The business of all these calculations was to determine the increase of strain either in arched structures or on straight beams, whenever the line of pressure or curve of equilibrium travelled along any other line than that of the neutral axis. Agreeing, therefore, with the Author upon the above portion of the Paper, he nevertheless regretted the absence of any opinion upon several matters connected with Dock Gates of great interest to practical men. These points were chiefly two in number: the relative advantages of wood and of iron for these gates; and the propriety or otherwise of doing away with the bearing roller, usually fixed near the outer end of Dock Gates in this country. On the first of the above heads a general feeling seemed to exist amongst engineers in favour of wood, on the ground that wooden gates were often quite as cheap, and sometimes cheaper than iron gates; that they were equally, if not more, durable; and that wood, arising probably from its more yielding character than iron, permitted the gate to accommodate itself better to the sill, and, when bearing rollers were employed, to adjust itself better to any slight irregularities in the roller path. One of the advantages claimed for iron gates was the buoyancy capable of being given to them by water-tight compartments. It had been urged that this could not be reckoned upon in practice, from the difficulty of keeping the gates water-tight. He thought, however, that this objection was untenable under the excellent workmanship of the present day. As to bearing rollers, strong opinions against their use had been expressed by Sir John Hawkshaw and Mr. Hayter; whilst the opposite view was entertained by Sir W. Armstrong, Mr. Brunlees, Mr. Abernethy, and Mr. Duckham.³ Sir John Hawkshaw argued that bearing rollers were unnecessary, as shown by the universal practice in Holland; but Sir W. Armstrong and other engineers considered that without rollers, far too great a weight, with con-

¹ *Vide* Minutes of Proceedings Inst. C.E., vol. lviii., p. 154.

² *Ibid.*, vol. xxii., p. 537.

³ *Ibid.*, vol. I., p. 90 *et seq.*, and vol. Iv., p. 13 *et seq.*

sequent wear and friction, would be thrown upon the heel-pivot Mr. Phipps. and anchorage. Now it appeared to him that the use of rollers ought to depend upon the firm and permanent character of the roller path; for if this was at all out of the correct position of its plane at right angles to the hollow quoin, it was obvious that it might give rise to a tremendous strain on the roller and path. But even if the plane were kept quite true, mechanical experience proved how impossible it was with a rigid roller to properly apportion the strain on the heel-post and anchor to that upon the roller. In order to meet this difficulty, he would adopt an arrangement of levers, as represented in Fig. 1, whereby any

FIG. 1.

required pressure might be brought upon the roller, which would enable the latter to rise and fall on the occurrence of irregularities or obstructions in the roller-path.

In the Avonmouth Dock¹ the weight of a single gate was given as 102 tons, which, equally divided between the heel-pivot and roller, would give 51 tons on the latter, without deduction for buoyancy. This, with the proportion of levers represented, namely 49 to 1, would require the application of a weight just exceeding 1 ton.

Mr. H. HAYTER said an arrangement, not unlike that mentioned by Mr. Phipps, had been introduced in the dock gates of the Elizabeth Dock at Maryport by the late Mr. Rendel, but it did not answer in practice. Such a contrivance would seldom be brought into operation, and the joints would not be kept oiled; and although ingenious, he thought the contrivance was somewhat too elaborate for practical application in Dock Gates. There was

¹ Vide Minutes of Proceedings Inst. C.E., vol. lv., p. 13.

Mr. Hayter.

probably not much room for discussion on the theoretical part of the Paper; but there was in regard to its practical aspect. The Author had stated that the most economical form of gate was that in which the rise was equal to a third of the span, and that was perhaps true. He had also stated that the most economical was not necessarily the most advisable form for a pair of dock gates, and that a convenient form for small, or medium-sized gates, was that in which the rise equalled a sixth of the span. Dock Gates in England were generally made in accordance with that view. In Holland they were, as a rule, flatter; but there the differential head was small. He agreed with the Author that the best, or at any rate a very suitable form of gate was that in which the rise was equal to about a sixth of the span. If one-third of the span the construction became inconvenient, and the recesses too deep, entailing practical difficulty in working. The Author had further stated that the faces of the gates, when open, should be in line with the side wall of the entrance. He had found it better to set the gates back at least 1 foot from the line of the wall, so that they might be well-housed and protected from injury. With that exception he agreed with the Author's conclusions both theoretical, as far as he had studied them, and practical.

With reference to the comparative merits of wood and of iron in the construction of Dock Gates, Mr. Hayter could not quite agree with Mr. Phipps. He had erected many gates both of iron and of wood. Iron gates had to be constructed as caissons, and it was difficult to keep caissons subjected to rough usage water-tight; and it was, moreover, difficult accurately to fit and adjust wrought-iron gates. Wooden gates, at any rate if made of greenheart, lasted as long, or longer, than iron gates, especially near the sea, where the sea-water and exhalations from the sea so rapidly deteriorated both wrought and cast iron, especially the former. Moreover, wooden gates were less costly to construct and to maintain; and on the whole he thought they were better than iron. He had gone into this aspect of the question in the discussion on the dock at Avonmouth and the dock at Whitehaven,¹ and he would not repeat what he then said. On that occasion he had also alluded to the abandonment of rollers in Dock Gates, to which he would again briefly refer. In England rollers were generally used in gates, unless they were small in size. Abroad, at any rate in Holland, they had almost universally been abandoned, and there was no doubt a considerable advantage in doing without them. As a rule, Dock Gates without rollers were manipulated

¹ *Vide Minutes of Proceedings Inst. C.E., vol. lv., p. 71.*

with greater facility. With reference to the question of cost, he Mr. Hayter. had found that by abandoning rollers there was a saving of between £400 and £500 in the cost of a pair of gates in a lock about 60 feet wide, taking into account that the roller, the spindle, the adjusting apparatus, the roller path, and the elaborate masonry to receive it were then unnecessary. Obstructions sometimes occurred on the roller path, and it became necessary occasionally to send down a diver to remove them. A diver could not always be had; and where the water was shut back by one pair of gates, it was evident that if they could not be closed, the water would get out of the dock, and much damage might accrue to the shipping. Practically gates were generally strong enough to do without rollers. The anchor was always of excessive strength and also the pivot, and the gates as a rule were very strong. Sometimes in erecting gates before the roller was attached, and before the gates were supported by water, they were allowed to swing to and fro. This he had noticed, and yet he had never heard that they had sustained injury. There were, however, some exceptional cases where rollers ought perhaps not to be dispensed with. Thus in the case of gates of large size, say in a lock 100 feet wide, rollers and roller-paths ought perhaps to be introduced. It was generally the practice to adopt two rollers in such a case in each leaf. He thought that one roller would be sufficient. Further, there had lately been put up at Dover, gates which were sometimes subjected to the pressure of a wave of 3 feet on the concave side at high tide. In that case the rollers had steadied the gates. In addition a locking apparatus had been introduced, consisting simply of an eye riveted to the leaf of each gate, into which, when the gates were together, a strong bolt or pin was inserted. One such contrivance was placed at the top of the gate and another about 6 feet down. By these means the gates were enabled to withstand the pressure of a wave of 2 or 3 feet without movement. Before this contrivance was adopted the gates were held tight by the chains that closed them, and for that purpose the crabs had to be made very strong. Since the introduction of the locking apparatus, the chains had not been used to hold the gates when at high water there was a sea disturbance. He would not further allude to the subject, inasmuch as the Institution had accepted from him a Paper on the Amsterdam canal, in which there were some thirty or forty pairs of gates. These presented features of interest to which he should have to call the special attention of the members when that Paper was read.

Prof. Unwin.

Professor W. C. UNWIN remarked that others were more competent than himself to deal with the practical details of the Paper; but he might be permitted to make one or two remarks on some of the theoretical points contained in it. It would be obvious that the question of the strength of the parts of a lock gate was one of considerable complexity, and that in fact theory was incapable of dealing exactly with the conditions of such a problem. Certain approximate assumptions, therefore, had to be made as to the conditions in which the gate was, and the only fair criticism on the theory of such a thing as a lock gate was that which dealt with the question, whether the assumptions were fairly approximate ones, or the best that could be made. He thought the Author had shown that he had fully considered the conditions of the problem, and that on the whole he had fairly treated it from the most approximate point of view which was possible. He had practically drawn for lock gates what engineers would recognise as the well known line of pressure, which appeared in most treatises of applied mechanics, but which he was sorry to find he had called by a new name. He thought it would be convenient to keep to recognised names for recognised curves. To call the line of pressure the line of position of resultants was almost as if a new name had been invented for the circle or the parabola. In using the line of pressures from which to determine the stresses, one assumption was at once made, namely, that no great deformation of the gate occurred from its constructed dimensions, that the pressures did not greatly alter the form of the gate; and on the whole he should think that for such a problem as a lock gate that was a fair assumption, because at best any solution of the problem must be an approximate one. The Author had adopted one method, which seemed to him perfectly right. Instead of fixing upon a particular line of pressures for the lock gate, he had found two limits within which the lines of pressure must lie, according as the pinch of the gate occurred at the up-stream or the down-stream edge of the mitre sill, and he calculated the gates on those two extreme assumptions, and took the worst stresses occurring in either of those cases. That was a rational way of dealing with a problem which could not be exactly solved,—to fix the limits within which the stresses must lie. In determining the position of the lines of pressure, however, he made one assumption, possibly inaccurate. He had assumed that the line of pressure passed through the centre of the heel-post. Now in shutting, the gate came in contact with the hollow quoin; and if it were supposed that after the gate was just closed and pressure was

upon it, there was an almost infinitesimal movement of the hard Prof. Unwin. wood of the heel-post against the still more rigid stone of the hollow quoin, then a considerable moment of friction would be induced at the heel-post, and the line of pressures, instead of passing through the centre of the heel-post, would deviate from it. To neglect that possible deviation, while taking account of the deviation at the mitre-post, could only be justified if it was difficult to take account of it, or if the amount of deviation were small. It was not difficult to take account of the greatest possible friction at the heel-post, and the moment of friction might be considerable. Let r be the radius of the heel-post, ϕ the angle of repose of wood on masonry. At the centre of the heel-post let a circle be drawn with a radius $= r \sin \phi$. Then when friction was taken into account, the line of pressure would be a tangent to this circle. Fig. 2 showed the thrust P at the heel-post touching a circle having a radius $= r \sin \phi$. After using a great deal of applied

FIG. 2.

mechanics to determine the exact stresses in the different parts of lock gates, it appeared to him that the Author had abandoned applied mechanics in using the results, because he stated that instead of proportioning the gate so that the maximum stress should not exceed a certain limit, he proposed that the average stress should not exceed a certain limit. Instead of dealing with the greatest stress, he dealt only with the average on the whole section of the wooden beams. The reasons given for that did not appear to justify the course adopted. The Author stated that in crushing posts and so on, what was obtained was not the maximum stress on the section, but the average stress. That was true; but in those experiments the greatest possible care had been taken, if they had been made rightly, that the average stress should not widely differ from the maximum stress, whereas in lock gates the

Prof. Unwin. average stress might differ in almost any degree from the maximum stress. It appeared, therefore, to him that it was to abandon applied mechanics altogether, if, after going through those laborious calculations, a limit was merely fixed to the average stress on the sections of the beams of a lock gate. The Author was right in saying that experiments with small specimens were bad guides in determining what the maximum stress in such a gate should be. Experiments with small specimens might be misleading, and there were possibly no good data for determining what the maximum stress ought to be; but the proper way of determining it would be, to apply those calculations to a number of gates which had actually stood, and to find what maximum stress had been safely borne. If a gate were found in which the wood carried, say, 1,000 lbs. to the square inch as a maximum stress, another gate might safely be built with the same limit, and it would be sure to stand also. He alluded to that subject, because it appeared to him to be one of capital importance in dealing with the question of the strength of materials. He thought if the Author had had less practical experience with lock gates, and more with the handling of formulæ, he might have simplified that portion of the Paper which related to iron gates, and Professor Unwin might possibly be able to suggest to him a simplification of the way in which he had treated the stresses.

Mr. Browne. Mr. W. R. BROWNE wished it had been stated more clearly by the Author in what relation his Paper was to be taken as standing to previous investigations. In his own communication on the same subject, read before the Institution in 1870,¹ he had mentioned the two earlier papers of Mr. Peter Barlow² and of Mr. Kingsbury.³ Again in June, 1873, "The Engineer" contained a series of articles on lock gates, founded on a memoir by M. de Périssé,⁴ giving a great deal of information derived from similar inquiries, both abroad and in this country. He thought the Author should have shown in what respect the previous investigations were useless, untrustworthy, and imperfect, and how far his method was intended to supplement them. The practice of not referring to the existing literature on any subject was rather common in engineering matters; but it led to a great deal of confusion, making it difficult for any one to take up the subject afterwards, to follow its history, and to see what had really been done.

¹ *Vide* Minutes of Proceedings Inst. C.E., vol. xxxi., p. 317.

² *Vide* Transactions Inst. C.E., vol. i., p. 67.

³ *Vide* Minutes of Proceedings Inst. C.E., vol. xviii., p. 445.

⁴ *Vide* Mémoires de la Société des Ingénieurs Civils, 1872, p. 319.

There were two points to which he desired to allude. In Mr. Browne. Mr. Blandy's treatment of the centre of pressure of the mitre-post, speaking of the mutual action of the gates on each other, he said: "The gates may be constructed so that, when under pressure, the meeting faces of the mitre-posts bear fair and true against each other, and distribute the mutual reactions uniformly throughout the width of the meeting faces. This is the normal condition of things."¹ He did not suppose that the Author meant to say (though the sentence looked as if he did) that whenever there were two surfaces so constructed as to bear fair and true against each other, it followed that the mutual reactions between those surfaces must be uniform; and consequently that the centre of pressure between those surfaces must coincide with the centre of the figure. He need not point out that the case of the voussoirs of an ordinary masonry arch was one where it was always assumed that the surfaces were perfectly bedded together, but where the whole problem was to determine how far the centre of pressure varied from the centre of the figure; and his own impression was that it was not, and could not be, the normal condition of things, that the pressures should be the same throughout the face of a pair of mitre-posts. In his Paper that question had been discussed, and he had assumed that the pressure varied from nothing at the outside, next the water, to a maximum on the inside of a mitre-post. That might or might not be a good assumption; but he thought it was at least better than to suggest, as the normal condition of things, that two gates when under strain had the pressure uniformly distributed over the surface of the mitre-posts.

The second point followed from an observation with regard to the best rise for dock gates. The Author stated: "Mr. Bramwell has pointed out that the most economical form of gate is that in which a pair of gates, when shut, form a continuous arc, subtending an angle of $133^{\circ} 56'$."² This referred to remarks made by Mr. Bramwell, in which that result had been given,³ founded, however, upon a principle which Mr. Browne had laid down, that the best form for a pair of lock gates, under all circumstances, was one in which they made, when closed, the exact half of a circle. In his Paper, and subsequently in the discussion, he had stated that he did not agree with that as a general principle; but the reasons then given had not, he believed, been fully accepted

¹ *Vide* Minutes of Proceedings Inst. C.E., vol. lviii., p. 158.

² *Ibid.*, p. 202.

³ *Ibid.*, vol. xxxi., p. 341.

Mr. Browne. as sufficient; and he hoped the members would pardon him for returning to that point. Mr. Bramwell illustrated his view by two diagrams, which were practically reproduced in Figs. 3 and 4. His argument was simply this: Suppose a cofferdam or cylinder to be built in the form of a circle to resist water-pressure (Fig. 3),

FIG. 3.

then, as the pressure upon every point would be the same, he asked, how would the circumstances be altered if the circle were cut in two, and either half, instead of bearing against the corresponding half, bore against a wall, as in Fig. 4? He further asked, How would

FIG. 4.

it be altered if it were cut again in the middle? And so he went on by a succession of easy steps to the ordinary case of a pair of lock gates. To this argument his own reply would be that, as far as concerned the closed cofferdam, he agreed that the circular form would be the right one. And he would point out that, supposing the cofferdam to be compressed by the water, it would take a form still that of a circle, but of a smaller circle, such as

was shown by the dotted lines in Fig. 3, where, of course, the Mr. Browne. compression was enormously exaggerated for the sake of clearness. But when Mr. Bramwell said, "Would not the same follow if a gate were made semicircular?" he should reply, he could not answer that question until he knew the nature of the construction at the two ends of that semicircle, and where it abutted upon the wall. If the construction was that of a pair of lock gates, he should say that Mr. Bramwell's conclusion did not follow, because in that case the end abutting against the wall would become an ordinary heel-post fitting into a hollow quoin, and confined at the top and bottom by the collar and pivot respectively; and consequently, when a pressure came upon that semicircle it could not take the form of a smaller semicircle such as would be the half of the dotted circle in Fig. 3, because the abutments could not move. It would take some form such as the dotted curve shown in Fig. 4; and all that could be said of that curve was that the two halves must be symmetrical with each other; it could not be said that either of the halves would be the arc of a circle, or that, if they were, they would be arcs of the same circle. All that must be matter of calculation; and the argument derived from symmetry at once ceased to be applicable. Therefore, without going into the question of what was theoretically the most economical value of the rise, what he submitted was this: that it could not be said off-hand that, whatever the rise might be, the cylindrical form of a pair of lock gates was always the best; it was a question to be decided by calculation in each case.

With reference to the question which had been raised as to the use of rollers, he might mention one fact. He was present, ten years ago, at the taking out of the wooden gates of the old north lock at the Bristol dock entrance. When one of those gates, which had been in use for many years, was removed, it was found that, through some maladjustment at the time when the gate was set to work, or at any rate the last time the gate had been removed, the roller had never borne upon the roller path, but was about $\frac{1}{4}$ inch off it. No difficulty had been experienced in working that gate; and the fact would not have been known to the present day had not the lock been destroyed and the gate taken away. The span of that lock was not large—about 35 or 40 feet—but it was not an excessively small span; and the rise and fall of tide was over 30 feet, so that the gate was by no means a light structure. That fact went to show that an ordinary wooden gate intended to work with a roller, and constructed with that view, could be worked without a roller for many years

Mr. Browne.

without any one knowing it. This appeared to confirm strongly the view expressed by Mr. Hayter, that if the roller of any existing lock gate were taken away, the gate would work just as well without it.

Mr. Vernon-Harcourt.

Mr. L. F. VERNON-HARCOURT said, the most essential points in designing a lock gate were the form and the rise. He believed it would be generally admitted that the best form was a continuous circular arc when the gates were closed, and that the best rise was one-third of the span. On account, however, of the natural objections that were raised, namely, that the gate recesses went too far back into the wall, if there was a great curve on the gate, and that with an increased rise there was an increased length of lock, the Author preferred taking the form for a gate of about 60 feet span, shown on Fig. 42, vol. lviii. Mr. Vernon-Harcourt thought that the ordinary rise would be found to be nearer one-fourth of the span than one-sixth. That was the rise given to the dock gates described by Mr. Kingsbury¹ which were erected at the Victoria docks, and a similar rise was given to the gates of the Albert dock at Hull, and to those at the Avonmouth docks, and to the gates at the dock with which he was, himself, more intimately acquainted—the south dock of the West India docks. Fig. 5 showed one of the gates of the south

FIG. 5.

The radius of A B is 60 feet.

The radius of E D C is 120 feet.

dock.² The gates were made in the form of a gothic arch of wrought iron, and resembling, except as to the rise, the one shown

¹ *Vide Minutes of Proceedings Inst. C.E.*, vol. xviii., p. 445.

² *Ibid.*, vol. xxxiv., plate 19.

by the Author in Fig. 42. There was only one difference in the form, namely, that the outer skin CDE was curved instead of straight as proposed by the Author. He thought it was preferable to have it curved, because at point B in the Author's figure there would be an excessive strength in the gate, whereas, in the other case, the strength was more proportionate. But there was one slight disadvantage in the gates of the West India dock as shown in Fig. 5; namely, with regard to the question of flotation. If there was the same level of water on each side of the gates, as was the case when the gates were opened, that disadvantage would not exist; but in the case of the water being very high on one side and very low on the other (which would especially apply to the outer lock gates at low water spring tides) the pressure tending to cause flotation must not be reckoned merely over the area between the skins A B C D E, but the total area A B C F E must be considered. Taking into account merely the area between the skins, he had found, in calculating how much water would have to be put into the gates, that about 7 feet depth of water would counterbalance their tendency to float; but taking the whole area—including the piece beyond the skin, which was added in order that the sill might be made straight—it was necessary, allowing for an extreme case, that 11 feet depth of water should be put into the gates. Accordingly, when those gates were worked, they had between 3 and 4 feet more water in them than was required at that time. For this reason he thought it would be better to make the sill curved in gates of that kind. Of course there were disadvantages in curved sills, chiefly in the matter of fitting the woodwork of the gate to the sill, and a straight line, as far as the granite sill was concerned, was rather easier to dress; but these were matters of minor importance. Then, with regard to the question of flotation, when it was seen that it was necessary to put 11 feet depth of water into such a gate in order to prevent it floating, it did seem as if it would be most advantageous to use that flotation and to get rid of the roller. A roller path was awkward to set true, and bedding and setting it on the gate floor stones were costly. It was also necessary to put the gate recess further back than would be required if there was no roller. In the West India docks it was put a foot from the back of the gates, and one of the sluice ways had to be recessed at the top in order to receive the roller and the roller-box. He thought that by adopting the self-adjusting system for counterbalancing flotation, described by Mr. Harrison¹ in the discussion

Mr. Vernon-Harcourt.

¹ *Vide Minutes of Proceedings, Inst. C.E., vol. xxxi., p. 350.*

Mr. Vernon-
Harcourt.

on Mr. Browne's Paper, on "The Strength of Lock Gates," rollers might be safely dispensed with in gates of not more than 60 feet span. The Author stated that there was a disadvantage in having a recess in lock walls; but he did not see how that argument could apply more to gates of 60 feet span than to gates of 80 feet span. In the Victoria docks, and in the Albert dock at Hull, there were segmental gates, of 80 feet span, not in a straight line with the lock wall when fully opened. It seemed to him rather an advantage for the gate to be out of the way, and not liable to be pressed against by vessels, instead of being in a line with the lock wall. It was important that gates should be formed in the best manner. They were but a small item in the total cost of a lock or a dock; yet they constituted by far the most important part. Engineers ought, therefore, to try so to combine theory and practice as to get a gate as light as consistent with strength, and one that would work as easily as possible.

Mr. Aird.

Mr. JOHN AIRD suggested that the members should avail themselves of the opportunity of seeing the lock gates which had been completed at the Victoria Dock extension. The gates had been made by Messrs. Brassey and Co., of Birkenhead, and he believed they were as perfect a piece of workmanship as anything of the kind ever seen. Such an inspection would probably enable them to form an excellent opinion as to the merits of rollers and roller paths. He was sure that it would be a pleasure to the Dock Company, and to all connected with the work, to give every information to those who took an interest in the subject, for it was beyond doubt a matter of the greatest importance that the gates should be perfect and be easily worked. The best dock in the world would be a failure if the gates were not in working and in workmanship a success.

Mr. Cowper.

Mr. E. A. COWPER said that in the case of a pair of lock gates, as soon as the shape was settled, it was possible to calculate the strains without difficulty; but if any tolerable sized pieces of floating wood got nipped in shutting the gates, or if rubbish laid on the sill, one gate would not bear fair against the other gate, and the twisting strain brought upon it would be very severe. Every one who built lock gates provided for that, and made them strong enough, but it did away with all the fine theoretical calculations as to the gate acting exactly like an arch or a girder. It might really act as a girder, but there was no support in the middle if the two gates did not touch each other. A gate should be made strong enough, not only to take the pressure when standing against the sill fairly and truly, but to bear straining

or twisting to a considerable extent. That point had not been sufficiently dwelt upon. As to the shape of a lock gate, he agreed with Mr. Hayter. Practically it was endeavoured to make gates of a reasonable shape, with a moderate amount of curvature, so as not to cut away the walls too much, and there was no difficulty in calculating the strength. If the posts and footstep were made strong enough, there was no difficulty in doing without a roller. He knew a case in which the footstep was so flimsy, that it smashed up like a piece of cardboard. When a new one was put in of reasonable strength, it answered perfectly well, and was at work to the present day.

Mr. J. B. REDMAN remarked, with reference to Fig. 38,¹ for which the Author had made Mr. Bramwell sponsor, as the theoretical form of strongest lock gate, that practically, in the pointing sill, the versed sine of the entire span of a lock was usually made less than one-half of the proportion given by Mr. Bramwell ($\frac{1}{33}$ of the span). In the first volume of the 'Transactions' of the Institution,² there was a Paper by Mr. P. W. Barlow on the subject, in which $\frac{1}{25}$ was the proportion adopted. The usual projection of one-sixth had been practically adopted; but as the span of gates had been so enormously increased to adapt them to the increased size of shipping, it had become a material consideration, because the projection of one-sixth, which was theoretically weak, gave a much heavier gate than theory showed to be necessary, and it had led to the application very largely (especially by private firms, where they were limited by the river on one side, and possibly by a public road on the other, and every inch of length of dock was of importance) of the caisson in lieu of the gate. There were many obvious advantages in the introduction of the caisson instead of a lock gate. In the first place, the caisson might be adapted to the theoretical form laid down by Mr. Phipps. It did away with the necessity of the gate recesses, and the gate platform and the pointing sill were got rid of, as well also as rollers, segment rails, and much complicated and heavy masonry. Of course there was a straight sill for the caisson to abut against, but it materially enhanced the value of a dock, especially a graving dock on a river like the Thames, to have floating caissons of wrought iron where there was a shell approximating to the skin of a ship which was trussed midships, and where there was the advantage of a counter skin to

¹ *Vide* Minutes of Proceedings Inst. C.E., vol. Iviii. p. 200.

² *Ibid.*, p. 217.

Mr. Redman. take the strain from the outer side, giving the best possible form of gate which might be floated into the river and swung out of the fair way of the channel. That was, of all expedients, the most admirable in such sites. But when the caisson was applied in the manner in which it had been applied by the Government under Colonel Clarke, R.E., Assoc. Inst. C.E., who carried out the great Somerset dock at Malta,¹ with a recess for the caisson to slide into, and an expensive apparatus connected with it, those advantages were almost neutralised by the excessive cost for moving the caisson. He thought those points arose entirely from the fact that the projections given to the pointing sill, being about one-half of what was theoretically necessary, had introduced the large and economical application of caissons to the entrance of docks, especially of private graving docks.

Mr. Price. Mr. JAMES PRICE asked if it was the Author's practice to allow the gates to touch first at the bottom of the mitre-post, leaving them slightly apart at the top—in fact to cut away a portion of the mitre-post, so that, if there was no pressure behind the gate, the mitre-post would be touching at the bottom so as to strike the sill first, then gradually closing at the top as the pressure came against it. He had adopted that method, and had found it greatly added to the staunchness of the gate. It allowed the mitre-post to touch the bottom first, striking against the sill firmly, and then gradually closing by a slight twist of the gate. In that way he had been able to get the gates more staunch, particularly against the sill, than by any other method. He thought that wooden gates possessed an advantage in allowing a certain amount of elasticity, so that they could close at the bottom first, and then by a slight twist close at the top.

Mr. Blandy. Mr. A. F. BLANDY said he had some difficulty in replying to the criticisms on his Paper, from the fact that in most cases the speakers either agreed with him, or he agreed with them. Mr. Phipps had referred to the subject of simplicity of calculation. He, too, agreed that simplicity was the great element in all calculations; still, under certain circumstances, it was absolutely necessary to carry the calculation to its conclusion. He had, perhaps, entered a little more elaborately into the subject than he should otherwise have done, in consequence of a memoir written by a French author, in which it was stated that for the most part English engineers did not take sufficient care in their calculations of resistance, but rather trusted to their experience and empirical

¹ *Vide* Minutes of Proceedings Inst. C.E., vol. xxxiii., p. 352.

formulae, which had no other merit but simplicity. Mr. Phipps Mr. Blandy. had asked why engineers had a prejudice for wood rather than iron gates? He thought they had no such prejudice. It was rather a question of locality and expediency as to which material was best suited for the particular place. Probably in the early days of the profession wood was preferred to iron, because engineers knew more about it, iron being then in its infancy. No doubt wood, if carefully selected, would last, not indeed an unlimited time, but for a considerable period, without deterioration or decay. Some years ago he superintended the alteration of the old Waterloo dock at Liverpool, where it became necessary to take down the existing gates. They were removed to the north end of the Mersey, where they remained on a mud bank "between wind and water" about ten years. Altogether they had been under water every high tide for forty years, subject to the constant change of wind and water during the whole period. The specimen in his hand had been cut from one of the gates broken up in December 1873, after that long exposure, and he thought it was as sound a piece of oak as had ever been seen. When engineers saw a piece of timber like that it was no wonder that in former days they gave the preference to wood, knowing, as they then did, but little of iron. He agreed with Mr. Hayter and some other speakers as to the desirability, as far as possible, of swinging the gates from their anchor blocks; but he should be sorry to make a gate which had not a roller attached, so as to take the strain in case of accident to the anchor block or suspenders. It had been said that a gate was made sufficiently strong, and that the abutments and the heel-post were sufficiently solid, to carry the weight of the gate. That was no doubt true, but he should be loth to trust entirely to anchor blocks. He had seen abutments to heel-posts where, without any apparent reason, the material had given a little one way or the other. Sometimes a crack would occur in an abutment, no one could tell why. Sometimes the mortar itself would give, and sometimes the anchor bolts would be injured by rust, and that would affect the masonry. It was certain that masonry would occasionally move in a very curious way, and he should therefore be sorry not to have a roller to take up the strain when necessary. With regard to the question of the gate being in a line with the side wall, he agreed with Mr. Hayter that the fenders might with advantage be put back 12 inches from the wall. It had not occurred to him to notice this small extent of setting back, as differing from the line of wall. What he had particularly thought of was the fact that the gang-

Mr. Blandy.

way, at the top of the gate, was more convenient if it formed a straight path with the coping of the side wall. He thought that a shallow gate-recess was in most cases an advantage. In some places there was ample room, and it did not matter what scoop was taken out of the side of the wall; but in others every foot of land was valuable, and there might be a warehouse within 5 feet of the gate-recess, and then it was desirable to keep the gate-recesses as small as possible. He agreed with Mr. Hayter that wood was better than iron near the sea; but there were other cases in which iron was better than wood. Professor Unwin had spoken of the curve of equilibrium. It was, perhaps, a mistake on his part to call the curve by a different name from that by which it was generally known, as it was a good rule to apply the same terms to the same things. He had called it the "line of position of resultants," to identify it with the resultants in the calculations referred to in the course of the Paper. He agreed with Professor Unwin with regard to the line of pressure not passing through the centre of the heel-post. He had omitted to notice this in the Paper; but he was glad that it had drawn forth the opinion of Professor Unwin. No doubt there was a condition of friction round the heel-post which would throw the line of pressure away from the centre as the gate moved under deformation. He had read Mr. Browne's Paper many times with great interest, and had no intention to ignore previous authorities; but if his communication had drawn forth the opinions of others and thrown a little light upon the subject, it might be of some use, and that was all he wished. The object of the Paper was rather to do away with calculations, and his aim had been to reduce the subject to the scope of the chalk line and the set-square. With regard to the twisting strains arising from substances coming between the gate and the sill, there was no doubt that that difficulty would sometimes arise; but he was at a loss to know how to make any definite calculations to meet it. Of course it was necessary to have a margin of strength, and it was impossible to tell at what particular point of the sill the obstruction might occur. Mr. Redman had alluded to the statement of Mr. Bramwell as to the rise being one-third of the span. Theoretically that was the most economical form of gate, taking it simply as a structure, but he did not think that it was necessarily the best form for any particular dock; and Mr. Bramwell, he believed, did not so intend it. The enormous increase of span in dock gates was a question which might now be shelved, for he thought that the increase had reached its limits. He had seen gates of 100 feet span, but he did

not expect to see many more. With reference to the question of Mr. Mr. Blandy. Price, his experience was that gates generally fitted best when they were made to meet first at the bottom; then, as the pressure of water came on, the heads were drawn together, and the upper parts of the mitre-post were brought to form a good joint.

Mr. W. H. BARLOW, Vice-President, said that not only was the Mr. Barlow. Paper one of great merit in itself, but it had also elicited a good discussion. He certainly thought it would be desirable for the Authors of Papers to state what had been done in the same direction before. Not only had Mr. Browne written upon the subject, but Mr. Barlow's brother had written upon it forty years ago,¹ and it was just as well that should be known, and that it should be seen that the Author himself knew it. Mr. Blandy had so freely admitted the corrections of some of the speakers who had criticised the Paper that there was little left for him to say. Mr. Aird had suggested that members should take the opportunity of seeing the Victoria docks and the large lock gates made there. He had seen them himself, and he strongly recommended all who had the time and opportunity to go and see that admirable specimen of workmanship.

COLONEL B. H. MARTINDALE, C.B., R.E., said that the London and Colonel St. Katharine Docks Company would be happy to give every Martindale. facility to the members who desired to see the gates to which Mr. Aird had referred, or any other part of the works now nearly completed at the Victoria Docks.

Correspondence.

Mr. A. C. ANDROS observed that the Paper dealt in an exhaustive Mr. Andros. and able manner with the construction of, and the strains induced on, Dock Gates, into which he did not propose to enter further than to coincide in a general way with the practical conclusions arrived at by the Author. These conclusions might be carried further than in the case of curved gates up to 60 feet span. With some modification they would equally apply to gates of the largest size. He failed, however, to see why the rise of the gates should be fixed at one-sixth of the span. By increasing the versed sine to one-fifth, or one-fourth, the line of resultant pressure would be brought more in the direction of the length of the side walls, thereby reducing in an appreciable degree the mass of masonry necessary to withstand the thrust of the gates. Then,

¹ *Vide Transactions Inst. C.E.*, vol. i., p. 67.