Discussion.

Mr. Bruce. Mr. G. B. BRUCE, President, said that the subject of the Paper was of great importance, and it was one on which the Author was a distinguished authority. The questions brought forward for discussion were the various causes of accidents in mines, falls in the roofs, dangers in hauling up and letting down cages in the shafts, and dangers from the variations in the barometric pressure and the presence of firedamp. The object should be to ascertain what could be done in the way of lessening those accidents from the roofs and the shafts, to decide what was the value to be ascribed to the difference of barometrical pressure at different times, how best to detect firedamp and discover the extent to which it was present, how far coal-dust added to the danger, what was the safest way of using explosives, what were the safest explosives to use, and the best means to be employed for getting coal when explosives could not be used; also to consider the nature of the lamps to be employed in mines. Those appeared to him to be the points chiefly requiring consideration.

Sir Frederick Abel. Sir FREDERICK ABEL said that his Paper, long as it was, presented so many imperfections, there being several subjects on which he might have touched, such as inundations in mines and other minor causes of accidents, that he wished to be allowed to make a few supplementary observations before the discussion commenced. He desired especially to refer to one important topic, because it might be alluded to in the course of the discussion, namely, the measures for dealing with casualties in mines. The Royal Commissioners were greatly impressed with the desirability of some system being instituted, whereby more effectual and generally applicable arrangements for dealing with casualties might be secured, and they pointed out two or three steps that might be taken by mine-owners and those interested in mines, quite apart from any action of the Government in the matter. They referred, for example, to the importance of having ambulances, stretchers and appliances ready for immediate use at every mine, and also of having centres where apparatus of a more special character might be kept, so as to be available at short notice in the event of serious accident; as, for example, the Fleuss apparatus, the employment of which rendered the user independent of the external air. They further pointed out how important it was that men should receive some amount of training in the use of simple appliances for saving life, or at any rate for dealing with accidents; and also in simple means

of dealing temporarily with wounds or other casualties. It was very satisfactory to note that in the Mines Regulation Act a clause had been introduced which prescribed that ambulances, stretchers, splints and other such appliances should be kept at mines; and also that no sooner had the Act been passed than the St. John's Ambulance Association, which did an important work in this country, set about actively to endeavour to introduce a system of training miners in simple operations useful in dealing temporarily with casualties when they occurred. He had referred to the Fleuss apparatus; he might also allude to others which had been brought forward from time to time to assist in the exploration of mines after accidents. There were different kinds of respirators, of which one or two of a very efficient character had been exhibited, notably one from Prussia, devised by Mr. Loeb, a respirator which enabled an explorer to go a short distance into a mine and remain there, this respirator being connected by means of a pipe with the external air. Mr. Fleuss had also furnished a very powerful and useful self-contained lamp of high illuminating power for exploring purposes; and, of late, electric lamps of comparatively high illuminating power, much higher than those which would probably come into use as substitutes for miners' lamps, had been brought forward, and would, no doubt, prove very valuable in explorations. He had in the Paper dealt with the subject of the great advance made within the last two years, he might say within the last twelve months, in the development of self-contained electric lamps for mines. As the latter part of his Paper was necessarily gone over rather cursorily, he might be permitted to refer briefly to the question of primary batteries. In reference to secondary batteries he had pointed out the great advance that had been made, especially by Mr. Swan, and the promising efforts made by Mr. Pitkin. He had also seen that evening a capital lamp of the same type exhibited by Mr. Urquhart, which was of comparatively small weight, and appeared to furnish a very satisfactory light. With regard to primary batteries, he had mentioned one or two that seemed to promise good results, notably that brought forward by Mr. Blumberg, the chloride of silver battery, and a single liquid battery in which sulphate of mercury was used, viz., the battery of Mr. Schanschieff. He had lately seen an important advance made by Mr. Schanschieff in the development of his battery, which combined very low internal resistance with high electromotive force; the experimental observations, which he and others had made with lamps in which this battery was used, indicated that

Sir Frederick
Abel.

Sir Frederick Abel. it afforded very great promise of furnishing the miner with a light and comparatively cheap electric lamp. He had himself found that a lamp of that kind, weighing 5 or 6 lbs., gave over half a candle light at starting, at the end of five hours four-tenths, and at the end of ten hours (more than the time of an ordinary shift) it gave a greater illuminating power than an ordinary Davy lamp. Those results were very satisfactory, but no doubt they might be further improved upon. Both the Schanschieff and other primary batteries, such as the Eclipse lamp, were comparatively cheap in regard to maintenance; thus, the cost of the Schanschieff lamp just referred to had been found to be somewhat less than 1d. per hour. There was, of course, the one difficulty, that they had to be charged at every shift, but the charging could be reduced to as simple an operation as that of filling an ordinary lamp with oil, and he did not think that it would stand prominently in the way of the introduction of primary electric lamps. It was evident that the question of the application of electricity to portable lamps, for general purposes in mines, was on the way of being achieved with success.

Professor Lupton. Professor ARNOLD LUPTON observed that, after Sir Warrington Smyth, he thought he might claim to be the senior professor of mining engineering in the country, and for that reason he might be permitted to remark, speaking for Yorkshire, how much mining men appreciated the efforts made by the Author to bring before them, in a clear and comprehensive manner, many of those questions which could only be thoroughly dealt with by a gentleman of his great scientific attainments. When the Royal Commission on Accidents in Mines was appointed, there was considerable anxiety as to what the results would be. Practical men had been interfered with by legislation for many years; they had been constantly told by lawyers what they were to do, and what they were not to do, and when they heard the names of the distinguished men on the Commission, it was hoped that they would not recommend laws which, though well intended, would only have the effect of hindering their operations, without saving human life; because he could prove that some of the most popular prescriptions would not only cause injury to trade but increase the risks and loss of life. The result, he thought, had borne out their hopes. The Commissioners were a long time in making their report, but they most thoroughly investigated the question, and their report would stand as an interesting and valuable record of the researches of a period to which Englishmen might look back with pride. That was the opinion which he had formed, not because he agreed

with everything in the report (which it would be impossible for any active-minded man to do), but because he hardly thought it was possible to have produced a more exhaustive and valuable record. The Paper, he thought, condensed the report, if it added to it still further information. Referring to special points in the report, he desired to answer one suggestion of the President as to the means of diminishing accidents. He had the honour of making the suggestion before the Commission itself. He said, or intended to say, to the Commissioners: "Gentlemen, sit in permanence; let those men of scientific attainments, and practical mining engineers, be always sitting in London, so that any one who had an invention or idea might bring it before them; let it filter through their minds, and then let the information be made public." It would be much better to enlighten and guide the public in that way, than to order them. Mining engineers sometimes felt rather irritated when they were told by lawyers what they ought to do. Suppose that any member of the Institution were laying out a garden with beautiful flowers and shrubs, and Parliament by statute were to say "You shall plant daisies here, and mignonette there," and then, if the order was not strictly obeyed, there came a threat of prosecution, and if it was obeyed, the Government took all the credit of the garden to itself. That was how the matter stood with regard to some of the mining regulations. They were told to do this, that, and the other; but if they did not do ten times as much as they were ordered by law, it would not be practicable to manage the mine at all. They were told, for example, to put a fence round the fly-wheel; but they were not told to put a piston on the engine or a valve on the cylinder. The greater part of the work was left to their own intelligence; they were only instructed as to a few minute details, and were liable to be prosecuted if they did not attend to them. He hoped that so far as the intelligence of the meeting could affect the future legislation of the country it would be in favour of allowing mining engineers to manage their mines in the best way they could. The inspectors of mines used their great experience and position to guide or help the management. He considered they did great good; it was not the living hand of the Inspector to which objection could be taken, but the dead hand of a law about ever-changing mechanics to which he objected. The Author had alluded to the question of gas issuing from goaves. The danger of a goaf depended upon two things, the depth of the mine and the age of the goaf. In the case of a deep mine and an old goaf of large area, there would not be any hollows or places in

Professor
Lupton.

Professor Lupton. which gas could accumulate. He had never seen a hollow in driving through old workings in the goaves in a deep mine; it was only on the verge of the workings, where the goaf was new and the subsidence of the strata had not had time to crush and fill up every hole and interstice, that any opening could be found where gas could accumulate. With regard to the belt of goaf on the verge of the workings, the danger depended upon whether it was ventilated or not. In working mines, on the system of bringing back and having no air-road through the goaf, there might be a danger of a large quantity of gas accumulating, which, with a fall of the barometer, or some other cause, might come out and help to produce an explosion; but if air-roads were taken through the goaf, and it was properly ventilated, there was comparatively little danger. He was pleased to observe the statement in the Paper, that the ratio of accidents in mines had been diminishing. This was true. In 1856 one life was lost for every 64,700 tons of coal raised; but in 1886 one life was lost for every 188,800 tons of coal raised. Thus the death-rate was now only about one-third, a diminution most remarkable, and he thought in the highest degree creditable to the owners, managers, inspectors, officials of all degrees, and to the workmen. The amount of coal raised had very rapidly increased; with that increase new dangers had arisen, and mining engineers had hardly acquired the amount of experience which enabled them fully to cope with all the dangers that were met with. Some accidents occurred through overwinding, through the cage being drawn up too far. Many mechanical engineers had set to work to devise means for preventing overwinding by disengaging hooks, so that the rope might be separated from the cage and not be drawn over the pulleys. Now, if he were in a cage suspended in a shaft, the last thing he should want to happen would be to be separated from the rope. Of course if he were just going over the pulley it would be a desirable thing, but he would rather go over the pulley than go down to the bottom of the pit. It had unfortunately happened that just when the safety apparatus was most wanted it had generally failed. When winding up at a slow rate it acted effectually; but if it was wound up fast through some mistake of the engine man it was generally smashed to pieces. That showed how much a safety apparatus could be relied upon to prevent accidents. Many different kinds of hooks were used, and he thought that his observations would apply to all of them. Safety-hooks were not regarded as of high value by continental mining engineers, who preferred safety-cages, which in their turn were despised by

English engineers. Thus safety-cages were adopted almost universally on the Continent, while safety-hooks were almost universally adopted in England. That was a matter which should be taken into consideration by those who were inclined to pass regulations for the working of coal-mines. He thought an automatic contrivance, to regulate the speed of winding and stop the engine if it went too far, was much better than a disengaging hook; he had seen such an apparatus in France and also in England. He wished to ask the Author a theoretical question as to the pressure of gas existing in coal, whether he thought there was some connection between that and the depth of the mine. Of course the pressure could not be greater than was due to the superincumbent strata, and he wished to ask whether any measurements could be thoroughly relied upon to give the maximum gaseous pressure existing in the coal, considering that there were great practical difficulties in driving a bore in coal a sufficient distance, and then plugging it up so as to prevent the escape of any portion of gas. Allusion had been made in the Paper to the means of testing for gas in mines other than safety-lamps, such as Ansell's indicator. He believed he was present at the first practical test ever made in a mine with that instrument twenty years ago, and it was then a failure. It was evident that there was gas in the mine before the indicator showed it. He had carried a modified form of the indicator in his pocket, but had generally found it fail. The Author had alluded to the cheap way in which the electric fuze was now made. He had himself used thousands of those fuzes, or fuzes that bore the Author's name, which he had bought in London, and the only fault he had to find with them was their cost. If they could be reduced from $2\frac{1}{2}d.$ to $\frac{1}{2}d.$ each a great boon would be conferred upon the mining community. The Royal Commission attached great importance to the testing of safety-lamps before they were allowed to go into the mine. He had tested safety-lamps for many years, and the method he adopted was to take a lead pencil, push it through the gauze, and make a hole $\frac{1}{4}$ inch in diameter, so as to render it a thoroughly unsafe lamp, and then put it to the test; such a lamp often resisted a test in still gas. He thus tested the testing apparatus to see whether it would give him the assurance that he could not put an unsafe lamp into the mine after it had been through the apparatus. That was the difficulty. What he wanted was a testing apparatus that had been thoroughly tested, so that he could apply it to testing lamps. Until he had that he should prefer a safety-lamp that had been subjected to ten thousand practical tests, and then, when he knew the lamp was right, he

Professor
Lupton.

Professor Lupton. would trust the eye and skill of the lamp-man and those who saw it put together, so as to feel sure that he had a practically safe lamp. With regard to a very important question, that of coal-dust, the Author had dealt with it in a masterly way, as he did all such questions. He believed that his experiments upon coal-dust, as well as those which he had reported in connection with the Prussian Firedamp Commission, had established without doubt the possibility of what might be called a pure coal-dust explosion; but as a mining engineer Professor Lupton would rely more upon the evidence found in the mines that had exploded. When he went into a mine and found an explosion originating in an intake air-road close to the pit, and that the explosion had gone through the intake roads, and not into the return roads, or working places where gas might be expected to be exuding from the coal, confining itself (though it had penetrated the workings of three or four seams) to the roads where gas would not be expected, and simply taking place where there was oxygen and coal-dust, he thought that was evidence going a long way in support of the pure coal-dust explosion theory. But the Author had asked what was the use in theorizing about a pure coal-dust explosion unless the air had been first analysed, and it was certain that there was no gas? Now there were places in mines where, if a chemist should say that he had analysed the air and found firedamp, he should be inclined to dispute the analysis. He should say "That coal was hewn twenty years ago, cut up into pillars, and roadways have been draining those pillars of gas for twenty years: there is an overwhelming supply of fresh air continually rushing along, and are you going to tell me that there is any coal-gas there? Because, if you do, let me ask how much coal-gas I may expect further in? If in 200 yards a main intake air-road will give an appreciable percentage, how much may I expect when I have gone through 20 miles of roads—not an uncommon length in one mine? How much firedamp may I expect in the return air that has passed through all that?" It was a simple question of rule of three. Allowing for the greater quantity of gas that came out of the workings nearer the face, it was not so simple; but the case was strongly in favour of the theory that there was no firedamp in the intake air-road close to the pit—not 1 per cent., not 0.1, or 0.01, or even 0.001 per cent., and if he came down to 0.001 per cent. he thought the Author would agree with him that if an explosion occurred, and if it was a question between firedamp and coal-dust, it must be a pure coal-dust explosion. He had recently studied the subject, and he had done so by the aid of information given him by the Author

and also by Messrs. Atkinson. Referring to the coal-dust question, Professor he thought the mining engineers of the country owed a great Lupton. debt of gratitude to Mr. William Galloway, mining engineer, of Cardiff, to whom in a great measure the bringing forward of the subject was due. His investigations, experiments, and persistent demonstrations had elicited a great deal of knowledge upon the subject. He had always in his own mind connected Mr. William Galloway with the coal-dust theory. He brought the subject before the Royal Society in 1876, and was the first mining engineer in England who drew attention to its importance. His investigations of many mines proved, he thought, almost beyond the possibility of doubt, that there had been large colliery explosions which might be correctly described as pure coal-dust explosions. Of course there had been many others which might be described as firedamp and coal-dust explosions, and there had been others which might be called pure firedamp explosions. But of late years most deaths had been produced not by pure firedamp explosions, but by firedamp and coal-dust explosions, and by pure coal-dust explosions. The means of laying the dust were now well ascertained and largely practised in different parts of the country. A short time ago he visited several collieries in South Wales, one of which was the Ynishir Colliery, managed by Mr. John James Thomas. Under his energetic management a length of about 3 miles of pipes had been laid through the workings, carrying water at a pressure of 70 or 80 lbs. on the square inch, in pipes $1\frac{1}{2}$ inch or 2 inches in diameter. At intervals of 25 or 30 yards he had stand-pipes, 4 feet high, with little jets sending out water in a fine spray, which were caught by air-currents and damped the mine. In that way the whole mine was damped, and when that was done the formation of dust was stopped. No harm was done to the roads by the water-spray; the duration of the timber was increased, the temperature of the mine was lowered, and the horses had a good supply of drinking-water at hand in the pipes. Even if the whole intake road was damped it was not likely that there would be much dust in any part of the mine. That plan was carried out by Mr. Archibald Hood at Llwynipia and at other collieries in South Wales. In some places there were not merely jets of water at high pressure, but of water and compressed air, the compressed air carrying water out in a fine spray into the mine, so that no puddles of water were formed which might cause injury to the road. This was the invention of Mr. Martin of Dowlais. There were several other ways of damping mines. Perhaps one of the most ingenious was that of Mr.

Professor
Lupton.

Stratton, in the Pochin pit, Tredegar Collieries. He turned the exhaust steam of an engine into the downcast shaft, and it had the effect of heating the air and damping it at the same time. It was well known that it was impossible to damp the air unless it was heated, and Mr. Stratton did both at the same time. He succeeded in damping the whole of the mine by putting steam into the intake air in the downcast shaft. It did very well in spring, summer, and autumn, but in winter it was not sufficient, because it would not heat the air enough, and in winter therefore the steam was supplemented by water-carts for laying the dust. This method of damping the air by steam was only applicable to mines of moderate depth, and consequently low temperature, say under 65° Fahrenheit, because it would make deeper mines too warm. The steam had done no harm to the roads or timber at the Pochin pit, and it made the mine much pleasanter. He would only say that it would be interesting to calculate what would be the probable effects of an explosion in a coal-dusty mine. He should measure the effect by the amount of oxygen in the mine, because he assumed that wherever there was coal-dust there was more than enough for chemical combination with the oxygen. He had made one calculation in the case of a large colliery which had exploded, and the combination of oxygen and coal-dust, assuming that all the oxygen in the air-ways where the explosion occurred was burned, was equal to an explosion of 90,000 lbs. of gunpowder, or of 4 lbs. for every lineal foot of the roadway. He did not pretend to say that was a trustworthy calculation; he merely used it as an illustration, and would rather put it interrogatively to the Author, or to some other chemist.

Mr. Tylden-
Wright.

Mr. C. TYLDEN-WRIGHT said all persons interested in mines, and in the working population, owed a deep debt of gratitude to the members of the Royal Commission, who had undertaken a Herculean task. The work had occupied them seven years, and it was a standard work for every one connected with mines throughout the country. The Commissioners had given an immense amount of detail which would be of great service, and absolutely without fee. He regretted, however, that the present discussion had not taken place before the Bill was considered in the House of Commons, because in that case the coal-owners would have been spared the trouble of combating many amendments that were introduced, which were certainly of an extraordinary nature. It was proposed to form "harbours of refuge" underground, which were to be hermetically sealed from the surrounding atmosphere, to be explosion-proof, and to be erected

in different parts of every colliery. It was also proposed that there should be two engine-men in every engine-house,—he supposed for the purpose of occupying one another's attention. Another proposal was that wherever gas was found in a mine, no underground furnace for ventilating purposes should be used for twelve months. The effect of that would have been to close absolutely the largest collieries in the country. Again, it was proposed, and he was sorry to find that the Author to some extent endorsed it, that all safety-lamps should be tested with gas. He might not be aware that there were hundreds of collieries in the country that had no gas-mains within miles of them, and how, in such cases, safety-lamps were to be tested by means of gas it was difficult to say. The public had to thank the common sense of the Home Secretary, and the calm judgment of the House of Lords, that coal-owners had been saved from the harassing legislation proposed by certain members of the House of Commons. The Bill was in some respects one of the most stringent ever passed, but in others it was thoroughly workable and practicable, notably with regard to the use of explosives in mines. Whereas there was formerly a great restriction put upon the use of gunpowder and explosives if gas had been found within three months, that time had now, without any risk whatever, been reduced to forty-eight hours, which was a very great improvement. No one understood the use of powder so well as the Author, who was *facile princeps* in everything connected with explosives; but he wished to tell him that for the purposes for which an explosive was wanted in mines no nitro-glycerine compound had been yet invented equal to gunpowder, and if he would devote his talents to the adoption of powder in some water-cartridge, he would do the greatest service to the coal-owning interest. With regard to safety-lamps, he had been greatly surprised and pleased to see the admirable collection of electric lamps produced for exhibition. They had their disadvantages, and safety-lamps of the old type must, he thought, always be used. One of the disadvantages was that they were all apparently of the nature of a bull's eye lamp, only throwing the light on one side, which he considered a fatal objection to a lamp underground in a pit. Again, the cost was, he thought, eight times that of an ordinary protected or unprotected Davy lamp, and what the effect would be of dropping them on the ground, which was a frequent occurrence in mines, he could not say; but he imagined that they would not long survive. Again, some of the lamps weighed 5 or 6 lbs., whereas an ordinary safety-lamp would only weigh from $1\frac{1}{4}$ to $1\frac{1}{2}$ lb. In that respect,

Mr. Tylden-Wright.

Mr. Tylden-
Wright.

therefore, he thought that the old safety-lamps were likely to hold their own for some time. They would also probably do so in other ways, because electric light was absolutely useless in testing for gas. One might walk into choke-damp with an electric light and fall to the ground without the light affording the slightest indication of danger, but with a safety-lamp the danger was at once apparent. The Author had raised a question on which he was bound to join issue with him with reference to "protected" and "unprotected" lamps. The House of Lords had met with very unmerited abuse for having altered the Bill, as it left the House of Commons, to the state in which the Home Secretary had originally drawn it. Nothing could be more definite with regard to the use of lamps than the present clause: "Wherever safety-lamps are used they shall be so constructed that they may be safely carried against the air current ordinarily prevailing in that part of the mine in which the lamps are for the time being in use, even though such current should be inflammable." The Author seemed to think that the part of the mine where the lamps were in use applied only to the working place where the man happened to work. His own view was that it was wherever the working man happened to take the lamp, and that the lamp must be perfectly safe in that particular place. He therefore thought that the House of Lords was perfectly justified in striking out the words which were hastily added in the Committee of the House of Commons, saying that unprotected Davy lamps should be prohibited. He thought it would be a great pity for the name of Davy to be under, however small, an amount of obloquy by being expressly prohibited in mines. He came from a district in South Staffordshire where the Davy lamp was looked upon as the most delicate and best practical apparatus for testing for gas. He would not say that it was the best for working throughout the shift in gaseous pits; but the condition of mines in that and some other districts was not generally gaseous; they only wanted examining by a safety-lamp, and then naked candles were used for the work. There was also a proposal, to which the Author had alluded, that "detaching hooks" should be enforced. He did not know how many accidents had happened from the want of them during the last fifteen years. In South Staffordshire not a single life had been lost from their not being used in working pits. As to the rest of England eleven lives had been lost from over-winding during the last year, of which ten were lost where detaching hooks had been employed. There was one other matter to which he would wish to refer connected with the safe working of mines,

and that was inspection. It might be thought that coal-owners were most unscrupulous, and workmen most incompetent to take care of themselves, from the number of inspectors supposed to be necessary. There were (1) the Government inspector and his staff of assistants, of whom he would wish to speak in nothing but praise; (2) Inspectors of weights and measures, who were compelled to test every machine at least twice a year; (3) Boiler inspectors, as provided by the Bill presented to the House of Commons by the President of the Board of Trade; (4) School inspectors; (5) Inspectors on behalf of workmen. The House of Commons altered the Bill so that any person who might have worked a month or so in a pit twenty or thirty years ago, might be sent by the men as often as they liked, to make this official inspection. He need not say that the experienced and trained managers of the pits, than whom a finer class did not exist, objected most strongly to taking such men through the most dangerous parts of the workings. The House of Lords did no more than bare justice to the colliery officials when they restricted the examination to actual working miners. He trusted mining legislation was now at rest for many years.

Mr. Tylden-Wright.

Mr. EMERSON BAINBRIDGE said he would name one or two points, which had been omitted by the Author, and there were one or two others on which he joined issue with Mr. Tylden-Wright. Reference had been made in the Paper to the increase of accidents due to a fall of the roof, but no cause for it had been assigned. He ventured to suggest that it was due to the fact that the seams which had the best roofs had, year after year, gradually become exhausted. The coal now produced in the various mining districts of the country from coal seams, had, in many cases, a roof which was not so good to manage as formerly, and therefore was more liable to cause accidents. In reference to the various means of breaking down coal, the Author had spoken of several mechanical wedges, but he thought he was right in saying that, in nearly all cases, the wedges referred to were not now used. As a matter of fact there was scarcely a single wedge, perhaps with one exception, that was now able to hold its own as a means of breaking down coal. The cause was much the same as that which had been the means of limiting the use of the lime-cartridge. The Author had warmly defended the lime-cartridge, and with good cause; but the fact that it was not used on a large scale, in more than about a dozen collieries, was rather against the idea of its being a success. The want of success was due almost entirely to the fact that it was difficult to get combined, a face of coal which would break

Mr. Bainbridge.

Mr. Bain- down easily, a roof which would separate freely, and a coal which
bridge. would break off well, conditions which were generally required, whether the wedge or the lime-cartridge was used, both being slow means of applying force to break down coal. There was one wedge now in use with great success in Belgium and the North of France. It consisted of two long steel wedge-pieces, which were placed in the shot-hole, the thick end inwards, and a third long wedge was driven between the two. The wedge was not employed in England on a large scale, but in France and Belgium it had been largely adopted. The objection to it was that whilst with the lime-cartridge or any other means of breaking down coal simple ordinary explosive force was applied, with the wedge a considerable quantity of "elbow-grease" was required, and a man had to take five or ten minutes in striking the centre wedge in order to get the coal broken down. No mention of that wedge, or of any wedge in practical use was made in the Paper. As to the question of safety-lamps, it might be a bold thing to say, but his impression was that there had been a great tendency to over-legislation, and to making restrictions upon means of mining which had never been proved to be the causes of any accident. In all the accidents of the last thirty years it would, he thought, be impossible to find five cases where an accident by explosion had been actually proved to be due to the use of such lamps as were condemned by the new Act. But in spite of the new regulation, which perhaps would cause nearly a million lamps to be altered, he was sure that every manager of a mine, who knew what a serious thing an accident was, would welcome the results of such important experiments as had been made by the Royal Commission. He was glad that the Author had passed a merited encomium upon Mr. C. E. Rhodes for his endeavour to test lamps, which he had done on a large scale in Yorkshire; but the moment a lamp was now put to a test, the idea was to have it tested at a current of 50 or 60 feet per second, which was an impossible velocity in any mine in existence. The ordinary velocity of an underground air-current was not more than 10 or 15 feet per second, and he ventured to assert that if a lamp would stand safely double that, or 30 feet per second, it might be considered, for most mines in the kingdom, practically and perfectly safe. It was not, therefore, necessary to fall back upon the elaborate designs of safety-lamps, some of which had been mentioned by the Author, and many of which were very complicated and costly. He might be permitted to give a sketch of a lamp which he was now endeavouring to bring out, and which had been on the previous day

tested by Mr. C. E. Rhodes, as a lamp of very simple construction, and which stood a 30-foot per second test by actual experiment. It was a bonneted Clanny lamp. First of all, the bonnet with holes in it at the top allowed the escape of carbonic acid gas; next, the gauge allowed the admittance of the fresh air into the lamp, the shield bonnet being a necessary addition. This lamp had been proved by experiment to stand a velocity of current of 30 feet per second, instead of exploding, as did the ordinary Clanny, at about 8 feet. The ordinary safety-lamp which stood severe tests had eight or nine parts, but the lamp he had designed was so arranged that the glass was fixed in the top of the lamp; the top or bonnet part unscrewed, so that when the top was removed the gauze could be examined and cleaned; the bottom part was also unscrewed to trim the lamp, and the glass was therefore left untouched, and could be left for six months, instead of, as was usual with the ordinary Clanny lamp, being removed every day. In speaking of the means of preventing accidents, the Author had referred to cages which were caught by self-acting catches, but he had failed to mention what appeared to be the most important invention of all. Perhaps he had not heard of this, as it was that of a working man who had been for twenty years trying to bring it before the mining public. Mr. Calow had invented a method of having a safety-cage so arranged, that the grip attached to the cage, which, if the rope broke, prevented it from falling down the shaft, only came into action when the cage actually became a falling body. In all other "cage-catchers," he believed that the catch itself was dependent upon the loosening of the winding-rope, but by means of a simple spring, Mr. Calow's was so arranged that the moment the cage became a falling body, the grips caught and stopped it. The Author had referred to substitutes for gunpowder, and Mr. Tylden-Wright had stated that no substitute had yet been found for gunpowder as an explosive which seemed to answer the purpose. It had been his good fortune during the last few months to come across an explosive of that character. In June last, he was engaged to go to Germany to report upon an explosive known as "roburite." He was told, that in Germany, there were some mines that had a stratum of 4 or 5 inches of gas constantly floating under the roof, that he might go down one of them, take this new explosive, put it in a ordinary blasting-hole, and fire it off, and there would then be no danger of any flame appearing! He need hardly say that he declined the experiment, but said that in a mine where there was no gas, he should be prepared to try it. He made the first experiments in July, for

Mr. Bain-
bridge.

Mr. Bain- safety, in a quarry, where the roburite was tested under very
bridge. trying conditions. He had first gunpowder, then dynamite, and then roburite, placed in small heaps, and covered with about $1\frac{1}{2}$ inch of sand. The experiment was tried at nine o'clock at night, and when the gunpowder exploded there was a very large illumination; when the dynamite exploded there was a large flame; but when the roburite was exploded by a detonator, there was not the least spark. He then proceeded to try the same experiment underground, and on the following day he placed, in the presence of twenty persons, a cartridge of roburite into a hole in the coal and the shot was fired, but there was no spark. He then tried, for the first time with this explosive, an experiment with a blown-out shot, which, as the Author had stated, had probably been the main cause of nearly all the most serious explosions that had happened in this country; and if anything could be done to prevent the disastrous effects of blown-out shots, one of the main causes of accidents by explosion would disappear. A charge of roburite was put into a hole, a small "stemming," of about $\frac{1}{2}$ inch, was put next to the charge, and a detonator was applied. The charge was then fired, and he had the satisfaction of seeing that the "blown-out shot" did not produce the least spark. If, therefore, roburite turned out to be, practically and economically, a good thing, it would prove a very important agent in future for mining. He also discovered in Germany that there were two other explosives, one named carbonite, and the other securite, which appeared to have similar action. The Author had spoken of carbonite with some degree of doubt, but Mr. Bainbridge thought that one or all of those explosives would be a very important means for putting an end to the risks attending the use of gunpowder, and to the danger of blown-out shots. A well-regulated mine, however, as a rule, ran very little risk of serious accident from the latter cause. At present, instead of leaving every man to fire his own shot, as was done years ago, a well-managed mine had a number of men called shot-frisers, who attended to that matter and nothing else. They gained experience as to the size of the hole, as to the amount of gunpowder required, and as to whether the explosive was exactly regulated according to the work to be done; and, of course, if those things were well balanced there was little fear of blown-out shots taking place. As a point of economy it might be mentioned that whilst the lime-cartridge, the water-cartridge, and wedges required a hole about 2 inches in diameter, an explosive like roburite acted perfectly well with a hole $1\frac{1}{4}$ inch in diameter. Colliery managers in

Germany reported that in using this explosive, there was an increase in the quantity of large coal produced.

Mr. Bain-bridge.

Mr. WILLIAM MORGANS stated that he was unable to agree with the views of the last speaker as to the testing of safety-lamps. It was necessary that lamps should withstand higher velocities than the ordinary currents met with in mines, because they might be exposed to sudden outbursts of gas. Turning to the subject of explosions, if the manager of a colliery was wise, he would attach due importance to both coal-dust and firedamp accumulations in mines. By all means let the moistening of coal-dust be carried to any extent desired, but let not the danger of firedamp accumulations be overlooked, which, though rarely seen in working places, were often found in adjacent goaves or contiguous old workings, and unfortunately so by the sanction of the law. One speaker appeared to feel very positive that more explosions were due to coal-dust than was generally realized, but so far as Mr. Morgans could judge, it had become the fashion to apply the coal-dust theory too commonly. Not only had there been a disposition to subordinate the evils of firedamp to those of coal-dust, but the active pursuit of the coal-dust theory had engendered a disposition to ignore firedamp altogether. This had done harm by diverting attention from a long standing danger. It was to be hoped that the height of enthusiasm respecting coal-dust was reached in the case of the Altofts explosion. Firedamp was known to occur in that colliery, but the explosion was attributed to coal-dust alone. The official report afforded reason for considering that firedamp was the backbone of that explosion, and that it occurred mainly in the disturbed roof strata where gas was often found in cracks and partings over intakes, as well as in other ways. Those who believed in explosions of coal-dust alone must find some better example than Altofts, which belonged to the armoury of their opponents, because firedamp was given off in that colliery. As yet there was not a single example to be brought forward of a colliery explosion in any of the dusty workings in this country which were free from firedamp, notwithstanding that blasting was extensively carried on in them day by day. Consequently, explosions of coal-dust could not be regarded as anything more than supplementary to explosions of firedamp. Experiments might be pointed to in opposition to this view, but experience would be found arrayed against those experiments. The thanks of the mining community were due to Mr. Joseph Dickinson for recently taking a step to divert the pursuit of coal-dust extremes to a safer course. In his Report on the Udston Colliery explosion,

Mr. Morgans. he subjected the coal-dust theory (which appeared to have been ridden rather hard by some witnesses) to criticism, and suggested alternative views, giving firedamp its due prominence, and directing attention to the gas in the stoopings or goaves. On p. 19 of his Report, the following paragraph occurred:—"The mine being dry and dusty, and the coal a Splint coal of a highly inflammable kind, gives plausibility to the supposition that the explosion was aggravated by dust. The evidence, however, showed that the main roads were the most dusty part of the mine, and not the rooms. It was, however, in the rooms not cut through and least dusty that there were the greatest signs of coking, extending not quite up to the face, and not in the main roads, some of the principal coking being in rooms which were not at work." Notwithstanding that in one instance the danger of goaves had been made light of, the authority of many Inspectors of Mines, of the late Royal Commission and of the Author, was against this, and the reasons advanced as to their safety would have to be greatly modified to harmonize with facts and with experience. As regarded the ventilation of goaves, he thought the day had passed for appealing to that impracticable idea. To ventilate the inaccessible ramifications of goaves, caused by the collapse of the broken roof strata over the excavated parts of a thick seam, was a physical impossibility. What was euphoniously called the ventilation of goaves would be more correctly described as the aerating of goaves. Unfortunately goaves could be aerified and brought to an extremely dangerous condition; and it could be shown that in ordinary cases it was impossible, if once goaves were permitted to exist, to prevent them from assuming that threatening character. The most dangerous goaves were found in collieries where thick fiery seams were extracted and little rubbish remained to occupy the wastes; and it was in collieries answering to that description that the examples of the greatest explosions which had happened in this country must be sought. It was the practice of allowing the roof to be crushed down in large masses which was the great mischief. The fallen débris, by filling up the excavated plane of the seam and getting compacted therein, was very misleading in giving an idea that the goaves were closed, but the dangerous goaves were the cavities and ruins of the broken roof strata overhead and out of sight. Goaves were by no means confined to the plane of the seam. When the dislodged masses of roof strata were very hard, the interstitial spaces and arched cavities were a long time closing, and they formed gas-holding goaves, often many acres in extent,

bordering on the workings. These magazines of firedamp were Mr. Morgans, in direct communication with the colliers, not only at the edges of the goaves, but through many joints and fissures developed in the roof, in consequence of not providing it with adequate support in the goaves. The strain thus set up in the roof converted what would be a safe top into a dangerous one, and increased the accidents by falls, which were the most prolific cause of fatalities in mines. This was an important part of the goaf question which should be mentioned, although he was now more particularly dealing with explosions. The remedy for the evils consisted in adequately stowing the goaves with rubbish, but he would not here enter upon the commercial considerations beyond expressing his convictions that, apart from the saving of life and limb, great pecuniary benefit would accrue to the coal-mining industry and to the nation at large were the remedy applied. People must first be convinced that goaves were the cause of great disasters in mines. A good test of the existence of dangerous goaves in a fiery colliery was the effect of barometric changes upon the condition of the return air. Whenever a rapid fall of the barometer caused a great increase of firedamp in the return air, it might be concluded that the colliery was beset with dangerous goaves. This test had been incidentally confirmed in a Paper "On the Effect of Atmospheric Changes upon the Development of Firedamp," read before the Manchester Geological Society, on the 1st of December, 1885, by Mr. J. S. Martin, H.M. Inspector of Mines,¹ dealing with experiments made in the Gabriel colliery, near Karwin, in Austro-Silesia. But whilst the presence of dangerous goaves could be detected during a decided fall of the barometer, they remained an element of risk in a colliery under all barometric conditions, because gas might be suddenly expelled from them into the workings by a subsidence of the roof strata when the barometer was rising, or it might be exploded in the goaves by blasting elsewhere, or by some accident at any time independently of atmospheric conditions. The views referred to by the Author on the goaf danger appeared in a little book on the "Solution of Colliery Explosions." In it Mr. Morgans had endeavoured to strip the question of some of the glamour with which it had been surrounded; but the chief point in view was to direct attention to a factor in colliery explosions which aggravated the goaf danger, and had been overlooked. That was the dangerous character of cracks and fissures in the roof strata (1) as affording means of aerifying firedamp in

¹ Transactions of the Manchester Geological Society. Vol. xviii. p. 351.

Mr. Morgans, goaves; (2) as introducing unrecognized risks in shot-firing, whereby gas might be ignited in an unseen crevice at or near the seat of the cartridge or charge; and (3) as constituting avenues for the communication of the flame of an explosion from a working place or other point of origin to a goaf, and from one goaf to another over extensive ranges throughout the mine, without necessitating that the flame of the explosion should pass entirely through the ventilated ways and roads. The view thus indicated attributed the extension of the most violent and widespread colliery explosions to the firing of gas in the goaves and in the passages developed in the disturbed roof strata overlying the roads and workings of the mine. It accounted for the large falls often seen after explosions by the forcing down of the roof-beds, owing to the pressure of the explosions in their partings and joints. It explained the occurrence of conflicting blasts, or back explosions, bursting down into the roads at different points, and of apparently simultaneous explosions at parts of the workings very remote from each other, and other problems which could not be cleared up by the coal-dust theory. It suggested that the principal zone of the explosion was not necessarily in the plane of the workings, but oftentimes in the gas-charged goaves and roof strata overhead; and that the courses of the explosion, instead of being restricted, as by the coal-dust theory, to the ordinary roads, were frequently to be traced in the disturbed strata immediately above. One of the most conspicuous features of extensive colliery explosions had been the traces of violence, and of burning or charring, in widely-separated districts or portions of the mine. To account for the transmission of the flame from one district to another had been an object for investigation for a long time. Investigators appeared to have confined their attention to the overt ways of the colliery; while the dangerous system of communication opened by covert ways overhead had been overlooked. It was impossible to account for the presence of firedamp in most of those overt ways, since they were known to be abundantly ventilated. In this difficulty the coal-dust theory had been promulgated, and had done duty ever since. But it had certainly been accepted in some instances subject to the somewhat narrow view that an explosion must always pass through the roads, forgetting the fact that it might often pass above and cross over the roads. Dangerous goaves were not commonly found in thin seam workings, because the comparatively low wastes were usually so well stowed by the rubbish at hand as to prevent the wreck of the roof strata, and there was hardly a case on record of an explosion of mag-

nitide in workings of that description, however dry, dusty, Mr. Morgans. and fiery they might be. But workings in the thicker seams, where goaves were formed, owing to the insufficiency of the rubbish provided for stowing them, furnished the scene of almost every extensive colliery explosion on record, and all of the most disastrous and widespread explosions of the thirty-two on the Author's list had been confined to fiery seams of from 6 to 9 feet thick, or, in other words, to those precise conditions under which the most capacious and dangerous goaves were found to exist. Were not these grave facts which called for serious reflection? Was it not time that the investigation of the highly important goaf agency should be undertaken? It had long been neglected; it presented many features which demanded searching enquiry. Now that the Author had directed attention to the dangers of gas-holding goaves, it was to be hoped that the day was not far distant when they would be made a subject of thorough examination. At present, in some mines extensive surfaces of dust were watered whilst huge volumes of firedamp were warehoused. He readily joined in the expression of thanks due to all who had taken a prominent part in directing attention to coal-dust. Mr. Galloway had been more fortunate than many men in having his efforts freely recognized, and everyone would feel glad to acknowledge the capacity he had shown. But the labours of other workers must not be forgotten, of men on the French, Prussian and English Commission, and especially of the Author of the Paper now under discussion. In pointing out that the violence of explosions, where coal-dust was a prominent factor, would be far less pronounced than when firedamp was the chief agent, the Author had, he believed, supplied a very valuable key. Mining engineers could never lose sight of their indebtedness in the first instance to Faraday. Whatever experiments might indicate, actual experience had so far taught them that there was very little in the coal-dust question beyond what Faraday disclosed and put upon record, although its importance might have been in danger at one time of being forgotten. Had the goaf agency received a tithe of the attention which had been devoted to coal-dust, the prevention of accidents in mines would have made much greater progress.

Mr. SYDNEY F. WALKER said he was rather surprised to find that Mr. Walker. the Author had not referred to electric signals as one source of the avoidance of accidents. It was perhaps a humble one, but he believed that it had saved many a broken leg, and possibly a good deal of damage to the road. With regard to casualties it was

Mr. Walker. surprising that there were so few telephones in use in the working of mines. The amount of injury that a man received after an accident varied very closely in proportion to the time taken by the doctor in getting to him. If the telephone were at work, or could be attached to the existing signal wires, establishing a communication between the workings and the surface, a message could be sent that a man was hurt, and how, and a good deal of valuable time might thus be saved. With reference to the question of electric lighting, he had under his own superintendence twenty installations at different collieries, pit-bottoms, sidings and main roads; but in no case had they been taken to the face of the coal. In one instance the farthest lamp was a mile distant from the dynamo. He would only refer to the matter in regard to the question of cost. There was no difficulty in maintaining the lamps day and night, and the cost came out at from one-fourth to one-twelfth of the cost of gas. In the case of one-twelfth, the gas was made at the colliery. The main point dealt with in the Paper, in regard to the illuminating of collieries, was the lighting of the face of the coal. He thought that the eventual method of lighting the face of the coal by electric light would be similar to that adopted for the main roads, namely, from the supply mains. His experience, like that of every electrical engineer, was that no matter what light was displaced, immediately electric light came on the ground the user was not satisfied with the same amount of light that he had before. No matter whether a small candle was in use in a Cornish mine or a large argand lamp in a light-house, a great deal more light was wanted. That was shown, he thought, by the avidity with which the electric lamps exhibited in an adjoining room were taken up, on account of the extra light which they gave. But it was impossible to go far in that direction with a portable lamp, as the weight increased very rapidly in proportion to the degree of light. If, therefore, more light was wanted, and both the collier and the colliery owner would very soon appreciate the advantages of more light, it would become a question of providing it in another way. Then it should be borne in mind that at the same time the education of the collier was going on among the rising generation. There were science schools in the villages, and miners were getting accustomed to the use of electricity and electric lighting in all parts of the mines, and they would discover that by connecting the wires of a lamp, which possibly they carried in their pocket to their work, properly protected, they could have the light they needed, and that if the connection was broken they would have no light; when they arrived at that

point there would be no serious difficulty in working from supply- Mr. Walker.
mains, properly and carefully fixed. Of course the grave danger would be the spark at the moment of connection; but it was by no means necessary that the final connection should be made in contact with the atmosphere. Many simple kinds of apparatus had been, and could be arranged for the purpose of making the final connection out of contact with the atmosphere. He might also mention that, from some experiments made by Mr. Mordey and himself, it had been proved that it was not a spark *per se* which ignited the gas, but a spark of a certain energy, and that that degree of energy did not exist at the end of a connection with a single lamp. As to the question of primary versus secondary lamps, he agreed with the Author that the operation of charging any properly-designed primary lamp would be quite as simple as the operation of cleaning and re-filling existing lamps. He thought, therefore, if a portable electric lamp came into use, that the primary lamp offered the greatest advantages in the present state of knowledge possessed by electrical engineers and by colliers. A secondary battery lamp looked more simple, but it was not so in operation. If there were five hundred lamps to connect in the colliery, there would be at least two thousand connections, the greater portion of which would be hidden. The case was not on all fours with the mechanical arrangement of emptying out liquids and putting them in again. Connections might go wrong at any time without anything to show it. Then again, how was the current to be obtained? The Author had suggested that it could be got from the existing dynamo at the colliery; but, in his opinion, to work from the existing dynamo would entail a considerable amount of complication, because it would entail a series multiple arrangement, which would be out of place at a colliery. He also most strongly condemned all switches, resistances, and automatic cut-outs and circuit-breakers for work in a colliery. Strength and simplicity were wanted, nothing else.

Colonel PAGET MOSLEY observed that it had been stated in the Colonel
course of the discussion that the lime-cartridge system was quite Mosley.
unable to get coal from where the parting between the roof and the coal was not a good one; or, at all events, where the circumstances were not exceedingly favourable to the operations of any dislodging power. He had had on many occasions ocular demonstrations of the working of the lime in the collieries at Shipley, where the system was first brought out. The top was there of a particularly sticky nature; indeed, there was practically no parting at all in a great part of the colliery; so much so that, when

Colonel Mosley. wedges were formerly employed to dislodge the coal, after the wedges had dislodged as much coal as could be got by that means, there still remained a layer of 2 or 3 inches of very hard sticky coal, which had to be hacked off the roof with picks, but the lime got the entire seam down without leaving any coal on the roof. He regretted that Mr. Sebastian Smith, the inventor, was unable to be present, or he would have been able to give many more instances of the lime acting perfectly well in coal where the roof was of a very sticky nature. That had been evidenced also by the reports of managers in collieries where lime had been tried on many occasions. The system only wanted fair play, and the fact that it was not more largely adopted at present was perhaps in some measure due to the comments which were made by Mr. Stokes, one of the Government Inspectors, on the conclusions at which the Royal Commission had arrived with regard to the lime process in a Paper read before the Chesterfield and Midland Counties Institution of Engineers. Those comments were characterised by the Author as not being quite of a dispassionate nature; but ever since the system was brought out at the collieries at Shipley, Mr. Stokes had opposed it. He should have imagined that, as one of the Government Inspectors Mr. Stokes would have done all he could to encourage a system which, the Commissioners stated, would in some seams perform work quite equal to that done by powder, at no greater cost, and with absolute immunity from risk of explosion.

Mr. Hall. Mr. HENRY HALL remarked that the Author was not a mining engineer, but men outside the profession would often hit upon expedients that men inside it might fail to see. The principal points for discussion were, in his opinion, the method of lighting mines, and the method of blasting. With regard to lighting, he contended that too much stress had been laid upon the necessity of procuring a large amount of light from the lamps. The Author had recommended glass lamps, but these, he thought, were subject to many more dangers than the old-fashioned lamp which had gauze round the flame. A glass lamp was often broken by heat, and it might also be broken by being dropped on stone, or by anything falling on it. More than a dozen glass lamps would be broken in a colliery against one gauze lamp. It was pointed out in the Paper that falls of roofs would be less frequent if the men had a good light. He did not himself believe that such accidents ever happened from a collier having a bad light. The collier judged of the state of the roof by sounding it and listening, and he could do that whether he had a good or a bad light. As to

blasting in mines, if the water-cartridge was as safe as had been Mr. Hall. represented, it would no doubt prove to be the greatest blessing that had ever fallen to the lot of miners. But there were certain points which needed some precaution. The water envelope was a weak contrivance, and it had to be used in a rough way. A thousand shots might be fired in one day by all kinds of hands; and if it was something that the colliers could manage to make dangerous, some of them would be sure to effect that object. With reference to dust, he did not think that any explosion had happened in a mine of importance where there was no firedamp. Still, there could be no doubt that the presence of coal-dust did greatly aggravate explosions. A good deal had been said about tests for gas. Certain instruments had been recommended as likely to be useful for that purpose. The difficulty that he and others had met with was not that they could not find the gas, but that when found they did not know how to deal with it. Even if much finer tests were available the difficulty would not be removed. He had used some of the apparatus suggested, but he had always to fall back upon the ordinary Davy lamp. He believed it was possible to test gas with a Davy lamp better than with any other instrument. Liveing's instrument had been recommended, but he was very unsuccessful in its use. It appeared that the handle had to be turned at a certain fixed speed, and if it was not turned at that speed the effect was not always constant. There was one point, which, he thought, might have been entered into more fully by the Royal Commissioners. They might have given some information as to the explosive force of certain quantities of firedamp. Officials found large volumes of gas here and there, but thought nothing of it, and said that it was not dangerous. It was difficult to say how much gas was dangerous. His own opinion was that a very small quantity, if it was really at the most explosive point, was very dangerous; but he had never come across any law on the subject.

Colonel J. D. SHAKESPEAR objected to the idea that coal-dust exploded; all it did was to get hot in the flame of a lamp and then, from being in minute particles, it might be driven through the wire gauze by the ventilating current, and if at a white heat it would ignite any firedamp present, whether in large or in small quantities. If coal-dust really exploded, coal-cellars would have been wrecked years ago. As to shot-firing its evil consequences were the concussion it gave to surrounding strata. With respect to the gunpowder and water-cartridge he contended that the gases, from the ignited powder, instantly overcame the extinguishing

Colonel
Shakespear.

Colonel Shakespeare. influence of the water which the inventor vainly hoped it might exert. Much ingenuity had been expended on electric safety-lamps, but he considered their intense brilliancy unsuitable to the hewer, since they cast a white beam that in the extreme darkness of the surroundings materially dazzled his sight. Rather than a dazzling speck of light close to him, a cutter of coal needed a diffused, soft light. On Tyneside, gas had been found to escape from the surface of the coal at a tension of 600 lbs. per square inch; and at Boldon Colliery, Mr. Lindsay Wood had found the tension to be 461 lbs. per square inch,¹ compared with which 50 lbs. per square foot, the force of wind in a hurricane, was a trifle.

Mr. Humble. Mr. STEPHEN HUMBLE observed that reference had been made to an accident which was attributed to the failure of the apparatus connected with a detaching hook. At the Houghton Main Colliery, where the accident occurred, the depth of the shaft, from pit-bottom to the girders on which the catch-plate was fixed, was about 570 yards. The engines were 1,000 HP., and under steam forty seconds, and at the time of the accident the steam-brake had not been applied; consequently the force at which the cage went into the head-frame had been computed to be equal to a dead shock of 90 tons, which that part of the head-frame was not capable of sustaining; and although the hook detached the rope, the force of the overwind was so great as to tear away the bolts holding the catch-plate to the girders, which with the hook and cage dropped to the bottom of the shaft. Here the hook and catch-plate were found intact, and subsequently put into use again. Ten men lost their lives, but the accident was not attributable to the hook, and at the inquest the evidence proved that the hook acted perfectly well, and that the deaths occurred from the inadvertence of the engine-man in overwinding. At the neighbouring colliery of Messrs. Briggs, Son and Co., only a short time previously a similar case of overwinding had occurred, and there the hooks saved the lives of ten men; and only that morning he had received, from another neighbouring colliery, a letter which had been spontaneously written by Messrs. Pope and Pearson, stating that "during the six years we have had your 12-ton hooks in use at our Silkstone pit, where we work 1,000 tons per day, they have given every satisfaction. In a recent case of overwinding, the only one we have had, the action of the hook was all that could be desired."

¹ Transactions of the North of England Institute of Mining and Mechanical Engineers, vol. xxx. p. 221.

Sir GEORGE ELLIOT, Bart., stated that he had had something to do, in consultation with Lord Cross, with the constitution of the Royal Commission on Accidents in Mines. It was thought that at a time like the present, when intelligence and education and all sorts of practical skill were combined, it would be well to have a hybrid Commission, including what he might term philosophers and practical men. The Commission was accordingly constituted on those lines, and its members had worked together very earnestly; their Reports supplied a vast amount of information which was worthy of the study of every young mining engineer, and of discussion at every mining institution in the country. He might mention that he had taken part in the formation of the first mining institution in Durham, as well as the first mining institution in Wales. He had also suggested, in a Presidential Address in 1868, that the North of England Institute of Mining Engineers should be connected with the Durham University, in order that they might have the assistance of the professors there, and the many collateral advantages co-operation with a University would supply. He had also suggested an alliance between the great mining institutions of the country and the Institution of Civil Engineers, which he hoped the present President would do his best to bring about, mining engineering and everything connected with it being closely associated with civil engineering. He was unable to go fully into the great question of how to lessen accidents in mines, to which both as an employer of labour, and as an active public man, he had given much anxious thought; but as he had been a member of the Institution nearly forty years, had been a member of the Royal Commission, and had been long and largely associated with mines, he felt it a duty not to let the opportunity pass of testifying before his brother professional men the keen and abiding interest he took in this vitally important subject.

Sir WARINGTON SMYTH said he proposed to make a few remarks upon the Paper, taking the various subjects in the order in which they had been presented. He should indeed be acting the part of an unnatural parent if he had any quarrel with, or were to be unduly critical of, the Paper, seeing that the Author, being no doubt aware of the repugnance with which the greater part of the public looked upon Blue Books, had put their joint report into a readable form; and he hoped that much good might come of people taking up a book that was more convenient to read than the Blue Books, which they were so apt to thrust on one side. The Paper dealt with the whole of the subject which had been, after a very long period of thought and labour, brought before the Government as the Report of the Royal Commission. Some

Sir George Elliot.

Sir Warington Smyth.

Sir Warington
Smyth.

additional points, however, had been introduced at the beginning and in the course of the Paper, upon which alone he thought it necessary to say a few words. He agreed so thoroughly with the great bulk of the Paper, which was in fact mostly in the words of the Commission, that he had very little to say on those points which his friend and colleague had made so much his own, namely, explosions, blasting, and safety-lamps. But since reference had been made to the history of legislation on the subject of mines from the year 1835, he could not help suggesting that it had not been legislation alone that had done the great good which had been undoubtedly accomplished. He had observed, throughout the whole country, the totally different tone which now actuated those who performed their duties as managers of mines; and he found that the great exertions made by Mr. Nicholas Wood and others in the North, the establishment and active working of the Institutes of Mining Engineers, which began at Newcastle, and had since been carried out in almost all the important mining districts, had contributed quite as much, if not more, to the safer condition of mines than any legislation that had been passed. He saw that instead of holding aloof from one another, as people did formerly, instead of attending exclusively to their own occupation, men now met together to discuss all the difficult points, to make long series of experiments, and to discuss them in the most fair and friendly manner. He saw that they had been upon the right road, and that what had been accomplished in the Report of the Royal Commission was really contributing to confirm them in keeping that right road. He allowed there was much that the Commission had accomplished which was not new, but which others had been previously driving at, and he hoped that the authority conferred upon some of the statements made had proved a source of additional confidence and satisfaction in those Institutes, and in the men who composed them. There was also another remark which he desired to make in connection with the introductory part of the Paper—that whilst there was a very strong feeling entertained by a part of the public that legislation could do everything, that everything was to be referred to some Act of Parliament and some particular clause, and that a greatly increased Government inspection should be introduced for the purpose of rendering mines more safe, he must say from his own experience he held that nothing could be more pernicious or mischievous than the idea of substituting, for the daily and hourly inspection of the agents in the mines, any Government officials. When it was remembered what an extensive mine was, the miles of working that had to be gone through in order to examine

the whole place thoroughly, and that they had to be inspected every day by a series of, it was to be hoped, very competent persons, any notion of sending a Government official down even once a week was preposterous, and might produce the worst effects, in removing responsibility from those who were constantly amongst their men and placing it on outsiders. On what did the safety of a colliery depend? It depended from hour to hour, it might be almost said from minute to minute, upon the care and attention which were bestowed upon every portion of it by the subordinate officials, who had in the first place to go round the whole of the workings to see that they were safe, and then from time to time to visit the men at their respective places of work. A man might go through a colliery and find everything perfectly safe, and in five minutes afterwards there might be a blower bursting out, and the whole condition of things might be changed. Or some careless person might go through a ventilating-door and leave it open instead of shut, and in five minutes after the Government Inspector had been there, the whole place, instead of being safe, might be in a condition of extreme danger. It was the same with regard to lamps and many other particulars with reference to collieries. He held, therefore, that any idea of substituting an outside inspection for that daily and hourly care, which had to be expended upon the mine by subordinate agents, over-men, deputies, firemen, or whatever they might be called, was altogether out of the question. The Author had pointed out the satisfactory results, which had been obtained during the last thirty years, in the great diminution of accidents from most causes—from explosions and from accidents by machinery in shafts. Undoubtedly an enormous advance had been made in that particular direction, an advance which he thought was not exceeded in any other country. But from other points of view the retrospect was not so satisfactory. The Paper had stated the fact, that, of the average number of deaths which had occurred for several years past, 23 per cent. only were attributable to explosions, while over 40 per cent. were due to falls of ground or of the coal or mineral itself, and in other cases to falls from the roof or the sides made of other material, miscellaneous accidents forming about 35 per cent. The two last items had in one case been somewhat diminished, not greatly, and in the other case they hardly seemed to have diminished at all. He would therefore say a few words upon both. The accidents and the numbers of the deaths resulting from explosions and their consequences were extremely fluctuating. Of course, where at one particular colliery one hundred or two hundred men were carried

Sir Warington
Smyth.

Sir Warington
Smyth.

away at one fell swoop, such an occurrence would very much disturb the run of the numbers. But the accidents from falls of ground, to which men were always subject, though they had some small fluctuations, kept at a very uniform level. The same thing occurred in regard to accidents from falls of ground in metalliferous mines, and also in the mines of Prussia, Belgium, and France. The Author had very properly opposed the contention of some persons, that causes of explosions having long been well understood should be readily guarded against. It was sometimes stated, both in and out of Parliament, and sometimes in speeches, which were to be greatly deplored from their violence and misstatements, that all accidents of that kind were preventable. He very much objected to that term. The same thing might be said with regard to all the accidents of life—"If you had avoided doing such and such a thing you would not have slipped down on the pavement, you would not have been thrown from your horse, or upset in a boat." No doubt there were many colliery accidents the origin of which could be traced and reasoned upon, but it was by no means the case that they were always preventable. There were so many ways in which the accidents took place, as shown by the annual reports of the inspectors, that although their origin might be explained they could scarcely be called preventable. For example, with the very best ventilation and the best safety-lamps, if gas broke out suddenly, accidents might be occasioned from various causes. There were safety-lamps for giving better light fitted and guarded with glass, but glass was a substance of a very uncertain nature, and, however carefully it might be fitted and examined, it might sometimes be so chipped that the flame might pass. Again, there were well authenticated instances in which a mere blow, by a pick on some quartzose material, had inflamed the gas which was present perhaps in small quantities. He did not assert that any very serious accidents had occurred in that way. There was, however, the analogous case of the sparks produced by the steel mill in former days before the general introduction of safety-lamps. Explosions on a considerable scale had actually been traced to the action of those sparks falling into a gaseous mixture from the action of the steel mill. And, if that were the case, the stroke of a miner's pick might in many cases, as it assuredly had in some, have been the cause of an explosion. He mentioned that matter because there was no working without a pick or a bar, and if they were capable of producing dangerous sparks only once in five hundred thousand times, that was a source of accident akin perhaps to others that might be mentioned. With regard to shaft

accidents, he was happy to agree with the Author that they had diminished in a most remarkable degree, and that the safety with which men were now conveyed to and from their work by means of machinery was really wonderful. It was, however, often proposed that the means at present in use should be supplemented by various other contrivances, and the subject of parachute- or safety-clutches had often been brought into notice. In the adjoining room various ingenious contrivances of the kind had been exhibited, and he supposed it might be said that there were not less than fifty or sixty different contrivances for that purpose. But, considering the rapidity of the winding now needed in the coalfields of the North, he had a strong sympathy with a number of thoughtful mining engineers who considered that, by adding an apparatus of that kind, they were merely introducing a new source of danger. Nor could he help recollecting that in two remarkable cases of late years there had been fitted to certain shafts apparatus of that kind, considered to be the very best that could be obtained. He was at the Botallack mine a few years ago, when the subject of lowering the men to their work and bringing them up again was discussed by the agents. He told them that he had very strong suspicions about the apparatus, although they showed him that they had an automatic contrivance, which was sure to clutch the rails in such a way as to make it certain that if the rope broke the cage would be sustained. The shaft was an inclined plane about 400 fathoms in length, and dipping at a steep angle. They then resolved, in order to avoid every sort of risk, to employ a man who should be thoroughly practised in dealing with the safety-clutch by means of his arm. He was to go down and come up with every batch of men. He was a very careful man, and he went regularly up and down with the apparatus, the rest of the "gig" being filled with miners. But on one unfortunate day in 1863 the chain broke and the cage fell away. The clutch was unavailing, the automatic apparatus did not act, the man who had his hand upon the lever which was to work it was either paralysed, or lost his presence of mind, or something else occurred which prevented its use, and all the men were smashed to death at the bottom of the shaft. Then there was another case which occurred only two years ago at Duke Hardenberg Colliery, in Westphalia, where no fewer than twenty-five men were dashed to pieces at the bottom of the shaft in consequence of the breakage of the rope, and the safety apparatus, which had been approved by everyone up to that point, failing to act. He believed that there were gentlemen present, who would bear him out in

Sir Warington Smyth.

Sir Warington
Smyth.

saying that they had not a sufficient trust in any of the varieties of safety-cages at present introduced, to make use of them, instead of adopting the ordinary plan of getting the best plant they could, and constantly looking to its being in good action. He need not refer to other causes, but he might mention that in several districts of England, to his certain knowledge, there had been a number of safety appliances of that kind attached to some of the collieries. Mr. Fourdrinier attached them to a number of collieries, which he saw about the year 1850, and more recently some ingenious kinds of apparatus had been applied at other pits; but it was a very significant circumstance that they were now all taken away. After owners had incurred the expense of fitting out pits in that manner there must, he thought, be some very strong practical objection to their remaining, if they had all been removed in a few years. The importance of a good light in collieries and other mines was a subject upon which the Author had properly enlarged. That mining engineers were not asleep about those matters might be seen from the various experiments that had been made, and the various lighting apparatus now on trial in different places. He would merely refer to one example. He had been struck, during the last two or three years, with the excellent progress made in the sinking of a very difficult shaft in the Foxdale mine in the Isle of Man. This shaft had been sunk about 206 fathoms, a large proportion of it being in exceedingly hard granite, so that it would have taken a very long time to have proceeded upon the old plan; air compressors were introduced, and the whole boring was done by machine borers. High explosives were used in the shape of tonite, and a telephone was carried down to give instantaneous messages to and from the men. Four electric lamps were used at the bottom and four at the surface, so that the men could go on night and day. After 10,000 lbs. of tonite had been used in that way, he was glad to receive a report from the agent to say that, in that long-continued sinking, there had not been a single accident. He thought that that said a great deal for high explosives, as well as for the completeness with which all the other matters had been carried out. In fact, the agent stated that as long as tonite had been used—a period of five or six years—there had never been a fatal accident. The Author had laid emphasis upon the different varieties of emission of firedamp. Upon that subject he would only say, that, whilst doubt had been cast upon the alleged emission by sudden outbursts occasionally overpowering all possible ventilation at the time, the Royal Commissioners, during the progress of their examinations and their

report, had had sufficient evidence to show, with the utmost clearness, that those accidents were unfortunately too common, having occurred over and over again, in connection with the increasing depth and other circumstances. He was himself not in a condition to throw the least doubt upon such statements, for he had once the misfortune of being at the bottom of a shaft in Abercarn mine. Fourteen persons were assembled at the bottom, when the floor suddenly began to heave. The men had only naked lights with them, but there was a supply of air from a compressor through a pipe a few feet above. After the first two or three heaves, there was a sudden upbursting of gas and water, violent enough to extinguish the whole of the lights. The kibble was signalled for instantly, it was lowered gently in the dark, and all the men were sent up in batches. It was found that, from the agency of the compressed air, in about an hour and a half the whole of the gas had been carried off; but there were marks in the bottom of the heaving up of the ground, while at the same time an advance bore-hole was being made 3 feet in depth below the bottom, and yet the gas and water had been able to burst up the shale floor. He was not likely to forget a scene of that kind, and he therefore attached due importance to the phenomenon, which was now vouched for by so many able and trustworthy managers. With reference to the remarks of Mr. Morgans as to the liability (about which not much was known) of open spaces existing sometimes, not for a very great height, but over a large area through the workings, the Royal Commission had paid some attention to that subject; but he might say in addition that there could be no doubt that it was the source of considerable danger. A few years ago a terrific explosion took place in the Risca pit. It was found that the explosion from a shot took place in the midst of a very strong current of fresh air, and those who had seen the place could not but adhere to the opinion that gas must have been about somewhere, that there must have been open spaces in communication by means of the cracks constantly made as the roof came down. There might have been such a communication as would have allowed some flame to pass through and thus ignite the gas. That, however, was a point, he thought, that required further investigation on the part of mine managers. With regard to blown-out shots, there could be no doubt that they had been the origin of a great many accidents of late years. Why should those shots be blown out? It arose mostly from mistakes in charging, or in applying them, or in not sufficiently cutting away the ground below or at the side to take fair advantage of the direction in

Sir Warington
Smyth.

Sir Warington
Smyth.

which the shot was likely to blow. Such accidents were far less frequent in metalliferous mines. Why should that be the case? He believed it was simply because the men, instead of putting in a charge at right-angles to the face of the work, were accustomed to weigh carefully every place in which they had to put a hole. They considered the physics of the subject, the direction of the joints, the surface of the face and the nature of the material, and then they put in the shot to correspond with those joints, taking care, by means of a little heavy pick-work, to break away the rock in such direction as to be able to take advantage of the line of least resistance. He thought that in collieries sufficient attention was hardly paid to that point; and, therefore, if shots were to be carried on, as they must be in a great proportion of the collieries, the plan referred to by the Royal Commission of taking up the Author's original idea of blowing a mass asunder, by means of a comparatively small charge of high explosive immersed in water, promised to be of the very highest value in collieries as well as perhaps in some other mines. When it was called to mind that the Author brought forward that principle in the year 1873 before the Royal Society, and then experimented upon it in the presence of his friends and colleagues at the Garwood Pit, in Lancashire, and remembering the results produced as compared with the results of other charges, it was somewhat amusing to find people now quarrelling over the patent rights for what the Author had opened out for the benefit of the public. The experiments were not simply made in the sight of the few persons present, but they were published by Mr. Smethurst for the advantage of the public in the year 1881. The only satisfactory point about it was that, while people were disputing over their patents for some little modifications, so much attention was being paid to the subject, and that a long series of most valuable experiments had been made, especially those carried out in North Staffordshire with the assistance of Mr. Sawyer, Her Majesty's Inspector in the district. He thought, if the Royal Commission had done nothing else, it had done a valuable thing in starting and furthering that view which was likely to lead to so much good. As to the question of the lamp, he thought he must join issue with the Author in his onslaught, first on some of the lamps, and secondly on the House of Lords. There were many districts in the country where no gas had been perceptible from generation to generation. Why should lamps be forced upon people in such districts? Why go further (as had been done for some time past) than have a law that, in fear of any gas accumulating, a man should go round the whole of the works

with an ordinary Davy lamp in his hand, and test for gas. It had been objected that an ordinary Davy would not stand a current of explosive air; but in the collieries to which he had referred, which were scattered broadcast throughout the land, as in the Forest of Dean, South Staffordshire, and other districts, gas was never noticed, and it would be very hard upon the people there to say to them: "You must not have a Davy or a Clanny lamp; you must take some new patent lamp capable of withstanding the effect of a strong current." In many of the collieries there was no strong current, but only just enough to bring the air quietly along. He thought that the present clause was a very fair one, that in no districts should lamps be used which had not the authorization of the Secretary of State for the Home Department. At the same time he was very glad to be able to confirm the statement, that there were now several lamps quite capable of standing against any current likely to be brought against them. Reference had been made by a previous speaker to the enormous pressure under which gas issued from the body of the coal, but he thought that that point was a little misunderstood. Besides having lamps capable of resisting any currents likely to be produced in a mine, it would also be desirable to have lamps free from the objections made to the more complicated ones, that they were not so convenient to test for gas as the ordinary Davy. The simple Davy had been very largely used, but he had been assured by a very competent authority, Mr. Lindsay Wood, that the Cased Davy, or Tin-Can Davy, the lamp placed in a cylinder in which a good part of the front was glass, was capable of testing for gas just as well as the open Davy, and that it was a thoroughly safe lamp for all ordinary conditions. He stated that his firemen were now using it, and that they could see the effect of the gas flame within just as well as they could with the ordinary Davy. At the same time he might mention that Mr. Sawyer had very carefully made a long series of experiments, which he had published, and he held that he could test for gas more satisfactorily by means of a Mueseler lamp than by any other. The glass of most modern lamps had been objected to by many old stagers, who were competent to give an opinion; but a still greater objection was that most of them were covered with a cap or bonnet, which gave a greatly increased heat to the lamp, and concealed everything above a certain plane in which the light was given out. He could not help thinking that that was a very serious matter. It tended to make miners wish to pull the cover off, as it prevented them from seeing what was doing

Sir Warington
Smyth.

Sir Warrington
Smyth.

in the lamp and whither they were going. They had to look to their feet to see that they did not run against a pulley, and at the same time to their heads to see that they did not strike against the beams. It was very important that light should be given freely on all sides, so that the men might be able to look both up and down. The question of the setting and drawing of timber was a most serious matter. It would be remembered that by far the greatest proportion of accidents happened under circumstances where protection could only be hoped for by setting the timber suitably and in good time. Lack of skill and promptitude, and a want of coolness and courage, were the circumstances under which many men lost their lives from not setting up timber at the proper time and in a proper way. But in collieries they stood on *terra firma*; there was a more or less horizontal plane to prop from, and everything was comparatively simple. When, however, those conditions were reversed, as in a metallic mine, where, instead of a solid horizontal ground, the deposit on which the working took place stood upon end, nearly perpendicular, and the men had to stand upon movable platforms, or upon thin pieces of plank, or some slippery ledge, then it was that skill, experience and courage on the part of the men were needed in an extra degree. It was under those circumstances that so many accidents occurred, which could not always be prevented. They were due to the fact that when men were underground they were subjected to the action of gravitation, tending to make everything fall about them. It was for that reason that he passed to the final subject, upon which he proposed to make a few remarks. It was impossible to begin that sort of experience too young. Unless men went early to mining, and got accustomed to use the pick and shovel and shooting-gear, they never became familiar with it; and therefore it was not to be wondered at that many working men now-a-days complained, amongst other things, that people were put in charge of a working place who were not capable of protecting either themselves or their mates. Men taken from agriculture, or other fields of labour, after a certain age never learned the thing properly, but were a source of constant difficulty and danger. When, therefore, he saw men like Mr. Pickard, the late miners' agent at Wigan, an excellent collier, and scores of others, who told him that they had gone into the pit at ten years of age, and had passed through all the successive stages of the work, he believed that those men, to say nothing of their thews and sinews, formed a much better class of men than those who were brought up to the age of fourteen or fifteen to hold nothing

heavier than a slate pencil or a pen. It was the constant wielding of their mining implements, and the skill acquired in setting timber, that made men cool afterwards and prompt to assist one another, and to act in such a way as might tend to reduce the number of accidents occurring from falls, somewhat in the same proportion as that in which they had been happily reduced, in other branches of mining over which scientific agencies could exercise a greater control. Sir Warington Smyth.

Mr. A. R. SAWYER proposed, owing to the great amount of matter brought forward, to confine his observations to a few points only, namely, those to which he had lately given his greatest attention. As the Author had been good enough to allude to his book on "Accidents in Mines arising from Falls of Roof and Sides," he might be permitted to read a few lines from Chapter IX. of the book, pp. 97-98, which were of importance at the present time, when special rules were being made under the new Coal Mines Regulation Act:—"From many years' observation of the nature of accidents from falls of roof and sides, the writer is of opinion that the best way to reduce the number of these accidents is to establish rules for timber setting at every colliery, prescribing definite maximum distances, and other matters in connection with timbering and packing. All rules in connection with timbering must be based on the method of working, the nature of the roof and the inclination and thickness of the seams. These differ considerably, even at the same colliery, and at times in the same seam. These rules should be made by the manager, to the best of his ability, in conformity with the experience which he gains of the seam, and should be liable to alteration at any time in accordance with altered conditions or evidence of insufficiency. The enforcement of such rules would not only ensure regularity, but would indicate to fresh workmen the best and most approved manner of keeping themselves safe in seams in which they may perhaps have had no experience. Only maximum distances can, of course, be prescribed. It will frequently be necessary to set timber over and above the requirements of the rules. The erection of these additional supports must be left to the discretion and judgment of those immediately employed, who alone are cognizant of the momentary changes which the roof and sides present." It was therefore most important, as the Author had pointed out, that the men should be properly trained in the operations of timbering, and it was with a view to assist them in acquiring information, bearing on the subject, that he brought out the book. As many men, however, and these often well qualified Mr. Sawyer.

Mr. Sawyer. men, had been killed by falls owing to over-confidence as from ignorance, and he thought that such rules would restrain the over-confident, as well as instruct the inexperienced. If rules were thought too binding, the requirements might be presented in the form of advice, as had been done at the Dukinfield and other collieries. He thought it was idle to try to establish a connection between barometrical variations and colliery explosions. He was perfectly satisfied that a barometrical depression would cause gas to issue out of old workings containing it, but the gas need not necessarily be ignited, and so no explosion need follow. If, as used more generally to be the case formerly, this gas had to pass over a furnace, and was not sufficiently diluted by mixing with air before reaching it, an explosion would certainly ensue; so that the connection which it was sought to establish was dependent on another factor, namely, the presence or absence of flame. Two explosions, the causes of which he had had to inquire into, occurred at the same colliery within a short space of time from that very cause. A dumb drift was then constructed; and although gas still flowed out of the old workings invariably with a descending barometer, no explosion had since taken place, nor could any take place. Many explosions were due to causes which would have existed under any barometrical variation. Approaching barometrical depressions were soon detected by observant firemen, as outflows of gas were sure to show themselves at some point or other in most collieries, if not before, at least quite as soon as any barometrical indication. At some collieries the men were withdrawn when a barometrical depression reached a certain point. The quantity of air passing through the workings should possess a sufficient margin to cope effectually with an increased quantity of gas due to barometrical depression. He had noticed that some explosions, presumably caused by a blown-out powder-shot, had occurred when the barometer was very high and the thermometer very low. In a Paper on "The temperature and moisture of air-currents in Mines,"¹ he had pointed out, from observations made at the Dukinfield and other collieries, that the difference between the quantity of vapour in a cubic foot of air on the surface and in the return was greater the lower the temperature was on the surface, and he thought that on very cold days the air, by taking up moisture during its passage through the mine, owing to its temperature being raised as it proceeded

¹ Transactions of the North Staffordshire Institute of Mining and Mechanical Engineers, vol. viii. p. 8.

along the workings, might have a drying effect on the coal-dust Mr. Sawyer. and make it more susceptible to ignition by the flame of a blown-out shot. With regard to the supposed great sensitiveness of the Mueseler lamp, he would say that the Mueseler lamp was much liked by those who had become accustomed to its use, and the men who had once become accustomed to it were as wedded to it as they once were to the "Old Davy." This lamp could be tilted long enough to examine the roof by without being extinguished, and if preferred, he had found Mr. Brooks' reflector a convenient and effective adjunct for that purpose. He invariably carried his own Mueseler lamp during inspections, and had seldom known it to be extinguished under ordinary circumstances even in steep mines, although once in his hand he did not give it any further thought. The proper handling of it became instinctive. As a rule, especially in fiery mines, even Mueseler lamps should be bonneted, but the bonnets should be easily movable to facilitate an examination of the gauze by the fireman. With reference to lamp glasses, experiments made by Mr. Haines, Assoc. M. Inst. C.E., Secretary of the North Staffordshire Institute of Mining and Mechanical Engineers, and himself, showed that a cracked glass was not necessarily unsafe. In several of these experiments the lamp glass was cracked by the gas flame, which continued to burn within the lamp without any bad effects. Even where these cracks extended to all parts of the glass the pieces were kept in their places by the top and bottom rings, and in no case allowed the flame to pass, showing the necessity of well-fitting top and bottom rings. Though these experiments were reassuring, as showing that no immediate danger was to be apprehended from a cracked glass, especially when the crack was a perfectly vertical or diagonal straight, clean fracture, yet the moment a glass cracked the light should at once be put out, as a piece of the glass, if detached by a three-cornered crack, might fall out by a subsequent knock on the lamp. In these experiments lamps were also tilted at an angle of 45° . In the Marsaut and Clanny, with an ordinary flame, the glass cracked after from thirty seconds to one minute, whilst the Mueseler was extinguished before this could occur, which spoke in favour of the Mueseler type of lamp. With regard to the clause, in the new Coal Mines Regulation Act, concerning the conditions which shall determine the safety of lamps, he believed it would be found in practice to meet all the requirements of those who would have preferred a more specific prohibition of certain lamps. The sense in which it was understood in his neighbourhood was all that could be desired, and these

Mr. Sawyer. unprotected lamps were rapidly disappearing in all fiery mines. The safety of an unprotected gauze lamp, when it was carried against an inflammable current of the smallest velocity, depended entirely on the rate at which the person who was carrying it was travelling, and this varied much and could not be regulated. An explosion occurred very recently which was attributed to a Davy lamp, which was being carried by a collier, who was hastening in a direction contrary to that of an inflammable current, which at that place had a velocity of only 2 feet per second; so that this showed that an unprotected gauze lamp might not always be safely carried in an inflammable current of even the smallest velocity. He had made a Table, showing graphically the different sizes and shapes of "blue caps" produced by different percentages of gas in the air, and this was now put up in a conspicuous position at most of the North Staffordshire Collieries, and was serviceable in educating firemen and colliers with regard to the importance of even small caps. With regard to coal-dust; the explosion which fully convinced him that coal-dust, with possibly the faintest trace of firedamp, was sufficient of itself to cause an extensive explosion, through ignition by a badly-placed powder-shot, was the one which occurred at the Great Fenton Colliery in 1885. It was fully described in the Inspectors' Reports for that year. He had made numerous experiments with the water and the gelatinous-cartridges, and placed the result of his observations before the North Staffordshire Institute of Engineers so recently,¹ though these experiments began in May 1885, that it would be better for him not to discuss their merits again on the present occasion. He had come to the conclusion that if properly manipulated they were perfectly safe, but he thought it important to warn firemen and shot-firers that much depended on themselves to ensure perfect safety, and that this warning would become the more necessary later on, when the novelty of these cartridges had worn off, and when from their introduction fewer explosions occurred, thus having the effect of lulling them into a false sense of security. He saw these cartridges in use in the mines of North Staffordshire almost daily, and they had now been in use some years, with the satisfactory result that for that time such a dangerous coalfield had been exempt from explosions. The manner in which the gelatinous compound of Messrs. Heath and Frost's cartridge was blown out with a blown-out shot was interesting. From microscopical examinations made by Mr. C. M. Stuart, Fellow of

¹ Vol. viii. p. 266 *et seq.*

St. John's College, Cambridge, it appeared that the front portion Mr. Sawyer. of it was honeycombed with bubbles of hot gases, and was much dispersed or spread, but some portion of it, presumably from the back of the cartridge, was evidently only sucked out in small lumps, without spreading. It would be well to know whether, by the hot gases being so subdivided, much the same result was not obtained with this compound as with moss. A number of experiments which he had made with it pointed to this conclusion. With regard to the lime-cartridge, he would bring forward the experience gained by Mr. Bridgett, Manager of the Chatterley Coal and Iron Co.'s Collieries at Bucknall, which he could fully corroborate from personal and frequent observation. The Author had referred to the variable thicknesses and inclinations of the seams of coal in North Staffordshire. The Bucknall Mines had an inclination of 30° and a thickness of from 4 feet to 5 feet. Owing to their being in part extremely fiery, powder had been entirely dispensed with by Mr. Bridgett, and he had found lime-cartridges particularly suitable for getting the coal. Since the introduction of the high explosives with their safe surroundings, he had adopted them in one of the seams which was a particularly difficult one to get with lime, owing to the coal adhering strongly to the roof. In an ordinarily dry mine he had never heard of any complaints from handling the coals with the slight deposit of hydrate of lime, but the falling of the coal was accompanied by the distribution of some portion of it in the air in the form of fine dust. This was only a slight objection in a well-ventilated mine in which it was immediately carried away, but if the ventilation was defective it might remain suspended in the air for some time, and that was objectionable. He believed a person might be killed by the discharge of a blown-out lime-shot if he stood immediately in front of the hole after the lime was wetted. The dangerous moment was from one minute to two minutes after the lime was watered; if the stemming was strong enough to hold the lime then, it would hold it during the whole of the time that the action was going on. The heat produced during the slaking process was no doubt very great, but it was hardly sufficient to ignite gas. He had himself charged a hole in a very fiery colliery, with gas abounding in the place, without its being ignited, and this confirmed the Author's view of the matter. The cost of the lime-cartridges as compared with the new cartridges was found to be slightly less, when the greater amount of round coal produced was taken into account. In steep mines the districts were more circumscribed than in flatter mines, and as

Mr. Sawyer. the new cartridges required special persons to charge and fire them safely, and in some cases even to make them up at the face, more men would be needed for that work ; whilst with the lime-cartridges, which were manipulated by the stall men themselves, the cost entailed by special shot-lighters was dispensed with. Comparing the lime-cartridges with explosives generally, there was a constant temptation with the latter, as Sir Warrington Smyth had pointed out, to neglect the holing and cutting of the coal. It was sought to make the explosives do what should be done with the pick. This at some collieries conduced to make the men slovenly in their work, and it was from this cause that so many explosions had occurred from badly placed and fast shots, as he had pointed out lately in a Paper on blown-out shots.¹ With lime-cartridges there could not be such a temptation, as it was absolutely necessary to properly cut and hole the coal if it was to be removed by that means. In some seams it would then be found that, if properly cut and holed, the coals would come down without the intervention of the lime. Many accidents had occurred almost immediately after a shot had been fired, the roof or side having been shaken by the concussion of the explosive, whereas if the lime-cartridge had been in use, the piece of roof would, probably, have kept its place long enough to enable the workmen to remove the coal and set the necessary props. With explosives, props were also frequently knocked out, which was seldom the case where lime-cartridges were used, and this was particularly important with a bad roof. Danger from missed shots with explosives could occur from two causes : (1) where the mode of lighting the charge was by means of a fuze there was danger from returning to the shot too soon ; it was well known that a shot might go off from twenty to thirty minutes after it had been lighted, and it was also asserted that a shot might go off after a much longer delay ; and (2) all missed shots, whether lighted by means of a fuze or by electricity, were dangerous owing to the charge being necessarily and rightly left in the coal, according to the Act, until it was blown down by another shot, and then recovered by breaking up the coal. Where high explosives were used, a blow on the detonator might cause the charge to explode, and in the case of powder a spark produced by the tool might cause it to explode with fatal effects to those engaged in the work. An instance had occurred to his knowledge in which a powder-shot

¹ Transactions of the North Staffordshire Institute of Mining and Mechanical Engineers, vol. viii. p. 209.

missed fire, and the piece of stone which contained it was displaced Mr. Sawyer. by another shot. Whilst this piece was being split up the powder exploded and killed the unfortunate workmen. These were accidents which of course could not occur with lime-cartridges. He had recently made several experiments with Mr. Mould's patent coal-getter. There was no time to describe its construction further than to say that it was a hydraulic machine, the water necessary for its action being contained in the machine itself, and that, contrary to other such machines, its action was outwards. The experiments which he had witnessed had been satisfactory when the getter was properly applied, and he believed that the principle of its action was the right one. He considered it very important that none of these safe methods of removing coal should be discountenanced in any way, and that no one should be deterred by the difficulties which the want of practice in the first instance necessarily entailed, as these difficulties were frequently overcome by further experience. With regard to the prevention of explosions, he was particularly anxious that the lime-cartridge and mechanical coal-getters should receive all the encouragement possible, as they were absolutely safe. The high explosives, with their safe surroundings, though perfectly free from danger when properly used, were more or less dependent on human treatment for their safety, and though he was quite satisfied that the risk of an explosion was very greatly reduced where they had taken the place of powder, it would be desirable to have some other method of coal-getting to resort to, in case future experience were to show that these cartridges failed either from misuse or from a neglect of the ventilation, owing to a belief in their infallibility under any conditions. In conclusion he would express his sense of the indebtedness of the mining community to the late Royal Commission for its very arduous labours, and to the Author in particular for his valuable communications. The steadily diminishing death-rate in the North Staffordshire coalfield from one hundred and three persons killed in 1880, to twenty-six killed in 1886, could not but have been promoted by the stimulus given to the question of safety by the Commissioners' labours, and they were sure to bear still further fruit in future.

Mr. A. GILES, M.P., hoped it would not be allowed to go forth Mr. Giles. from the Institution that its members advocated the employment in mines of boys under twelve years of age. It would be remembered that an Act of Parliament was passed last session providing that no boy under the age of twelve should be allowed to go underground.

Mr. Bedlington.

Mr. R. BEDLINGTON said that some explosions might be due to other causes than those that had been mentioned. He remembered a case of several men timbering during the night, and a fall ensuing while they were at work, the concussion put out their lamps. The fireman coming up found the heading full of gas. He turned on one side and waited for some time, and then the gas disappeared. He went up to the men who were in the dark and found that there was no appearance of gas. If there had been an explosion in that case there would have been nothing to show how it occurred. He remembered another case in which there was a rupture making an opening in the floor. The gas came from the seam below in large volumes, and overcame the ventilation for a considerable time, but after a while the issue of gas ceased. So in many cases it was difficult to account for explosions that took place. There might have been a sudden emission, but there was no subsequent appearance of gas. As shown in the Paper the loss of life from explosions was 23·57 per cent.; and although the source of only one-fourth of the total loss of life, public attention was drawn much more to this class of accidents than to others, because of the great number of lives lost at one time. When an explosion took place the proportion burned to death was very small, seldom reaching 10 per cent. The great loss of life was due to suffocation. This arose from the air-doors being smashed, and the course of the ventilation being stopped through the greater part of the workings, the air taking the shortest course to the upcast. Where fans were used, they should as far as possible be fixed in positions that would not be affected by the rush of air after an explosion. In several cases they had been so damaged as to be useless for some time after an explosion. With ventilating furnaces the ventilating power was not much affected by an explosion. Assuming that the ventilating force was continued, the weak points were the air-doors. To lessen the risks from suffocation after an explosion, it appeared to him that the following arrangement might be adopted. Let the return air-way be at the top of the range, and the system of ascensional ventilation be carried out as far as possible. The splits of air should be as numerous as the total volume would permit of, so that each split was sufficient to properly ventilate the area assigned to it. The coursing of the air would then be as followed:—Passing from the downcast along the intake, No. 1 split would be coursed through the panel, or district, it had to ventilate, and then pass into the return air-way on the rise, the quantity allowed being regulated by a wall near the entrance to the return, strongly built in mortar, with an open-

ing of the proper size. The same thing should be done with the other splits. If an explosion took place in No. 1 split, and if the doors were broken within that area, the air would still pass through in the most direct course, and would continue in the other districts. At present, when an explosion took place, nearly all the ventilation was cut off from the workings owing to the smashing of the air-doors, and so the men were suffocated. In many cases the men were able to run some distance, but at last they dropped down. He was not yet convinced that dust alone would cause an explosion. If it did, explosions would be very frequent; but without contesting the matter he allowed that where much dust was about a gas explosion was aggravated by it. It was therefore desirable that the dust should be damped, and also for the reason that it was so injurious to health to breathe it. The temperature of the mine also would be cooled by the damping. A good system had been adopted of laying pipes from the pumping lift, along the level headings into the working places, with fine sprays at the requisite distances. The dust was thus damped and the temperature reduced continually without attendance. No doubt there had been many improvements in safety-lamps, making them safer in strong currents; but he thought that the electric lamp, such as Swan's, Pitkin's, &c., would be the safest of all to work by. At present they were heavy and expensive, in future he trusted these objections would be modified; yet the Davy lamp would be generally used for examinations by the firemen. The greatest loss of life arose from falls of roofs and sides, being 40·77 per cent. In the South Wales coal-basin there were dangers in working coal which were not met with, or not to such an extent, in other districts. He thought the roofs there were generally weaker than in most districts. The slips in the coal ran into the roof, and so caused a continuous break. Slants, threads, bells, and large nodules of ironstone also occurred. The principal seams of coal in South Wales ran up to a thickness varying from 5 feet to 9 feet, and the thicker the coal the more danger there was in working it. This was especially the case where the seam consisted of two or more veins with partings of shale. As the collieries became deeper the pressure increased, and it became more difficult to support the roofs, &c. The only means that could be adopted were careful timbering, double timber and props, with close packing of goaves to sustain the roof, holing props where the coal was being holed, and props against overhanging parts of the coal. The question of timbering had been well considered by the managers and workmen in Wales, and their opinion

Mr. Bedlington.

Mr. Bedling- generally was that it was best for the collier to timber and secure his working place, and not depend on deputies. Such was the evidence before the Royal Commissioners. A collier was always present during the working hours, noticing the varying condition of his working place, and could promptly do what was necessary to make it safe. Of course for general repairs timberers were kept. It was surprising that so much as 35·66 per cent. of the loss of life was due to miscellaneous causes. Overwinding was of rare occurrence at the Welsh collieries, and great credit was due to the enginemen. At some collieries the appliances for the prevention of overwinding were fixed, but a majority of the managers thought it was best to depend on careful men, good machinery, and brakes. It was hardly necessary for him to speak of the great importance of good ropes, with a great margin of strength. Of late years mechanical haulage had been largely adopted, and there was now more liability to injury of persons than when the slow haulage by horses was employed. The man-holes, or refuges, were now 10 yards apart, instead of 20, and therefore it was hoped the danger would be lessened.

Mr. Combes. Mr. EDWARD COMBES, C.M.G., wished to point out a class of accident to which no allusion had been made either in the Paper or in the discussion, and his object in speaking was simply to invite the attention of the Author to the subject. In goaves or old workings large volumes of carbonic acid gas, or choke-damp often accumulated, and when any extensive fall of the roof took place, this deadly agent was, sometimes, by the consequent compression of the air, forced into the workings with fatal results to the miners, who were immediately suffocated. In some Australian mines, where no firedamp existed, this had been a fruitful source of accident, and had several times come under his notice. The question, he was aware, was one of ventilation; but it was rather a difficult one, inasmuch as with a rolling floor in a worked out part of the mine, the levels would vary so much, that in the lower portions the heavy choke-damp would find space in which to accumulate. Even when completely isolated, unless the brattices were made exceptionally strong, a heavy fall might cause sufficient pressure to blow them out and force the gas to positions where men were employed. This danger would escape the notice of any Government inspector. He therefore endorsed what Sir Warrington Smyth and others had said with regard to the constant and careful inspection by responsible employees of mining companies, as affording better protection than the periodic inspection by Government officers.

Mr. Seymour. Mr. GEORGE SEYMOUR said he wished to speak rather as a

metalliferous than as a coal-mining engineer. Although the Mr. Seymour. Paper, on which the discussion was founded, was in every respect an admirable one as regarded accidents in collieries, the Author had, after all, only taken one side of the question, since he had made no allusion to the frequent accidents and grave loss of life which occurred from time to time in metalliferous mines. It was, of course, true that the number of men employed in the latter amounted to but a fraction of those employed in collieries, and that consequently the output from coal-mines was vastly greater; but, nevertheless, metalliferous mines had in days past contributed enormously to the wealth of the country, and still continued to do so, notwithstanding foreign competition; whilst the value of the metallic, as compared with the carbonaceous products, was in itself to a certain, although limited, extent an equalizing factor as regarded the relative importance of the output in such instances. The accidents in coal mines were, consequently, to-day, ton per ton, far more numerous than in metalliferous mines; but a hundred years ago this was not the case. The proportion of accidents in 1886 in English coal-mines from falls of rock was 48 per cent., and in metal mines 32 per cent., so that, after all, the difference was not very great. Falls of roof in collieries were naturally more numerous than in metalliferous mines, since in the latter instance the workings were more or less vertical, whereas in the former there was what might be termed an almost constant horizontality of roof, and consequently a greater natural liability to falls, attended frequently by most disastrous results. Whilst, owing to the generally vertical character of the workings, and the greater hardness and cohesion of the rock, such accidents were rarer in metalliferous mines; still they were not of unfrequent occurrence, and a few years ago four men were killed in Cornwall through an enormous rock falling upon them in the "winze," or underground shaft, in which they were working. The most fertile causes of accidents in metalliferous mines were, however: 1. Explosions, due to carelessness in tamping or injudicious handling of explosives; 2. Falls from ladders or man engines. The latter cause was one which rarely occurred in the deep American mines, owing to the custom almost universally prevalent in that country of raising the men by mechanical means. It should, however, be borne in mind that the workings in this case were planned and laid out *ab initio*, with a view to this method of development; whereas in the Cornish mines, many of which had been worked for centuries, the tortuousness and irregularity of the shafts rendered such a mode of haulage impossible, whilst the expense of

Mr. Seymour. sinking perpendicular shafts through hard rock to a great depth could not reasonably be entertained. It was not an unusual thing for a Cornish miner to walk 5 or 6 miles to his work, climb down from 300 to 400 fathoms on ladders, work an eight-hours' shift on a close end, and then climb back to the surface, carrying a heavy load of tools to be sharpened. Under these circumstances, the frequent occurrence of accidents of this description was not a matter for surprise. So long, however, as the present system remained, such accidents were inevitable. As regarded accidents in collieries, he would express his opinion that it was quite unnecessary, as contended by Mr. Morgans, that in order for a lamp to be safe, it should be able to withstand the velocity of current produced by an outburst of gas. Should such extreme safeguards be insisted upon, in all commercial undertakings, there would be a serious limit to enterprise. Seldom, if ever, had an explosion taken place when safety-lamps were used at the point and at the time of an outburst. In order to get an explosion with a safety-lamp—say such as Mr. Bainbridge had described—in the immediate vicinity of an outburst, three conditions were indispensable: 1. The outburst; 2. An explosive atmosphere caused by the explosion; 3. A lamp in the exact position where the speed of the expelled gas would strike it with velocity greater than 30 feet per second. It was exceedingly improbable that a combination of such conditions would occur simultaneously; and if colliery managers were expected to anticipate such coincidences, their attention would have to be diverted from objects far more conducive to the safety of the men and material under their charge. In conclusion, he wished to remark that, although the Author had devoted several pages to the question of gas-indicators, experience had demonstrated that these were of but little practical use. The inspection of all fiery mines was now virtually continuous, and the true check upon danger was such a constant examination of the different parts of the mine, as would render the existence of a small quantity of gas in any particular locality of very little if of any importance. The manager of the fiery mine would watch not so much for the returns which carried away the gas yielded by the mine, but would aim, by constantly and vigilantly watching the working faces, at conveying such a regular and sufficient current of air round the faces in question, as would cause the returns to consist of air containing a safe and regular quantity of gas.

Mr. Harries. Mr. HENRY HARRIES said that the Author had stated, that the Royal Commission had come to the conclusion that no general connection had been established between colliery explosions and

barometric changes; but in the preceding paragraph of the Paper, Mr. Harries. and in two or three other places he had observed that a fall of atmospheric pressure might be attended by an escape of gas to a dangerous extent. The discrepancy was only another instance of the differences of opinion existing on the question of the emission of firedamp in connection with barometrical fluctuations. Although, however, there was some confusion on the question, it would be conceded that the vast majority of both miners and the general public had great faith in the idea that explosions were experienced only with a low barometer. He had carefully examined the occurrence of explosions in connection with weather changes, not dealing with the variations at individual stations, as had been the custom hitherto, but taking into account the distribution of pressure all over the country and throughout Western Europe. He had taken European and American explosions, and instead of finding that they were experienced only with a low barometer, he had found that they seldom occurred at such times, but mostly under opposite conditions. A great deal of the prevalent opinion was due to the practice of newspaper reporters and writers, who appeared to be imbued with Mr. Buddle's opinion with regard to explosions, and generally ascribed disasters to a deficiency of pressure, whereas a little enquiry would disclose the facts to be otherwise. That, however, was not peculiar to this country, for he found in a leading French coal-trade journal the statement that firedamp explosions were almost invariably coincident with a marked diminution of pressure. A disastrous explosion at Quaregnon, near Mons, in March last, was commented upon in the Belgian press as having taken place with a very low barometer. Mr. Lancaster of the Brussels Observatory took up the question, and pointed out, in *Ciel et Terre*, how misleading the newspapers were upon the subject. The explosion was one of a series which took place during the passage of a large anti-cyclone from the Atlantic. The first explosion was in the Rhondda Valley on the evening of February 18th. Then on the arrival of the anti-cyclone in the south of France on February 23rd, there was the Riviera earthquake. On the morning of March 1st, when the centre of the anti-cyclone had reached Central France, the Chatelus mine, near St. Etienne, exploded, and ninety lives were lost. Then, moving northwards, the anti-cyclone was directly over the district where it was stated in the Belgian press that the barometer was low, whereas it was about 30·5 inches. It was not until a week afterwards that the barometer descended at Brussels to 30 inches. The Author had given a list of the principal explosions that had

Mr. Harries, taken place in the eleven years 1875–1885. Mr. Harries had gone through the list with the distribution of pressure for each day, and he had found that instead of following what was supposed to be the general rule, only six out of the thirty-two had taken place when the barometer was at 29·5 inches or below; in other words, only 18·75 per cent. occurred with a low barometer, while the deaths in the same amounted to 17·4 per cent. of the total loss. Even out of the six with a low barometer it was observable that three occurred when the barometer was rising rapidly. On the occasion of the great disturbance in January 1884, the barometer had risen 0·75 inch in twelve hours, when the Naval Steam Coal Colliery at Penygraig exploded, another, but slight, explosion taking place on the following day at Rowley, the mercury still rising. With the remaining twenty-six disasters the barometer ranged between 29·8 and 30·7 inches. Time did not permit of his entering fully into the details of each explosion, but he might mention that in the present year, when the Walker Colliery accident occurred, five weeks ago, the barometer was at 30·3 inches and rapidly rising. The Udston explosion, in another anti-cyclone, had been heralded during the increasing pressure by less disastrous accidents at Darcy Lever and Wigan. Last year three out of the four principal cases took place under similar conditions. The Pochin accident in 1884 occurred when the barometer was at 30·3, and on the next day in Belgium, when twenty lives were lost at the Wasmes mine, the barometer was at 30·4 inches. In the Leycett explosion of 1880, the barometer was at 30·65, at Seaham it was at 30·1, at Penygraig, December 1880, 30·4, and at Mardy at 30·7 inches. The increase of pressure which set in at about midnight of December 3rd, 1875, was accompanied by the New Tredegar explosion on the 4th, the Llan on the 5th, and Swaithe Main on the 6th. There did not appear to have been any disaster with the exceptionally low pressure of December 1886. Miners were after all but human, and, if they believed that accidents could only occur at certain times, they were apt to think that at other times they could do very much as they liked in spite of all regulations to the contrary. He had endeavoured, in a communication to *Nature* on the 8th of September last,¹ to explain this frequency of explosions with the prevalence of anti-cyclonic distributions of pressure, by the production of evidence from independent sources, showing that the enormous changes in the weight of the superincumbent atmosphere caused a straining

¹ Vol. xxxvi. pp. 437, 438.

of the earth's crust, to such an extent as to favour the issue of gas Mr. Harries. from the strata at a time when, theoretically, the escape of gas should cease. Professor G. H. Darwin had calculated that, with a range of 2 inches of barometric pressure, the surface was from 3 to 4 inches nearer the centre of the earth when the mercury was high than when it was low; but in the past few years the range of the barometer in this country had been close upon 3.75 inches, so that the level of the British Isles would vary by about 7 inches. It would be absurd to contend that a fall of the barometer did not affect the gas in goaves and waste places; the knowledge of the fact secured careful attention in almost every mine, and this might account for the small number of explosions which took place with low pressure. The worst disasters were those which occurred when the danger was least expected, and if the perusal of these observations could lead to a more careful study of the subject, and tend to reduce the liability to explosions, the time devoted to the present discussion would have been well spent. His remarks on the coal-dust question would be very brief. Much had been said on the subject in recent years, and all agreed that if the dust was an agent in explosions, it was most dangerous when it was driest. This being so, the question resolved itself into a consideration of the hygrometric condition of the atmosphere. Professor Lupton's remarks forcibly illustrated this, the moistening of the dust being comparatively easy in the warm atmosphere of spring, summer, and autumn, but very difficult in the cold dry air of winter. In Mr. Sawyer's Paper on "The Temperature and Moisture of Air-Currents in Mines,"¹ it was shown that dry and dusty mines were drier, and the dust more inflammable, on cold days than on warm days; and, where blasting operations were permitted, the experiments accounted for the increase in the number of explosions in the winter months. Now, a dry atmosphere, when it was most difficult to damp the dust, was a characteristic of anti-cyclones, and rendered the dust inflammable. Cyclones were accompanied by an excess of moisture in the air. This was an additional reason, therefore, for paying more attention to periods of high barometer than had hitherto been thought necessary. Taking all the explosions, great and small, it seemed that at least 75 per cent. took place with a high barometer, but he did not say that they were directly due to it.

Mr. WILLIAM COCHRANE wished to state the result of experi- Mr. Cochrane.

¹ Transactions of the North Staffordshire Institute of Mining and Mechanical Engineers, vol. viii. p. 8.

Mr. Cochrane. ments with which he had been connected in 1875 and 1876, when the first steps were taken in this country, after certain indications given by Mr. Vital in the "Annales des Mines," that small coal-dust, *per se*, was explosive without the possibility of admixture with carburetted hydrogen. Probably everyone would be impressed by the perusal of the Paper with the idea that a slight admixture of firedamp was necessary for an explosion. He did not know what would be called an explosion, but if, as in an experiment which he conducted with Professor Marreco, in January 1876, in the laboratories of the Physical Science College at Newcastle-on-Tyne, a detonation and the projecting of two small cast-iron weights from the top of a model drift, one going uncomfortably near his head, and the other across the experiment room, were to be called an explosion, it certainly took place, with the use of coal-dust alone, there being no possibility of having gas anywhere near where they were operating. A Davy lamp gauze formed the roof of the model drift, on which the dust coal was placed, a small Guibal fan supplied the air-curret, and by rapping the side of the model drift the coal-dust fell, and a small pistol was fired into the drift. The result was an explosion, which ripped up the model and destroyed the Guibal ventilator employed to maintain the air-current. That showed that there was no necessity for the presence of even the smallest percentage of gas, which had been so much dwelt upon, and which the Author concluded was necessary.

* * * Sir FREDERICK ABEL's reply to the discussion will be found at the end of the Correspondence.

Correspondence.

Mr. Ashworth. Mr. JAMES ASHWORTH remarked that in general arrangement the Ashworth-Clanny lamp was similar to the Clanny lamps he sent to the Mines Accident Commission in May, 1882, known in the report as Clanny's Nos. 17, 18, and 19, which were the first completely shielded lamps tested by the commission; but the details of construction had been so greatly improved, that instead of the illumination produced by the wick flame being respectively 39, 64, and 56 per cent. of a standard sperm candle, the present lamp gave 79 per cent. as tested by Mr. Betley, of the Wigan Mining School. Attached to the screw ring which kept the glass in position, and at right-angles to it, was a thin metallic cylinder