Discussion.

The President. The PRESIDENT, in proposing a vote of thanks to the Author for his interesting Paper, remarked that the subject was one of growing importance. As the cost of labour and the difficulties of dealing with it increased, it became necessary to have recourse in larger measure to labour-saving appliances. As the Author admitted, the Paper did not mention all the interesting elevators and conveyors which were in use. The appliances for dealing with timber, for instance, were almost worthy of a Paper to themselves. In Norway, transporters had long been used for taking timber from the water to the mill. There were endless chains running on rollers in a trough and on an incline which passed just below the water-line, and the logs were floated over the chains, which were furnished with vertical spikes. When a log touched the spikes, its weight ensured a hold, and it was thus hauled out of the water and often transported a long distance to the mill. There were other appliances for stacking and transporting sawn timber, and appliances for getting rid of the saw-dust from the mill. The old plan had been a trough wherein ran an endless chain drawing small boards, which scraped up the saw-dust. The plan now used was to fix below each machine in the mill a hopper connected by a pipe with the chamber of an exhaust fan, which drew the whole of the saw-dust from the mill and conveyed it through the pipe to any convenient place. There it was delivered into that beautiful contrivance called a "cyclone," by which every particle of dust was caused to settle. In addition to appliances for timber, there were appliances for dealing with dredged material, such as the floating tubes used at the Amsterdam Canal, and various other contrivances used at the Suez Canal and the Manchester Ship Canal. He merely mentioned those to show that, numerous and interesting as were the appliances which had been dealt with in the Paper, there were many others which were also worthy of consideration.

The Author. The AUTHOR exhibited a number of lantern-slides illustrating various appliances for the mechanical handling of materials, including the Phillip lighter (*Figs. 41*) for carrying grain and for discharging it, at the rate of 120 tons per hour, to a barge elevator.

Between the double keelson ran a band conveyor 28 inches wide, The Author.
which delivered into the small fixed elevator placed in the stern

of the lighter. Both were driven by electromotors of $6\frac{1}{2}$ B.H.P.
The bottom of the barge was hoppers to save trimming. These

The Author. lighters carried 200 tons of grain, and a fleet of twenty-six brought grain from Tilbury to the Port of London, for the London Grain Elevator Company. He also described the appliances for conveying coke which were in use at the Margate gasworks. An inclined bucket elevator took the coke from the retorts immediately after it was quenched, and delivered it through a push-plate conveyor on to a coke-breaker. The coke next went through a revolving screen, which removed the breeze, and then passed along another push-plate conveyor, either into a series of coke hoppers, for delivery into carts, or to a swinging conveyor which deposited it in the yard. This latter conveyor was 130 feet long and 16 inches wide, and conveyed about 10 tons per hour. It was fitted with intermediate outlets with slides, so that the coke could be delivered at any point.

Mr. Patchell. Mr. W. H. PATCHELL considered that the members were indebted to the Author for having made an addition to the scanty literature of conveying-machinery. As users, if engineers had not had practical experience of their own, they were almost entirely in the hands of the manufacturers; and then the danger was the liability to take the lowest-priced plant, with the result that the wear and tear was found to be extremely heavy. The speeds and other particulars which the Author had given would be of considerable assistance to users; and they would be even more so if the engineer of the Nottingham gasworks could supplement the Table on p. 95 with a few particulars of the sizes of the machinery and the speeds at which it ran. He had had an unfortunate experience with an elevator of the kind illustrated in *Fig. 4*, with a boot at the bottom, and tightening-gear which gave a variable distance between the bottom of the bucket and the boot. When used for ashes or coal, such a contrivance was apt to become clogged; and it would be better to make the clearance at the bottom as small as possible, which meant that the tightening-gear must be at the top, instead of at the bottom. With grain that difficulty would not occur; but with ashes and clinker a sodden mass accumulated in the bottom, which seriously increased the wear and tear on the buckets and chains. The belt conveyor was one of the most fascinating of those which the Author had described. A long belt conveyor at work was a pretty sight; but, when desiring to use a belt conveyor about 500 feet long for delivering at different points along its length, he had considered the arrangement of a throw-off carriage with "jockey" pulleys, and had fought shy of it. For simple end delivery, for which they

were frequently used, belt conveyors ran admirably. In Mr. Patchell's connection with them the question of cost again arose. He had seen a low-priced conveyor in which the belt had given endless trouble by refusing to run straight without a number of guide-pulleys at the sides; and, in addition to pulleys for maintaining the dish of the belt, such as were shown in *Fig. 26*, little pulleys had had to be put on at right angles to those, in order to keep the belt in position. Side by side with that conveyor he had seen another higher-priced belt running practically without guide-pulleys. Those facts showed the necessity for care in the selection of a belt-conveyor. He had tried the trough or tray conveyor, and it was surprising what a difference there was in the wear and tear when the rollers which took the weight of the returning trough—supposing the trough to be returning underneath—engaged on the edge instead of on the flat of the trough or tray. If they were on the edge, the grit from the clinker soon cut a groove through the rollers, like the cutting of an emery-wheel. The conveyor shown in *Figs. 33 and 34* was known to most engineers as the Hunt conveyor, having been introduced originally into England by an American of that name. It was a useful and convenient conveyor if the engineer did not object to putting all his eggs in one basket; the great objection to it was, as the Author said, that if a breakdown occurred it stopped the work completely. The introducers of the contrivance into England had recommended it—and in some cases had used it—to bring the coal in and the ashes out. He thought that plan was open to criticism. It was impossible to get the ash-buckets clean after carrying wet ashes; and to use them in the way recommended seemed like getting the dustman to deliver bread. It would be useful if the Author would state what measures were generally taken for preventing choking in the ordinary form of bucket elevator. In the arrangement with large clearance at the bottom, some such steps must be taken. He had asked several contractors and manufacturers what they were doing in that respect, and at one time he had received a promise that he should be shown an excellent arrangement for preventing the choking. On going to the works he had found a boy sitting on the end of a cask, and holding a stick across the mouth of the boot! He thought manufacturers of conveyors ought to be able to give engineers something better than that.

Sir JOHN WOLFE BARRY, K.C.B., Past-President, asked whether the Author had devoted attention to the shipping of coal-cargoes in large ships, in which matter some arrangement of conveyors was

Sir John
Wolfe Barry

Sir John
Wolfe Barry.

one of the crying wants of the day. The speed at which coal could be shipped depended entirely upon manual trimming; and although special vessels were built, with a large number of hatchways, so as to diminish as much as possible the handling of the coal by men, yet the bulk of the coal was shipped in vessels which were not specially built for the traffic. In such vessels the handling of the coal was a source of expense and loss of time; and if any machinery could be devised which would be suitable to the different kinds of vessels used, and would serve to convey the coal rapidly from the hatchways where it was deposited to the different places between decks, it would no doubt meet an important want. In view of the many million tons of coal shipped every year from England, there was a wide field for any really well-devised scheme for such trimming of coal in vessels; and he would direct the attention of those engineers who had already exercised so much ingenuity in such matters, to that requirement of the present day. With regard to other modes of conveying materials, not touched upon in the Paper, he had one now at work under his direction in Scotland, for dealing with dredged material from a large dock. Instead of excavating in the dry and using tramways or similar appliances for transporting the spoil, the contractor was dredging out almost the whole of the excavation under water, after the construction of the walls; the material was delivered into barges, and from the barges it was transmitted 1,000 yards or more, through large pipes, by means of a centrifugal pump working under pressure. The plan seemed to be highly successful and profitable to the contractor. It was a mode of constructing docks which ought not to be neglected; because, as those who had to deal with such work knew, the great risk which had to be run in constructing a dock occurred while the excavation was being made, and before the water was let in. That mode of dredging enabled the water to be let in immediately after the walls had been built in trenches; and the walls thus had the support of the water while the excavation was being made. The transport was remarkably cheap, and the only thing necessary was that experience which would indicate the amount of power required for breaking up and adapting the material, so that it would pass readily through the centrifugal pumps under pressure. He commended the arrangement to other engineers. One thing about it he did not like, namely, to find that the whole of the apparatus came from Holland, and that British engineers had not been sufficiently ingenious to make it a more regular system of work. Engineers often pumped material through pipes by centrifugal pumps; but

what he had referred to was a systematic arrangement which had been carefully worked out by Dutch engineers, who came over to England and undertook the work there at lower prices than Englishmen could touch. Sir John Wolfe Barry.

Mr. J. N. SHOOLBRED described briefly an installation which performed work somewhat analogous to the loading or unloading of ships, to which Sir John Wolfe Barry had referred. The Doncaster power-station had, on one side, a large Yorkshire canal which could accommodate barges of 200 tons burden, and on the other side a line of rails. It was therefore particularly well situated for supplying the needs of the boilers. In the boiler-house there was a conveyor with a large bucket, by means of which $\frac{1}{2}$ ton of coal at a time could be dipped from the barge and conveyed to any part of the boiler-house, which contained a range of ten Lancashire boilers. By a similar arrangement, coal might be loaded from a lighter alongside a vessel. In the Doncaster power-station, the arrangement was driven electrically, and was controlled by one man, who could see the whole operation. The installation had worked for at least 2 years, and, as far as he could remember, 150 tons of coal were dealt with satisfactorily in a comparatively short time. Mr. Shoolbred.

Mr. H. B. MOLESWORTH remarked that one form of conveyor which he had seen in the United States was not mentioned in the Paper; it was used in connection with blast-furnaces, and saved a great deal of labour. The conveyor consisted of a series of trays with sloping sides, which ran under a ladle; the molten iron was run into the trays, which ran slowly for about 200 feet under jets of water. The pigs were then discharged into a railway wagon, having been cooled in their passage from the furnace. On p. 62 the Author said, "In order to effect perfect discharge, the centrifugal force must be sufficient to overcome the gravity of the material: so that for a specifically heavy material it is necessary to have a greater centrifugal force, *i.e.*, higher speed of elevator, than for a specifically lighter material." This he could not quite follow, and he would be glad if the Author would explain it. The centrifugal force, it appeared to him, was a function of the mass, and not of the density of the body; and, *in vacuo*, bodies travelling with equal circumferential speed would describe similar paths, irrespective of their densities. If the friction of the air were taken into account, a light body, no doubt, would not throw as far as a heavy body. He therefore thought the result would be that for a specifically heavy material a slightly lower speed, if anything, would be required, rather than a higher speed, as the Mr. Molesworth.

Mr. Molesworth. Author seemed to suggest. The means for handling material were often ill adapted to the end. A glaring instance of this was the use of the steam travelling jib-crane in workshops. That crane always reminded him of a boy's knife with twenty blades, etc., which was intended for every purpose. In attempting to open the gimlet, the boy generally broke his nails; and when he tried to make a hole with the gimlet, one of the blades shut on his fingers. The steam-cranes in workshops were like that knife. The average weight of a 3-ton steam-crane, for instance, was about 35 tons, and when under a load it was, to say the least, in a state of unstable equilibrium. The load was frequently concentrated almost entirely on one wheel, and, as could be imagined, a 35-ton wheel-load was destructive to the permanent way. As soon as the newness of the gear had worn off, the crane was nearly always breaking down and needing repair; it covered a large space in moving about, and spent half its time in going back for a fresh load, or carrying a bucketful of ashes.

Mr. Brown. Mr. ANDREW BROWN remarked that, with reference more particularly to coal-elevators and conveyors, he took exception to the Author's remarks as to the necessity of having coal-elevators inclined, and also as to less power being required for driving inclined elevators than vertical elevators. He could not see why, in lifting vertically a load suspended on a lubricated bearing, more power should be required than in performing the same work with an inclined elevator, which must of course be longer and also heavier, on account of the longer chain and the larger number of buckets attached to it. Having regard to the friction at the sides on which the buckets bore, an inclined elevator must require more power than a vertical elevator, for lifting the same quantity of coal through the same height in a given time. With regard to throwing off at the head, no doubt at first sight the inclined elevator was in a better position for throwing into the shoot; but he had found no difficulty whatever in arranging the throw-off of vertical elevators so as to be perfectly clear. The advantage to be reaped in either case was often a question of convenience. In many gasworks and boiler-ranges, the coal was delivered at the side of the building; and then it became necessary, if elevating was to be done, to throw the coal over at an angle, in order to get it into the continuous conveyor which was to deposit it at the various retorts or boilers. If convenience was taken into consideration, he agreed that under these circumstances the inclined conveyor should be used; but he had no hesitation in saying that where coal could be delivered at the

end of a building, and could be thrown directly into the longitudinal conveyor, the vertical elevator was the more easily adapted, because it could be fixed close against the wall, and heavy structures, such as were necessary for an inclined elevator, were not required. With regard to the speed of elevators, it was important that the speed required at the point of throw-off should be known exactly. In *Fig. 4*, the bucket was suspended in the centre-line of the pitch-chain, and as it passed over the sprocket its speed was the same as that of the chain. But in *Fig. 1* the bucket was attached to the outside of the chain, and when it arrived at the sprocket-wheel the mean radius of its path was increased by half the width of the bucket. Thus, if the buckets were 6 inches wide, and the sprocket-wheel 2 feet in diameter, the mean radius of the path of the buckets would be $12 + \frac{6}{2} = 15$ inches; so that the speed at

which the contents were thrown off at the top was here 25 per cent. higher than with such an elevator as was shown in *Fig. 4*, having a pulley of the same diameter, namely 2 feet. The vertical elevator was therefore capable of throwing the coal clear of the preceding bucket, and into the shoot. If the shoot, instead of being so close to the top as it was shown in the diagram, was extended horizontally and then inclined, the coal would be thrown off at the top almost horizontally, and would drop down the shoot. In calculating the speed of chain required to deliver a certain quantity of coal, it must be remembered that if the bucket was suspended on the outside of the chain, as shown in *Fig. 1*, it must be a little larger, and the speed of the chain a little less. With regard to the push-plate conveyors mentioned in the Paper, he did not think all had been said in their favour that might have been said. Such examples as were illustrated in *Figs. 16* and *17* were not altogether suitable for feeding hoppers connected with the stokers of boilers, or the hoppers of gas-retorts; because the return chain ran at the bottom of the conveyor-trough, instead of along the top. Apart from that, the section of trough shown in *Fig. 16* was so shallow that it would scarcely hold sufficient coal. In *Fig. 17* an arrangement was shown which the Author advocated, because it allowed the chain to be as nearly as possible in the centre of the push-plate. He had seen such an arrangement at work; and whenever it was loaded to its full extent the coal jumped over the top of the push-plate, and the arrangement was not effective. Again, the rubbing part shown in the centre was always covered with coal, and did not at all relieve the chain in its course through the trough. In a conveyor erected by him about 7 years ago, he had

[THE INST. C.E. VOL. CLIII.]

I

Mr. Brown adopted the arrangement shown in *Fig. 42*. The trough in which the push-plate ran was flat-bottomed and 12 inches wide, the sides being 6 inches deep. The runners ran upon channel bars 4 inches deep. The axle passed just above the top of the trough sides, the intention being that the wheels should be as low as possible, while a large area was obtained for the coal to travel in. On the boss of each pulley a grease-cap was screwed, which forced the grease on to the axle, and formed a bearing into which coal-dust could not penetrate. The conveyor delivered 20 tons of coal per hour: the pitch of the plates was 2 feet and the travel 150 feet per minute: the total length of the conveyor was 120 feet. It had now been working for 7 years, and the chain had never been off the sprocket-wheels. The amount of wear and tear was very small, and the conveyor was so free from repairing-charges that he thought it compared favourably with the figures given in the Paper. A similar conveyor, 18 inches wide, with the

Fig. 42.

push-plates 21 inches apart, delivered 60 tons per hour. It was 350 feet long, travelled at 150 feet per minute, and had been working for 18 months without any failure. The two conveyors in question had been designed for gasworks, with the intention that they should not work continuously. They worked for 5 hours out of the 24, the one delivering 100 tons and the other 300 tons in that time. The intention was that, when a fresh shift of men came on first thing in the morning, they would immediately fill the hoppers for the retorts; and in the afternoon, before they left, they would put in the supply for the night shift, so that the machines were not worked during the night. In the Table on p. 95, a conveyor which transported coal 30 feet was mentioned as costing £2 9s. 4d. per lineal foot, which meant under £70 for the total cost. But the first cost of that conveyor was given as £296; and he would like to know why the extra £226 had been added. Further, the cost of repairs to the same conveyor was stated at £70 6s. He would like

to know what period of years was covered by that expenditure, Mr. Brown. because it was difficult to understand how the cost of repairs came to be equal to the first cost of the conveyor. Possibly the £226 added in the first instance represented the cost of steam-engines, screens, crushers, and other accessories in connection with the plant. He thought the arrangement illustrated in Plate 2 courted disaster. In the first place, the hopper was shown as standing immediately above the coal-breaker, and there was no indication of any device for intercepting foreign material, such as stone sets, railway brakes, broken wheels, and other things which were found in railway wagons. Unless such things were intercepted, speedy destruction of the coal-crusher resulted. Another essential point was that, before passing into the crusher, the coal should be passed over a grid, which would allow the small coal to drop down to the elevator-boot, and not pass through the crusher at all. The addition of these two details would render more effective the arrangements shown in the diagram.

Mr. S. W. PORTER remarked that when the tightening-gear Mr. Porter. of an elevator for such materials as coal had a range inside the boot at the bottom, the distance between the lip of the bucket and the curve of the bottom plate of the elevator varied. In a good elevator that distance should always be about 1 inch. With a tightening-gear of 7 inches or 8 inches range, a block might be caused by large pieces getting in when the buckets were some distance from the bottom. In order to remedy that, elevators were designed with tightening-gear at the head. They worked satisfactorily until it became necessary to tighten the chains, which had to be done by lifting the sprocket-wheels: the whole of the gear which drove the elevator had then to be adjusted, and probably the positions of the delivery-shoot and the elevator-head had to be altered. He had had experience lately of such elevators, and had found that it was a good plan to have the tightening-gear at the bottom, but, instead of having the wheels rising and falling in the boot, to have the boot itself moving up and down; that was, the buckets at the lip were 1 inch off the bottom plate, the legs were supported by means of brackets from the floor, and the boot was arranged to slide up and down between the brackets. The tension-screws thus kept the chain tight, without altering the distance between the lip of the bucket and the curve of the boot. The buckets of the elevator were continuous. In most coal-elevators the dredging action was a cause of serious wear and tear and waste of power. His practice was to feed the material into the leg about 2 feet above

Mr. Porter. the bottom of the elevator. The buckets were made almost to fit the leg for this distance. The material was fed in gently from the feed-shoot and was deposited straight into the buckets, nothing being allowed to go past to the boot. The running of the bands in band conveyors depended chiefly on their quality. Bands varied considerably, and inferior bands always did run a little erratically; but a band of the best quality, such as was now made with a breaking-stress of 400 lbs. per ply per inch width, usually ran true; because, although a band of that quality stretched to some extent, it did so equally, and the tightening-gear could be arranged to take up the whole of the stretching of the belt, which, wherever possible, was endless. The Author advocated tightening-gear of the weight type, which was necessary when the throw-off was of the swivelling kind shown in *Fig. 23*. When the material had to flow past, it was necessary to have a throw-off of that description; but it was much better, where possible, to have a throw-off with the pulleys fixed, such as was shown in *Fig. 25*. The tightening-gear could then be made with tension-screws, which was by far the best method. With such gear there was a screw on each side; and instead of being pushed, as described in the Paper, the pulley was pulled, the screws being in tension; thus the tightening-gear could be made of almost any length. In practice he had found that about 4 per cent. of the length of the belt was sufficient allowance for the tightening-gear, if a belt of good quality was used. The true running of the belt depended also on the details, which were very important. The feed-hopper, for instance, must be so arranged that the grain or material came almost to rest on the back of the hopper, and then flowed down in a curve on to the band, in the line of travel, without any vertical drop. Further, the rollers must be balanced—an important detail which had not been mentioned. If the various points to which he had referred were attended to, no difficulty would be experienced from a belt not running true. Lubrication was of the utmost importance in conveying-machinery, on account of the large amount of grit and dust attending its working. He had found that thick grease, with automatic drop-pistons fitting into the caps of the bearings, gave the most satisfactory lubrication for the rollers.

Mr. Lockhart. Mr. WM. S. LOCKHART presumed that many of the conveyors described by the Author were for raising wheat. From an engineer's point of view, wheat seemed to have been specially created in order to be raised. Probably the boot with tightening-gear at the bottom was intended for wheat; it could never be cleared

out, but with wheat the buckets could easily be got through. One Mr. Lockhart.
 plan of clearing a boot, which had not been mentioned, was to have one or two of the buckets of the elevator a little longer than the others, so that while most of the buckets worked fairly lightly the larger buckets cleaned up after them. If that was done, the tumbler at the bottom must work on a fixed point; therefore, it would not do to have the tightening-gear at the bottom. On the whole, where it was practicable, it was more convenient to have the tightening-gear at the top. He would like to know if such material as slurry or slimes could be conveyed with a vibrating-trough conveyor. There was nothing so difficult to move, even in a horizontal direction, as slime, unless it was run at a high speed. Even in a pipe it had a tendency to settle and block the pipe, though sometimes flat pipes could be used with advantage. It was so difficult to move slime in a horizontal direction that it was often necessary to hoist it up vertically and let it run down to its destination. The swinging conveyor might yield a solution of the difficulty, because the solid matter, which was exceedingly fine, would be kept constantly stirred while it was travelling. He presumed that such a conveyor could not be used to raise the material uphill, but that it should be inclined slightly downwards. He would like to know whether the conveyor had been used for damp gravel, which was a difficult material to handle. If so, at what angle, according to size, could the gravel be conveyed? Probably when sand was reached difficulties would arise.

Mr. A. R. TATTERSALL remarked that he had seen many of the Mr. Tattersall.
 conveyors which the Author described, at work on various materials; particularly the one advocated for coal, minerals and wet gravel. It had not been at work on an incline, but it had seemed to convey wet gravel successfully; how it would convey slimes he was not able to say. With regard to conveyors for loading ships with coal, he did not see why either the push-plate conveyor or the swinging conveyor might not be fixed to every coal-carrying ship, and serve to load the coal without much expense for trimming. He thought the swinging conveyor, in which the plates could be made with openings, might be applied so that ships could be loaded cheaply. With regard to the cost of maintenance, he had understood, in conversation with the late Mr. Chester, that he had placed the conveyors all on the same footing, namely, on the results of 1 year's work; and that his experience had been that the push-plate conveyor showed heavy wear and tear. At that time Mr. Chester had not made the acquaintance of the swinging conveyor,

Mr. Tattersall. and had been unable to say how it would compare with the others. He would like to see the conveyor referred to by Mr. Brown as having conveyed coal for 7 years without ever having been off the sprocket-wheels: it would be a curiosity. The problem of conveying materials of all kinds in factories must necessarily force itself to the front as the difficulties connected with labour became recognized. In flour-milling it was rare to see the material handled at any stage; even the weighing, he believed, could now be done automatically.

Mr. Apjohn. Mr. J. H. APJOHN remarked that during the past 2 years he had had his attention specially called to the problem of loading coal mechanically. He had visited America twice in order to see what was being done there, and he had also inspected various conveyors at work in England. His experience was that the American systems were a great deal ahead. Nothing could be much better than the English practice of dumping the whole contents of a wagon into the ship, where it was practicable; but where it was not so, the American systems had great advantages. The conveyors described by the Author, which were apparently those in use in England, did not seem to be of large capacity, the speeds being low. In America much higher speeds were used, and thereby a much larger capacity was obtained. At Louisville, Nova Scotia, he had seen a ship loaded with 5,500 tons of small coal in 8 hours, by one belt conveyor giving off to the different hatches at intervals. It was usually worked at about 400 feet per minute, but when pressed the users did not hesitate to work it at speeds up to 700 feet per minute. He had been asked to draw up a scheme for loading coal for a large ship-owning company, and after carefully considering the matter he had decided in favour of an arrangement combining two kinds of conveyors—Brown hoist conveyors and Robins belts. The Brown hoist was necessary for putting the coal into stock, when the ship was not ready to receive it at once. The project he had submitted provided for stocking 50,000 tons of coal: it also provided for taking from stock and putting into the ship; or for putting into stock from the ship; or for loading direct from the wagons into the ship. The combined system provided for loading 400 tons per hour direct from wagons, and 170 tons from or into stock. For trimming in the ship there was an arrangement of scrapers. He had carefully considered the possibility of adapting a conveyor for trimming in the ship, but had found many difficulties. He had adopted a scraper which he had seen in operation in America, which worked very effectually, by electric power, and scraped the coal to the bulkhead.

At Toledo on Lake Erie he had seen a ship being loaded by one Mr. Apjohn. Brown hoist conveyor. The coal was dumped from wagons containing 40 tons of coal, into buckets, each containing nearly 7 tons. The buckets were then lifted, and their contents placed in the ship. One conveyor travelling backwards and forwards served the four hatches of the ship in turn, and put in on an average 7 tons every 75 seconds, or about 300 tons per hour.

Mr. J. W. HELPS remarked that gas-engineers looked forward Mr. Helps. to the perfecting of some good plan of conveying with as much hopeful anxiety as did members of any other branch of the profession. One material had not been considered in the discussion—namely, coke. Of all the materials with which engineers had to deal, perhaps coke was the most difficult, especially hot coke. He had lately been looking carefully into the question of conveying it, had visited several works both on the Continent and in England, and had inspected many different conveyors. Finally, he had advised his directors to put down a push-plate conveyor. He had not had any extensive experience with it, but hitherto he had found it particularly satisfactory, except in one direction: unfortunately it was necessary to take the coke out at the sides of the retort-house and not at the ends; consequently the two conveyors which ran in front of the retorts had to discharge their coke on to a transverse conveyor, which had then to elevate the coke to the hoppers. Severe wear and tear took place at the point where the transverse conveyor left the horizontal and assumed an inclined position; and he had had to renew the wearing strips within 3 weeks of putting the machinery to work. One speaker had expressed the opinion that it was a mistake to deliver into a boot, and then allow the elevator to scrape the material from that boot. He entirely agreed with that opinion. He had visited a works some time ago where the cross conveyor delivered directly on to the buckets of the elevator, and he had been told that the amount of breakage to which the coke was subjected—which was an important matter—had been diminished to a large extent by doing away with the boot, and by adopting the system he had mentioned. He could not help thinking it was a step in the right direction to do away with the boot, which ground up the coke so much, and to deliver directly on to the elevator.

Mr. APJOHN stated that in America he had seen coke carried Mr. Apjohn. very successfully by belt conveyors.

Mr. F. E. DUCKHAM observed that, although it was advisable to Mr. Duckham. use machinery wherever possible, the question whether it was

Mr. Duckham. advantageous or not to do so must always be considered. If a large capital outlay had to be made on a machine which was used only occasionally, that machine, however efficient, might not be worth the money expended on it. Moreover, for different materials different machines were necessary. Three or four different plans of conveying material were in use at the Millwall Docks. The oldest machine was used for conveying dredged material from a dredger to a point on land about 300 yards from the water-side. The dredged material was put into a tank, and air at a pressure of 20 lbs. to 25 lbs. per square inch was used for forcing it through pipes on to waste land. That process had been carried out successfully for the last 20 to 30 years. It was also necessary to convey timber from the water-side to a point 300 yards to 500 yards away from the quay. For that purpose conveyors like those to which the President had referred had been adopted. He had visited Norway and Sweden 3 years ago, for the purpose of inspecting such machinery, and seeing if it could be adopted at the Millwall Docks; and eventually he had come to the conclusion that it was admirably suited for the work. At Millwall the barges containing the deals were brought alongside the quay; at the quay-side there was a staging upon which were mounted four pairs of endless chains, which had dogs attached to them at intervals of about 6 feet. The men in the barge put a deal on to a pair of hooks, and each pair of travelling endless chains took up the deals one after the other, at the rate of about six per minute, to the top of the gantry, where they were tipped into a trough, in the bottom of which were a number of rollers revolving at about 120 revolutions per minute. On these rollers they were carried to the other end of the line or deposited immediately, as desired. The motive power was electrical. Lastly, grain had to be lifted and conveyed. For lifting it out of ships, the pneumatic elevator was undoubtedly the most suitable arrangement. It not only lifted the grain fairly cheaply, but it had also the advantage that the grain could be collected from the different parts of the ship without the expense of trimming. Trimming into the hatchways cost 2*d.* to 4*d.* per ton, which amount was saved by carrying the suction-pipes of the machine to any part of the ship where the grain was, and so collecting it and bringing it to the elevator itself. But the pneumatic elevator was not suitable for every purpose. For lifting from the ground to the top of a granary it was not better than the ordinary grain-elevators described in the Paper. The Millwall Docks were now being equipped with a granary

which would have a capacity of about 150,000 quarters, and a Mr. Duckham. loading capacity of about 300 tons per hour. The work would be done by four pneumatic elevators taking the grain out of the ships, and by four horizontal band-conveyors taking it thence to the shore. When it was ashore, the lifting into the granary would be done with machinery of the ordinary kind, and the distributing by pipes which conducted the grain into the different floors. The granary had a floor-area of 7 acres, and, by diverting the flow of the grain, any part of the building could be reached.

The AUTHOR, in reply, said that the tightening-gear was un- The Author. doubtedly an important detail of an elevator. It was usually arranged at the bottom, because, if arranged at the top, the tightening of the chain or band generally upset the driving-band, unless this ran at right angles to the elevator. Where grain-elevators were concerned, it did not matter about the distance between the buckets and the elevator-well being variable. Where ashes, coal, or other material of varying size was raised, it was advisable to keep the space between the buckets and the well fixed, as in the elevator shown in *Fig. 4*; the elevator-well was designed to move up or down with the sprocket-wheel when the chain was adjusted, as mentioned by Mr. Porter. He did not think the elevator was likely to become choked at the bottom if the buckets were large enough to cope with the feed—making due allowance for the largest pieces—and if the elevator was properly fed. If it was fed from a large accumulation of material, a block was very likely to take place, or the feed might be stopped altogether, by the material forming an arch over the shoot; but in such a case the elevator should be fed by an oscillating feeding-shoot which deposited at each backward and forward stroke about as much material as the elevator would take; there would then be no choking. This was necessary only when the material came intermittently—say a truck-load or grabful at a time—or from a stock-heap. The elevator-buckets should ascend and meet the stream of material entering the elevator well, and not vice versa, or, better still, the feed should be spouted into the elevator leg above the well, as mentioned by Mr. Porter. In reply to Sir John Wolfe Barry, almost any kind of conveyor could be fitted beneath the deck of a large ship for conveying the coal to the far ends, or to any intermediate point; but only such conveyors as could deliver at any point would be suitable for the purpose. Undoubtedly the swinging conveyor could be used, and the coal could be deposited at the hold, in a hopper which communicated with one end of such a conveyor. Of course, the

The Author. conveyor would have to be part and parcel of the ship, as it would take too much time to dismantle and re-erect it whenever the ship had to be loaded. There was, however, one class of conveyor which appeared to be more suitable for the purpose than any other. Being on the intermittent principle, this conveyor was not mentioned in the Paper. It was the invention of Mr. Hunt, and was largely used for filling coal-stores—work similar to that required on board ship. The appliance was inexpensive, and consisted of a line of rails and some self-emptying trucks: only the rails need be a fixture on the ship; the trucks could be removed and kept at the port for use with all vessels fitted with such rails. This conveyor was used for distances of 250 yards, so that it was long enough for the largest vessel. No driving-power was required, which was a point in its favour; and the man attending the apparatus need have no special training whatever. The capacity of such a conveyor would be 100 tons per hour for one line of rails, but several conveyors could of course be used for one vessel. The line of rails had a gradient of about 1 in 33 from the hold to the bulkhead, and upon it ran a specially constructed truck. As soon as the truck was full, it was released, and ran by its own weight to the point at which discharge was required, where it opened automatically and discharged its load, and then ran back uphill to the starting-point to be reloaded. A hopper was required, into which a coal-tip of any kind could discharge the coal, and from which the automatic wagons could be filled. When released, the truck ran down with steadily increasing velocity, so that by the time it approached the bottom of the incline the speed was considerable. Across the rails was arranged a cross-bar with which two projections on the descending truck came in contact, with the result that the bar was carried away in front of the truck for some distance. To the cross-bar was attached an endless rope connected to a counterweight. The momentum of the loaded truck was thus utilized in raising this weight, which, on being released, hauled the empty truck back to its starting-point. The bottom of the trucks was Λ -shaped, and there were two flap doors, one on each side, extending the whole length of the truck and hinged from the top at the ends of the truck. The doors were connected together by levers which, when released by an attachment fixed at the sides of the rails, opened the doors. The contents of the truck were thus immediately released on both sides of the rails, the form of the bottom of the truck preventing any coal from being spilt on the rails themselves. The empty truck was then hauled back by the descending counterweight, and, on

its return to the starting-place, a simple operation closed the doors The Author. in readiness for another load. The same arrangement could be provided on both sides of a hold, and two or four lines of rails could take coal from a common hopper. Probably for loading ships a modification would be necessary, because a line of rails far enough from the deck to allow of the truck running between the deck and the rails would occupy too much space in the ship's hold; but he saw no reason why trucks similar to those described could not be built with wheels at the top, instead of at the bottom, so that the rails could be fixed close to the top of the hold. He was well acquainted with the installation described by Mr. Shoolbred, but as that method was also an intermittent system, it had had to be omitted from the Paper. The machine described by Mr. Molesworth, though a casting-machine, might be called a conveyor, as it was similar to the travelling-bucket conveyor. There were quite a number of them at work, principally in the United States. In England they had been adopted by the Millom and Askam Hematite Company of Millom¹ and by the Palmers Shipbuilding and Iron Company, of Jarrow-on-Tyne. The former company had the Uehling, and the latter the Heyl-Patterson machine.² The two machines did not differ much in general design, except that with the Heyl-Patterson machine the pigs were cast in the moulds while partly submerged in water; and, in order to prevent sticking, the moulds of the Uehling machine were coated with a spray of lime water, while in the Heyl-Patterson machine they were coated with soot. There were two other varieties of casting-machines, the Ramsay³ and the Hawdon.⁴ In the Ramsay machine the moulds were placed round the circumference of a large circle, while in the Uehling and Heyl-Patterson machines they were in a straight line. In the Hawdon machine the moulds were arranged partly in a straight line and partly in a circle. There were several Hawdon casting-machines at work in England, on the Continent, and in America. With reference to Mr. Molesworth's question about discharging from elevators, the diagram (*Fig. 43*) showed the curve described by the material discharged from the elevator. No matter with what velocity a body might be thrown off tangentially from the elevator-pulley, the moment it was free of its support the attraction of the earth asserted itself, and caused the body to fall. If the initial direction of motion was horizontal, as was the

¹ *Iron and Coal Trades Review*, 1898, p. 912.

² *Ibid.*, 1899, p. 952.

³ *Engineering and Mining Journal*, 1901, p. 7.

⁴ *The Engineer*, vol. lxxxviii. p. 111.

The Author. case with the delivery from an elevator, the attraction of the earth caused the body to move in a parabolic curve, and the heavier the body the more would its path deviate from the horizontal at every instant. A light body with a given linear velocity would proceed in an approximately horizontal line for a longer distance than a heavy body, as the earth's attraction was more or less counteracted by the friction of the atmosphere. He thought that Mr. Brown, when questioning the advisability of slanting elevators for coal, had had only gasworks and boiler-stokers in view. For such purposes there was no objection to the elevators being in a vertical position, because the coal had already been broken to a

Fig. 43.

small size, and a little additional breakage would be immaterial. As stated in the Paper, vertical elevators for heavy materials were objectionable on account of the high speed at which they would have to run in order to deliver the material down the discharge-shoot, and the consequent breakage. If breakage was of no importance, there was no objection to the fast-running vertical elevator. An elevator handling friable material, and running at its proper speed, must be wholly or partially inclined, in order to deliver satisfactorily. Inclined elevators possessed an undoubted advantage for heavy loads, as the load was dragged up on the inclined supports, and therefore did not hang on the top gear of the elevator with its whole weight. The speed at which elevators should run

was given in the Paper for the ordinary type of elevator, in which the back of the bucket was attached to the chain or band. Buckets suspended from their sides, as shown in *Fig. 4*, were rarely used, and were adopted for convenience of discharging sticky materials, or where a slow-running elevator must be vertical. As a rule, such elevators would run at a lower speed than that stated in the Paper, in order to give the material time to drop out of the buckets. In this respect the construction must depend entirely upon the kind of material conveyed, and there was no occasion to go into the merits or demerits of various speeds of travel. The designs of push-plate conveyors were so numerous that within the narrow limits of a Paper it would be impossible to describe every one. The examples given in *Figs. 16* and *17* were approved designs by good makers, and were both in use in the gasworks at Nottingham, and at other places. The fact that the late Mr. Chester, who had had much experience with push-plate conveyors, had selected those two, proved their merit. The Author's own experience caused him to regard them with favour. In both, the friction between the coal and the trough occurred only at the bottom; and he did not think a narrow and deep conveyor-trough, such as that described by Mr. Brown, could be made at any less cost than a shallow and wider one. He had had the opportunity of seeing a conveyor of the same construction as *Fig. 17*, in a London electric power-station, where it had given satisfaction for a number of years, though the chain had lately shown such signs of wear that its renewal had become necessary. The appearance of this conveyor had proved clearly to him that the renewable bar at the bottom fulfilled its purpose, because he had found it brightly polished by friction against the chain. With reference to the point at which the push-plate should be attached to the chain, it would appear to any engineer that at or near the middle was the best place; for if the chain was attached to the top end of the plate there was a tendency for the latter to get out of square with the trough, and also a tendency for it to push itself away and ride over the top of the coal. He was unable to throw more light on the points raised in regard to the figures for the first cost of some of the conveyors, in the Table on p. 95; but he was sure that the cost of steam-engines, screens and crushers was not included in the cost of the different appliances. The installation illustrated in *Fig. 32*, Plate 2, was as complete a plant as could be desired for its intended purpose, namely, handling coal: it was not meant to deal with stones,

The Author.

The Author. railway brakes and broken wheels; and there was no machine known which would separate such articles from coal. A screen, which was occasionally provided, might or might not keep such articles back; but it would also retain large pieces of coal, which would have to be broken with a hammer in order to pass the screen. Such screens had usually a mesh of 6 inches, and might pass a piece of iron big enough to damage the coal-breaker. The only safeguard was to have a man to pick out any foreign matter that might be mixed with the coal. He had recently been informed by the engineer of a large gasworks that, beyond a miner's lamp and a blasting-cartridge, he had never found anything mixed with the coal. The cartridge had been in the scoop ready to go into the retort when it had fortunately been detected. If Mr. Brown had a device for keeping back such impurities, it would undoubtedly be of great interest to coal-users. The suggestion as to picking out the small coal was of little importance. The small coal dropped readily through the coal-breaker, which was set sufficiently far apart; and the addition of a screen as suggested would necessitate deeper excavation, which in most cases was objected to. The expense of making the excavation deeper, and the elevator longer, was not warranted by the slight advantage gained by the adoption of a screen. He agreed with Mr. Porter's remarks, and the practice of feeding elevators some distance above the neck of the elevator boot was a good one. It was especially applicable when the elevator was inclined, because then the buckets caught practically everything that came down the spout and allowed very little to drop into the boot. He could not agree with Mr. Helps as to the desirability of doing away with the boot altogether; in the event of anything from the shoot missing the buckets it would accumulate in the bottom, where it could easily be picked up, as it would contain no large pieces, and there would never be a sufficient accumulation to cause any trouble. Screw tightening-gears on band conveyors were practically the same, whether they were used for pushing or for pulling, and the use of either kind must depend upon circumstances. For long adjustments, the pulling action was undoubtedly preferable, as mentioned by Mr. Porter, because the screw was then in tension, and could be made of smaller diameter. Slimes would be rather difficult to convey with the swinging conveyor, but if a fall was available there would be no difficulty, provided the slimes were not too wet. The cable conveyor could also be used for this purpose; and probably it would be more suitable, as a large quantity of water could be run with the pulp, and the disks at intervals would prevent adhesion to

the trough. Wet gravel could easily be conveyed with the swinging conveyor, but if the material was sticky the trough needed cleaning at intervals. This conveyor was used not only for conveying but also for sifting and classifying sand or gravel. It was not advisable to make it convey uphill; if the material was at all damp, a downward incline was better, even if only 1 in 100. Dry gravel or sand could be conveyed up an incline of as much as 1 in 20. The size of the gravel to be conveyed was quite immaterial. He thought Mr. Apjohn's statement, that nothing could be much better than the appliances used for dumping the whole of the contents of railway wagons into ships, was open to question. The appliances Mr. Apjohn referred to were largely used, and were probably the best that had been used so far; but why should a railway truck weighing 5 tons be raised 50 to 60 feet, in order to empty 10 tons of coal into a ship's hold? The structures for such coal-tips must be exceedingly strong, and the power required by the machinery, even with the balancing-devices in use, was enormous. Would not a tipping-device on the level of the rails, depositing the coal in a hopper (which required no driving-power), and inclined elevators for raising it, be much simpler, lighter and require less driving-power? The elevator, or part of it, could be made to swivel like a jib, and thus be raised or lowered to suit the position of any ship to be loaded. The speeds of band-conveyors given in the Table were the best economical speeds. There was no reason why they should not be exceeded; but if conveyors were worked at higher speeds than those given in the Table there was greater danger of breaking the coal at the point of delivery; so that it was more economical to make the appliances larger and work them at a lower speed. The four new coal-tips at Penarth Dock were capable of loading 2,154 tons in 2 hours. He failed to see the wisdom of running a band, designed to work at 400 feet per minute, at the speed of 700 feet per minute, as the coal would fly off nearly twice as far with the fast-running band as with the slow one, and the breakage at the higher speed must be disastrous. The electrically-driven scraper in America might be a useful appliance for trimming, and was also used for the purposes of unloading. With regard to coke, there was no difficulty whatever in conveying it with either a good band or the swinging conveyor. Such a swinging conveyor had been at work at the Margate gasworks for more than 2 years with great success. For conveying hot coke the best conveyor was probably the De Brower, consisting of two chains concealed in the sides of the conveyor-trough, and connected by bars which pushed the coke along in the trough.

The Author.