Discussion.

The PRESIDENT, in moving the vote of thanks, remarked that the subject of the Paper was rather specialized, and was perhaps of greatest importance to engineers practising in countries subject to wet and dry seasons and to occasional intense falls of rain. The substantial accuracy for practical purposes of the formulas described by the Author could perhaps best be tested by applying them to existing channels, and that was what the Author had done to some extent. The formulas and views of a number of other investigators were also discussed, and at very considerable length; in fact, the Paper might be regarded almost as a book of reference on the subject.

Mr. E. S. LINDLEY observed that the Author had given him credit for certain data which constituted about half of those used in the Paper. It had not been possible for him to furnish the Author with his data at the time, and the Author had had to measure them from the rather inadequate published diagrams. There were two reasons why Mr. Lindley had tried to advance the subject. In the first place, it had long struck him that, as Mr. Kennedy's data were derived from one observation on each of a number of different channels, there was no guarantee that the silt-charges of those different channels were the same: Mr. Kennedy had offered a mathematical proof that the silt-charges must be the same, but had abandoned it later. The second reason concerned widths: according to Mr. Kennedy's rule, as long as velocity and depth had the necessary relation, the channel could be narrow and deep, or wide and shallow within wide limits. As a next step, Mr. Woods had put forward a set of normal data for the design of Kennedy channels. Such dissatisfaction as Mr. Lindley felt with those data came under two heads. In the first place they provided only for the one standard condition of V_0 . In the second place Mr. Woods's curve was far from smooth. At that time the channels of the Lower Chenab canal-system had just been surveyed for re-modelling and for fitting Kennedy gauge-outlets. There were 2,700 miles of channel, dealing with a total of about 11,000 cusecs. Obviously it was not possible or even necessary to take every point that had been surveyed, and he had therefore taken the mean dimensions of one typical and regular mile in every 3 to 5 miles. He purposely avoided trying to select sections in a state of regime according

Mr. Lindley: to his or anybody else's opinion. Such a selection would in any case have been impracticable, because when one was liable to be transferred at short intervals it was not possible to gain sufficient personal knowledge of channels. In the second place there was a feeling of suspicion about any selection of data: that that feeling was justifiable was shown by the fact that, in the discussion on his Paper¹ describing his investigation, two speakers quoted to opposite effect figures relating to the the same set of channels. His aim had been, therefore, to take the whole of a system and see to what the average would lead. He had obtained 786 points, which was one in $3\frac{1}{2}$ miles on the average. The surveys were only of water-levels and bed-levels, which gave gradients and water-depths, and of surface-widths. The areas had, therefore, had to be arrived at on the usual Punjab assumption that the channels were trapezoidal with side-slopes of $\frac{1}{2}$ to 1. Any figures of discharges or velocities had had to be arrived at by calculation, assuming Kutter's N at the usual 0.0225. These points were first plotted, a separate plot being made for the channels of any branch system; these were then divided into clumps at right-angles to the general trend of the line and averaged. That yielded about forty branch-average points, which were combined on one plot. Where there was any scatter, groups were averaged, and so the exact position of the final lines was arrived at. As was to be expected, there was very considerable scatter in the full observed data: in the average the maximum bed-width for any given depth was about double the minimum, and a ratio of 1 to 4 would be required to cover extreme variations. In averaging data with such a degree of scatter it was necessary to consider carefully whether the averages that were arrived at were fair or not. For example, the inverse of the arithmetic mean of a set of numbers differed from the mean of their inverses. Probably the fairest way of averaging in this investigation was to take the geometric mean. As far as his data carried him at the time, relations were quite distinctly indicated; but shortly afterwards he obtained data for the Main Line of the system, which he had not been able to get before, and those unfortunately differed, in that the width was considerably greater than was indicated by the rule derived from all the others. The Author, by relating the velocity to the hydraulic mean radius, did secure a law which increased the width more rapidly for wider channels. To that extent the formulas derived to express Mr. Lindley's hypotheses failed. He had still felt it necessary to have some formula and principle of design, so he had made another attempt. He took Mr. Woods's normal data, one of the principles

¹ Proceedings Punjab Engineering Congress, vol. vii (1919), p. 74c.

of which, going back to Mr. Kennedy's rules, assumed an upper Mr. Lindley. limiting velocity, and therefore an upper limiting depth for any given silt. He did not accept this upper limit, but his data had proved inadequate to yield an improvement on it. He reduced Mr. Woods's data to a formula and again tried to amplify it by making it applicable to different silts and different critical velocity ratios.¹ That Paper was not based on any new data, and he had still felt the need of verifying the velocity-depth relation. To that end he had initiated an experiment which would deal with the same water carrying the same silt, and so avoid any possibility of differences of silt-charge. He had taken a certain channel, starting with its own natural width, and then confined it between slowly converging walls which would compel it to scour. It was, of course, necessary to provide a sufficient depth of silt for it to scour. If the velocity-depth relation were, say, $V = KD^n$, it would be found that W varied inversely as D^{n+1} . He had been rather surprised to get the extraordinary result that WD was a constant. The area was constant and the velocity, therefore, was constant; there was no velocity-depth relation. The flume, of course, was comparatively short. The convergence was about 1 in 15 to the point where the width got so narrow that an unnaturally steeply scoured bed might be produced, and there the rate of convergence was reduced. This discussion did not give enough time to deal with other data in his possession. The Author gave in Table I different critical velocity formulas and said that they were not comparable. It would be easier to visualize how they were related if it were taken that the velocity for a depth of unity was the coefficient given in the Author's first column, and the velocities for a depth of 10, namely 3.67, 3.38, 2.38, 3.08, 3.53, and 2.09 for the six formulas respectively, were added as a fresh column. When working on Mr. Lindley's data before, it had been necessary to determine their relation as accurately as possible, with a view to extrapolation. The Author had now produced data well outside their range; he had also arrived at formulas with exponents in round numbers, which had at least the semblance of a rational basis; so now the problem was quite different. It was necessary to determine, due allowance being made for natural variations, whether they fitted in with and did not contradict his conclusions, and, beyond that, to confirm his numerical coefficients. It might be more clearly realized how closely the river data did confirm the Author's conclusions if his comparison was looked at in detail. On the river Ravi there was practically absolute agreement, not between a measured width and his calculated width, but with

¹ *Punjab Irrigation Technical Review*, 1925, pp. 69 103.

Mr. Lindley. what the engineers had arrived at as the proper width for the river. That was of some value. In the case of the Chenab there was a difference of only 0.3 per cent. With the Ganges it was $5\frac{1}{4}$ per cent., and for the Lower Ganges 2.3 per cent. On the Irrawaddy there were two possible figures, which gave results of plus 6 or minus $\frac{1}{2}$ per cent., and on the Jumna the figures were minus 0.6 or plus 4.3 per cent. Considering the nature of the investigation and of the facts dealt with, that was rather remarkably exact agreement. A useful device for preparing diagrams for reproduction on a small scale could be illustrated by reference to *Fig. 10*. At a casual glance it would seem that there was remarkable agreement between the data and a very nicely fitting line; but closer inspection would show that the ratio of the minimum to maximum values of Af^2 at any value of V_0 was about 1 to 2: in fact the scale for Af^2 was too small to show fine differences. If the vertical scale for V_0 was taken as before, but the horizontal scale plotted for Af^2/V_0^5 , divergence would be clearly evident. For absolute agreement the plotting would result in a vertical straight line of the value of 3.8. Thus the width required for the diagram needed to be only sufficient to cover the scatter of data, and a scale could be used big enough for divergences to be measured directly and accurately. In testing the Author's relations by Mr. Lindley's data, it was necessary to remember that discharges and velocities were not actually observed. In addition, therefore, to comparison of velocity with depth and R , and the Author's $P_w = 2.668\sqrt{Q}$, Mr. Lindley had derived two more test-formulas. Substituting the Author's value of V_0 in his formula (2) gave $P_w/R^{1.5} = 8\frac{1}{3}\sqrt{f} = 8.05$ with the Author's value for f on the Lower Chenab canal; and that was a test of shape. Combining his formula for V_0 with Manning's, $\sqrt[3]{RS} = fN^2/1.614 = 0.292$, taking the Author's value for f and an assumed value of N ; and this was largely a test of constant rugosity. Table IV gave the individual data of the surveys of three channels and exhibited the variations to which they were subject. The first three columns gave water-surface width, water-depth, and surface fall per thousand; omitting intermediate calculated factors, succeeding columns gave:—

- (4) The Author's $f = (V/1.17)^2/R$.
- (5) $V/D^{0.57}$ for comparison of agreement of the two relations.
- (6) $\sqrt[3]{RS}$, largely a test of constancy of N .
- (7) The Author's $P/\sqrt{Q}$, which should equal 2.67.
- (8) The Author's $P/R^{1.5}$, which should equal 8.05.
- (9) $B/D^{1.61}$, which should equal 3.8, for comparison of agreement with Mr. Lindley's previous rule for widths.

The three channels were each about 35 miles long. The first, the Tarkhani distributary of the Lower Gugera branch, had silt diffi-

TABLE IV.

1	2	3	4	5	6	7	8	9
W_s	D	S	f	$V/D^{0.57}$	$\sqrt[3]{RS}$	$P/\sqrt{Q}$	$P/R^{1.5}$	$B/D^{1.61}$
<i>Turkhani.</i>								
40.6	2.22	0.228	0.88	0.99	0.288	3.70	15.1	10.6
38.6	2.08	0.228	0.84	0.975	0.282	3.82	15.7	11.8
36.2	2.08	0.226	0.835	0.97	0.280	3.73	14.9	10.5
33.3	2.40	0.212	0.825	0.94	0.272	3.32	11.8	7.5
30.5	2.39	0.204	0.795	0.92	0.261	3.25	11.1	6.9
27.4	2.19	0.228	0.835	0.945	0.283	3.27	10.7	7.2
25.6	2.28	0.190	0.72	0.87	0.238	3.23	11.2	6.2
21.7	2.26	0.198	0.73	0.87	0.246	3.06	9.4	5.4
14.7	2.25	0.212	0.77	0.855	0.257	2.72	7.2	3.4
14.2	2.08	0.218	0.755	0.855	0.257	2.78	8.1	3.7
11.2	2.38	0.204	0.73	0.79	0.242	2.55	6.6	2.4
7.1	1.87	0.324	0.965	0.89	0.347	2.47	7.0	1.9
<i>Sultanpakra.</i>								
32.8	3.15	0.250	1.08	1.035	0.347	2.63	8.4	4.7
27.4	3.18	0.250	1.08	1.02	0.345	2.47	7.4	3.8
24.0	3.01	0.250	1.06	1.005	0.337	2.46	6.7	3.6
26.6	2.78	0.220	0.905	0.95	0.292	2.75	7.7	4.6
24.1	2.98	0.208	0.86	0.91	0.279	2.60	7.2	3.6
24.3	2.75	0.218	0.895	0.94	0.287	2.70	8.1	4.2
18.0	3.07	0.190	0.785	0.835	0.252	2.44	6.2	2.5
21.6	2.47	0.235	0.915	0.955	0.298	2.74	8.5	4.4
19.7	2.65	0.220	0.845	0.90	0.282	2.63	7.2	3.5
16.6	2.79	0.230	0.895	0.895	0.294	2.44	6.6	2.6
16.3	2.26	0.222	0.82	0.89	0.270	2.74	8.0	3.8
14.9	2.22	0.210	0.775	0.86	0.253	2.73	7.6	3.5
13.9	2.07	0.190	0.655	0.80	0.224	2.90	8.1	3.9
10.2	1.98	0.180	0.62	0.745	0.204	2.84	7.4	2.7
9.2	1.78	0.200	0.62	0.755	0.218	2.90	7.7	2.9
<i>Dhaur.</i>								
38.2	4.03	0.240	1.15	1.04	0.360	2.35	7.2	3.6
40.0	3.96	0.244	1.165	1.055	0.365	2.41	7.3	3.9
38.4	3.10	0.250	1.095	1.055	0.348	2.79	9.5	5.7
33.4	2.90	0.286	1.20	1.105	0.388	2.70	9.3	5.5
28.8	3.25	0.180	0.79	0.87	0.252	2.67	7.4	3.8
28.6	3.61	0.232	1.06	0.99	0.332	2.34	6.6	3.2
28.4	3.76	0.194	0.90	0.905	0.281	2.38	6.3	2.9
29.4	3.13	0.214	1.04	1.01	0.336	2.56	7.9	4.2
30.0	2.73	0.236	0.97	0.99	0.313	2.85	9.4	5.4
23.2	3.09	0.264	1.11	1.025	0.360	2.37	6.7	3.3
18.6	3.05	0.236	0.975	0.93	0.312	2.34	6.3	2.6
17.8	2.71	0.236	0.915	0.925	0.303	2.47	6.8	3.0
16.6	2.64	0.258	1.01	0.965	0.327	2.41	6.8	2.9
12.6	2.40	0.262	0.93	0.91	0.317	2.43	6.7	2.5
10.0	2.26	0.238	0.80	0.825	0.276	2.51	6.6	2.1

culties, and distributed 150 cusecs; the others, the Sultanpakra and Dhaur distributaries of the Jhang branch, each distributed

Mr. Lindley. 250 cusecs, and were average as regarded silt, especially the latter. The most striking point about the Tarkhani was that the depth hardly diminished from head to tail, and the width accounted for

TABLE V.

	W_s	D	S	f	$V/D^{0.57}$	$\frac{3}{2}RS$	$P/\sqrt{Q}$	$P/R^{1.5}$	$E/D^{1.61}$
<i>Branch Average Data.</i>									
JB	5.7	1.03	0.375	0.89	0.96	0.343	3.07	10.2	4.4
JU	5.7	1.10	0.356	0.76	0.91	0.331	3.11	9.9	3.9
MA	5.8	1.20	0.442	1.02	1.03	0.419	2.80	9.2	3.4
GB	5.7	1.26	0.434	1.13	0.93	0.415	2.66	8.8	3.0
R	7.6	1.24	0.298	0.81	0.96	0.328	3.07	9.9	4.5
JL	6.8	1.30	0.375	0.90	0.98	0.369	2.86	9.1	3.6
GU	7.7	1.40	0.336	0.98	1.03	0.341	2.76	8.9	3.7
JU	9.2	1.48	0.334	0.96	1.03	0.347	2.81	9.1	4.1
GB	8.5	1.65	0.356	1.07	1.00	0.380	2.56	7.9	3.1
MA	9.85	1.57	0.300	0.96	1.02	0.320	2.78	8.8	4.0
GL	8.2	1.60	0.327	0.93	0.98	0.345	2.63	8.1	3.1
JL	10.7	1.67	0.322	1.10	1.10	0.351	2.66	8.6	4.0
R	10.7	1.70	0.278	0.92	1.00	0.304	2.76	8.5	3.8
JB	13.0	1.85	0.238	0.77	0.92	0.270	2.90	8.7	4.2
GL	14.3	2.05	0.281	0.99	1.04	0.330	2.65	8.2	3.8
GU	15.1	2.10	0.266	0.95	1.01	0.315	2.69	8.0	3.9
R	16.5	2.10	0.257	0.93	1.01	0.307	2.76	8.6	4.3
JL	16.15	2.15	0.274	0.97	1.03	0.329	2.69	8.3	4.1
GB	14.6	2.22	0.256	0.93	0.99	0.307	2.61	7.7	3.5
MA	19.6	2.41	0.245	0.92	1.00	0.307	2.70	8.2	4.2
JB	23.6	2.58	0.222	0.87	0.98	0.286	2.79	8.5	4.5
JU	21.8	2.77	0.235	0.95	0.97	0.357	2.51	7.2	3.7
GL	27.4	3.04	0.230	1.02	1.04	0.312	2.58	7.9	4.1
GU	33.6	3.04	0.218	0.95	1.03	0.300	2.78	8.8	5.0
GB	30.0	3.12	0.202	0.90	0.99	0.279	2.68	8.0	4.3
JL	27.2	3.18	0.232	0.99	1.03	0.320	2.51	7.3	3.7
R	28.0	3.40	0.180	0.78	0.90	0.254	2.59	6.9	3.4
MA	27.9	3.47	0.201	0.92	0.97	0.245	2.47	6.8	3.3
JB	40.0	4.00	0.200	0.95	1.00	0.300	2.51	7.2	3.9
MA	47.5	4.38	0.178	0.88	0.96	0.277	2.58	7.3	4.0
R	46.0	4.60	0.125	0.65	0.82	0.197	2.67	7.0	3.6
R	66.0	5.50	0.133	0.75	0.88	0.224	2.63	6.9	3.9
GL	73.5	5.59	0.187	1.01	1.04	0.319	2.48	7.2	4.2
GB	70.5	6.55	0.152	0.89	0.94	0.270	2.32	5.9	3.1
JU	116.8	7.75	0.150	0.93	0.99	0.286	2.47	6.9	3.9
GU	139.8	9.16	0.163	1.10	1.05	0.329	2.29	6.4	3.7
ML	292.0	9.93	0.176	0.86	0.95	0.371	3.12	10.6	7.0
ML	291.0	10.80	0.157	0.63	0.84	0.340	3.12	9.4	6.1

nearly the whole reduction. That channel would fail to support any rule connecting widths and depths: but it was pertinent to mention Mr. Quinton's implicit suggestion¹ that silt-quality fixed the velocity-depth relation, and silt-quantity ruled widths. Channels

¹ *Punjab Irrigation Technical Review* (1925), p. 91.

were likely to be wider than their natural widths as berm-growth Mr. Lindley was slow; columns 7 and 8 showed factors gradually falling to values a little less than the Author's, thus supporting his theories more than Mr. Lindley's. Columns 4 and 5 in Table IV showed that depths were more nearly in agreement with theory: column 6 showed more variation, but this would be covered by a variation of N from 0.0204 to 0.0245. On the Sultanpakra and Dhauhar the figures gave quite reasonable support to the Author's theory for shape, both in

Figs. 17.

relative constancy and in mean value; the fit for depths was roughly as on the Tarkhani. Branch-average data were shown in Table V, the factors given in each column being the same as for distributaries. Shape was tested by the plotting of columns 7, 8, and 9 in *Figs. 17*; and depth was tested by the plotting of columns 4, 5, and 6 in *Figs. 18*. In *Figs. 17* the two points for the Main Line showed width in excess of theory in each case, including the Author's; the points under the Author's theory scattered slightly less than under Mr. Lindley's; and average values were fairly in

Mr. Lindley. agreement with the Author. If the Author's river data and the Main Line were ignored, a relation $P = 9 R^{1.3}$ could be deduced from *Figs. 17*. That would involve changing the Author's formula (2) to $A f^2 = 4.4 V_0^{4.6}$. A line to represent this on his *Fig. 10* would pass through 4.4 and 2,620 at velocities 1 and 4 respectively, and it probably fitted the data as well as his line. But extrapolation would give widths of 1,320 for the Ganges and 1,950 for the Lower Ganges, and be very much too low for all others too. There was

Figs. 18.

thus fair indication that the Author was right in taking the exponent 5 in his formula (2); and it illustrated the disadvantage of even the most careful work on a narrow range of data. In *Figs. 18* the inclined line representing Mr. Kennedy's relation had been indicated for comparison, and shown not to fit the data at all; the magnifying effect of this way of plotting could be judged by comparing the scatter of the same data plotted in *Figs. 18* and ordinarily on the Author's *Figs. 4* and *5*. The Author referred to elliptic sections. In the Punjab practically all the channels he had dealt with had

horizontal beds of clean sand and steep sides of clayey silt. He Mr. Lindley. agreed with the Author's first conclusion, that for a given discharge with a given silt-charge, natural depth, width, and slope were fixed ; but there was much latitude in width at the cost of the maintenance necessary to keep up an unnatural condition. If a channel narrower than was natural was wanted, the sides would have to be protected. If a wider channel was wanted, berm growth was a slow process and would not give very much trouble. He agreed with the Author's second, third, and fourth conclusions. With regard to the fifth conclusion, that there was a relation between Kutter's N and silt, he agreed, but with the proviso that it must be remembered that Kutter's N depended not only on the silt but also on such factors as the straightness or otherwise of the channel. The Author's sixth conclusion was a physical question with regard to which there were not sufficient observations at present. The Author had put forward formulas arrived at from facts. It was perhaps rather too much to expect that they would be generally accepted, but Mr. Lindley wished to emphasize that it was very necessary to accept some formula at least tentatively, and that was the reason why he had put forward formula after formula. Until channels were left alone as much as possible, and until they were designed on some rule that kept nearer to the facts than any of the older rules, better data would not be obtained, because the channels had quite a strong tendency to remain as they were designed and maintained. Another point was that the new canals in the Punjab took off lower down the rivers, where there was a lower critical velocity ratio. It was becoming more and more accepted that with lower critical velocity ratios deeper and narrower channels were needed ; but the principles of design that were being applied were rather chaotic. When he tried to get some of the new ideas described accepted, he was told that his channels were much too deep and narrow ; he was able to reply very promptly by showing the chief engineer one of his own main lines which was very much deeper and narrower than Mr. Lindley would have ventured to design it. The Author's formulas would not get the test of general use unless diagrams were provided to save the labour of calculation : in all probability even the Kennedy silt theory would not have come into use if Mr. Kennedy had not also provided designing-diagrams that were simpler to use than anything then existing. The diagrams should show the correct bed-width, depth, and gradient for a given discharge and silt factor. *Figs. 19* saved most of the work of calculation. The nomogram contained a scale of discharge Q at the extreme right, with a scale of wetted perimeter P_w on the

Mr. Lindley. opposite side of the same line, the two being related by the Author's formula (5), and on the extreme left was a scale of the silt factor f . Between these two scales there was a scale of hydraulic mean

Figs. 19.

radius R , related to f and P_w by the first of Mr. Lindley's derived formulas, and a scale of fall per thousand S , related to R and f by Mr. Lindley's second derived formula, with N fixed at 0.0225. To

use this nomogram, a straight-edge was laid across the diagram Mr. Lindley. through required values of Q and f , and the values of P , R , and S were read off, the scales of R and S on the left sides of the lines being used. For greater discharges, the scale values of Q were considered to be multiplied by 100, the scale values of P multiplied by 10, and the right side scales of R and S were used. If some other value of N was required, S should be corrected proportionately to N^2 and no other change should be made. For obtaining the bed-width B and depth D there was (placed, for convenience of reproduction, between the R and Q scales of the diagram) a pair of scales of the ratios P/R and D/R with values correctly related for trapezoidal channels with $\frac{1}{2}$ -to-1 side-slopes. The ratio P/R should be calculated, the corresponding value of D/R found, and from this D calculated; subtracting $2.24 D$ from P gave B .¹ For any other form of channel it would be necessary to calculate and draw another scale of D/R . It would be observed that 6.94 was the minimum value of P/R for this form of channel; this meant that the limit referred to by the Author (p. 283) excluded this form of channel when fQ^2 was less than 3.24.

Mr. F. W. Woods observed that in discussing the critical velocities Mr. Woods. requisite for stable channels in alluvium it was necessary to be critical, and he proposed to be so. The Author was, he understood, an engineer of the United Provinces, of 20 years' experience. There were some very fine old canals in the United Provinces—the great Ganges canal, 75 years old, and the Eastern Jumna canal, 100 years old. Those channels had had time to become stable, and it would have been interesting to hear from the Author something about their condition; but the Author was silent on the point. He discussed instead the Godaveri and Kistna canals in Madras, and some canals in the Punjab; so that it would appear that his speculations were theoretical rather than founded on practical experience. The Author complained of Kutter's formula as "complicated." Mr. Woods had never found any difficulty in working with that formula, though he had never used even a slide-rule. The formula seemed complicated only when expressed in British

¹ *Example*.—To design a channel to carry 100 cusecs with a silt factor of 1.0, side-slopes being $\frac{1}{2}$ to 1, and $N = 0.0225$.

(1) On the right-hand line, opposite $Q = 100$, read $P = 26.7$. (2) Laying a line across $Q = 100$ and $f = 1.0$, read $R = 2.17$ and $S = 0.245$. (3) By arithmetic, $P/R = 26.7/2.17 = 12.3$. (4) On the second line from the right read that, when $P/R = 12.3$, then $D/R = 1.21$. (5) By arithmetic, $D = 2.17 \times 1.21 = 2.63$. (6) Bed-width = $26.7 - 2.24 \times 2.63 = 20.8$.—E S.L.

Mr. Woods, units of measurement, but the more one worked with it the simpler it became; one saw the same old forms and figures occurring again and again. The Author's formulas looked quite as formidable though in practice they might be simple to work with. The subject, however, was not primarily mathematical. An eminent mathematician, the late Professor S. P. Langley, once remarked that the mathematical method as applied to physics was trustworthy or untrustworthy according to the trustworthiness or untrustworthiness of the data employed. In dealing with the Author's calculations, which were interesting, he therefore would say nothing about the mathematics, but go straight to the statistics on which they were based. The Author gave the statistics on which he relied in Appendix G, which contained thirty-one examples from practice. Twenty-one of those examples referred to river-channels, which were never in stable regime. The Author admitted that, but he said that if the maximum flood of a river persisted long enough for stabilization to take place the results presented in his formula were obtained. The reply to that was that such conditions never were obtained. The discharge of such a river as the Ganges, or the Chenab, fell to about 6,000 cusecs in January. As the snows of the Himalayas melted it rose steadily to, say, 60,000 cusecs in July and August; but in between, during the summer, whenever there was heavy rainfall in the hills great floods occurred. Floods of 200,000 and 300,000 cusecs took place every year; at longer intervals there might be floods of 400,000 or 500,000 cusecs; and once in every 30 or 40 years there might be a flood of 600,000 or 700,000 cusecs. No one man could depend upon being able ever to observe the maximum flood in any river he studied. Even if he should chance to witness it, he would probably not have on that rare occasion facilities for measuring its width, depth, velocity, etc.; and certainly it would not be a "stable channel in alluvium." Railway-engineers were chiefly concerned with the maximum flood-discharge of rivers through their bridges. They did not worry about the river as a stable channel in alluvium; they were content to get the maximum flood through as small a waterway as possible, consistently with safety. He would therefore not consider those river-discharges. That left eleven channels. In his fifth conclusion, the Author said (p. 285), "The rugosity coefficient in Manning's formula is a simple function of the silt factor, and the silt factor is a function of the average size of the silt-particles." Mr. Woods could not agree with that. The Author referred, of course, to Kutter's coefficient. Every student of the subject ought to know that Kutter's coefficient of rugosity was not a question

simply of the rugosity of the material of the channel ; Kutter had Mr. Woods. frequently explained that the alterations of section—enlargements, contractions, and turns and twists of a river—were all included in his coefficient of rugosity. The same point could perhaps be expressed more simply by reference to Venturi's experiment. Venturi measured the discharge through a pipe 36 inches long and $\frac{3}{4}$ inch in diameter, under a given head. The experiment was then repeated under similar conditions, but the pipe, though still 36 inches long, and of a minimum diameter of $\frac{3}{4}$ inch, had its diameter enlarged to 2 inches at five places. The discharge in that case was only half as great. The material of both pipes was smooth glass. The same reduction of velocity and discharge was effected in a river, which would overcome an excess of declivity by alternate enlargements and contractions of waterway as well as by meanderings. In the case of the Ganges, from Hardwar to Cawnpore there was a fall of 560 feet, the distance being about 350 miles. The Ganges canal took off from Hardwar and was roughly parallel to the Ganges down to Cawnpore, where it tailed back into the river ; but the gradient of its bed only accounted for 280 feet of fall ; the remainder was given by vertical masonry drops. The river itself had no vertical falls, and had to dispose of the extra 280 feet in the way he had explained. That mainly determined the value of Kutter's N ; the effect of the size of the particles of sand was quite small. The Author based his values for the silt factor f entirely on Mr. Kennedy's standard Upper Bari Doab silt experiments. Mr. Kennedy's experiments extended over 87 miles¹ of canal, from mile 57 to mile 144. The sand at the upper end, however, was by no means of the same degree of coarseness or fineness as that at the lower end. Mr. Woods made some experiments in that connection on the Upper Bari Doab canal in 1905. He took samples of sand from the canal-bed at miles 34, 42, and 48, and classified them by sifting through graduated wire sieves, as well as by dropping them through still water and noting velocities of vertical descent. For the second method, a glass tube about 1 foot long and $1\frac{1}{2}$ inch in diameter was graduated into twelve equal parts, each of 0.001 cubic foot capacity. To the top of that was fitted a tin tube about 3 inches in diameter and 6 feet long. That was filled with water, and sufficient sand to fill the glass tube was dropped into the water. The coarsest particles fell first, and the time required to fill each division of the glass tube was noted. In that way the sand was graded, the velocities for the first (top),

¹ "Canal-miles" of 5,000 feet.

Mr. Woods. fourth, ninth, and twelfth (bottom) divisions being as shown in the following Table :—

Division No.	Velocity : Inches per Second.			
	Mile 31.	Mile 42.	Mile 48.	Average.
1	2.1	2.00	1.70	1.93
4	3.1	3.05	2.20	2.80
9	6.9	6.60	3.40	5.60
12	12.1	10.30	6.40	9.60
Average .	6.05	5.5	3.4	5.00

Even in those short distances of 8 and 6 miles, therefore, very marked differences in coarseness or weight of sand were noticeable. Mr. Kennedy's observations extended from mile 57 to mile 144, and the quality of the sand must have been very different at mile 57 from what it was at mile 144. At mile 57, again, the sand must have been finer or lighter than it was at mile 48. Obviously throughout the length of the canal the sand must vary in coarseness ; yet the Author had assumed that the whole of the 87-mile length dealt with by Mr. Kennedy had the same kind of " standard sand." Evidently his definition of " standard sand " was much too vague ; for the figures Mr. Woods had just given showed that even in a single sample of sand, taken from a particular site, there was very great variety in the sizes of grains. In Appendix C the Author gave data for the Godaveri Delta canals. Items 2 and 3 in that Table were very similar to each other in discharge and could be lumped together, and so could 4 and 5 ; 6, 7, and 8 ; 13 and 14 ; and 12 and 15. In that way the number of separate cases could be reduced to nine. The Author assumed that all the Godaveri sand had a silt factor of 0.456, and from Appendix D it would be seen that the Author assumed that the Kistna canal, which was a bank canal, had a silt factor of 0.725. There was, however, no *prima facie* reason why the sand on the Kistna delta should be different from the sand on the Godaveri delta to such an extent as was represented by the difference between 0.456 and 0.725.¹ The

¹ Even if the sand of the Kistna Bank canal is really much coarser than that of the Godaveri Delta canals, the fact supports this contention. The Author's theory is that the ratio of width to depth of a channel depends on the silt ; and he assigns a silt factor of 0.725 to the former, and 0.456 to the latter. That implies that the ratio of width to depth is different on the Kistna canal from that of the Godaveri canals. But when widths and depths are plotted graphically, it is seen that the ratio for both sets of canals is that given by the equation $\log d = 0.434 \log w$; an equation that is independent of the quality of the silt-grains. The ratio of width to depth therefore evidently does not depend essentially, or primarily, on the latter consideration.—F. W. W.

Author referred in a footnote on p. 274 to Mr. Woods's article published in *The Engineer* in 1927. In that article Mr. Woods gave some formulas based on the theory that in a regime channel there must be a definite ratio between width and depth. The Author ascribed that discovery to Mr. Lindley; but Mr. Woods had been advocating that theory about 7 years before Mr. Lindley started his professional career. He had plotted logarithms of width against logarithms of depth, getting a straight line which showed the relation between width and depth of regime channels to be $\log d = 0.434 \log w$. Of the nine data (grouped in the way he had indicated) given by the Author in Appendix C, three came exactly on Mr. Woods's line, three above it, and three below it symmetrically. That line represented ratios of width to depth, and was in accordance with the *average* data of the Godavari canals, although the variation of three above and three symmetrically below showed that the ratio was not constant in those cases; yet the Author had taken the same silt factor for each and said the "shape of the channel"—that was, the ratio of width to depth (p. 273)—depended on the silt factor. In Appendix D the Author gave the Kistna bank canal a silt factor of 0.725 (different from the factor assigned to Godavari canals) and stated that that canal was reported to be in good regime. Its ratio of width to depth came directly on Mr. Woods's line, which showed that the width-to-depth ratio was exactly the same as the average of the Godavari canals, notwithstanding the alleged difference in the quality of the sand. In Appendix D there were two examples from the Ibrahimia canal in Upper Egypt. The Author said they were inconsistent, but in those two examples the discharge was only about 5,000 cusecs, whereas the full capacity of the canal was upwards of 26,000 cusecs. Naturally the ratio of width to depth would not be the same at one-fifth depth as at normal water-depth. No regime channel would have the same ratio of width to depth throughout the range from full supply to low supply. The Author also cited three examples from the Ismailia canal, but there also there was a visible variation which could be solved only if the surface-slope was stated, and nowhere in his calculations or formulas had the Author said anything about that, though the surface-slope was surely important, as it represented the factor that actually moved the water. In 1903 Mr. Woods had hydraulic measurements made of various channels in the Lower Chenab canal, and he presented those statistics to Mr. Kennedy as showing that the width-to-depth ratio increased definitely with the discharge of those canals. Mr. Kennedy accepted that, and issued instructions in 1904 that channels were

Mr. Woods, to be designed accordingly. For certain discharges there were certain bed-widths and certain depths. In 1916 he had similar hydraulic measurements made of the Lower Jhelum canal, and in 1917 he issued his Paper on the "Normal Data of Design for 'Kennedy' Channels," to which the Author referred (p. 266). Those were not Mr. Woods's prescriptions for the ratio of width to depth; they were merely intended to be a supplement to Mr. Kennedy's diagrams. In 1919 Mr. Lindley prepared a statement of the width and depth of certain channels of the Lower Chenab canal, which were given in Appendix B of the Author's Paper. Mr. Lindley read a Paper on the subject before the Punjab Engineering Congress¹ in 1919, and in the discussion which followed Mr. B. L. Uppal said that the "normal data of design" Mr. Woods had given were nearer to the actual results on the Lower Jhelum canal than were Mr. Lindley's results for all channels up to 40 feet bed-width, and Mr. J. H. T. Middleton said the Lower Jhelum canal results fitted Mr. Woods's Table better than Mr. Lindley's for channels exceeding 50 feet in width. Mr. Lindley, in a Punjab Irrigation Department Technical Paper, published in 1925, which the Author also mentioned, said "Mr. Woods's Table (the normal data of design) is still the best guide for V_0 channels." Mr. Woods did not claim peculiar accuracy for those data, which were simply derived from experience and observation. Any other observed hydraulic data were of equal authority; but in the particular case under discussion, hydraulic data had been collected for the Lower Chenab canal by Mr. Lindley and by Mr. Woods, and for the Jhelum canal by Mr. Uppal; yet the Author, having all those before him, chose only Mr. Lindley's. It would appear, therefore, that the data the Author presented were not all the data on which he could have based his arguments, and, as Professor Langley had said, if his premises were wrong, his conclusions would be wrong, even if his mathematical processes were correct. After all, it was necessary to bear in mind what was meant by a "silted channel." Usually the silt that gave trouble was deposited in the first 5 to 20 miles of a main canal, or the first few miles of any of its distributaries; rarely did it give any trouble anywhere else. In the Punjab experience had shown that it was possible to prevent excess of coarse silt from entering a canal at its head, by furnishing the head with a relatively high sill and passing the water over with relatively low velocity. It was not practicable for the designer of a new canal to predict what the quality of the silt at any particular part of the canal-

¹ *Loc. cit.*

system was likely to be. It would vary according as the water entered the main canal head with relatively high, or relatively low, velocity; or over a sill relatively high or relatively low. A formula of design, therefore, based on assumptions as to quality of silt was not likely to be of practical utility. The governing factor in the design of regime channels must be one that governed also the admission or exclusion of silt at the canal-head. Although he did not consider the Author's formulas and thesis to be of practical utility in their present shape, he had found the Paper very interesting; and he hoped the Author would persevere in his researches, and particularly in the direction of personal experimental investigation of hydraulic conditions in the great canals of the United Provinces of Agra and Oudh. Mr. Woods.

Mr. A. B. BUCKLEY remarked that the Paper would add considerably to the statistics regarding the question it discussed; but he was rather puzzled by the fact that the Egyptian silt factors given in Appendix D ranged from 0.379 to 0.599. There were about thirty-six stations carefully distributed over Egypt, from which silt-samples were taken once a week. Those experiments had been carried on for 3 years. Every week about 100 samples were analysed by the chemists of the Agricultural Department and classified under coarse sand, fine sand, and silt. The coarse sand remained on a sieve of 100 meshes to the inch; fine sand remained on a 200-mesh sieve; and what passed through the latter was called silt. He was sure those samples were representative, and in all the samples there was no variation, so far as he could see, that would warrant a variation of 50 per cent. in the silt factor. The variation in silt content was illustrated in a Note¹ he had written in collaboration with the late Mr. F. Hughes in 1919. The Author gave no precise indication of the classification of the silt or of the factor to be attributed to a given silt. Had the same factor been applicable for all the silt of Egypt, the formula might have been more useful. He felt that a good deal of work on the subject had still to be done. The problem was very complex; there were four significant variables and two insignificant variables, and mathematically the problem was quite beyond him. Although he doubted whether the Author's formulas could be justified as a mathematical entity, that did not mean that he doubted their utility, for, quite probably, like many other empirical formulas, they would prove useful in the hands of practical engineers. He felt that all the questions relating to rivers and floods depended Mr. Buckley.

¹ "Note on Silt Investigations," No. 1, Cairo, 1919.

²¹Mr. Buckley. largely on the silt-charge. A channel carrying little silt might have to be obstructed by a weir, and although the silt might take some time to accumulate, it would be deposited in time, and then there might be trouble.

Dr. Owens. Dr. J. S. OWENS remarked that the Author had not attempted to evolve from a physical basis the formulas put forward. None the less they must be based on physical processes. He proposed to draw attention to a few points which he thought were important and which indicated, in his view, that no formula such as the Author gave could be absolutely accurate, or even make a close approach to accuracy, under all conditions. Such matters, in his experience, were apt to arouse controversy, but that perhaps added to their interest. The temperature of the water was not unimportant. The process of silting was a sort of dynamical equilibrium where as much was deposited out of the water as was carried away; the processes of picking up and depositing were going on simultaneously. The silt considered by the Author was mostly small particles, and their rate of settlement through water was profoundly affected by the temperature of the water. The rate of settlement—and hence the distance a particle would be carried by a current of given velocity—was one of the governing factors in the question of transportation. The effect of temperature was so great that the rate of settlement could easily be doubled by a comparatively slight rise of temperature, which meant that a cold river would behave differently from a hot river. Most of the data from which the Author had evolved his formulas were derived from hot rivers, and there might be quite a difference in the behaviour of a cold river. Again, it was impossible to evolve a silt factor based on size alone that would apply to all cases. The rate of settlement through water, which was the governing factor, was not a function of the size of a particle only; it depended also on shape and density. Shape in particular had a profound effect. In some experiments he made several years ago he showed that flat particles invariably selected the position of greatest resistance. A disk would settle through water on the flat; a rod would settle with the long axis horizontal, and so on. Size alone, therefore, was not sufficient for determining the silt factor; sifting through sieves and screens took no account of the other factor of shape, and might lead to very fallacious results. When the particles were small, the factor governing their deposition through water was mainly the viscosity of the water, so that the rate of settlement varied very much with the temperature; but when the particles exceeded about 0.1 inch viscosity ceased to have much effect. Thus for particles of less than a certain size one

set of laws governed the rate of settlement, and consequently the rate of silting, while with larger particles the rate of silting was governed by a completely different set of laws. It did not seem to him probable, therefore, that the same sort of formula would apply to all sizes of particles. He had carried out some experiments which in a particular case showed that the rate of settlement through running water was more rapid than that through still water. That sounded anomalous, but he believed it to be true, and there were conditions which seemed to make it reasonable. If particles tended to dispose themselves in the position of greatest resistance to settlement, and if they were settling through a stream where velocity was varying from top to bottom, then the top of the particle would be exposed to a different velocity from the bottom, and there would be a tendency to revolve, so that the position of greatest resistance would not be taken up. In such conditions a particle might be expected to settle more rapidly than in still water. It might not be strictly correct, therefore, to apply rates of settlement in still water to the conditions of running water. When matter was suspended in water, it behaved as if it was in solution so far as the specific gravity of the water—as measured by a hydrometer—was concerned. He knew the point gave rise to a good deal of controversy, but he believed it was very important. If, for instance, very fine sand was shaken up in water and a hydrometer was put into it, the hydrometer would record a specific gravity greater than 1, and the specific gravity could be seen to fall as the sand settled. While the sand was in suspension the water functioned as a denser liquid, and would therefore have greater power of erosion. The Author referred to some experiments Dr. Owens had made which indicated a sort of physical constant in water. He had found that at a velocity of about 0·8 foot per second water acquired the power of moving fine sand, while with a lower velocity it could not do so. He had also found another curious critical velocity. Between 0·8 foot and $2\frac{1}{2}$ feet per second the movement of the sand was always in ripples, the ripple being moved forward by erosion of the back and deposition on the front; but when the velocity exceeded $2\frac{1}{2}$ feet per second, the method of transportation was suddenly altered and the sand was carried off in a sheet. He thought the facts he had mentioned would affect the bearing of the Author's formulas upon any particular conditions.

* * The Author's reply will be found at p. 353.