Editorial

Jeff Cooper BSc, MSc, FRGS, FCIWM

Former President of ISWA; Independent Consultant on Renewable Energy from Waste; Technical Editor, London, UK

The papers in this issue cover a very broad spectrum of different aspects of waste management that will enhance the utilisation of our resources and protect the environment. All of the papers contribute to the debate about clean cycles and safe final sinks for any wastes that are generated. There are currently very few safe final sinks because we still rely on the use of many potentially hazardous materials in our production processes. One option is to utilise any residual waste from waste treatment and processing as a construction material, especially as the demand for construction materials is increasing with global population growth and an increasing gross national product in most countries of the world. Sometimes these residues can be used directly in construction, but more frequently they need to be encapsulated – generally with cement – in order to ensure that any potentially hazardous components are rendered safe for their use in construction projects. However, as the first two of these articles show, there are environmental safety limits that may be exceeded even if solidification within a cementitious matrix is undertaken. Even in developing economies, as shown by Amaral *et al.* (2013), there is scope for waste to be incorporated into local building products and higher specification construction materials, as previously demonstrated by Guemidi *et al.* (2015). However, it is clear that both supply and demand pressures mean that it is more likely that these wastes are utilised in more developed economies.

Berra *et al.* (2016) tackle the complexities of the intrinsic compositional qualities of wood fly ash, which is now being increasingly produced from new energy-generating plants and power stations converted from coal burning. In Europe, we are at the early stages of a move to more renewable sources for electricity and heating. Biomass will be an important component of our future energy mix in that transition. Technologically the use of biomass, mainly wood chips, in boilers is easier than pyrolysis and gasification, which have the benefit of producing biochar. This biochar, when added to soils either directly or in compost, becomes a significant mechanism for increasing soil fertility, water and nutrient retention, and sequestering carbon, thus helping to mitigate climate change. Unfortunately the ash from conventional burning of biomass in thermal power plants offers very little in the way of fertilisation potential, as Berra *et al.* (2016) demonstrate.

Therefore the ash residue from the conventional combustion process becomes a waste that requires disposal and therefore

adds to the overall costs of using this material as an energy source. In their thorough analysis of the waste from three different wood sources, including a sample of ash from painted and treated wood chips, Berra and his associates look at the potential for using Portland cement as a solidification medium to contain the heavy metal compounds contained in the ash, even from untreated wood chips from poplar and chestnut trees. They looked at whether the initially produced ash and resulting cementitious material after treatment would be acceptable in the three types of landfill recognised by the European Union Landfill Directive.

Another residue from industrial production, the slag residue generated from welding, is the subject of the paper by Arunachalam and Jayakumar (2016). Although the amount being generated is only just over 10 000 tonnes a year, its disposal presents an environmental problem and there is an increasing demand for fine sand for the construction sector in India. Would weld slag therefore provide a potential source of fine sand? The testing of the addition of weld slag as an aggregate for production of high-performance concrete with use of Portland cement shows positive results, except with very high proportions of substitution with weld slag. However, with the overall the amounts of weld slag being so limited, it is unlikely that weld slag would ever be put into concrete in very large amounts.

Reid *et al.* (2016) also tackle construction issues from a similar perspective but this paper looks at the potential of utilising demolition, construction and excavation (DC&E) waste as an aggregate source for construction within the desert state of Qatar. However, in contrast to the detailed laboratory analysis of Arunachalam and Jayakumar (2016), Reid *et al.*'s analysis focusses on the bureaucratic and other barriers that limit the use of DC&E waste in Qatar. Although FIFA's decision is still disputed, Qatar is preparing to host the 2022 Football World Cup. The plan is to build nine new stadiums and the refurbishment of three existing stadiums with all the attendant climate control measures, to accommodate the teams, media and fans. In addition, there will be a need for infrastructure both for the World Cup and for Qatar's overall development strategy. The country therefore needs huge amounts of aggregate to fulfil these objectives. Due to adverse geological conditions, Qatar lacks hard rock sources and mainly imports its requirements from the United Arab Emirates; 770 km by boat through a

port with a restricted capacity. At present there is limited potential for the utilisation of DC&E waste materials in Qatar for a variety of reasons. As of 2015, there was only one small reprocessing facility for DC&E waste, mainly to recycle hard waste materials. In contrast to the UK, there are very few drivers to stimulate the use of recycled DC&E waste in Qatar, particularly the modification of standards for construction materials to allow for the use of recycled materials.

The paper by Al-Rahbi *et al.* (2016) also looks at the energy sector and the need to remove and reduce the nitrogen oxide gases (NO_x) generated by combustion processes, irrespective of whether the combusted materials are fossil-based or renewable. Reduction of NO_x is a regulatory requirement because NO_x is a greenhouse gas as well as a health hazard. The proposed materials to effect this removal were three waste-based products, all of which were shredded: waste biomass in the form of date pits imported from Oman, municipal waste in the form of refuse-derived fuel and waste truck tyres. The shredding increases the surface area and porosity of the material and hence the capacity to adsorb NO_x gases. But why should these materials be used rather than the conventional selective catalytic reduction? There are considerable cost-reduction considerations as well as the environmental advantages.

The final paper by Vasilyev and Vasilyev (2016) is the most unusual of the papers of this issue, dealing with the former Russian capital, St Petersburg's newly instituted 12 km-long siphon sewer. The article will be of particular interest to anyone interested in the newly approved Thames Tideway Tunnel as there are design features common to both projects. The main difference is that the St Petersburg sewer tunnel does not run under the bed of the River Neva but around the north bank of the river before discharging into the Gulf of Finland after treatment. There are several interesting innovations that have been introduced within the system to improve both the efficiency of the movement of the sewage through the system and improve the protection of environment.

The authors of this issue are based in different countries but all these papers have relevance to both developed economies

and developing regions in showing the complexities and problems in enhancing the management of waste in order to establish a more sustainable resource management system for our future.

REFERENCES

- Al-Rahbi ASS, Nahil MA, Wu C and Williams PT (2016) Waste-derived activated carbons for control of nitrogen oxides. *Proceedings of the Institution of Civil Engineers – Waste and Resource Management* **169**(1): 30–41, <http://dx.doi.org/10.1680/jwarm.14.00021>.
- Amaral MC, Siqueira FB, Destefani AZ and Holanda JNF (2013) Soil-cement bricks incorporated with eggshell waste. *Proceedings of the Institution of Civil Engineers – Waste and Resource Management* **166**(3): 137–141, <http://dx.doi.org/10.1680/warm.12.00024>.
- Arunachalam A and Jayakumar K (2016) Influence of weld slag aggregate in high-performance concrete. *Proceedings of the Institution of Civil Engineers – Waste and Resource Management* **169**(1): 14–20, <http://dx.doi.org/10.1680/jwarm.15.00002>.
- Berra M, Mangialardi T and Paolini AE (2016) Environmental quality of hardened wood fly ash-cement mixtures. *Proceedings of the Institution of Civil Engineers – Waste and Resource Management* **169**(1): 3–13, <http://dx.doi.org/10.1680/warm.15.00003>.
- Guemidi I, Abdelaziz Y and Nebbou A (2015) High-performance concrete reinforced with fibres from waste. *Proceedings of the Institution of Civil Engineers – Waste and Resource Management* **168**(4): 158–165, <http://dx.doi.org/10.1680/warm.14.00008>.
- Reid JM, Hassan KE-G and Al-Kuwari MBS (2016) Improving the management of construction waste in Qatar. *Proceedings of the Institution of Civil Engineers – Waste and Resource Management* **169**(1): 21–29, <http://dx.doi.org/10.1680/warm.14.00016>.
- Vasilyev V and Vasilyev F (2016) Innovations in Saint Petersburg's 12 km siphon sewer, Russia. *Proceedings of the Institution of Civil Engineers – Waste and Resource Management* **169**(1): 42–51, <http://dx.doi.org/10.1680/jwarm.14.00022>.