Corrigenda in a paper published in

Magazine of Concrete Research

Volume 31, Number 109 : December 1979

Influence of specific surface and concentration of solids upon flow behaviour of cement pastes*

W. vom Berg

The Editor very much regrets that, the proofs of the above paper not having been seen by the author, a number of errors occurred in the text and Figures. The following corrections should be made to the published paper.

Page 211, column 2, end of line 17:

insert ⁽⁸⁾

end of line 22:

for ^(1,8,13) *read* ^(1,8,12)

Page 213, column 1, lines 21 and 50:

for γ *read* $\dot{\gamma}$

column 2, last line:

the flow equation *should read*

$$\dot{\gamma} = B \sinh (\tau - \tau_t) / A$$

Page 214, equation at the top of column 2:

The equation should be numbered (6) and in the second line of this equation:

$$\text{for } -\frac{C}{4} \text{ read } -\frac{B}{4}$$

Five lines later the number of the computer program *should read* BMD 07 R/H⁽²⁰⁾

On Figure 4:

for γ *read* Ω

for lease-squares *read* least-squares

On Figures 4, 5, 6, and 7:

for N/mm² *read* N/m²

In the caption to Figure 5, second line:

for 299 *read* 2.99

Page 215, lines 10 and 11 from the bottom:

for C *read* B

*Pages 211 to 216 of MCR 109.