Editorial

by P. C. Hewlett

Interfaces

An interface may be defined, generically, as the line of demarcation between dissimilar materials. As such, they invariably represent discontinuities and areas of weakness. Each material surface can be characterised by surface tension in the case of liquids and surface energies in the case of solids. Quantitatively, they are the same. However, differences in surface energies create interfacial tensions and incipient weaknesses. The removal of interfaces creates a seamless continuity and would be the ultimate objective.

In a material, such as concrete, we are presented with a wide range of interfaces. These occur due to the discontinuous and non-monolithic nature of the material. Concrete's porosity, micro/macro cracked nature and the juxtaposition of aggregate within the binding matrix create interfaces.

In the area of reinforcements we have a progressive move towards non-ferrous materials, e.g. polyaramids and glass-fibre reinforced polyester pultrusions. Such materials are likely to have lower surface energies than steel and so the adhesive bond capability will be reduced. In such situations, mechanical grip may dominate and also become Poisson's ratio dependent.

In addition to these internal interfaces, we have the external interface that concrete represents to the outside world and affects appearance and durability. The bulk strength of concrete, the way it absorbs and/or transmits fluids and gases, and its durability in the outside environment all depend upon the form to, and the extent of which, interfaces are created.

Ideally, if interfaces could be eliminated, concrete would be transformed into a non-premeable monolithic mass of enormous strength. Indeed, present technologies aimed at minimising porosity, reducing cracks

from whatever cause, approach, albeit hesitatingly, this ideal situation. However, the technologies are rather inadequate.

These technologies are driven by engineering objectives but also require scientific understanding if we are to feel confident in the outcomes. For instance, bonding materials to concrete, whether it be a paint/coating or floor overlay, call into play forces at a nanometer scale controlling how well a coating/overlay will adhere to the concrete. The engineering vision does not focus on nanometer phenomena and yet the macro-engineering response is governed by such phenomena. An analogy with disease may help in making this point. Empirical medicine preceded the optical and electronic microscopes and the role of viruses and bacteria. While an empirical answer to the disease might have been discovered before an appreciation of the role of bacteria and viruses, confidence in, and development of, such cures would have been restricted. I have doubts about this approach and advances in understanding should run in phase with corroborating evidence.

In the fields of fibre reinforced plastic composites, minerals separation/flotation lubrication and friction, such fundamental interactions are recognised and, where possible, are exploited from a knowledge base. Such a culture is not common in the field of concrete performance and development. Why not?

Perhaps concrete departs so far from the ideal in its roughness, porosity and variable composition that most of the classical theories dealing with spreading, wetting and adhesion are very unlikely to apply. For instance, how can you define interfacial tension between a liquid and concrete if the liquid is absorbed as it spreads on the surface?

In principle, such a tension would be negative and that creates physical/mathematical difficulties. Many surface characterising techniques are also difficult to apply because concrete, being a high surface energy material, contaminates readily and attempts to decontaminate often alter the surface under study. The surface is also rough, causing inclusions and points of weakness.

All these difficulties should foster fundamental study rather than preclude it. However, it would appear not to and it is worth asking why? Recent publications in the area of freeze-thaw response of concretes and mortars

has shown the benefit of fundamental research that facilitates later logical development.

On the other hand, perhaps the development of high strength yet tough concrete, concrete that is durable and ages in appearance well and, additionally, concrete that can be bonded to permanently, does not require an understanding based on science and that development routed in pragmatism is all that is required.

Such a view is to be doubted, was it not Francis Bacon who said, 'chance favours the mind that is aware'.