Editorial

Ashraf F. Ashour MSc, PhD, CEng, FStructE, FHEA
Reader in Structural Engineering, School of Engineering and Informatics,
University of Bradford, UK

This issue of *Structures and Buildings* presents five international papers on various technical topics. The first paper, by Yang *et al.* (2014), presents a series of physical experiments on pre-tensioned lightweight concrete beams. The authors carefully selected a good combination of lightweight concrete and prestressing technique to achieve a sustainable construction system. Lightweight concrete has several advantages including light self-weight, better thermal insulation and reduced transport cost. Additionally, prestressing the lightweight concrete is likely to achieve considerable synergistic benefits in minimising cracks and controlling deflections. The test results are well documented and discussed. The paper also develops simplified equations for flexural cracking moment and the capacity of pre-tensioned lightweight concrete beams for practical use.

The second paper, by Gasch *et al.* (2014), presents load measurements during the construction of reinforced concrete slab floors in Madrid, Spain. The data provide insight on how loads are transferred between slabs and shores in the course of a shoring, clearing and striking process. The results can assist in the planning of shoring systems used in the construction of cast in situ reinforced concrete floor slabs, with the goal of recovering most of the items in the shortest possible time in order to cut costs and keep execution time to the minimum. Field data have also been used to validate the finite-element model and simplified numerical techniques of the building.

The third paper, by Sahoo *et al.* (2014), investigates the efficiency factors of recycled concrete bottle-shaped struts compared with those made of natural coarse aggregate in current design codes. The comparisons show that the ACI 318-08 (ACI, 2008) provisions give unsafe efficiency factor predictions for all beams considered, whereas Eurocode 2 (BSI, 2004) strut efficiency factors are found to be unsafe in some cases.

The critical load estimation for non-prismatic, thin plates simply supported on four edges subjected to shear is presented in the fourth paper, by Bedynek *et al.* (2014). The paper carries out a comprehensive parametric study of 500 numerical models using finite-element analysis software. Different design expressions for the critical shear buckling coefficient in tapered steel panels are also proposed to be implemented in EN 1993-1-5 (CEN, 2006).

The final paper of this issue, Burdzik *et al.* (2014), explores the reasons for recent roof failures of multiple-ply nail plated timber trusses in South Africa. They show that the relative slip between plies owing to the torsional moment as a result of eccentric

loading is a possible cause of failure. The authors employ the matrix stiffness method to show that, by ignoring the eccentric loading and relative slip between the trusses, the member and plate forces may be underestimated by a factor in excess of two for a three-ply girder truss. A physical testing of a three-ply girder truss is also presented to illustrate the merits of the proposed theoretical method.

I hope you find these papers stimulating and informative. As always, comments and discussions from readers on the papers in this issue are most welcome through the submission of discussion articles.

REFERENCES

- ACI (American Concrete Institute) (2008) ACI 318-08 and ACI 318R-08: Building code requirements for structural concrete and commentary. ACI, Farmington Hills, MI, USA.
- Bedynek A, Real E and Mirambell E (2014) Shear buckling coefficient: proposal for tapered steel plates. *Proceedings of the Institution of Civil Engineers – Structures and Buildings* **167**(4): 243–252, <http://dx.doi.org/10.1680/stbu.12.00044>.
- Burdzik WMG, Skorpén SA and Jansen van Rensburg K (2014) Effects of slip on eccentrically loaded multiple-ply girder timber trusses. *Proceedings of the Institution of Civil Engineers – Structures and Buildings* **167**(4): 253–262, <http://dx.doi.org/10.1680/stbu.12.00034>.
- BSI (2004) BS EN 1992-1-1: 2004 Eurocode 2: Design of concrete structures. Part 1-1: General rules and rules for buildings. BSI, London, UK.
- CEN (Comité Européen de Normalisation) (2006) EN 1993-1-5. Eurocode 3: Design of steel structures, Part 1-5. Plated structural elements. CEN, Brussels, Belgium.
- Gasch I, Alvarado Y, Calderón PA and Ivorra S (2014) Construction loads using a shoring–clearing–striking process. *Proceedings of the Institution of Civil Engineers – Structures and Buildings* **167**(4): 217–229, <http://dx.doi.org/10.1680/stbu.12.00006>.
- Sahoo DK, Singh B, Mathew P and Bhargava P (2014) Efficiency factors of recycled concrete bottle-shaped struts. *Proceedings of the Institution of Civil Engineers – Structures and Buildings* **167**(4): 230–242, <http://dx.doi.org/10.1680/stbu.12.00029>.
- Yang K-H, Mun J-H and Lee J-S (2014) Flexural tests on pre-tensioned lightweight concrete beams. *Proceedings of the Institution of Civil Engineers – Structures and Buildings* **167**(4): 203–221, <http://dx.doi.org/10.1680/stbu.12.00003>.